"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

work in Leningrad.

chemical-heat treatment and is used successfully in the automobile industry.

3. Hardening of the drilling bits for use in the oil industry.

4. "Bright" annealing of steel strip.

5. Two-frequency heating of steel blanks for heating by applying pressure, particularly for rolling.

6. Heating and hardening of leaf springs on automatic machines.

7. High speed tempering of hardened components using high frequency heating etc. For automating technological processes, the following are at present manufactured: An automatic machine for heating and hardening of leaf springs; manipulator for horizontal forging machines; automatic machines for hardening of small components. Of the new apparatus used in induction heating, the author mentioned a stabiliser of the temperature of components being heated, a photo-electric pyrometer with a direct reading off of the temperature, relay for dosing the energy, etc. Of particular interest were the data he gave on the two-frequency heating of gears. The entire process

Card 3/14

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8



APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

...ments and can be used in mass production
...atment of gears with average moduli. Heating
...blanks which are to be shaped by applying pressure is
also effected by two-frequency induction heating using
50 c.p.s. current for heating to 700-750°C followed by
heating with high frequencies to 1100-1150°C. The two-
frequency induction heating reduces the consumption of
electricity in the case of heating right through of blanks.
For tempering and annealing of weld joints, induction
heating with 50 c.p.s. and with higher frequencies is used.
The paper of M. G. Lozinskiy, Doctor of Technical Sciences,
Institute of Engineering Technology, Ac.Sc. USSR
(Institut Mashinovedeniya AN SSSR) dealt with the problems
of strength of surface hardened components and the
features of high frequency heating. The deformation
detected by the author in engineering magnetic steels
"45" and "40X" forms in the surface layer as a result
of magnetostriction caused by the a.c. electromagnetic
field of the inductor. On a smooth surface of blanks
consisting of magnetic steels which were subjected to
repeated cycles of heating and cooling, "mounds" and

Card 4/14

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

129-4-12/12

[illegible] conference on industrial use of high frequency currents [illegible] in Leningrad.

"valleys" form at spacings equalling the half-wave of the supersonic oscillations generated by the high frequency. In non-magnetic steels no such phenomenon was observed. It was also observed that with increasing number of cycles, heating-cooling, the diameter of the cylindrical specimens in the heating zone increases, whilst the height of the specimens decreases. Furthermore, the author reported on the method of G. V. Uzhik which enables increasing the static strength up to 300%; this is achieved by using h.f. heating of a thin layer in the zone of stress concentrations at the surface of steel components. Thus, for instance, cylindrical specimens made of hardened 40X steels with a stress concentrator in the form of a notch will be 2.5 times stronger if the notch zone is tempered by using h.f. heating. M. G. Lozinskiy considers that use of the method of strengthening applying h.f. tempering of the stress concentration zones will permit evolving specifications which would justify more rational designs than those used hitherto.

K. Z. Shepelyakovskiy (ZIL) read the paper "On reducing the hardenability as a means of achieving contour (surface)

Card 5/14

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

All-Union Conference on industrial use of high frequency currents held in Leningrad.

hardening of toothed gears of average moduli". For this purpose a steel with low hardenability, ЭИ 937, was used. Gears made of this steel, of 180 mm dia. with a modulus of 4.2, were heated by means of an 8000 c.p.s. current of 100 kW capacity for a duration of 24 secs. The heating was effected in a ring-shaped inductor after which the gears were moved into a ring-shaped shower with a fixed direction of the holes. The teeth and the rims of the gears were subjected to hardening. The strength of the hardened teeth was investigated by loading until failure. In the case of gears made of the steel 30ХГТ (after carburisation and hardening) this load was 15.6 tons, for the steel ЭИ 937 the load was 16 tons. In the case of hardening of gears made of the steel ЭИ 937, a minimum deformation occurs, the fluctuations along the pitch circle after hardening amounted to 0.01-0.02 mm. In some cases the contact strength should be increased by increasing the carbon content to 0.6-0.7%.

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

Card 6/14 N.F. Scientific Research Institute imeni V.P. Vologdin (NII TVCh imeni V. P. Vologdina) presented a paper on

129-4-12/12

[illegible] Union Conference on industrial use of high frequency currents held in Leningrad.

surface hardening of gears by induction heating with two frequencies. The method ensures heating along the contour of gears with moduli of 3.5 to 5. During heating with a lower frequency (1000 to 2000 c.p.s.), the bottom of the tooth gap is heated intensively, whilst at radio frequency (300 000 c.p.s.) the tip of the tooth is heated. The same inductor is used for both frequencies. The heating with the lower frequency lasts 2.5 to 4 secs; thereby the specific power consumption is 1.5 to 1.7 kW/cm^2. Heating with the higher frequency is effected for 0.5 to 0.7 sec using a specific power of 1.1 to 1.2 kW/cm^2. The 1000 c.p.s. current is generated by a 500 kW rotary generator, whilst the 300 kc/sec current is generated with an oscillator circuit of 400 kW rating. During hardening of gears made of steel "45" cracks occur and, therefore, the carbon content was reduced and alloy steels 36Г2С, 35СГ etc. are being used. For fracturing a tool of a surface hardened gear a force of 9.5 to 17 tons is required, whilst the force required for fracturing case hardened gears after hardening, made of the steel 18ХГТ, did not exceed 10 tons per tooth. Gears produced by using

Card 7/14

0007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

129-4-12/12

All-Union Conference on industrial use of high frequency currents held in Leningrad.

two-frequency hardening wore down three times faster than gears produced according to the old technology. Therefore, in the further tests the steels 65Г, 50ХГ, 40ХН and 40ХНМА were used.

The paper of N. M. Rodigin, Ural Branch of the Ac.Sc. USSR (Ural'skiy Filial AN SSSR) was devoted to the new method of induction heating of steel strip. The novel feature consists in the fact that the electro-magnetic field produced by an alternating current is directed perpendicular to its surface and not in the longitudinal direction of the strip. This enables using economical sources of current of elevated frequency, namely, rotary generators. The required temperature distribution along the width of the strip is ensured by an appropriate configuration of the magnetic path and by an air gap between the poles. This method can be used for annealing cold rolled strip, for heating and for preheating of strip during rolling, pickling,

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

All-Union Conference on industrial use of high frequency currents held in Leningrad. 129-4-12/12

Staleprokatniy Zavod). The optimum frequency depends on the thickness and the width of the strip. For a thickness of 0.2 to 0.6 mm and a width of 100 mm it is recommended to use a current of 8000 c.p.s.; for strip of 200 mm a current of 2500 c.p.s. and for a width of 400 mm a current of 1000 c.p.s. On heating strip to 700-900°C, the uniformity of the temperature along the breadth of the strip is ± 25°C. For heating, a two-turn inductor was used, whereby the conductors of the current and of the magnetic flux were water cooled. This method was applied in the case of bright annealing of cold rolled strip. For a speed of movement of the strip of 25 m/min the required power was 200 kW (for a frequency of 2500 c.p.s.). The productivity of the equipment equalled 1 ton/hr. The specific power consumption during induction heating is 180-190 kWh/ton. Compared with annealing in chamber furnaces, this method has a number of advantages since thereby the productivity per m^2 of production space is increased two to threefold, the annealing time is reduced by several hundred times, uniform mechanical properties are ensured along the entire length of the

Card 9/14

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

strip coil and welding together of the strip during annealing is prevented. The specific consumption of electricity is higher for induction heating than for electrical furnaces.

V. N. Gridnev, Doctor of Technical Sciences, Kiyev Polytechnical Institute (Kiyevskiy Politekhnicheskiy Institut) dealt with the influence of the speed of heating on the structure and the properties of steel. Apparatus was built for the investigations which enabled simultaneous recording of several physical parameters so that the following could be oscillographically recorded: temperature, change in the length of the specimen and in its electric resistance and also current intensity in the inductor. The recording was effected with a speed of 50 to 10 000 °C/sec and the dilatometric curves were recorded with a speed of 60 000 °C/sec. The following binary alloys were investigated - Fe-Cr (up to 8%);

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8



APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8



APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

equal conditions of heating and cooling. Cooling in a 30 to 35% solution of glycerine and a 5% solution of potassium permanganate brings about a reduction in the deformation and in the crack formation, particularly in the case of alloy steels (40X, 40XH). Tempering at 140 to 200°C reduces the dimensions as compared to the hardened state and thereby the changes in the dimensions of the height and the internal diameter are compensated but the changes of the external diameter are amplified. Increase of the tempering temperature brings about an increase of the deformation.

Representatives from Roumania and East Germany participated in the Conference. The German delegate E. Trippmacher reported on the designs of compact h.f. transformers with built-in magnetic paths produced in East Germany.

NOTE: This is a complete translation and not an abstract.

AVAILABLE: Library of Congress.

Card 14/14

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHOVICH, Ye.M.; KISILENKO, V.A.

Metastasis of Brown-Pearce carcinoma following intratracheal implantation. Medych.zhur.24 no.3:111-116 '54. (MLRA 8:10)

1. Kiivskiy medichniy stomatologichnky institut, kafedra patologichnoi anatomii.

(NEOPLASMS, experimental,
Brown-Pearce carcinoma, intratracheal grafting, metastases)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHOVICH, Yu.I., inzh.; ZAV'YALOV, V.V., inzh.; SHCHUKIN, P.V., inzh.

Concerning V.V.Bulgakov's article "Mechanization of repair operations." Elek.sta.33 no.1:89-90 Ja '62. (MIRA 15:3)
(Electric power distribution—Equipment and supplies)
(Electric power plants—Maintenance and repair)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I. V.

USSR/ Physics - Spectral analysis

Card 1/1 Pub. 43 - 20/62

Authors : Peysakhson, I. V.

Title : Evaluation of the distorting effect of the optical system of a monochromator on the observed spectral line contour

Periodical : Izv. AN SSSR. Ser. fiz. 18/6, page 680, Nov-Dec 1954

Abstract : It is shown that the final width of the monochromator aperture, the diffraction on the boundaries of light pencils and the aberration of the optical system distort the results of spectrophotometric measurements. This is the main reason why the measured contours of spectral lines and bands do not express the actual spectral distribution of energy entering the test instrument. A method of calculating the distorting effect of the optical system, for the purpose of compensation, is described.

Institution : The A. A. Zhdanov State University, Leningrad

Submitted : .....

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I. V.

USSR/Physics

Card 1/1 Pub. 127 - 10/12

Authors : Peysakhson, I. V.

Title : Taking into account the distortion effect of the optical system of a monochromator on the observed contour of a spectral line

Periodical : Vest. Len. un. ser. mat. fiz. khim. 5, 129-143, May 1955

Abstract : A derivation is presented of an analytical expression for its practical application to the determination of the true contour of spectral lines observed through a monochromator, i.e., the contour of a spectral line should be determined taking into account the diffraction of a finite width of the monochromator's slit and the abberation of the optical system. Nine references: 1 German, 3 USA, and 5 USSR (1928-1953). Tables; graphs.

Institution : .....

Submitted : Marcy 20, 1954

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

24(7) PHASE I BOOK EXPLOITATION SOV/1700

L'vov. Universitet

Materialy X Vsesoyuznogo soveshchaniya po spektroskopii, 1956. t. II: Atomnaya spektroskopiya (Materials of the 10th All-Union Conference on Spectroscopy, 1956. Vol 2: Atomic Spectroscopy) /Lvov/ Izd-vo L'vovskogo univ., 1958. 568 p. (Series: Its: Fizicheskiy sbornik, vyp.4(9)) 3,000 copies printed.

Additional Sponsoring Agency: Akademiya nauk SSSR. Komissiya po spektroskopii.

Editorial Board: G.S. Landsberg, Academician, (Resp. Ed.); B.S. Neporent, Doctor of Physical and Mathematical Sciences; I.L. Fabelinskiy, Doctor of Physical and Mathematical Sciences; V.A. Fabrikant, Doctor of Physical and Mathematical Sciences; V.G. Koritskiy, Candidate of Technical Sciences; S.M. Rayskiy, Candidate of Physical and Technical Sciences; L.K. Klimovskaya, Candidate of Physical and Mathematical Sciences; V.S. Miliyanchuk (Deceased), Doctor of Physical and Mathematical Sciences; A.Ye. Glamberman, Doctor of Physical and Mathematical Sciences; Ed.: S.L. Gazer; Tech. Ed.: T.V. Saranyuk.

PURPOSE: This book is intended for scientists and researchers in the field of spectroscopy, as well as for technical personnel using spectrum analysis in various industries.

COVERAGE: This volume contains 177 scientific and technical studies of atomic spectrography presented at the 10th All-Union Conference on Spectroscopy in 1956. The studies were carried out by members of scientific and technical institutes and include extensive bibliographies of Soviet and other sources. The studies cover many phases of spectroscopy: spectra of rare earths, electromagnetic radiation, physicochemical methods for controlling uranium production, physics and technology of gas discharge, optics and spectroscopy, abnormal dispersion in metal vapors, spectroscopy and the combustion theory, spectrum analysis of ores and minerals, photographic methods for quantitative spectrum analysis of metals and alloys, spectral determination of the hydrogen content of metals by means of isotopes, tables, and atlases of spectral lines, spark spectrographic analysis, statistical study of variation in the parameters of calibration curves, determination of traces of metals, spectrum analysis in metallurgy, thermochemistry in metallurgy, and principles and practice of spectrochemical analysis.

Card 2/31

Materials of the 10th All-Union Conference (Cont.) SOV/1700

Vaynshteyn, E.O., and L.I. Pavlenko. Studying the Effect of Total Rock Composition on the Results of Quantitative Spectral Determination of the Mo Content of Granitoids 120

Kopystyanskiy, A.A. The Vertical Sun Telescope and the Small-size Diffraction Spectrograph of High Resolving Power at the L'vovskaya astronomicheskaya observatoriya (L'vov Observatory) 123

Kokyrev, B.P. The FEOU-17 and FEOU-18 Photoelectric Optical Amplifiers for Recording Extremely Small Infrared Radiations 125

Malyavkin, L.F., A.N. Mogilevskiy, and I.S. Abramson. Improving the Stability of Photomultipliers for the Photoelectric Recording of Spectra 129

Peysakhson, I.V. Effective Spectral Slit Width of a Monochromator When Aberrations Are Present 133

Card 9/31

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AUTHOR: Peysakhson, I. V. Sov/51-4-4-8/24

TITLE: Distortion of Spectral Lines in Mirror Monochromators (Iskrivleniye spektral'nykh liniy v zerkal'nykh monokhromatorakh)

PERIODICAL: Optika i Spektroskopiya, 1958, Vol IV, Nr 4, pp 481 - 485 (USSR).

ABSTRACT: In the spectral apparatus using prisms a monochromatic image of an infinitely narrow rectilinear slit is an arc of a curve which, with sufficient accuracy, may be regarded as a parabola (Ref 1). In spectrographs bending of lines has no effect on the resolving power and is only inconvenient in measurement of spectrograms using a microphotometer. In monochromators, the same bending of the entrance-slit image when this slit is in fact rectilinear, widens the transmission band of the monochromator and this lowers its resolving power leading to errors in spectrophotometric measurements. To decrease these errors, curved entrance slits are used with a radius of curvature r_0 which, for light of a certain wave-length λ_0, make the image of the slit rectilinear. This means, however, that for any other wavelength λ, for which the image of a rectilinear slit has a radius of curvature r

Card1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

Sov/51-4-4-8/24

Distortion of Spectral Lines in Mirror Monochromators

the spectral lines has a curvature R given by $1/R = (1/r) - (1/r_0)$. The value of R may be large in monochromators where changeable prisms are used with strongly differing refractive indices. The paper gives formulae which allow calculations of curvature of lines produced in monochromators with prisms and diffraction gratings. Curvature of the slit image in a spectrophotometer IKS-11 (Figure 4) was calculated. It is shown that in an autocollimating monochromator with a plane reflection grating and a parabolic mirror placed off the optical axis (Figure 5) it is possible to correct for curvature of the spectral lines occurring when rectilinear slits are used. There are 5 figures and 7 references, 3 Soviet, 3 English, 1 Japanese.

ASSOCIATION: Gosudarstvennyy opticheskiy institute im. S.I. Vavilova (State Optical Institute im. S.I. Vavilov)

SUBMITTED: June 21, 1957

Card 2/2 — Spectrum analyzers--Performance

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AUTHOR: Peysakhson, I.V. [illegible]

TITLE: An Effect of Aberrations of the Optical System of a Monochromator on its Resolving Power (Vliyaniye aberratsiy opticheskoy sistemy monokhromatora na ego razresha ushchuyu silu)

PERIODICAL: Optika i Spektroskopiya, 1958, Vol IV, Nr [illegible], pp [illegible]-677 (USSR)

ABSTRACT: The notion of an effective spectral width of monochromator slits $\Delta\nu_e$, where ν is in cm^{-1}, is specified more precisely than in earlier publications and is generalized to the case of an optical system with aberrations. The value of this $\Delta\nu_e$ for a monochromator with aberrations is defined as the width which in the absence of diffraction and aberrations would produce the same distribution of energy at the exit slit as the energy distribution produced by the given real monochromator. An effective geometrical slit-width s_e is related to the effective spectral slit-width $\Delta\nu_e$ by the equation $\Delta\nu_e = s_e\nu^2/(dl/d\lambda)$, where $dl/d\lambda$ is the linear dispersion. The value of $\Delta\nu_e$, determined as a half-width of the "apparatus function" of the monochromator, may be used as a measure of its resolving power. The "apparatus function" gives the

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

An Effect of Aberrations of the Optical System of a Monochromator on its Resolving Power 51-4-5-17/23

distribution of monochromatic light at the exit slit of the monochromator. The author calculates the energy distribution in a monochromator with aberrations using the method of element areas due to Slyusarev (Ref 5, 6). Resolving power of monochromators with two identical concave mirrors is calculated and the effect of the meridional increase of the dispersing system (prism or grating) on the magnitude of aberrations of objectives is determined. It was found that on meridional increase of the dispersing element the aberrations of the first (collimator) objective are increased by a factor of Γ, where Γ is the angular magnification. Due to the change in the light-beam width after dispersion the effective relative aperture of the second (camera) objective and its aberrations also depend on Γ. There are 3 figures and 10 references, 8 of which are Soviet, 2 American and 2 German.

Card 2/2

ASSOCIATION: Gosudarstvennyy opticheskiy institut im. S.I. Vavilova (State Optical Institute imeni S.I. Vavilov)

SUBMITTED: June 28, 1957

1. Spectrometers - Analysis 2. Monochromators - Theory - Theory 3. Monochromators - Diffraction 4. Monochromators - Characteristics

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AUTHOR: Peyzakhson, I.V. SOV/51-5-2-20/26

TITLE: The Conditions of Resolution of Spectral Lines of Absorption. In Answer to a Paper by Mitra and Sodha (Ref 1). ((Ob usloviyakh razresheniya spektral'nykh liniy pogloshcheniya. Po povodu stat'i Mitra i Sodkha (1))

PERIODICAL: Optika i Spektroskopiya, 1958, Vol 5, Nr 2, pp 209-210 (USSR)

ABSTRACT: Mitra and Sodha (Ref 1) regard two absorption lines to be more easily resolvable than two identically spaced emission lines. Mitra and Sodha confuse the concepts of the resolving power of a spectral instrument and the resolution obtained in particular cases of application of such an instrument. The possibility of resolution of spectral lines depends on the properties of the objects studied and the method of recording the spectrum. For one and the same instrument the resolution may be different in different cases but its resolving power is uniquely determined by the "apparatus function" and cannot be different in the study of absorption and emission spectra. For comparison of the conditions of resolution of absorption and emission lines it is necessary to establish a criterion which would be equally applicable to both absorption and emission. The present author shows that two

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

SOV/51-5-2-20/26

The Conditions of Resolution of Spectral Lines of Absorption. In Answer to a Paper by Mitra and Sodha (Ref 1)

lines of equal intensity are resolved, both in absorption and in emission, if $B_{min}/B_{max} = I_{min}/I_{max} = c$, where B is the absorption intensity and I is the emission intensity. The suffixes "max" and "min" refer to the line peaks and the trough between them respectively. The value of c is determined by the method of recording the spectrum. Thus the resolving power of a spectral instrument is identical for both absorption and emission. There is 1 German reference.

ASSOCIATION: Gosudarstvennyy opticheskiy institut im S.I. Vavilova (State Optical Institute imeni S.I. Vavilov)

SUBMITTED: February 17, 1958

Card 2/2 1. Spectroscopy 2. Spectrum analyzers--Operation 3. Spectrum analyzers--Analysis

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

24(4)

AUTHOR: Peysakhson, I.V. SOV/51-6-5-32/34

TITLE: Letter to the Editor (Pis'mo v redaktsiyu)

PERIODICAL: Optika i Spektroskopiya, 1959, Vol 6, Nr 5, pp 713 (USSR)

ABSTRACT: In an earlier paper (Ref 1) the author quoted Rautian's value (Ref 2) of the radius of curvature of the edges of the entry slit of the monochromator IKS-11. This value was quoted as r_0 = 105 mm and it was suggested that the curvature of spectral lines is not completely compensated in this monochromator. Actually the value of this radius, given by the factory which makes this instrument, is r_0 = 158 mm and this means that both the dispersion and the aberration curvatures of the spectral lines are almost completely compensated for all interchangeable prisms in the monochromator. This is a complete translation. There are 2 Soviet references.

Card 1/1

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

24(4)

AUTHOR: Peysakhson, I.V. SOV/51-6-6-32/34

TITLE: Optical Systems for Focusing of Infrared Radiation on a Receiver of Small Dimensions (Opticheskiye sistemy dlya fokusirovki infrakrasnoy radiatsii na priyemnik malykh razmerov)

PERIODICAL: Optika i spektroskopiya, 1959, Vol 6, Nr 6, pp 831-832 (USSR)

ABSTRACT: In many infrared instruments (such as IKS-11, IKS-6) radiation leaving the exit slit of a monochromator is focused on a receiver by means of an elliptical mirror. Apart from the difficulty of producing a perfect ellipsoidal surface, this arrangement limits the dimensions of the receiver which has to be placed in the beam of light falling on the elliptical mirror. Moreover, the image of the exit slit, although free from aberrations on the mirror axis, exhibits considerable coma at non-axial points. Projection systems consisting of two spherical mirrors (a convex mirror I and a concave one II) are free from these disadvantages. One of the systems proposed is denoted by 1 in the figure on p 831. It has an aperture in the concave mirror and it was first used in 1950 as an objective in an infrared microspectrometer (Gershgorin's design). The other system, denoted by 2 in the figure, is a reversed mirror micro-objective proposed by V.M. Chulanovskiy (in 1951) for

Card 1/3

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

imaging of the exit slit of a monochromator onto the surface of a thermal receiver in an infrared spectrometer ISF-1 made at the Experimental Workshop of the Physics Institute at Leningrad State University (the author's design). A special case of the second system has been described by Greenler (Ref 1) in 1956. It was found that spherical aberration can be corrected for in both systems when the latter are used at reductions of 4 to 10. Such a correction still leaves one free parameter (distance d between mirrors or distance s from the slit to the first, convex mirror). Consequently coma can be corrected for in system 1. In system 2 coma cannot be eliminated but its value is somewhat lower than that produced by an elliptical mirror at the same conditions of reduction. Trigonometric calculations showed that both two-mirror systems give a better image than an elliptical mirror under the same conditions (the same slit height, the same reduction and the same length of the device). To avoid vignetting of oblique beams and to decrease the dimensions of the mirrors and apertures in them, it is useful to employ a collecting lens near the monochromator slit. This

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

Optical Systems for Focusing of Infrared Radiation on a Receiver of Small Dimensions SOV/51-6-6-32/34

lens should be designed in such a way as to place the entry pupil at the convex mirror in system number 1 and to make the exit pupil the same in position and dimensions as the aperture in the convex mirror A collecting lens may be made of fluorite, rocksalt or potassium bromide. Use of such a collector in a system corrected for spherical aberration does not affect the magnitudes of other aberrations. There are 1 figure and 1 English reference.

Card 3/3

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

CHULANOVSKIY, V.M.; PEYS[illegible], I.V.; [illegible], D.[illegible].

Determination [illegible] solute values of parameters characterizing the intensity in the infrared absorption spectrum when time distortions [illegible]. Part 1. Opt. 1 spektr. 7 no. 6:763-769 D '59. (MIRA 14:2)
(Spectrum, Infrared) (Absorption spectra)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

68311

SOV/51-8-1-10/40

24.3410

AUTHORS: Chulanovskiy, V.M., Peysakhson, I.V. and Shchepkin, D.N.

TITLE: Determination of the Absolute Values of the Intensity Parameters in an Infrared Absorption Spectrum when Secular Distortions are Absent. II.

PERIODICAL: Optika i spektroskopiya, 1960, Vol 8, Nr 1, pp 57-60 (USSR)

ABSTRACT: In Part I (Optika i spektroskopiya, 1959, Vol 7, 763) the authors described three methods of determination of the intensity parameters for the case when secular distortions are absent (no details of these methods are given here). The present paper reports the results of a comparison of these methods and deals with the possibility of their use in current spectral apparatus. To compare their methods the authors used the $\nu_{C-H} = 3020\ cm^{-1}$, $\nu_{C=O} = 3417\ cm^{-1}$, $\nu_{C\equiv C} = 2120\ cm^{-1}$ and $\nu_{N-H} = 3437\ cm^{-1}$ bands of chloroform (Table 1), methyl ethyl ketone (Table 2), hexine (Table 3), and a solution of diphenylamine in CCl_4 (Table 4) respectively. Each of these bands had a different half-width b (b ranged between 12 and 35 cm^{-1}). A Perkin--Elmer monochromator (LiF prism) was employed together with an amplifier FEOU-18 and a recorder EPP-09. Before measurements the entry and exit slit-widths were equalized. The results are given in Table 1-5, where the following symbols are used: S is the geometrical width of the

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

68318

24,3420

SOV/51-8-1-19/40

AUTHOR: Peysakhson, I.V.

TITLE: Determination of the Parameters which Give the True Contours of Absorption Bands

PERIODICAL: Optika i spektroskopiya, 1960, Vol 8, Nr 1, pp 116-117 (USSR)

ABSTRACT: This is a summary of a paper presented at the Conference on the Theory of Spectroscopic Instruments (Leningrad, March 5-7, 1959). The apparatus function of a monochromator is governed by widths of the monochromator slits, diffraction phenomena and optical aberrations of the system. The monochromator can be regarded as free of aberrations, if geometrical-optics calculations show that the width of the "scattering figure" in the infinitely narrow slit representation is not greater than the normal slit width. This condition is satisfied for example in IKS-11 in those regions of the spectrum where NaCl and KBr prisms are used; in the case of LiF prisms the condition is satisfied when the slit height is limited to 10-12 mm. The apparatus function can then be represented in the form of a triangle:

Card 1/5

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

68318

SOV/51-8-1-19/40

Determination of the Parameters which Give the True Contours of Absorption Bands

$$A(x) = \frac{1}{\Delta\nu_e}\left(1 - \frac{|x|}{\Delta\nu_e}\right); \quad |x| < \Delta\nu_e \qquad (1)$$

whose half-width is given by:

$$\Delta\nu_e = \sqrt{\Delta\nu^2 + \Delta\nu_0^2} \qquad (2)$$

where $\Delta\nu$ is the spectral width of the slits related to the geometrical width, s, and the linear dispersion of the instrument, $d\ell/d\lambda$, by the expression:

$$\Delta\nu = \frac{s\nu^2}{\frac{d\ell}{d\lambda}}$$

and $\Delta\nu_0$ is the normal slit width expressed in wave-numbers. Eq (2) is more precise than the expressions, proposed by several authors, of the type:

$$\Delta\nu_e = \Delta\nu + \varphi \cdot \Delta\nu_0 \qquad (3)$$

Card 2/5

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

68318

SOV/51-6-1-19/40

Determination of the Parameters which Give the True Contours of Absorption Bands

where φ is a constant. When the slits are five or more times wider than the normal slit, the role of diffraction in broadening of the slit images is small and can be neglected. When considerable aberrations are present we can still use the approximation to the apparatus function in the shape of a triangle (Eq 1) and the effect of the optical part of the monochromator on the results can be given in terms of a single quantity: an effective spectral slit width, $\Delta\nu_e$, i.e. the half-width of the apparatus function. If $k(x)$ and $K(x)$ are the true and observed optical densities (x is the distance along the wave-number axis from a certain fixed point on the absorption band contour), then, in the case of the apparatus function described by Eq (1) and small values of $\Delta\nu_e$, we have:

$$k(x) = K(x) + \left\{\left[K'(x)\right]^2 - K''(x)\right\} \frac{\Delta\nu_e^2}{12}. \qquad (4)$$

Let k_m and K_m be the true and observed maximum optical densities and b and b_0 the corresponding values of the band half-width. Then, if $\Delta\nu_e < \frac{b}{2}$, we find that:

$$K_m = k_m - c_1 \Delta\nu_e^2 \qquad (5)$$

Card 3/5 and

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

$$b^2 = b_0^2 + c_2 \Delta\nu_e^2 . \qquad (6)$$

The coefficients c_1 and c_2 depend on the band contour, but they are constant for one particular sample. Consequently by measuring K_m and b for several values of the slit widths, we can determine k_m and b_0 by linear extrapolation to the infinitely narrow slit width of the dependences $K_m(\Delta\nu_e^2)$ and $b^2(\Delta\nu_e^2)$; no assumptions are made about the band contour, except that it is approximately symmetrical. The quantity k_m can be also found approximately from the values of $K(x)$ for three equidistant values of x:

$$k_m = K_m + \left[K_m - \frac{K(x_m + h) + K(x_m - h)}{2}\right] \frac{\Delta\nu_e^2}{6h^2} . \qquad (7)$$

The expression in the square brackets in Eq (7) can be easily found graphically (cf. figure on p 117). For absorption-band contours, given by the Lorentz dispersion formula:

$$K(x) = \frac{A}{x^2 + \left(\frac{b}{2}\right)^2} ,$$

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

68318

SOV/51-6-1-13/40

Determination of the Parameters which Give the True Contours of Absorption Bands

we have the following relationships:

$$K_m = K_m \left(1 + \frac{2\Delta\nu_0^2}{3b^2}\right) \qquad (8)$$

and:

$$b_0^2 = b^2 - \left(2 - \frac{K_m}{3}\right)\Delta\nu_0^2. \qquad (9)$$

which give the values of K_m and b_0 with an accuracy of not less than 2-3% when $\Delta\nu_0 \leqslant 0.4b$ and $K_m \leqslant 2$. There is 1 figure.

Note. This is a complete translation.

Card 5/5

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I.V.: TARNAKIN, I.N.

Generalized formulation of the laws of refraction and reflection for calculating the path of rays in optical systems. Opt. i spektr. 18 no.5:906-907 My '65. (MIRA 18:10)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I.V.; TARNAKIN, I.N.

Calculation of the aberration of concave diffraction gratings. Part 2: Calculation of aberrations and estimation of the resolving power of the grating. Zhur. prikl. spekt. 2 no.3: 218-222 Mr '65. (MIRA 18:6)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

L 64494-65 EWT(1)/EPF(c) IJP(c) WW/GG

ACCESSION NR: AP5012628 UR/0051/65/018/005/0906/0907

535.312 + 535.314

33

B

AUTHORS: Peysakhson, I. V.; Tarnakin, I. N.

TITLE: Generalized expressions for the laws of refraction and reflection for ray tracing in optical systems

SOURCE: Optika i spektroskopiya, v. 18, no. 5, 1965, 906-907

TOPIC TAGS: light reflection, light refraction, optic system, geometric optics

ABSTRACT: The authors indicate that when the standard vector expression for the refraction of light is used to trace reflected rays, it is impossible to obtain a correct result if the projections of the incident and reflected rays on the optical axis have the same sign, something which frequently occurs in high-transmission mirror systems. The standard equation is presented in the form

$$n'a' = na + [\sqrt{n'^2 - n^2 + (naN)^2} - (naN)]N, \quad (1)$$

Card 1/3

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

L 64494-65

ACCESSION NR: AP5012628

where n and n' are the refractive indices of the first and second media, a and a' are the unit vectors of the incident and refracted rays, and N is the unit vector normal to the surface at the point of incidence. It is shown that Eq. (1) can be generalized for the case of reflection in the following way

$$n'a' = na + \{\pm[\mathrm{sign}(naN)]\sqrt{n'^2 - n^2 + (naN)^2} - (naN)\}N. \quad (2)$$

where the plus sign in the front of the square brackets refers to the case of refraction and the minus sign to the case of reflection. In reflection from a surface, n' = n and Eq. (2) takes the form

$$a' = a - 2(aN)N, \quad (3)$$

which is the well known reflection law. If the expression under the square root in (2) turns out to be negative, this means that there is no refraction at the surface in question, but there is total internal reflection. When using (2), no limitations are imposed on either the choice of the positive direction for the normal N at the

Card 2/3

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

L 64494-65

ACCESSION NR: AP5012628

point of incidence of the ray at the interface or on the choice of the positive direction of propagation of the rays in the optical system. Orig. art. has: 1 figure and 3 formulas.

ASSOCIATION: None

SUBMITTED: 05Jun64 ENCL: 00 SUB CODE: OP

NR REF SOV: 000 OTHER: 002

Card 3/3

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I.V.; PARITSKAYA, G.G.

Characteristic function for a spherical reflecting diffraction grating. Opt. i spektr. 18 no.3:534-535 Mr '65. (MIRA 18:5)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

REYSAKHSON, I.V., Cand Phys Math Sci -- (diss) "Effect of aberrations of the optical system of a monochromator ~~on~~ upon its resolving force and ~~on~~ upon the distribution of energy in ~~the~~ spectra under observation." Len, 19[illegible], 10 pp (Len Order of Lenin State Univ im A.A. Zhdanov) 1[illegible] copies (KL, 3[illegible], 111)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I.V.; GUREVICH, D.B.

Optical system of a high-intensity spectral instrument for the visible and ultraviolet spectral regions. Izv. AN SSSR. Ser. fiz. 26 no.7:963-964 Jl '62. (MIRA 15:8)
(Spectrograph)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I. V.

PHASE I BOOK EXPLOITATION SOV/5151

Leningrad. Universitet

Molekulyarnaya spektroskopiya (Molecular Spectroscopy) [Leningrad] Izd-vo Leningr. univ., 1960. 198 p. 4,700 copies printed.

Resp. Ed.: F. I. Skripov; Eds.: Ye. V. Shchemeleva and V. D. Plastro; Tech. Ed.: S. D. Vodolagina.

PURPOSE: This collection of articles is intended for scientific workers, instructors and students of physics and chemistry. It may also be used by engineers and technicians employing molecular spectroscopy.

COVERAGE: The collection of articles describes spectroscopic studies of liquids and solutions, and includes data on applied molecular spectroscopy. Individual articles deal with the molecular interaction in solutions, and specifically with the hydrogen bond problem. Works on the optimum utilization of spectral apparatus and on the analytical application of molecular spectroscopy are also included.

Aspects of the structure of high and low molecular compounds and of molecular complexes are also covered. The collection was published in honor of the 70th birthday of Professor Vladimir Mikhaylovich Chulanovskiy, Soviet specialist in molecular spectroscopy and spectral analysis. There are no references.

TABLE OF CONTENTS:

Chulanovskiy, V. M. Spectroscopy of the Liquid State 3

Stepanov, B. I. Basic Principles of the Spectroscopy of Negative Luminous Fluxes 20

Neporent, B. S., and N. G. Bakhshiyev. Effect of the Internal Field on Spectral Characteristics of Polyatomic Organic Molecules in Solutions 35

Kecki, Z., S. Osiecki (deceased), S. Kurowski, and S. Minc [Warsaw]. Application of Raman Spectra to the Study of Intermolecular Interaction in Electrolyte Solutions 52

Bobovich, Ya. S. On Raman Spectra Polarization and the Structure of Molecules 68

Mironova, A. N. Application of Spectroscopy in the Chemistry of Fats 82

Meyster, T. G. Study of the Absorption Spectra of Some Alkyl Nitrites 90

Denisov, G. S., and A. Ye. Semenova. Investigation of Intermolecular Interactions in Chloroform-Ketone Mixtures by Infrared Absorption Spectra 100

Shuvalova, Ye. V. Spectroscopic Study of Intermolecular Interaction in Monosubstituted Derivatives of Acetylene 108

Gol'denberg, A. L., L. I. Tarutina, and G. F. Fratkina. Application of Spectroscopy in the Manufacture of Plastics 118

Gol'denberg, A. L., L. N. Miroshnaya, G. S. Popova, and L. I. Tarutina. Application of Infrared Absorption Spectra to the Study of Polymer Aging 131

Vlovenko, V. M., and D. N. Suglobov. Investigation of the Formation of Complexes in Organic Uranyl Nitrate Solutions by the Method of Infrared Absorption Spectra 145

Peysakhson, I. V. Effect of the Optic System of a Monochromator on the Results of Spectrophotometric Measurements 153

Sverdlova, O. V. On the Contour of the Electron Absorption Bands of Some Benzene Solutions 160

Gutman, T. L. Semiempirical Calculation Method for Single-Electron Wave Functions and Transition Probabilities When the Spin-Orbital Interaction Is Taken Into Account 165

Trifonov, Ye. D. Plotting Antisymmetric Wave Functions 174

Zhukova, Ye. L., and M. I. Rabar. On the Nature of Intermolecular Linkage in Acetonitrile-Ketone Systems 184

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

67155

24.3410

AUTHORS: Chulanovskiy, V.M., Peysakhson, I.V. and Shchepkin, D.N.

TITLE: Determination of the Absolute Values of Parameters Characterizing the Intensity in Infrared Absorption Spectra in the Absence of Secular Distortions

PERIODICAL: Optika i spektroskopiya, 1959, Vol 7, No 6, pp 763-769 (USSR)

ABSTRACT: In currently used infrared single-beam automatic-recording spectrophotometers the so-called secular distortions, due to inertia of the amplifying and recording parts of the apparatus at the usual scanning rate cause great difficulties in determination of the true values of spectral parameters. The authors employed the following method which avoids these secular distortions. Recording was started with the beam cut off in order to obtain the zero level of intensity. Then a cell containing pure solvent was introduced into the beam (the corresponding intensity was I_0). As soon as the recorder started to draw a straight line parallel to the zero line a cell containing solution was introduced into the beam and the corresponding intensity I recorded. Again when the recorder began to draw a line parallel to the zero line the beam was cut off completely. In this way a record shown in a figure

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

67155

SOV/51-7-[illegible]

Determination of the Absolute Values of Parameters Characterizing the Intensity in Infrared Absorption Spectra in the Absence of Secular Distortions

on p 764 was obtained. The time lost by this process was fully compensated by the great simplicity and reliability of measuring intensity I, which was required to determine optical density. The return to zero after each cycle of measurements avoids the necessity of controlled records. Under the conditions described, the secular distortions are avoided entirely and the distortions due to noise can be easily found. The authors describe three methods of determining spectral parameters, such as optical density at the band maximum, integral density and half-width of the band, corrected for distortion due to the monochromator and expressed in terms of the latter's apparatus function. The computational work reported in this paper was carried out by I.V. Peysakhson and the experimental part was carried out by D.N. Shchepkin. There are 1 figure and 5 references, 3 of which are Soviet and 2 English.

4

SUBMITTED: May 14, 1959

Card 2/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEISAKHZON, B.E.

Organizatsiia dvizheniia na zheleznodorozhnom transporte. [Organization of railroad traffic]. Izd. 2., ispr. i dop.; pod obshchei red. B. V. Isaeva. Uchebnik dlia vtuzov zheleznodorozhnogo transporta. [Moskva], Transzheldorizdat, 1939. v. 2 (360 p.)

Vosstanovlenie propusknoi sposobnosti zheleznodorozhnykh linii. [Rehabilitation of traffic capacity of railroad lines]. Moskva, Transzheldorizdat, 1944. 42 p.

SO: Soviet Transportation and Communications, A Bibliography, Library of Congress Reference Department, Washington, 1952 Unclassified

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B. E.

POVOROZHENKO, V.V., professor; PEYSAKHZON, B.E., dotsent

Thirty years of the Soviet system of operating railroads. Tekh. zhel.dor.6 no.12:1-6 D'47. (MLRA 8:12)
(Railroads--Management)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B.E., kandidat tekhnicheskikh nauk; ZABELLO, M.L., redaktor.

[Problems of electric railroad operation] Voprosy ekspluatatsii elektricheskikh zheleznykh dorog. Moskva, Gos. transportnoe zheleznо-dorozhnoe izd-vo, 1952. 122 p. (MLRA 6:8)

(Electric railroads--Management)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B.E., kandidat tekhnicheskikh nauk, redaktor; YUDZON, D.M., tekhnicheskiy redaktor.

[Work practice by engineers of heavy freight trains] Opyt raboty mashinistov-tiazhelovesnikov. Moskva, Gos. transp. zhel-dor. izd-vo, 1954. 165 p. (MLRA 8:1)

1. Moscow. Vsesoyuznyy nauchno-issledovatel'skiy institut zheleznodorozhnogo transporta.
(Railroads--Traffic) (Locomotives--Performance)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

ZABELLO, M.L., kandidat tekhnicheskikh nauk; MEZHOVA, R.V., inzhener; PEYSAKHZON, B.E., kandidat tekhnicheskikh nauk, redaktor; YUDZON, D.M., tekhnicheskiy redaktor.

Organizaing the transport of perishable goods. Trudy TSNII MPS no.93: 3-115 '54. (MIRA 8:6)
(Railroads--Freight) (Refrigerator cars)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PLATONOV, Aleksandr Il'ich, doktor tekhnicheskikh nauk; PEYSAKHSON, B.E., redaktor; VERINA, G.P., tekhnicheskiy redaktor.

[Interaction of operations in marshalling yards; theory, practice and calculations] Vzaimodeistvie protsessov na sortirovochnykh stantsiiakh; teoriia, praktika i rashchety. Moskva, Gos.transp. zhel-dor.izd-vo 1955. 223 p. (MLRA 8:11)

(Railroads--Making up trains)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

VEBER, I.R.; PEYSAKHZON, B.E., kand. tekhn. nauk, retsenzent; PERMINOV, A.S., inzh., retsenzent; ZABELLO, M.L., kand. tekhn. nauk, red.; BOBROVA, Ye.N., tekhn.red.

[Weight and speed of freight trains; potentials for their increase] Ves i skorost' gruzovykh poezdov; rezervy ikh povysheniia. Moskva, Transzheldorizdat, 1963. 99 p. (MIRA 17:2)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B. E.

DOBROSEL'SKIY, Konstantin Mikhaylovich, kandidat tekhnicheskikh nauk; NIKOLAYEV, Ivan Ivanovich, doktor tekhnicheskikh nauk; CHERNYSHEV, Mikhail Andreyevich, kandidat tekhnicheskikh nauk; SHILOVSKIY, Viktor Anatol'yevich, kandidat tekhnicheskikh nauk; NIKOLAYEV, I.I., professor, redaktor; PEYSAKHZON, B.E., kandidat tekhnicheskikh nauk, redaktor; VERINA, G.P., tekhnicheskiy redaktor

[A general railroad course] Obshchii kurs zheleznykh dorog. Pod obshchei red. I.I.Nikolaeva. Moskva, Gos. transp.zhel-dor. izd-vo, 1956. 382 p. (MLRA 10:2)

1. Chlen-korrespndent Akademii nauk SSSR (for Nikolaeyv, I.I., redaktor)
(Railroads--Management)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, B.E., kandidat tekhnicheskikh nauk.

Selection of weight and speed for freight trains using different types of traction. Tekh.zhel.der.15 no.4:9-13 Je '56.(MLRA 9:9)
(Railroads--Freight)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PRYSAKHZON, B.B.; GOLOVANOV, A.L., red.; BOBROVA, Ye.N., tekhn. red.

[Weight and speed of freight trains] Ves i skorost' gruzovykh poezdov. Moskva, Gos. transp. zhel-dor. izd-vo, 1957. 199 p. (Moscow. Vsesoiuznyi nauchno-issledovatel'skii institut zheleznodorozhnogo transporta. Trudy, no.141). (MIRA 10:12)
(Railroads--Freight)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B.E., kand. tekhn. nauk.

Establishing standards for vertical loads from rolling stock to be used in designing bridges. Vest. TSNII MPS 17 no.8:43-46 D '58. (MIRA 12:1)

(Railroads--Rolling stock) (Railroad bridges--Design)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

DEYEV, Vladimir Vladimirovich, kand.tekhn.nauk; PEYSAKHZON, B.E., kand. tekhn.nauk, red.; KHITROV, P.A., tekhn.red.

[Heavy trains; practices, theoretical analyses, and technical and economic efficiency] Tiazhelovesnye poezda; opyt, teoreticheskie razrabotki i tekhniko-ekonomicheskaia effektivnost'. Moskva, Gos.transp.zhel.-dor.izd-vo, 1959. 331 p. (MIRA 12:6)
(Railroads--Trains)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON B E

ZHAVORONKOV, I.I. [translator]; NEMUKHIN, V.P. [translator]; GRAMP, A.N. [translator]; SHTEYNBERG, A.D. [translator]; MADEYEVA, R.I. [translator]; KARPUSHINA, I.M. [translator]; PEYSAKHZON, B.E., kand.tekhn.nauk, otv.red.; VERINA, G.P., tekhn.red.

[World railroads; survey of the operation and equipment of railroads throughout the world] Zheleznye dorogi mira; obzor ekspluatatsionnoi raboty i tekhnicheskogo osnashcheniia zheleznykh dorog mira. Moskva, Gos.transp.zhel-dor.izd-vo, 1959. 587 p. (MIRA 13:2)

(Railroads)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

BARANOV, Abram Moiseyevich, kand.tekhn.nauk; BERNGARD, Konstantin Alekseyevich, doktor tekhn.nauk; MEL'NIK, Aleksandr Lukich, kand.tekhn.nauk; PEYSAKHZON, Boris Emanuilovich, kand.tekhn. nauk; AL'TERMAN, S.L., inzh., red.; KHITROV, P.A., tekhn.red.

[Organizing the train traffic on electrified lines] Organizatsiia dvizheniia poezdov na elektrifitsirovannykh liniiakh. Moskva, Vses.izdatel'sko-poligr.ob"edinenie M-va putei soobshcheniia, 1960. 222 p. (MIRA 13:5)
(Electric railroads--Traffic)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B.E., kand.tekhn.nauk

Calculating the required traffic capacity of railroads.
Vest. TSNII MPS 20 no.6:46-51 '61. (MIRA 14:10)
(Railroads—Traffic)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, B.E., kand. tekhn. nauk

Modeling of traction calculations for train operation. Vest. TSNII MPS 24 no.6:15-19 '65. (MIRA 18:9)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

TIMOSHKOV, Vladimir Mitrofanovich; BASOV, A.V., inzh., retsenzent; MIL'DVARF, M.D., inzh., retsenzent; PEYSAKHZON, B.E., kand. tekhn.nauk; MANYUKOV, G.S., inzh., red.; USENKO, L.A., tekhn. red.

[Organization of the operations of combined trains for lengthened haul distances] Organizatsiia raboty sbornykh poezdov pri udlinenii tiagovykh plech. Moskva, Transzheldorizdat, 1963. 89 p. (MIRA 16:4)
(Railroads--Management)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, I.

New trends in the planning, design, and construction of coke and coal chemicals plants in the United States and Canada. Koks i khim. no.10: 60-62 '62. (MIRA 16:9)

(United Statod—Coke industry)
(Canada—Coke industry)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

TAYTS, Ye.M., doktor tekhn. nauk; SHVARTS, S.A., kand. tekhn. nauk[deceased]; FEYSAKHZON, I.B., inzh.; GEL'FER, M.L., inzh.; DMITRIYENKO, M.T., inzh.; DORFMAN, G.A., inzh.; IZRAELIT, Ye.M., inzh.; KULAKOV, N.K., inzh.; KUSHLYANSKIY, B.S., inzh.; MEYKSON, L.V., inzh.[deceased]; LEONOV, A.S., inzh.; SHVARTS, G.A., inzh.; SHVARTSMAN, I.Ya., inzh.; YATSENKO, N.Ya., inzh.; BABIN, P.P., inzh.; KHANIN, I.M., doktor tekhn. nauk, prof., red.; KOZYREV, V.P., inzh., red.; KUPERMAN, P.I., inzh., red.; LGALOV, K.I., inzh., red.; LEYTES, V.A., inzh., red.; LERNER, B.Z., inzh., red.; POTAPOV, A.G., inzh., red.; SHELKOV, A.K., red.

[By-product coke industry worker's handbook in six volumes] Spravochnik koksokhimika v shesti tomakh. Moskva, Metallurgiia. Vol.2. 1965. 288 p. (MIRA 18:8)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON I. B.

CA

19

Modifications for silica refractory materials for coke ovens. I. B. Peisakhson. *Coke and Chem.* (U. S. S. R.) 1933, No. 9, 18-20.—A crit. discussion. First-class silica bricks should have a sp. gr. not higher than 2.38 and 2nd class 2.40.

A. Pestoff

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

Regenerative coke oven I. B. Persakhson Russ
[illegible] 395, July 31, 1937 Construction details

ASM-SLA METALLURGICAL LITERATURE CLASSIFICATION

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

21

Ca

Combined regenerative coke oven R. B. Mordukhovich, I. B. Peisakhson and I. F. Khalabuzar. Russ. 46,521 2, April 30, 1936. Construction details

ASM SLA METALLURGICAL LITERATURE CLASSIFICATION

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

CA

The influence of the construction of the interwall space of coke ovens on the yield of chemical products I. B. Prisakhson. *Coke and Chem.* (U. S. S. R.) 9, No. 3, 30-4 (1939); *Chem. Zentr.* **1939**, II, 3362. Since the temp. of the upper mass of gas in the operating coke oven has a marked influence on the quality and yield of chem. products, this temp. must be held as const. as possible and must not exceed 650-750°. The causes of a possible overheating of this region were investigated and some minor improvements in the construction of the Becker furnace are proposed. M. G. Moore

ASM-SLA METALLURGICAL LITERATURE CLASSIFICATION

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, I.B.; KULAKOV, N.K.

Achievements in the field of the designing of coking ovens. Koks i khim. no.11:23-29 '57. (MIRA 10:12)

1. Giprokoks.

(Coke ovens)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

Peysakhzon, I. B.

5(1) PHASE I BOOK EXPLOITATION SOV/2127

Koksokhimicheskoye proizvodstvo; sbornik statey (By-Product Coking Industry; Collection of Articles) Moscow, Metallurgizdat, 1959. 240 p. 2,500 copies printed.

Ed.: B. S. Filippov; Ed. of Publishing House: A. A. Revyakin; Tech. Ed.: P. G. Islent'yeva

PURPOSE: The book is intended for engineers and technicians in the by-product coking industry and in scientific research institutes. The book may also be used by students in secondary and higher technical schools.

COVERAGE: The articles in this collection on the by-product coking industry appeared originally either in the periodical Koks i khimiya (Coke and Chemistry) or in other publications during 1955-1958. The book discusses the development of raw-material reserves for coking, technology of the manufacture of coke, quality of coke and further enlargement of the number of chemical coking products obtained. Some articles are devoted to a new procedure for preparing and beneficiating coals, new methods for coking, and to the mechanization and automation of industrial processes. References accompany individual articles.

Gryaznov, N. S., I. M. Lazovskiy, and M. G. Pal'dbrin. [VUKhIN] The Basic Principle for Preparation of Coals for Coking by Crushing

Goporkov, V. Ya. [Candidate of Technical Sciences, UKhIN]. Beneficiation of Coking Coals in Heavy Media 76

Kaminskiy, V. S. [VNIIUgleobogashcheniye], and A. Z. Turovskiy [IGI AN SSSR]. Centrifugal Beneficiation of Coking Coals 92

Bidenko, V. Ye. [Gosplan SSSR]. Constancy of the Quality Indices of Blast-Furnace Coke 119

Peysakhzon, I. B., and N. K. Kulakov [Giprokoks]. Progress in Coke-Oven Construction 137

Filippov, B. S. [Candidate of Technical Sciences, Gosplan SSSR]. Improvement in the Operation and Lengthening of the Life of Coke Ovens 149

Virozub, I. V., A. I. Voloshin, and S. A. Shvarts. [Candidates of Technical Sciences, UKhIN]. Improvement of the Heating and Technological Regimes of Coke Ovens 156

Yerkin, L. I., L. I. Lobanova, and M. A. Bernatskaya [VUKhIN]. Coking of the Eastern Coals with the Use of Stamping 167

Lerner, R. Z. [Gosplan RSFSR]. Partial Mechanization and Automation in Coking Plants 183

Kashchenko, D. S. [Metallurgizdat], and S. A. Sazonov [Gosplan RSFSR] Ferro-Coke and Its Use in the Blast Furnace 197

Krol', V. L. [Magnitogorskiy metallurgicheskiy kombinat - Magnitogorsk Metallurgical Combine]. Methods of Increasing the 60-80 mm Fraction of Metallurgical Coke 212

Litvinenko, M. S., and I. M. Bosalevich [UKhIN]. Prospects of the Development of Processing Chemical Obtained in the By-Product Coking Industry in the USSR. During 1959-1965 227

Bosalevich, I. M. [UKhIN]. Progress in Developing a Larger Number of Primary Products in the Processing of Coal Tar 234

AVAILABLE: Library of Congress

Card 4/4

TM/mg
10-30-59

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

KOZYREV, V.P.; MOLODTSOV, I.G.; PEYSAKHZON, I.B.; PODZOLKOV, M.I.; TORYANIK, I.Kh.; FLORINSKIY, N.V.

Comments on the article of R.Z. Lerner "Changing the coke unit layout for considerable increase in the number of ovens per battery." Koks i khim. no.5:29-31 '57. (MIRA 10:5)

1. Gosudarstvennyy Institut po proyektirovaniyu predpriyatiy koksokhimicheskoy promyshlennosti.
(Coke ovens) (Lerner, R.Z.)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AUTHORS: Kozyrev, V.P., Molodtsov, I.G., Peysakhzon, I.B., 68-5-6/14
Podzolkov, M.I., Toryanik, I.Kh., and Florinskiy, N.V.

TITLE: On the paper by R.Z. Lerner "On changes of the composition of coke oven department in order to increase considerably the number of ovens in a battery". (K stat'e R.Z.Lernera "Ob izmenenii komponovki koksovogo tsekha dlya znachitel'nogo uvelicheniya chisla pechey v batareye".)

PERIODICAL: "Koks i Khimiya" (Coke and Chemistry), 1957, No.5, pp.29-31 (U.S.S.R.)

ABSTRACT: In the original paper, L.Z. Lerner proposed some changes in the composition of the coke oven department in order to increase the number of ovens in one battery to 100. Servicing of such a battery would be carried out by one set of coke oven machines. According to Lerner the proposed composition of the coke oven department: 4 batteries of 100 ovens each in comparison with the standard composition (65 ovens per battery) has the following advantages:- the number of personnel required will remain the same as for the standard battery but the labour productivity will increase by 64.2% and the capital expenditure will be 10-12% lower. The present authors consider that the advantages Lerner expects are unfounded. To prove this point the

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

On the paper by R.Z. Lerner "On changes of the composition of coke oven department in order to increase considerably the number of ovens in a battery". (Cont.) 68-5-6/14

authors quote labour requirements for the often practised separation of 2 batteries with 90-110 ovens into an independent unit (Table 1) and compare them with those stated by Lerner (Table 2). A similar comparison for the labour productivity of main coke oven craftsmen for 78-110 oven units and 61-69 units is given in Table 2. Very approximate calculations indicated that the capital expenditure will remain the same. The editorial office communicates that Lerner's paper was discussed during a special session of Glavkoks with the participation of Giprokoks. In view of the division of opinion Giprokoks was requested to design a coke oven department according to Lerner's proposals and to prepare a technical-economical comparison with the usual design. The final decision on the problem will be published in this journal. There are 3 tables.

ASSOCIATION: Giprokoks

AVAILABLE:

Card 2/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

VODNEV, G.G.; SHELKOV, A.K.; DIDENKO, V.Ye.; FILIPPOV, B.S.; TSAREV, M.N.; ZASHVARA, V.G.; LITVINENKO, M.S.; MEDVEDEV, E.P.; MOLODTSOV, I.G.; LGALOV, K.I.; RUBIN, P.G.; SAPOZHNIKOV, L.M.; TYUTYUNNIKOV, G.N.; DMITRIYEV, M.M.; LEYTES, V.A.; LERNER, B.Z.; MEDVEDEV, S.M.; REVYAKIN, A.A.; TAYCHER, M.M.; TSOGLIN, M.E.; DVORIN, S.S.; RAK, A.I.; OBUKHOVSKIY, Ya.M.; KOTKIN, A.M.; ARONOV, S.G.; VOLOSHIN, A.I.; VIROZUB, Ye.V.; SHVARTS, S.A.; GINSBURG, Ya.Ye.; KOLYANDR, L.Ya.; BELETSKAYA, A.F.; KUSHNEREVICH, N.R.; BRODOVICH, A.I.; NOSALEVICH, I.M.; SHTROMBERG, B.I.; MIROSHNICHENKO, A.M.; KOPELIOVICH, V.M.; TOPORKOV, V.Ya.; AFONIN, K.B.; GOFTMAN, M.V.; SEMENENKO, D.P.; IVANOV, Ye.B.; PEYSAKHZON, I.B.; KULAKOV, N.K.; IZRAELIT, E.M.; KVASHA, A.S.; KAFTAN, S.I.; CHERMNYKH, M.S.; SHAPIRO, A.I.; KHALABUZAR', G.S.; SEKT, P.Ye.; GABAY, L.I.; SMUL'SON, A.S.

Boris Iosifovich Kustov; obituary. Koks i khim. no.2:64 '55.(MLRA 9:3)
(Kustov, Boris Iosifovich, 1910-1955)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHSON, I.V.

Effect of a distorted spectrographic camera objective on the curvature of spectral lines. Opt.i spektr. 11 no.1:125-127 Jl '61. (MIRA 14:10)

(Spectrograph)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, L.B., kand.ekonom.nauk, dotsent

Using production cost norms for measuring the volume of production and labor productivity. Izv.vys.ucheb.zav.; tekh.leg.prom. no.1:21-27 '63. (MIRA 16:3)

1. Kiyevskiy tekhnologicheskiy institut legkoy promyshlennosti. Rekomendovana kafedroy ekonomiki promyshlennosti o organizatsii proizvodstva.
(Productivity accounting) (Costs, Industrial)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AFANAS'YEV, O.O. [Afanas'iev, O.O.]; GORVITS, S.M. [Horvits, S.M.]; IGNATOVA, L.P. [Ihnatova, L.P.]; KOTOV, M.P.; NOVIK, G.B. [Novyk, H.B.]; OHLOV, I.V.; PEYSAKHZON, L.B.; ROZENMAN, G.S. [Rozenman, H.S.]; SKATERNOY, V.A.; TSITRIN, L.I.; CHECHENEV, M.I. [Checheniev, M.I.]; SHOSTAK, S.I.; NAZARENKO, N., red.; GORKAVENKO, L. [Horkavenko, L.], tekhn.red.

[Light industry of the Ukraine] Lehka promyslovist' Ukrainy. Kyiv, Derzh.vyd-vo tekhn.lit-ry URSR, 1960. 197 p. (MIRA 14:4)

(Ukraine--Industries)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, L.B., kand.ekonomicheskikh nauk

Some potential savings of labor in the clothing industry. Izv. vys.ucheb.zav.; tekh.leg.prom. no.6:3-15 '60. (MIRA 14:1)

1. Kiyevskiy tekhnologicheskiy institut legkoy promyshlennosti. Rekomendovana kafedroy ekonomiki promyshlennosti i organizatsii proizvodstva.

(Clothing industry—Management)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, L.B., kand.ekonocheskikh nauk, dotsent; ALEKSEYEVA, L.L., kand. tekhn.nauk; MESEZHNIKOV, G.Sh., kand.ekon.nauk; BARANOV, V.F., inzh.; AFANAS'YEV, A.A., kand.tekhn.nauk, dotsent

Some potentialities for better use of time and equipment in cutting artificial leather in footwear enterprises. Izv.vys.ucheb.zav.; tekh.leg.prom. no.6:16-21 '60. (MIRA 14:1)

1. Kiyevskiy tekhnologicheskiy institut legkoy promyshlennosti. Rekomendovana kafedroy ekonomiki promyshlennosti i organizatsii proizvodstva.

(Shoe industry) (Leather, Artificial)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, L.B., kand.ekon.nauk dots.

Methods for measuring labor productivity in light industry. Report No.1. Izv.vys.ucheb.zav.; tekh.leg.prom. no.5:3-15 '59. (MIRA 13:4)

1. Kiyevskiy tekhnologicheskiy institut legkoy promyshlennosti. Rekomendovana kafedroy ekonomiki i organizatsii proizvodstva.
(Labor productivity)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AUTHORS: Peysakhzon, I.B., and Kulakov, N.K. 68-11-5/11

TITLE: Achievements in the Field of Design of Coke Ovens (Dostizheniya v oblasti konstruirovaniya koksovykh pechey)

PERIODICAL: Koks i Khimiya, 1957, No.11, pp. 23 - 29 (USSR)

ABSTRACT: The development of the Soviet design of coke ovens (Bekker type) is described in some detail. The first ovens of Soviet design were built in 1934. In 1945-1946, two types of ovens were established ПК-2К and ПВР. Up to 1951, the size of the ovens was standardized: width 407 mm, height 4 300 mm, length 13.12 m, the difference in width between pusher and coke side 50 mm. From 1951, the length was increased to 14.0[illegible] m. Coking period 14 to 15 hours. In 1955, both types of ovens were modernized. At present, the design of coke ovens is developing in two directions: complete revision of all dimension of the oven (width, height and length) towards their increase and improvement of heating systems and elements of ovens. A 77 oven battery with ovens 450 mm wide, 5 000 mm in height and 15.04 m long will soon be completed. Ovens for coking pitch for the production of electrode coke of Soviet design have already been operating satisfactorily for some years. Plant for dry quenching of coke of a bunker type with the production of steam

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

Achievements in the Field of Design of Coke Ovens. 68-11-5/21

of 40 atm. was developed and the construction of such plant was started. There are 4 figures.

ASSOCIATION: Giprokoks

AVAILABLE: Library of Congress

Card 2/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, L.B., kand.ekon.nauk

Indices for the production capacity of clothing plants. Izv. vys. ucheb. zav.; tekh.leg. prom. no.2:123-130 '58. (MIRA 11:6)

1.Kiyevskiy tekhnologicheskiy institut legkoy promyshlennosti.
(Clothing industry)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PRYSHCHEPA, L.B., kand.ekonomich.nauk, dotsent

Indices of the utilization of capital assets in light industry. Izv.vys.uchebn.zav.;tekh.lot.prom. no.4:3-10 '61. (MIRA 14:11)

1. Kiyevskiy tekhnolo icheskiy institut legkoy promyshlennosti. Rekomendovana kafedroy ekonomiki promyshlennosti i organizatsii proizvodstva.

(Industrial organization)
(Capital)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

NOVIK, G.B.; PEYSAKHZON, L.B.

Potentialities of a labor productivity increase in the Ukrainian clothing industry. Leg.prom.15 no.9:8-13 S '55. (MLRA 9:1)

1.Glavnyy inzhener Glavshveyproma Ministerstva promyshlennykh tovarov shirokogo potrebleniya USSR (for Novik).2.Dotsent Kiyevskogo tekhnologicheskogo instituta legkoy promyshlennosti (for Peysakhzon).
(Ukraine--Clothing industry)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSAKHZON, L.B., kand.ekonomicheskikh nauk, dotsent

Some problems of the measurement of labor productivity in light industry. Izv.vys.ucheb.zav.; tekh.leg.prom. no.5:3-16 '61. (MIRA 14:12)

1. Kiyevskiy tekhnologicheskiy institut legkoy promyshlennosti. Rekomendovana kafedroy ekonomiki promyshlennosti i organizatsii proizvodstva.

(Work measurement)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

RASHEVSKIY, A.N. [Rasheve'kyi, A.N.], inzh.; PEYSAKHZON, N.Ya. [Peisakhzon, N.IA.], inzh.

Mounted universal loader for DT-20 tractors. Mekh. sil'. hosp. 11 no.9:20-21 S '60. (MIRA 13:9)

1. Khar'kovskiy proyektno-tekhnologicheskiy eksperimental'nyy institut mashinostroyeniya.
(Loading and unloading)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

RASHEVSKIY, A.N., inzh.; PEYSAKHZON, N.Ya., inzh.

Universal mounted loader for the DT-20 tractor. Trakt. i sel'-khozmash. 30 no.8:32-33 Ag '60. (MIRA 13:8)
(Loading and unloading)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

ACC NR: AP6029989 SOURCE CODE: UR/0413/66/000/015/0194/0194

INVENTOR: Peysel', M. A.; Samoylov, Ye. I.; Malkin, Yu. A.

ORG: none

TITLE: Vibration damper for the front landing gear strut of an aircraft. Class 62, No. 184143

SOURCE: Izobret prom obraz tov zn, no. 15, 1966, 194

TOPIC TAGS: vibration damping, aircraft landing gear, airframe component

ABSTRACT: This Author Certificate introduces a vibration damper for the front landing gear strut of an aircraft containing a cylinder mounted on a stationary section of the strut and a piston containing a throttle valve, which is hinged to a rocker. For more dependable vibration damping in the front strut and better ground handling of an aircraft while the piston is in multistaged nonlinear motion, the piston is equipped with two pairs of rods. The rods form an articulated link in series between the piston rod and the movable controlled section of the strut and between themselves; the piston has an annular throttle aperture of variable cross-section. [SA]

SUB CODE: 01/ SUBM DATE: 10Oct64

Card 1/1 UDC: 629.135/138

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

SHIKINA, Ye.S.; MESHALOVA, V.N.; PEYSEL', S.G.; CHIRKOVA, O.O.

Experience in the production of antimeasles horse serums and gamma globulin. Trudy Len.inst.epid.i mikrobiol. 22:55-63 '61. (MIRA 16:2)

1. Iz virusologicheskoy laboratorii Leningradskogo instituta epidemiologii i mikrobiologii (rukovoditel' - chlen-korrespondent AMN SSSR prof. A.A. Smorodintsev) i immunologicheskoy laboratorii Leningradskogo instituta vaktsin i syvorotok (rukovoditel' - prof. A.V. Ponomarev).
(GAMMA GLOBULIN) (SERUM) (MEASLES)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

USSR/General Problems of Pathology - Cytotoxins U-1

Abs Jour : Ref Zhur - Biol., No. 18, 1958, 84773

Author : Peysel', Z. G.
Inst : Institutes of Vaccines and Sera of the Ministry of Health USSR
Title : Distribution of Cytotoxins between the Various Fractions of the Serum Proteins

Orig Pub : Materialy po obemeny opytom. Gl. Upr. in-tov vaktsin i syvorotok M-va zdravookhr. SSHR, 1956, 2-52, 213-217

Abstract : In two series of horse antireticular cytotoxic sera (ACS), studies were made of the distribution of the cytotoxins (C) between the different fractions. The ACS was fractionated by the methods of electrodialysis, of isoelectric precipitation with subsequent removal of the isostable globulins by salting with $(NH_4)_2SO_4$, and by means of sequential salting-out with $(NH_4)_2SO_4$. The C were associated with two different fractions of the isostable globulins, which

Card 1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

USSR / General Problems of Pathology. Immunity. U

Abs Jour: Ref Zhur-Biol., No 22, 1958, 102398.

Author : Peysel', Z. G.; Yarmolenko, A. G.; Vorob'yev, A. A.
Inst : Not given.
Title : The Influence of Nonspecific Stimuli on the Production of Diphtherial and Tetanus Antitoxin.

Orig Pub: Zh. mikrobiol., epidemiol. i immunobiol., No 2, 121-122. Feb '58

Abstract: Rabbits were immunized by diphtherial anatoxin. Prior to immunization, they had 0.0005 active units in 1 ml. After the 3rd immunization, both in those receiving pilocarpine (I;0.5 mg/kg) and in control rabbits, after a small decrease, the titer active unit reached the maximum (0.06 and 0.04) towards the 48th hour. With introduction

Card 1/2

16

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

AUTHORS: [redacted], G.P., Kormilitsyn N.S. 130-58-5-14/16

TITLE: On the Organisation of Product Quality Control in Southern Open-hearth and Bessemer Shops (Ob organizatsii kontrolya kachestva produktsii v martenovskikh i bessemerovskikh tsekhakh yuga)

PERIODICAL: Metallurg, 1958, Nr 5, pp 35 - 36 (USSR).

ABSTRACT: This is a contribution to the discussion of the organisation of product quality control started by the publication in "Metallurg", 1957, Nr 9 of the article by Inozemtsev, Sokol, Rysev, Tarasenkov and Zamyatin. The present authors show how existing organisations differ at the Makeyevka, Stalino, imeni Dzerzhinskiy, imeni Liebknekht and imeni Petrovskiy Works. They maintain that the functions of the quality control department had been expanded beyond their original bounds even though the qualifications of production personnel had greatly improved and that this undermines the authority and responsibilities of production personnel and has been an important source of unsatisfactory product quality. They give data for the above works to show that quality-control inspectors have often failed to prevent incorrect procedures and state that their qualifications are often inferior to that of production personnel in melting shops

Card1/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

130-58-5-14/16

On the Organisation of Product Quality Control in Southern Open-hearth and Bessemer Shops

(Stalino and Makeyevka Works). The authors consider quality control in open-hearth and bessemer shops in more detail again contrasting those at the different works and propose the following organisation: production personnel to be responsible for hot-metal quality and mixer charging, discharging and de-slagging; ingot-mould preparation-bay or casting bay personnel to be responsible for all operations in the preparation of bogies and bays; production personnel to have full responsibility for adhering to technological instructions in steel melting and the foreman himself to sign the certificate; teeming ladles, runners, teeming procedure to be the responsibility of the section head and teeming foreman who complete the appropriate sections of the certificate. The authors briefly discuss the functions of the works' laboratories whose staffs, they maintain, should be augmented by quality-control personnel made redundant by the new organisation.

ASSOCIATION: VNIIOCHERMET

Card 2/2

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSIK, M.I.

Geology, and oil and gas potentials of the Polish-Lithuanian depression and adjacent areas. Trudy SGPK no.1:174-240 '60. (MIRA 13:10)
(Baltic Sea Region--Petroleum geology)
(Baltic Sea Region--Gas, Natural--Geology)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSIK, M.I.; STANKEVICH, L.I.; YAROSHENKO, V.N.

State of underground gas storage in the Leningrad industrial area. Trudy SGPK no.3:103-124 '62. (MIRA 15:10)
(Leningrad region—Gas, Natural—Storage)
(Prospecting)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

LYUTKEVICH, Ye.M.; PEYSIK, M.I.

The northern part of the Russian Platform. Trudy VNIGRI no.1 (MIRA 10:9)
'57.

(Russian Platform--Geology)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

LYUTKEVICH, Ye.M.; PEYSIK, M.I.

Oil- and gas-bearing prospects of the northern and northwestern parts of the Russian Platform. Trudy VNIGRI no.111:5-28 '57. (MIRA 11:6)
(Russian Platform--Petroleum geology)
(Russian Platform--Gas, Natural--Geology)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

LYUTKEVICH, Ye.M.; PEYSIK, M.I.

The northwestern part of the Russian Platform. Trudy VNIGRI no.101:89-140 '57. (MIRA 10:[illegible])

(Russian Platform--Geology)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"

"APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8

PEYSIK, M. I.

Peysik, M. I. "Problems of the method of structural mapping of drilling," Razvedka nedr, 1948, No. 6, p. 23-29

SO: U-3264, 10 April 1953, (Letopis 'Zhurnal 'nykh Statey, no. 3, 1949)

APPROVED FOR RELEASE: 06/15/2000 CIA-RDP86-00513R001240720007-8"