Declassified in Part - Sanitized Copy Approved for Re STANDARD FORM NO. 64	elease 2012/02/16 : CIA-RDP78-03424A001200020005-3
Office Memorandum	• UNITED STATES GOVERNMENT
TO : Chief, R&D Branch	DATE: 3 February 1959
FROM : Chief, R&D Laboratory	BOR 30 REV CAR 0105 0 27 010956 BRIE BORT 033 CRI 56 20 02 BRIE BLADS M REV 3 201 56
SUBJECT: Final KE-6 Keyer Tests	GRIE SLADS M LARC 3 CONSTRUCT JUST 22 CIRCUIV 2010 CREET CONST
	escribes the results of the final
electrical and mechanical te	ests conducted on the KE-6 Keyer, 25X1
	[.] 25X1
Attachment: A&A Report No. 182-C (Part	IV) ORIGINAL CL BY 235979 \Box DECL P REVW ON $20/0$ EXT BYND 6 YRS BY SHAPE REASON 30 30

CONFIDENTIAL

Declassified in Part - Sanitized Copy Approved for Release 2012/02/16 : CIA-RDP78-03424A001200020005-3



. . .'

A&A Report No. 182-C (Part IV)

Project No. 2004-144

3 February 1959

FINAL KE-6 ELECTRICAL AND MECHANICAL TEST RESULTS ANALYSIS AND APPRAISAL

1. INTRODUCTION

One KE-6 was delivered to the R&D Laboratory for final tests. Previous to this date, the unit had been returned to the manufacturer for rework to eliminate several electrical and mechanical deficiencies.

2. ELECTRICAL TEST

The keyer performed during the electrical test as follows:

- (a) The voltage applied to the motor input terminals is 5.2 volts, DC.
- (b) The keyer operated satisfactorily during the keying test. All characters were transmitted correctly. The keyer did not exhibit evidence of incorrect keying when the keyer buttons were not fully depressed.

3. KEYER CODE

The keyer transmits the following International Morse Code letters when the specified numbered buttons are depressed:

Keyer Button	International Morse Code
1	А
2	N
3	U
4	R
5	K
6	D
7	L
8	С
9	X
10	F
11	AA

CONFIDENTIAL

Declassified in Part - Sanitized Copy Approved for Release 2012/02/16 : CIA-RDP78-03424A001200020005-3

ر Declassified in Part - Sanitized Copy Approved for Release 2012/02/16 : CIA-RDP78-03424A001200020005-3 توجه 2

منسو در م

CONFIDENTIAL

4. MECHANICAL TEST

The manufacturer has improved the mechanical features of the keyer as follows:

- (a) A cable clamp has been installed in the keyer to secure the keyer cable.
- (b) The collector ring contact tip has been silver plated.
- (c) The individual segment pin contacts beneath each key button have been raised above the height of the common contacts. This mechanical improvement eliminates the possibility of transmitting incorrect characters when the key is depressed.

5. CONCLUSIONS AND RECOMMENDATIONS

The KE-6 Keyer is considered to be a satisfactory device. No specific recommendations are given.

