

6 PCS OSC. SEUS ETAROID RS-6 XMTN MOP. RA. TAN 6 4-4-5V
Eb-400 - 1N45E Ra=73Ω

f.	I _{tot}	I _p	E _g	I _a	P _i	P _o	Eff
3 I	72	56	18	330	22.4	7.95	35.5
6 I	71	54	26	386	21.6	10.9	50.5
6 II	71	54	22	380	21.6	10.55	48.5
7 I	68	52	26	386	20.8	10.9	52.4
7 I	70	53	15	325	21.2	7.7	36.7
8 I	76	61	14	335	24.4	8.2	33.6
8 II	68	52	10	322	20.8	7.56	36.4
8 III	70	53	6	318	21.2	7.36	34.8
9 I	76	59	14	340	23.6	8.44	35.9
9 II	76	60	10	340	24.0	8.44	35.0
9 III	70	53	5	310	21.2	7.0	33.0
12 II	74	58	9	355	23.2	9.19	39.6
14 II	71	54	8	360	21.6	9.45	43.7
16 II	70	53	5	345	21.2	8.66	40.8
16 III	72	56	15	315	22.4	7.25	32.4
		Ra = 600Ω					
3 I	72	56	18	120	22.4	8.65	38.6
6 I	73	57	25	145	22.8	12.6	55.5
6 II	73	57	20	140	22.8	11.8	51.8
7 I	73	57	24	145	22.8	12.6	55.5
7 I	72	56	14	122	22.4	8.94	39.9
8 I	71	54	15	126	21.6	9.54	44.1
8 II	72	55	9	122	22.0	8.94	40.6
8 III	72	56	5.5	120	22.4	8.65	38.6
9 I	71	54	15	130	21.6	10.15	47.0
9 II	71	54	11	128	21.6	9.84	45.6
9 III	73	57	3	120	22.8	8.65	38.0
11 II	71	54	9	130	21.6	10.15	47.0
14 II	71	54	7	132	21.6	10.45	48.5
16 II	73	57	5.5	123	22.8	9.07	39.9
16 III	76	59	5	112	23.6	7.52	31.8

4-4-82

ABOVE READINGS AFTER REWORKING.
NB. P. A TANK AND ADJUSTING TAP.