

**TOP SECRET**

Approved For Release 2000/08/31 : CIA-RDP78B04767A000300050018-3

**CORONA**

25X1A  
██████████

11 October 1968

Copy 1

MEMORANDUM FOR: See Distribution

SUBJECT: Mission 1105 Flight Plan

25X1A 4  REFERENCE: ██████████ Dated 9 August 1968

1. The purpose of this memorandum is to re-state the flight plan of Mission 1105. The projected flight plan of this and other upcoming missions was originally disseminated to the addressees through the above referenced memorandum.

25X1D

2. KH-4B, Mission 1105, ██████████ will be configured in the following manner:

a. There will be no Dual Improved Stellar Index Camera (DISIC) on this mission. All vehicle/camera attitude information will be derived from nominal values and horizon imagery.

b. SO-380, ultra thin base (UTB) film will constitute the primary film load of both panoramic cameras. The use of UTB results in a film load increase of approximately fifty percent. There will be approximately 48,000 feet of primary camera film compared to the normal 32,000 feet of 3404.


c. The use of UTB film necessitated a change in the film roller configuration (for this mission only) which resulted in an increase in the format length. However, there has been no film metering modification. Therefore, there will be image overlapping between every second panoramic camera frame and horizon image pair. The overlap will be approximately 0.25 inch and will involve the bonus area (out-of-focus) of the panoramic camera photography and the terrain side of the horizon imagery. The NPIC component responsible for determining attitude from the horizon photography, has concluded that the overlap will render the attitude solution weaker but will not constitute a serious degradation.

**CORONA**

Approved For Release 2000/08/31 : CIA-RDP78B04767A000300050018-3

**TOP SECRET**

25X1A  
██████████



SUBJECT: Mission 1105 Flight Plan

d. There will be 500 feet of SO-121 Ektachrome, tri-pack reversal color film exposed during the mission. It will constitute the last 500 feet of the aft panoramic camera film load and will be exposed in stereo with the forward camera black and white record. The SO-380 and SO-121 film thickness difference will result in an estimated 300-500 feet of SO-380 forward camera film available for monoscopic coverage. To alleviate an abrupt film thickness change in the camera system, a 50 foot section of film type 3404 (standard thin base) film will be spliced between the SO-380 and the SO-121 (standard base) films.

e. A third generation Petzval lens will be used in the forward camera and a second generation Petzval in the aft. The difference in lens design should result in a significantly better product from the forward camera than from the aft. This is the same combination of lenses used on Mission 1104.

25X1A  
[REDACTED]

Chief, Applied Photo-Science Division,  
NPIC/TSSG

Distribution:

- Cy 1 - NPIC/TSSG/APSD 22538-8 / 450020
- 2 - NPIC/PPBS
- 3 - NPIC/IEG
- 4 - NPIC/PSG
- 5 - NPIC/TSSG/ARTS
- 6 - NPIC/TSSG/PPS
- 7 - NPIC/TSSG/ESD
- 8 - NPIC/TSSG/APSD chrono 10/68
- 9 - NPIC/TSSG/DED

NPIC/TSSG/APSD [REDACTED]:lms/3305 (11 Oct 68)

25X1A

**TOP SECRET**

25X1A

CONTROL NO. [REDACTED]

Cy 1

REFERRED TO OFFICE	RECEIVED			RELEASED		SEEN BY	
	SIGNATURE	DATE	TIME	DATE	TIME	NAME & OFFICE SYMBOL	DATE
NPIC/TSSG/APSD	(22538-8)						

Handle Via Indicated Controls

[REDACTED]

25X1A

Access to this document will be restricted to those persons cleared for the specific projects;

**CORONA**

.....

.....

**WARNING**

This document contains information affecting the national security of the United States within the meaning of the espionage laws U. S. Code Title 18, Sections 793 and 794. The law prohibits its transmission or the revelation of its contents in any manner to an unauthorized person, as well as its use in any manner prejudicial to the safety or interest of the United States or for the benefit of any foreign government to the detriment of the United States. It is to be seen only by personnel especially indoctrinated and authorized to receive information in the designated control channels. Its security must be maintained in accordance with regulations pertaining to [REDACTED] Control System.

25X1A

**TOP SECRET**

GROUP 1 Excluded from automatic downgrading and declassification

ROUTING SLIP

TAD		DATE	
FROM	TO	DATE	INITIALS
	CH/TSSG - for info.	10/18	JWC
	CH/TAD		
	DC/TAD		
	SEC/TAD		
	CH/IEB		
	DCh/IEB		
	CH/IEB/SEC I		
	CH/IEB SEC II		
	CH/ISAB		
	DCh/ISAB		
	CH/ISAB/PAS		
	CH/ISAB/DAS		
	CH/OAB		
	DC/OAB		
	FILE: 450020		

Please return to  
TAD  
a good piece!