

On the Prospects of Employing D.C. Transmission
in the USSR

105-58-5-20/28

covering reactive (idle) power are unfounded because the rectifier plant has a $\cos \varphi = 0.90 - 0.95$. Polovoy does not take power losses in compensation devices into account. He assumes the specific costs of the transformer plant of D.C. substations to amount to 36% of the substation costs. According to Teploelektroproyekt they amount to 26%, and according to the Institute for Direct Current and the All-Union Institute for Electrical Engineering - 17%. According to experience gathered in connection with the line Kashira hydraulic station - Moscow, and according to technical conditions the life of valves between two repairs amounts to 15 000 hours or two years and not one year.

2.) Criticism of the article by Mel'gunov. It is wrong to declare that the costs of D.C. - and A.C. substations including devices for the increase of stability are the same already at the present stage of transformer-engineering, that in the case of long-distance transmission no intermediate output is necessary, that by means of the mercury valve grids the intermediate substations can be reliably disconnected from the long distance line. Advantages and disadvantages of a D.C. line are enumerated.

Card 2/3

GARIF'YANOV, N.S.; AKSEL'ROD, M.M.

Magnetic resonance in some coals. Khim. i tekhn. topl. i masel
4 no.3:64-68 Mr '59. (MIRA 12:4)

1. Kazanskiy filial AN SSSR.
(Coal--Magnetic properties)

AKSEL'ROD, M.M.; KRYATKOVSKIY, V.M.

Technological and economic indices of d.c. power transmission
and its comparison to other modes of transporting power resources.
Izv. NIIPT no.6:92-111 '60. (MIRA 14:7)

(Electric power distribution—Direct current)
(Power resources—Transportation)

2
POSSE, A.V., GROYS, YE.S., ALEKIROV, M.M.

Electrical transmission of Direct Current, Central Siberia-Urals, and its
Technical-Economic Indices.

Report to be submitted for the Conference on Electrification of Siberia,
Development and unification of its power systems, 7-9 Dec. 61

AKSEL'ROD, M.M.; VIDGON, L.N.; ROKOTYAN, S.S.; TURETSKIY, V.Ye.

Comparison of the economic efficiency of d.c. power transmission
and transportation of gas to electric power plants. Izv. NIPT
no.8:20-31 '61. (MIRA 15:7)

(Electric power distribution--Costs)
(Gas, Natural--Transportation)

AKSEL'ROD, M.M.; ROKOTYAN, S.S.

Engineering and economic ~~indices~~ of d.c. power transmission lines
with intermediate power take-off. Elektroenergetika no.5:120-
128 '62. (MIRA 15:4)
(Electric power distribution--High tension)

TSIDIL'KOVSKIY, I.M.; SOKOLOV, V.I.; AKSEL'ROD, M.M.

Resistance of ~~semi~~metals in strong magnetic fields. Fiz. met. i
metalloved. 16 no.2:318-320 Ag '63. (MIRA 16:8)

1. Institut fiziki metallov AN SSSR.
(Antimony--Electric properties)
(Magnetic fields)

L 24772-65 EWT(1)/EPA(8)-2/EWT(m)/EWP(t)/EWP(b) Pt-10 IJP(c) JD

2. $\frac{1}{2} \times \frac{1}{2} = \frac{1}{4}$ (the probability of getting heads on both coins)

1. *Chlorophyll a* and *Chlorophyll b* were determined by the method of Lichtenthaler and Whistler (1973).

SECRET. For Official Use Only

[illegible]

ABSTRACT: The authors investigated the longitudinal and transverse magnetoresistance of PbTe at temperatures from 4.2 to 300 K. A new type of oscillation of the transverse magnetoresistance in a strong magnetic field was first predicted by Ehrenreich and Harlow (1961) and by Lifshitz (1962). In this paper the authors report on the first experimental observation of this effect in PbTe . The oscillations were first observed and is attributed to the Landau level oscillations.

Core 1/2

L 24772-65

ACCESSION NR: AP5003467

the electron takes place. The probability of such a scattering can
be comparable with the probability of a scattering of an electron

longitudinal and transverse magnetoresistances against the field are
discussed in light of the published data. "The authors thank G. I.
Kharus for a discussion of the measurement results." Orig. art.
has: 1 figure and 1 formula.

ASSOCIATION: Institut fiziki metallov AN SSSR, Sverdlovsk
Sverdlovsk AN SSSR

10/10/10
10/10/10

Card 2 2

L 10914-66 EWT(1)/EWP(t)/EWP(b) IJP(c) JD/WW/GG
 ACC NR: AP6002037 SOURCE CODE: GE/0030/65/012/002/0667/0678
 AUTHOR: Tsidilkovskii, I. M.; Akselrod, M. M.; Uritsky, S. I.
 ORG: Tsidilkovskii, Akselrod/ Institute of Metal Physics, Sverdlovsk /TsidiIkovskii,
 Uritsky/ Ural State University
 TITLE: Spin-magnetophonon resonance in semiconductors
 SOURCE: Physica status solidi, v. 12, no. 2, 1965, 667-678
 TOPIC TAGS: semiconductor, magnetoresistance, phonon, conduction electron, *electron spin, electron interaction, semiconducting material*
 ABSTRACT: A theory of spin-magnetophonon resonance is presented. The spin interaction of electrons with optical phonons is described by the introduction of vector and scalar potentials of the optical vibrational field. It is shown that the spin-magnetophonon resonance should cause a minimum in the longitudinal magnetoresistance. The experimental data for n-InSb and N-InAs are discussed on the basis of this theory. In experiments conducted on N-InSb, a maximum transverse magnetoresistance was observed at 82 kg. This peak corresponds to the spin-magnetophonon resonance. The g-factor for the conduction electrons calculated from this maximum is in good agreement with the theoretical value. A minimum in the longitudinal magnetoresistance observed at 24 kg was attributed to the combined magnetophonon and spin-magnetophonon resonance scattering. Orig. art. has: 17 formulas and 3 figures. [CS]
 SUB CODE: 20 / SUBM DATE: 05Jul65/ ORIG REF: 004/ OTH REF: 008/ ATD PRESS:
 Card 1/1 4170

L 44814-66 EWT(1)/EWT(m)/T/EWP(t)/ETI IJP(c) JD
 ACC NR: AP6032017 SOURCE CODE: UR/0386/66/004/006/0205/0208

AUTHOR: Aksel'rod, M. M.; Tsidil'kovskiy, I. M.
 ORG: Institute of Physics of Metals, Academy of Sciences SSSR (Institut fiziki metal-
 lov Akademii nauk SSSR)

TITLE: Spin magnetophonon and magnetophonon oscillations of magnetoresistance in
 n-InAs

SOURCE: Zhurnal eksperimental'noy i teoreticheskoy fiziki. Pis'ma v redaktsiyu.
 Prilozheniye, v. 4, no. 6, 1966, 205-208

TOPIC TAGS: phonon interaction, magnetoresistance, galvanomagnetic effect spin
 phonon interaction, spin resonance, indium compound, antimonide

ABSTRACT: This is a continuation of earlier work (Fiz. tverdogo tela v. 7, 316, 1965;
 Phys. Stat. Sol. v. 12, 667, 1965) on spin-magnetophonon resonance (SMR). It is shown
 that in n-InSb the results explain the observed minimum of the longitudinal magneto-
 resistance (ρ_{zz}), which is due either to SMR or to combined transitions. Investiga-
 tions of longitudinal magnetoresistance in single-crystal n-InAs with $n = 2.2 \times 10^{16}$
 cm^{-3} at 300K have shown that ρ_{zz} does indeed have a minimum located at 480 kG. If it
 is assumed that this minimum is due to SMR, then the value $|g_0| = 19$ obtained for the
 g-factor is in good agreement with theory. The authors investigated also the trans-
 verse magnetoresistance (ρ_{xx}) in the temperature interval 250 - 220K, and found that
 ρ_{xx} has a maximum at 76 kG, corresponding to MPR transitions. It is shown, however,
 that these transitions do not cause the minimum of ρ_{zz} observed at 78 kG. The maxi-

Card 1/2

AKSEL'ROD, N.M.

Industrial efficiency and the development of inventions in the Main Administration for the Supply of the National Economy with Petroleum Products of the Russian Soviet Federated Socialist Republic. Transp. i khran. nefti i neftprod. no.6:32-33 '64. (MIRA 17:9)

1. Glavnoye upravleniye po transportu i snabzheniyu nef't'yu i nefteproduktami RSFSR.

AKSEL'ROD, P.L., inzh.

Simple method of determining the heat losses of insulated overhead
pipelines. Teploenergetika 7 no.11:87-88 N '60. (MIRA 14:9)
(Steam pipes--Testing)

VLASOV, Sergey Afonas'yevich; ~~AKSEL'ROD~~, P.S., redaktor; SEREBRENNIKOVA, L.A.,
redaktor; MATUSEVICH, N.L., tekhnicheskiiy redaktor

[Bricklaying of hollow walls] Kolodtsevaia kladka sten. Moskva,
Vses. uchebno-pedagog. izd-vo Trudrezervizdat, 1956. 50 p. (MLRA 10:1)
(Bricklaying)

Aksel'rod, Polina Savel'yeva

MOSKATOV, Yevgeniy Petrovich; AKSEL'ROD, Polina Savel'yeva, inzh., nauchnyy red.; KONTSEVAYA, E.M., red.; OSTRIROV, N.S., tekhn.red.

[Do it yourself; collection of articles] Svoimi rukami; sbornik.
Moskva, Vses. uchebno-pedagog. izd-vo Trudrezervizdat, 1957. 192 p.
(Technology) (MIRA 11:3)

BRUYEVICH, N.G., akademik, otv. red.; AKSEL'ROD, P.S., red.

[Precision and reliability of automatically controlled
manufacture of machinery] O tochnosti i nadezhnosti v
avtomatizirovannom mashinostroenii. Moskva, Nauka, 1965.
137 p. (MIRA 18:4)

1. Gosudarstvennyy nauchno-issledovatel'skiy institut ma-
shinovedeniya.

AKSEL' ROD, R. S.

7

Rapid analysis of alloys of AMC type (aluminum, manganese, zinc). R. S. Aksel'rod and Kh. A. Raduts-kaya. *Zavodskaya Lab.* 13, 1137(1947).—The detection of Mn is best done by Feigl's spot test: the sample is treated with a drop of 20% NaOH, after 2-3 min. it is re-mooved by a filter paper which is treated with a drop of benzidine-AcOH soln. Blue color indicates Mn. The sample surface, if blackened by NaOH, indicates Duralumin; the Al-Mn alloys either show no change or are yellowed. If a sample can be dissolved (HCl-HNO₃-H₂SO₄ mixt.), a black ppt. indicates AK type alloy; in absence of black ppt., NH₄OH can be used to detect Cu, in case of Duralumin alloy.

G. M. Kosolapoff

AKSELROD, R. S.
^

Dec 50

USSR/Metals - Steel, Analysis

"Determination of Oxygen in Steel," R. S. Aksel-
rod, L. S. Tarasova, Dnepropetrovsk Plant for
Metallurgical Equipment

"Zavod Lab" No 12, pp 1494, 1495

Suggests better method for sampling molten steel
and describes detn of oxygen in steel by improved
Heurty method. Roasted residue was fused with 2-3
g potassium bisulfate and, after lixiviation and
electrolysis of soln with Hg cathode, detn was
photocolorimetric using color reaction with aluminon.

182T93

CAKSEL' ROD, R. S.

Rapid determination of moisture in plastics. R. S.
Aksel'rod, R. I. Genkina, and F. I. Yudelovich. *Zavod-
skaya Lab.* 16, 112(1950).—Heat the samples in weighed
crucibles with linseed oil or paraffin, so that 165° is
reached in 4-5 min.; keep at 165° for 3 min.
O. M. Kosolapoff

AKSEL'ROD, S.

Cell for the introduction of radioisotopes into the well.
Razved.i prom.geofiz. no.31:89-92 '59. (MIRA 13:4)
(Oil well logging, Radiation)

USANOVICH, M.; AKSEL'ROD, S.

Physicochemical study of the system Na^+ , Mg^{++} , Cl^- , SO_4^{--} , H_2O .
Part 2: Electric conductivity, viscosity, and density of the
ternary system Na^+ , Cl^- , SO_4^{--} , H_2O . Izv. AN Kazakh. SSR. Ser.
khim. no.1:3-14 '60. (MIRA 13:11)
(Systems (Chemistry)) (Salt) (Sodium sulfate)

AKSEL'ROD, S.B.

Determining flow characteristics of the "nozzle-damper" type
control system. Inform. sbor. TSNIIMF no.64. Tekh. ekspl. mor.
flota no.9:27-31 '61. (MIRA 16:6)
(Hydraulic control) (Marine gas turbines)

AKSEL'ROD, S.B.

Comparison of diagrams for marine gas trubine plants and controlled
pitch propellers. Trudy TSNIIMF 7 no.34:124-131 '61.

(Marine gas turbines)

(Propellers)

(MIRA 14:8)

S/752/61/000/038/001/001
A026/A126

AUTHOR: Aksel'rod, S.B.

TITLE: Approximate formula for evaluating the magnitude of the jet influence on the damper of the control mechanism type "nozzle-damper"

SOURCE: Tsentral'nyy nauchno-issledovatel'skiy institut morskogo flota. Trudy. no. 38, 1961. Tekhnicheskaya ekspluatatsiya sudovykh silovykh ustanovok

TITLE: The author develops the approximate formula for determining the power characteristics of the control mechanism when the regulating system uses an incompressible fluid as working substance. All previous investigations on this subject assumed a flow toward the damper, the incompressible fluids used being air, kerosene and AMG10 (AMG10) oil. However, for a large number of marine gas-turbine installations it is necessary to know the damper characteristics when the flow is directed away from the damper (Fig. 1). The fluid used for this particular investigation was diesel oil. The author finds the final formula (8) for the case of flow as shown in Fig. 1:

Card 1/2

AKSEL'ROD, S.B.

Approximate formula to evaluate the flow pressure on the valve
of a "nozzle - flap" type control system. Trudy TSNIMF
no.38:102-105 '61. (MIRA 15:9)
(Hydraulic control)

AKSEL'ROD, S.B.

Automatic regulation of starting arrangements of marine gas
turbine plants. Trudy TSNIIMF 8 no.44:40-45 '62.

(MIRA 16:1)

(Marine gas turbines)

(Automatic control)

AKSEL'ROD, S.B.

Pulse slection for an antipumping regulator of a marine gas
turbine plant. Trudy TSNIIMF 3 no.44:72-78 '62. (MIRA 16:1)
(Marine gas turbines--Safety appliances)
(Governors (Machinery))

AKSEL'ROD, S.B.

Determining the efficiency of marine gas turbine compressors in
operation. Inform. sbor. TSNIIMF no.94 Tekh. ekspl. mor.flota
no.21:56-60 '63. (MIRA 17:4)

AKSEI'ROD, S.B.

Effect of the stability of equilibrium regimes of marine gas
turbines driving controllable pitch propellers on the selection
of the idling parameters. Trudy TSNIIMF no.58:65-75 '64.
(MIRA 18:8)

L 5181-66

ACC NR: AP5022032

SOURCE CODE: UR/0286/65/000/014/0100/0100

AUTHOR: Aksel'rod, S. B.

ORG: none

TITLE: A starting regulator for a gas turbine installation. Class 46, No. 173073

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 14, 1965, 100

TOPIC TAGS: gas turbine, turbine compressor, turbine design

ABSTRACT: This Author Certificate presents a starting regulator of a gas turbine installation. The regulator contains pressure pickup tubes before and after the compressor (before and after throttle socket in the air duct) and a directing member activated by a computing device when the correlation of pressures corresponds to the extremes of pumping (see Fig. 1). To improve the performance, the computing device is made in the form of a chamber connected to the pressure pickup tube behind the throttle socket. The tube carries three nipples. One of these is connected to the pressure pickup tube behind the compressor, the other to the pressure tube in front of the throttle socket, and the third serves as the re-

Card 1/2

UDC: 621.438-522.6

09010721

L 5181-66

ACC NR: AP5022032




Fig. 1. 1- pressure pickup tube behind the compressor; 2- same, at the intake of the compressor before the throttle socket; 3- same, after the throttle socket; 4- directing member; 5- computing device chamber; 6- nipples; 7- compressor; 8- throttle socket

ceiving nipple for transmitting the signal from the computing device to the directing member. Orig. art. has: 1 figure.

SUB CODE: PR/

SUBM DATE: 18Nov63/

ORIG REF: 000/

OTH REF: 000

Card 2/2 *hd*

AKSEL'ROD, Solomon L'vovich

N/5
850.11
.A3

Sportivnyye sorevnovaniye v kollektive fizicheskoy kul'tury (Sports competitions in the physical culture group) Moskva, Fizkul'tura i Sport, 1956.
126 p. tables.

AKSEL'ROD, S.^{L.}, zasluzhenny master sporta; KIR'YAKOV, Yu.

Callisthenics in industry. Okh.truda i sots.strakh. no.1:54-55
Ja '60. (MIRA 13:5)

(Callisthenics) (Industrial hygiene)

AKSEL'ROD, Solomon Moiseyevich; BERMAN, Mark Mikhaylovich; VINOGRAY,
Lazar' Il'ich; GOL'DZAND, Samuil Shlemovich; DUGIN, Yakov
Sergeyevich; DULEPOV, Konstantin Vasil'yevich; KALUGA, Ivan
Ivanovich; LERNER, Yefim L'vovich; LUTSKIY, Moisey Leybovich;
PILETSKIY, Vladimir Kirillovich; SADOWNIKOV, Petr Pavlovich;
SHIYAMOVICH, Abram Aronovich; VASIL'YEV, B.A., red.; SOBOLEV,
Ye.M., tekhn. red.

[Problems of radio engineering and radar] Zadachnik po radiotekhnike i radiolokatsii. [By] S.M. Aksel'rod i dr. Moskva, Gosenergo-izdat, 1962. 414 p. (MIRA 15:12)

(Radio) (Radar)

AKSEL'ROD, S.M.

Instrument for repelling magnetic points. Razved.i prom.geofiz.
no.12:43-50 '55. (MIRA 9:7)
(Magnetic measurements) (Oil well logging)

AKSEL'ROD, S. M.

"Radioactive Isotopes Used in Surveying Azerbaydzhan Oil Wells," Utilization
Of Radioactive Isotopes & Emanations in the Petroleum Industry (Symposium), Min.
Petroleum Industry USSR, 1957.

Results of the Joint Session of the Technical Council of Min. off the Petroleum
Industry USSR and Soviet Sci. and Technical Association, Moscow 14-19 Mar 1956.

AKSEL'ROD, S.M.; PUTKARADZE, L.A.

Determining the absorption profile of injection wells by the
activated suspension method. Azerb. neft. khoz. 36 no.10:10-11
0 '57. (MIRA 11:2)

(Secondary recovery of oil)

AKSELROD, S.M., Cand Tech Sci—(diss) "Radioactive methods of ^{quality} ~~control~~ ^{the} ~~trolling the quality~~ of cementing ^(of petroleum) ~~oil~~ wells." Baku, 1958.

16 pp (Min of Higher Education USSR. Azerbaydshan Order of Labor
Red Banner Industrial Inst im K. Azizbekov), 100 copies (ML, 22-58, 107),

-75-

AKSEL'ROD, S.M.

3(5)

PHASE I BOOK EXPLOITATION

SOV/2819

Vsesoyuznyy nauchno-issledovatel'skiy institut geofizicheskikh metodov razvedki

Razvedochnaya i promyslovaya geofizika, vyp. 23 (Exploration and Industrial Geophysics, Nr 23) Moscow, Gostoptekhizdat, 1958. 77 p. (Series: Obmen proizvodstvennym opytom) Errata slip inserted. 4,000 copies printed.

Ed.: A.I. Bogdanov; Exec. Ed.: Ye.G. Pershina; Tech. Ed.: A.S. Polosina.

PURPOSE: This booklet is intended for geophysicists as well as engineering and technical personnel in the petroleum industry.

COVERAGE: This collection of articles describes new equipment and instruments used in the petroleum industry. Individual articles discuss the single-cable electronic thermometer and the magnetic logging locator. Regional exploration problems such as electrical sounding at sea, electrical survey in permafrost areas etc. are also treated. References accompany each article.

TABLE OF CONTENTS:

Datskevich, A.A. Magnetic Logging Locator

3

Aksel'rod, S.M. Single-Cable Electronic Thermometer
Card 1/2

16

AKSEL' ROD S.M.

3(5)	PHASE I BOOK EXPLOITATION	SOV/2821
	Vsesoyuznyy nauchno-issledovatel'skiy institut geofizicheskikh meto- dov razvedki	
	Razvedochnaya i promyslovaya geofizika, vyp. 24 (Exploration and In- dustrial Geophysics, No. 24, Moscow, Gosizdatkhizdat, 1958, 96 p. (Series: Obmen proizvodstvennykh opytom) 4,500 copies printed.	
	Ed.: M.K. Polshkov; Exec. Ed.: Ye. G. Perahina; Tech. Ed.: I.G. Fedotova.	
	PURPOSE: This booklet is intended for geophysicists as well as en- gineers and technicians engaged in geophysical work.	
	COVERAGE: This collection of articles discusses new methods of in- terpreting electrical logging, geoelectric and seismic data, and describes industrial logging instruments (cementometer, per- forator, etc.), and cementing made on older apparatus (e.g., a change in the design of a perforator for radioactive electric logging) are also discussed. References accompany each article.	
	Popov, Yu. N. Interpretation of Telluric Current Observations 17	
	Popov, Yu. N. Monogram for the Control of Angles in Constructing Vector Diagrams in the Telluric Current Method 22	
	Bordovsky, V.P. Computing Coefficients of Dipole Units in Cur- rent Logging 24	
	Beloserev, I.P. Gravity Effect of a Vertical Cylinder of Finite Dimensions 28	
	Molochnikov, Z.I. Evaluating the Character of Oil Saturation of Carbonaceous Reservoir Rocks Through Electrologging Data 34	
	Aksel'rod, S.M. Well Cementometer for Operation With a Single- Strand Cable 37	
	Zel'tman, F.A. Substituting the Inclinator ISh-3 and ISh-4 Inclometers Without Subsequent Rescaling 42	
	Gorbenko, L.A. New Perforators for Oil Wells 46	
	Katkov, G.N., and N.P. Sumerov. Automatic Hoist Switch-off for Large Cable Loads 56	
	Gorskii, Ya.Ye. Change in the Design of a High Voltage Trans- former in a Depth Appliance for Radioactive Logging 57	
	AVAILABLE: Library of Congress	
	Card 3/3	MS/MS 12-31-59

14(5)

SOV/112-59-5-9497

Translation from: Referativnyy zhurnal. Elektrotehnika, 1959, Nr 5,
pp 148-149 (USSR)

AUTHOR: Aksel'rod, S. M.

TITLE: Instrument for Checking Cement Distribution Around a Column

PERIODICAL: Prikl. geofizika, Nr 18, 1958, pp 210-231

ABSTRACT: Until recently, the quality control of cementing was restricted to determining the height of cement outside the casing. The height of cementing was determined on the basis of a temperature curve taken 18-40 hours after cementing had been finished. This method has a number of serious disadvantages, and for that reason a radioactive measurement method has been used during recent years. This method includes activating the mortar by a radioactive isotope. As the intensity of gamma-radiation is a direct function of the quantity of cement, a notion can be derived from a gamma-radiation curve about the distribution. The activated mortar can also aid in determining

Card 1/3

SOV/112-59-5-9497

Instrument for Checking Cement Distribution Around a Column

the quality of cementing. After the cementation has been completed, a probe with a cylindrical screen and a longitudinal slit is lowered into a drill hole. By turning the probe, a gamma-intensity curve can be plotted against the turning angle of the screen. This curve characterizes the variation of cement-layer thickness around the hole. Irregularity of cement distribution over the cross-section of the hole, which corresponds to the offset of the column axis with regard to the hole axis, is characterized by the difference between the maximum and minimum values of the curve. The instrument sensitivity to variations in the cement-layer thickness is characterized by the ratio $I_{\max}/I_{\min}$, which depends, other things being equal, on the ratio of the total attenuation of gamma-radiation to the useful gamma-radiation; the latter values depend on the screen parameters (wall thickness, slit angle). The deep probe intended for determining the cement-layer thickness is referred to as a "cementometer." The cementometer comprises: a gamma-radiation indicator,

Card 2/3

SOV/112-59-5-9497

Instrument for Checking Cement Distribution Around a Column

power supply for electric motor that drives the slit screen, and a set of contacts. The gamma-radiation indicator is similar to a radioactive-logging probe. The most favorable results come about when the screen thickness is the greatest possible for a given size of the probe. With a probe about 110 mm diameter, the optimum slit angle is 75° for 1.2 mev gamma-radiation and 30° for 0.65 mev. Isotopes with a monochromatic gamma-radiation are most suitable for cement activation. Isotopes with a compound gamma-radiation spectrum make processing of the cement-distribution curves difficult. Fifteen illustrations. Bibliography: 5 items.

A.A.R.

Card 3/3

AKSEL'ROD, S.M.

Electronic thermometer with a single-core cable. Razved. i prom.
geofiz. no.23:16-19 '58. (MIRA 11:12)
(Thermometers) (Logging (Geology)--Equipment and supplies)

AKSEL'ROD, S.M.

Cement meter for work with a single-core cable. Razved i prem.
geofiz. no.24:37-42 '58. (MIRA 11:12)
(Oil well logging, Radiation--Equipment and supplies)

AKS & LTR, D, S.M.

PHASE I BOOK EXPLOITATION

**Источники геофизики; сборник статей по спутниковой радиоактивной изучению
и изотопов в геологии нефти (Nuclear Geophysics; Collection of Articles on
the Use of Radioactive Radiation and Isotopes in Petroleum Geology) Moscow,
Geostroyizdat, 1959. 370 p. Errors slip inserted. 1,000 copies printed.**

Ed.: V.A. Alekseyev, Professor, Doctor of Geological and Mineralogical Sciences;
Exec. Ed.: A.P. Molantarov; Tech. Ed.: A.S. Polovina.

PURPOSE: This book is intended for petroleum geologists, geophysicists and scientists engaged in geological research who are interested in radiometric techniques of petroleum prospecting.

CONTENTS. The collection contains 28 articles compiled by staff members and specialists of the Institute of Geology and Geophysics of the Petroleum Academy of Sciences USSR, the Laboratory for Radiometric Analysis of the All-Union Scientific Research Institute of Geophysics, and the heads of councils for planning research projects for petroleum enterprises. The articles treat new material on radiometric surveying in petroleum geology, describe radiometric instruments (counters, etc.) for registering neutrons and gamma rays, give the results of research with models of rock strata, introduce gamma-rays of rock samples from interpretation of radiometricity in the analysis of rock samples from petroleum-survey bore holes, etc. Problems of holes are reviewed. The results of studies in the accumulation of tritium in tracing the movement of water in a stratum are presented. Finally, a new method of surveying based on measuring the radiometricity of the surface of a prospective petroleum deposit is described. No parallels are mentioned. References accompany each article.

Abel, Rod, S. M. Mapping Petroleum-Water Surfaces of Contact in Aerobaydabas Oil Fields by the Method of Induced Radioactivity of Sodium

BEVANOY, E.A. Possibility of the Method of Induced Radioactivity for Quantitative Evaluation of the Petrologic Capacity and Other Characteristics of Strata

Blankens, T.E. The Effectiveness of the Methods of Induced Radioactivity of Sodium and Chlorine to Compute the Oil- and Water-Bearing Capacity of Devonian Sandstones

Barov, B.M., G.M. Darvov, F.Yu. Denisik, B.P. Odintsov, and V.O. Sotchenitskaya. Utilization of Epithermal Emissions in the Neutron-Neutron Method (NNM) of Evaluating the Porosity of Sand and Carbonate Collections.

Labayev, F.A., S.A. Denilskii, I.V. Miller, and V.P. Odolotov. The Use of Gamma-Ray Spectrometry to Investigate Bone Moles 174

Sh. A. Gerasimov, Gamma-Ray Spectroscopy of Natural and Artificial Radioactive Isotopes Under Bare Hole Conditions

Monator, V.F., S.A. Denisik, and Yu. A. Shmel'sovich. Determination of the Point of Water-Neutron Contact From Data Obtained Using the Neutron Gamma Method With Scintillation Counters (BSP-15) and the Neutron-Neutron Method Based on Thermal Neutrons (BSP-1).

unkov, Ye. B. Separation of the Radiation of Different Elements During the Investigation of Petroleum-Burvy Bore Holes by the Method of Induced Radioactivity of Sodium and Chlorine

orkin, I. L., and N. A. Ryzayev. The Use of Scintillation Counters to Count Slow Neutrons in Petroleum Survey Bore Holes

197	198
199	201
203	205
207	209
211	213
215	217
219	221
223	225
227	229
231	233
235	237
239	241
243	245
247	249
251	253
255	257
259	261
263	265
267	269
271	273
275	277
279	281
283	285
287	289
291	293
295	297
299	301
303	305
307	309
311	313
315	317
319	321
323	325
327	329
331	333
335	337
339	341
343	345
347	349
351	353
355	357
359	361
363	365
367	369
371	373
375	377
379	381
383	385
387	389
391	393
395	397
399	401
403	405
407	409
411	413
415	417
419	421
423	425
427	429
431	433
435	437
439	441
443	445
447	449
451	453
455	457
459	461
463	465
467	469
471	473
475	477
479	481
483	485
487	489
491	493
495	497
499	501
503	505
507	509
511	513
515	517
519	521
523	525
527	529
531	533
535	537
539	541
543	545
547	549
551	553
555	557
559	561
563	565
567	569
571	573
575	577
579	581
583	585
587	589
591	593
595	597
599	601
603	605
607	609
611	613
615	617
619	621
623	625
627	629
631	633
635	637
639	641
643	645
647	649
651	653
655	657
659	661
663	665
667	669
671	673
675	677
679	681
683	685
687	689
691	693
695	697
699	701
703	705
707	709
711	713
715	717
719	721
723	725
727	729
731	733
735	737
739	741
743	745
747	749
751	753
755	757
759	761
763	765
767	769
771	773
775	777
779	781
783	785
787	789
791	793
795	797
799	801
803	805
807	809
811	813
815	817
819	821
823	825
827	829
831	833
835	837
839	841
843	845
847	849
851	853
855	857
859	861
863	865
867	869
871	873
875	877
879	881
883	885
887	889
891	893
895	897
899	901
903	905
907	909
911	913
915	917
919	921
923	925
927	929
931	933
935	937
939	941
943	945
947	949
951	953
955	957
959	961
963	965
967	969
971	973
975	977
979	981
983	985
987	989
991	993
995	997
999	1001

dev. O.V. Development of New Types of Radiocentric Apparatus for Use in
Petroleum Survey Operations

222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

keevy, P. A., N. I. Yermakov, and V. A. Filonov. The Problem of Radium and Uranium Content in Oil-Field Waters. *Tr. Vsesoyuzn. nauch. issled. inst. khim. i tekhn. neftepromyshl.* 1954, No. 1, p. 105.

Smakov, V.Y., A.I. Laubenbach, M.O. Ovanesov, Yu. A. Romanov, and Stoksyeva. Results of Yantrol'.

Results of Investigations of Natural Gamma Fields in Oil-bearing Regions, Using Aerial and Ground Radiometric Survey Methods

AUTHOR: Aksel'rod, S.M. and Chernyak, G.Ya. SCV/132-59-1-7/16
TITLE: The Dielectric Coring of Bore Holes (Dielektricheskiy karotazh skvezhin)
PERIODICAL: Razvedka i okhrana nedr, 1959, Nr 1, pp 28-30 (USSR)
ABSTRACT: VNII of VODGEO and the Azneftegeofizika Trust investigated the possibilities of using the dielectrical properties of rocks - dielectrical penetrability (ϵ) and dielectrical losses (ϵ'') - for the coring of the bore holes. The experimental dielectrical coring equipment, designed by these organizations and built by TsNIL of the Trust, consists of a device placed in the bore hole, and of a surface installation. The device in the hole contains a measuring generator of high frequency oscillations (frequency of 10 mc) with a specially-designed capacitor attached to its oscillatory circuit. The variation of the dielectrical penetrability of the rocks changes the capacity of the capacitor, which causes the change in the frequency of the generator and in the amplitude of the voltage in the circuit. At the same time, the variation of the dielectrical losses of rocks influences

Card 1/2

SOV/132-59-1-7/18

The Dielectric Coring of Bore Holes

the amplitude of the voltage between the ends of the oscillatory circuit, and to a certain degree, the frequency of the generator. Thus the frequency of the generator and the amplitude of the voltage on its oscillatory circuit are functions simultaneously of the dielectrical penetrability and of the dielectrical losses of rocks in the bore hole where the capacitor was placed. The frequency of the generator and the voltage on the circuit are sent up to the surface installation and registered as two curves. The analysis showed that these curves of the dielectrical coring have considerable differentiation and divide the whole cross-section of the bore hole into separate layers. There is one diagram.

ASSOCIATION: Trest Azneftegeofizika (The Azneftegeofizika Trust) VODGEO

Card 2/2

AKSEL'ROD, S.M.; GULIYEV, A.S.

Experimental induction logging apparatus. Azerb. neft. khoz. 38
no.8:12-13 Ag '59. (MIRA 13:2)
(Oil well logging, Electric)

AKSEL'ROD, S.M.; GADZHI-KASIMOV, A.S.; LISTENGARTEN, B.M.; PUTKARADZE, L.A.

Using the induced sodium activity method for determining the water-oil contact in the Balakhan'-Sabunchi-Ramany field (Oil Field Administration of the Lenin Petroleum Trust). Azerb.neft.khoz.
38 no.11:11-12 N '59. (MIRA 13:5)
(Apsheron Peninsula--Oil well logging, Radiation)

S/169/61/000/011/029/065
D228/D304

AUTHORS: Aksel'rod, S.M., and Putkaradze, L.A.

TITLE: Applying radioactive methods of well investigation in the oil industry of the Azerbaydzhan SSR

PERIODICAL: Referativnyy zhurnal, Geofizika, no. 11, 1961, 35, abstract 11A308 (V sb. Yadern. geofiz. pri poiskakh polezn. iskopayemykh, M., Gostoptekhizdat, 1960, 21-36)

TEXT: Gamma-ray logging (GL) and neutron gamma-ray logging (NGL) are included in the rational complex of commercial-geophysical investigations for all deposits. The high economic effect of the application of GL in wells of the old stock is pointed out. The data of GL and NGL are used in complex interpretation together with those of electric logging for appraising the oil- and gas-content of beds and, mainly, for distinguishing gas-bearing beds amongst petroliferous strata, as well as for dissecting the profile. The application of NGL for determining the porosity is impeded by the high content of clayey material in rocks of the productive series. An inverse relation between GL readings and the porosity, for whose

Card 1/3

S/169/61/000/011/029/065
D228/D304

Applying radioactive methods of ...

construction relative GL values and core data on the porosity were used, is noted in some formations. The curve's coefficient of correlation comprises 0.7. Similar relationships may be used only for separate horizons. The accuracy for determining the porosity from the data of GL does not exceed 25 - 30 %. The possibility of applying the method of neutron activation (NA) for sodium to strike off the position of water neutron logging (WNL) in strata with a stratal-water salinity of 70 - 120 g/l is established. The effect on WNL does not usually exceed 30 - 40 %. The influence of a number of well conditions on the striking off of WNL was experimentally investigated in models. It was shown that in water-filled holes of diameter 110 mm, with an unevenly cemented collar, the influence of the equipment's eccentricity does not exceed 3 - 3.5 %. The magnitude of the effect on WNL becomes greater when the salinity of a water-filled hole is increased. The moving of the device to the wall of the hole and the use of high- and low-speed counters somewhat increase the effectiveness of the WNL determination. NA is measured by low-speed counters in the interval between 15 and 22 hours after the end of the irradiation. A similar method is used, too, when

Card 2/3

AKSEL'ROD, S.M.; PUTKARADZE, L.A.

Calibration of apparatus used in radioactive logging. Razved. i
prom. geofiz. no.38:112-114 '60. (MIRA 14:3)
(Oil well logging, Radiation—Equipment and supplies)

AKSEL'ROD, S.M.

Calibration of an induction logging unit. Izv. vys. usheb.
zav.; neft' i gaz 3 no.5:19-25 '60. (MIRA 15:6)

1. Azerbaydzhanskiy institut nefti i khimii imeni
M. Azizbekova.

(Oil well logging, Electric)

ABRAMYAN, S.L.; AKSEL'ROD, S.M.; ALEKSEYEV, E.A.; AL'TSHEL', S.A. [deceased],
BESPALOV, D.F.; GADZHI-KASIMOV, A.S.; ZHILIN, K.A.; LISTENGARTEN, B.M.;
ODINOKOV, V.P.; PUTKARADZE, L.A.; SHIMELEVICH, Yu.S.

Neutron-neutron pulse method for investigating wells and results of
its use in the Balakhan'-Sabunchi-Ramany field. Azerb. neft. khoz.
39 no.11:9-13 N '60. (MIRA 13:12)
(Apsheron Peninsula—Oil well logging, Radiation)

AKSEL'ROD, S.M.

PHASE I BOOK EXPLOITATION SOV/5592

Vsesoyuznoye soveshchaniye po vnedreniyu radioaktivnykh izotopov i yadernykh izlucheniye v narodnom khozyaystve SSSR. Riga, 1960.

Radioaktivnyye izotopy i yadernyye izlucheniya v narodnom khozyaystve SSSR; trudy Vsesoyuznogo soveshchaniya 12 - 16 aprelya 1960 g. g. Riga, v 4 tomakh. t. 4: Poiski, razvedka i razrabotka poleznykh iskopayemykh (Radioactive Isotopes and Nuclear Radiation in the National Economy of the USSR; Transactions on the Symposium Held in Riga, April 12 - 16, 1960, in 4 volumes. v. 4: Prospecting, Surveying, and Mining of Mineral Deposits) Moscow, Gostoptekhizdat, 1961. 284 p. 3,640 copies printed.

Sponsoring Agency: Gosudarstvennyy nauchno-tekhnicheskyy komitet Soveta Ministrov SSSR. Gosudarstvennyy komitet Soveta Ministrov SSSR po ispol'zovaniyu atomnoy energii

Eds. (Title page): N. A. Petrov, L. I. Petrenko, and P. S. Savitskiy; ed. of this volume: M. A. Speranskiy; Scientific ed.: M. A. Speranskiy; Executive Eds.: N. N. Kuz'mina and A. G. Ionel';

Card 1/11

Radioactive Isotopes and Nuclear (Cont.)

SOV/5592

Tech. Ed.: A. S. Polosina.

PURPOSE : The book is intended for engineers and technicians dealing with the problems involved in the application of radioactive isotopes and nuclear radiation.

COVERAGE: This collection of 39 articles is Vol. 4 of the Transactions of the All-Union Conference of the Introduction of Radioactive Isotopes and Nuclear Reactions in the National Economy of the USSR. The Conference was called by the Gosudarstvennyy nauchno-tekhnicheskii komitet Sovet Ministrov SSSR (State Scientific-Technical Committee of the Council of Ministers of the USSR), Academy of Sciences USSR, Gosplan SSSR (State Planning Committee of the Council of Ministers of the USSR), Gosudarstvennyy komitet Soveta Ministrov SSSR po avtomatizatsii i mashinostroyeniyu (State Committee of the Council of Ministers of the USSR for Automation and Machine Building), and the Council of Ministers of the Latvian SSR. The reports summarized in this publication deal with the advantages, prospects, and

Card 2/11

Radioactive Isotopes and Nuclear (Cont.)

SOV/5592

development of radioactive methods used in prospecting, surveying, and mining of ores. Individual reports present the results of the latest scientific research on the development and improvement of the theory, methodology, and technology of radiometric investigations. Application of radioactive methods in the field of engineering geology, hydrology, and the control of ore enrichment processes is analyzed. No personalities are mentioned. There are no references.

TABLE OF CONTENTS:

Aleksyev, F. A. Present State and Future Prospects of Applying the Methods of Nuclear Geophysics in Prospecting, Surveying, and Mining of Minerals	5
Bulashevich, Yu. P., G. M. Voskoboynikov, and L. V. Muzyukin. Neutron and Gamma-Ray Logging at Ore and Coal Deposits	19
Gordeyev, Yu. I., A. A. Mukher, and D. M. Srebrodol'skiy. The	

Card 3/11

Radioactive Isotopes and Nuclear (Cont.)

SOV/5592

Khaydarov. Certain Methods for the Interpretation of the Complex Gamma Spectra in Analyzing the Activated Samples of Rocks 172

Yakubovich, A. L., and Ye. I. Laytsev. Plant of the "Neutron" Type and Its Possible Utilization for the Analysis of the Material Composition of Rocks 180

Yakubovich, A. L., and V. Yu. Zaleskiy. Roentgenoradiometric Method and Equipment for Accelerated Analysis of the Chemical Composition of a Substance 187

Narbutt, K. I., R. L. Barinskiy, and I. S. Smirnova. Application of Nuclear Radiation in Roentgenospectral Analysis 198

Abramyan, S. L., S. M. Aksel'rod, and L. A. Putkaradze. Application of Radioactive Isotopes and Nuclear Radiation for the Investigation of Boreholes in Azerbaydzhan 201

Shnurman, G. A. Experience With Radiometric Investigations

Card 8/11

LISTENGARTEN, Boris Moiseyevich; AKSEL'ROD, S.M., red.; SHTEYNGEL',
A.S., red.; MIRKISHEVA, S., tekhn. red.

[Practice of the Oil Field Administration of the Lenin
Petroleum Trust in using radioactive methods in oil-field
geology] Radioaktivnye metody v neftspromyslovoi geologii;
opyt NPU "Leninneft". Baku, Azerbaidzhanskoe gos. izd-vo,
1961. 150 p. (MIRA 15:2)
(Azerbaijan--Oil well logging, Radiation)

AKSEL'ROD, S.M.

Scale for induction logging curves. Izv. vys. ucheb. zav.; neft'
i gaz 4 no.3:23-26 '61. (MIRA 16:10)

1. Azerbaydzhanskiy institut nefti i khimii im. M.Azizbekova.

AKSEL'ROD, S.M.

Analysis of the operation of the induction logging tool while
adjusting to resonance the network of the receiving and generating
coils. Prikl.geofiz. no.30:206-214 '61. (MIRA 14:10)
(Electromagnetic prospecting)

AKSEL'ROD, S.M.; SOKHRANOV, N.N., nauchnyy red.; KRAVCHENKO, M.D.,
red.; BORUSHKO, T.I., red.izd-va; SHMAKOVA, T.M., tekhn.
red.

[High-frequency methods for studying boreholes; induction and
dielectric logging]Vysokochastotnye metody issledovaniia
skvazhin (induktsionnyi i dielektricheskii karotazh). Moskva,
Gosgeoltekhizdat, 1962. 31 p. (MIRA 16:2)
(Oil well logging, Electric)

AKSEL'ROD, S.M.; ORBELYAN, N.M.; SARKISOVA, Ye.A.

Charts for calculating the effect of the well and the permeability
zone on the results of measurements in inductive logging. Azerb.
neft.khoz. 41 no.7:12-14 J1 '62. (MIRA 1612)
(Azerbaijan—Oil well logging, Electric)

AKSEL'ROD, S.M.; DANEVICH, V.I.; MELIK-SHAKHNAZAROV, A.M.

Theory of nuclear magnetism logging. Izv. vys. ucheb. zav.;
neft' i gaz 6 no.4:93-98 '63. (MIRA 16:7)

1. Azerbaydzhanskiy institut nefti i khimii imeni Azizbekova.
(Oil well logging)

AKSEL'ROD, S.M.; AKHUNDOV, A.M.; TER-GRIGORYAN, Yu.N.

New method for determining the point at which the pipe is
frozen. Neft. khoz. 41 no. 11:14-18 N '63. (MIRA 17:7)

L 23058-65 EWT(1)/EWC-L/EWC(t)/EWC(t)-2/EWC(t) EWT(1)/EWC-L/EWC(t)/EWC(t)-2/EWC(t)

ACCESSION NR AP4039609

5 OCT 1964

SOURCE: AN AzerSSR. Izv. Seriya fiziko-tekhn. nauk (Fizmatmat. nauk)
[1964, no. 1, 1964, (p. 4)]

1. PIR TAGS: input impedance, antenna theory, space, antenna, antenna
impedance

ABSTRACT: The determination of the input impedance in the antenna theory has been solved for an emitter in vacuum, and therefore cannot be used for the analysis of the electrical parameters of a material medium in which the emitter is operating. The purpose of the present paper is the determination of the input impedance of a spatial vibrator in a given medium and the excitation of the vibrator in a material plane by a source of an external field of a given frequency and

Card 1/2

L 23058-65

ACCESSION NR: AP4039609

which is embedded in an infinite homogeneous and isotropic medium of given
conductivity and permittivity. The problem is to find the field in the
medium.

ASSOCIATION: None

SUBMITTED: 00

ENCL: 00

SUB CODE: EC

NR REF SOV: 000

OTHER: 000

Cord 2/2

AKSEL'ROD, S.M.; ISMAYLOVA, Kh.I.

Dielectrical properties of water-saturated rocks. Neftgaz.geol. i
geofiz. no.7:27-29 '65. (MIRA 13:8)

1. Trast "Azneftegeofizika".

L 27362-66 EWT(1)/FCC GW

ACC NR: AP6005276

SOURCE CODE: UR/0413/66/000/001/0009/0009

INVENTOR: Aksel'rod, S. M.; Danevich, V. I.; Ismaylov, A. Kh.; Melik-Shakhnazarov, A. M.

ORG: none

TITLE: A signal standard for nuclear magnetic coring equipment. Class 5, No. 177373

SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 1, 1966, 9

TOPIC TAGS: nuclear magnetic resonance, earth science instrument, earth magnetic field, prospecting


ABSTRACT: This Author's Certificate introduces a signal standard for nuclear magnetic coring equipment which may be connected to the measurement system in place of the pickup coil. The standard is independent of the direction of the terrestrial magnetic field with respect to the axis of the instrument and proportional to the intensity of this field. The device is made up of 3 identical toroids with mutually perpendicular axes. The internal cavities of these toroids are filled with the working substance.

UDC: 621.317.44
550.83

Card 1/2

L 27362-66

ACC NR: AP5005276



SUB CODE: 08/

SUBM DATE: 29Nov63

Card 2/2

ABASHINA, V.I.; AKSEL'ROD, S.S.; RUTKOVSKIY, G.M.; SMIRNOVA, K.A.

The SF-8 recording spectrophotometer. Zhur. prikl. spekt. 3
no. 2:182-186 Ag '65. (MIRA 18:12)

L 10411-67 FSS-2/EWT(1)/EWP(t)/EWT(m)/ETI IJP(c) DS/JD/HW
 ACC NR: AP6029881 SOURCE CODE: UR/0413/66/000/015/0043/0043 52

AUTHORS: Tomashevskiy, F. F.; Lamedman, E. M.; Aksel'rod, Sh. S.; Gryadinskaya, V. P.; Dubnova, A. L.; Rozovskiy, V. M.; Basharina, Yu. I.

ORG: none

TITLE: Nonlamellar negative electrode of an alkaline iron-nickel battery. Class 21, No. 184300 [announced by plant "Leninskaya Iskra" (Zavod "Leninskaya Iskra")]

SOURCE: Izobret prom obraz tov zn, no. 15, 1966, 43

TOPIC TAGS: electrode, battery, potassium compound, iron, nickel

ABSTRACT: This Author Certificate presents a nonlamellar negative electrode of an alkaline iron-nickel battery. After reducing the iron oxides free of impurities, the electrode contains 40--70% of metallic iron in its active volume. To simplify the technique of its preparation by eliminating the operation of fusing, the potassium base is added to iron oxides before their reduction. Specific weight of the potassium base is 1.40--1.48 g/cm³, and its amount is 0.5--5%.

SUB CODE: 10/ SUBM DATE: 10Sep65

Card 1/1

UDC: 621.355.8.035.222

AKSEL'ROD, V.A., inzhener; SMOLYAR, A.A., inzhener.

Self-unloading trailer D-258 of 12-15m³ capacity. Mekh.stroi 10 no.5:14-
19 My '53. (MLRA 6:6)

(Automobiles--Trailers)

TATARSKAYA, R.I.; ABROSIMOVA-AMEL'YANCHIK, N.M.; AKSEL'ROD, V.D.;
KORENYAKO, A.I.; VENKSTERN, T.V.; MIRZABEKOV, A.D.; BAYEV, A.A.

Guanylic ribonucleases of actinomycetes. Dokl. AN SSSR 157
no.3:725-728 J1 '64. (MIRA 17:7)

1. Institut radiatsionnoy i fiziko-khimicheskoy biologii AN
SSSR. Predstavleno akademikom V.A. Angel'gardtom.

AKSEI, ROD, V.D.; VENKSTERN, T.V.; BAYEV, A.A.

Ion-exchange chromatography of oligonucleotides in a ribonuclease hydrolyzate of s-RNA. Biokhimiia 30 no.5:999-1006 S-O '65. (MIRA 18:10)

1. Institut radiatsionnoy i fiziko-khimicheskoy biologii AN SSSR, Moskva.

ABROSIMOVA-AMEL'YANCHIK, N.M.; TATARSKAYA, R.I.; VENKSTERN, T.V.;
~~AKSEL'ROD, V.D.~~; BAYEV, A.A.

Specificity of guanyl ribonuclease from Actinomyces.
Biokhimiia 30 no.6:1269-1276 N-D '65. (MIRA 19:1)

1. Institut molekulyarnoy biologii AN SSSR, Moskva.
Submitted May 12, 1965.

AKSEL'ROD, V. S. - VILENKINA, A. M.

Factory Management

Competition for excellent accomplishment of each production operation. Leg. prom.
12 no. 7, 1952.

9. Monthly List of Russian Accessions, Library of Congress, November 195²₃, Uncl.

AKSEL'ROD, V.S.

Pressed samples of infrared spectroscopy. Opt. 1 spektr. 8 no.5:721-
722 My '60. (MIRA 13:9)

(Spectrum, Infrared)

SOROKIN, N.G.; AKSEL'ROD, V.S.

New developments in the dispatching systems of clothing factories.
Shvein.prom. no. 5:20-21 S-O '62. (MIRA 15:10)
(Clothing industry—Equipment and supplies)

GORSHUNOV, G.S., inshener; AKSEML'ROD, Ye.I., inshener.

Heating concrete aggregates at place of storage. Stroi.prom. 33
no.9:4-6 S '55. (MLRA 9:1)

(Concrete)

AKSEL'ROD, Yevsey Zelikovich, inzh.; GODYNA, A.K., inzh., red.

[Prestressed reinforced concrete trusses having a 30 m. span with unanchored reinforcement; practices of the Kaunas Plant for Reinforced Concrete Elements of the Lithuanian Ministry of Construction and of the All-Union Scientific Research Institute for the Management of Rural Construction Operations] Predvaritel'no napriazhennaya zhelezobetonnaya ferma proletom 30m so sterzhnevoy neankerovanoi armaturoi; opyt Kaunasskogo zavoda zhelezobetonnykh konstruktsii Ministerstva stroitel'stva Litovskoi SSR i Giproorgsel'stroia. Moskva, Gosstroizdat, 1963. 41 p. (MIRA 17:9)

1. Moscow. Nauchno-issledovatel'skiy institut organizatsii, mekhanizatsii i tekhnicheskoy pomoshchi stroitel'stvu.

AKSEL'ROD, Yu.

Automatic blocking on the M-3-5-5 crane. Stroitel' 8 no. 5:24 My '62.
(MIRA 15:7)

1. Glavnyy mekhanik tresta Dneprokhimstroy.
(Cranes, derricks, etc.--Safety measures)

5 (4), 5 (2)

AUTHORS:

Kasatkin, A. G., Doctor of Technical
Sciences, Professor, Popov, D. M.,
Aksel'rod, Yu. V.

S/064/59/000/07/021/035
B005/B001

TITLE:

Heat Transfer Through the Walls of the Spiral Cooler Under the
Conditions of Bubbling

PERIODICAL:

Khimicheskaya promyshlennost', 1959, Nr 7, pp 622 - 624 (USSR)

ABSTRACT:

The authors of this paper investigated the heat transfer on
absorption of sulfur trioxide in concentrated sulfuric acid
(98% H_2SO_4) for the preparation of standard oleum and on
absorption of sulfur dioxide in a solution of ammonium sulfite-
bisulfite. In both cases, cooling spirals were fixed to the
sieve plates of the absorption column. Table 1 shows the
characteristics of the apparatuses used and the working con-
ditions on investigation of the absorption of SO_3 and SO_2 .
The temperature of the cooling water was measured when entering
and leaving the cooling spiral; moreover, the consumption of
water (kg per hour) and the temperature of the bubbling layer
at the plate were measured. This temperature was considered

Card 1/3

Heat Transfer Through the Walls of the Spiral Cooler
Under the Conditions of Bubbling

S/064/59/000/07/021/035
B005/B001

to be constant at all points which corresponds to a complete blending of the layer at the bubble plate. The heat transfer coefficient K was computed from these values. The coefficients of the heat transfer from the cooler wall to the cooling water (α_2) and of the heat transfer from the bubbling layer to the wall of the cooling spiral (α_1) were also computed. The respective equations are given in the paper. Table 2 shows the results of the experiments and computations. It appears that the values of K are very high and reach $950 \text{ kcal/m}^2\text{hours}^\circ\text{C}$. Since the heat transfer through the cooler walls under the conditions of bubbling is considerable, the same apparatus can also be used for the cooling of hot liquids. In connection with it, the hot liquid is conducted through the cooler; the bubbling layer is cold. The evaluation of the obtained results showed that α_2 increases from 1950 to $6500 \text{ kcal/m}^2\text{hours}^\circ\text{C}$ at increasing velocity of flow of the cooling water. α_1 remained constant in the investigated range of bubbling gas velocities $0.85 - 1.35 \text{ m/sec}$ and was $1200 \text{ kcal/m}^2\text{hours}^\circ\text{C}$ on an average. This means that the total heat transfer coefficient must be

Card 2/3

Heat Transfer Through the Walls of the Spiral Cooler
Under the Conditions of Bubbling

S/064/59/000/07/021/035
B005/B001

constant and independent of the gas velocity when α_2 is given. Table 3 shows a comparison of the value for α_1 obtained by the authors with the results obtained by other authors (M. E. Aerov and others, Ref 3, K. N. Shabalin and I. G. Blyakher, Ref 2, M. Ye. Pozin and others, Ref 1). The comparison proves the above assumption that α_1 is independent of the velocity of flow of the gas in the apparatus. The values for α_1 are in good agreement except for the data of M. Ye. Pozin and co-workers. It may be concluded that in plate apparatuses the maximum turbulence for the respective apparatus is always realized in the entire load range because α_1 depends neither on the turbulence nor on the physical properties of the bubbling layer if the cooling spirals are completely submerged in the bubbling layer. There are 3 tables and 4 Soviet references. ✓

Card 3/3

KUZ'MINYKH, I.N., doktor tekhn.nauk [deceased]; AKSEL'ROD, Yu.V.

Bubble absorption of sulfuric anhydride with the production of
oleum. Khim.prom, no.8:680-685 D-159. (MIRA 13:6)

1. Moskovskiy khimiko-tekhnologicheskii institut im. D.I.
Mendeleyeva.
(Sulfur trioxide) (Sulfuric acid)

AKSEL'ROD, Yu.V.; SURKOV, Ye.I.; RA'M, V.M.

Investigation of hydrodynamics and mass transfer in the system
sulfurtrioxide - sulfuric acid under the conditions of bubbling
on a turbogrid-type sieve tray. Trudy MKHTI no.33:33-42
'61. (MIRA 14:10)

(Mass transfer)
(Plate towers)
(Sulfuric acid)

ANOSHIROD, Yu.V.; SUTYIN, Yu.I.; ...

Dependence of rate of absorption of sulfuric anhydride by sulfuric acid and ... on various factors occurring in ... sieve plates. Trudy NGHTI no.35:134-139 '61. (MIRA 14:10)
(Sulfur trioxide)
(Absorption)
(Plate towers)

AKSEL'ROD, Yu.V.; RAMM, V.M.; SURKOV, Ye.I.

Hydrodynamics of the $\text{SO}_3 - \text{H}_2\text{SO}_4$ bubble system. Trudy MKHTI
no. 40178-85 '63. (MIRA 18:12)

RAMM, V.M.; SURKOV, Ye.I.; AKSEL'ROD, Yu.V.; GUROVA, N.M.;
Prinimali uchastiye: VASIL'YEV, B.T., inzh.; RYKOVA, T.G.

Absorption of sulfuric anhydride in the contact process
manufacture of sulfuric acid in bubble columns with sieve
and tubular plates. Trudy MKHTI no.35:140-146 '61.
(MIRA 14:10)

(Sulfuric acid)
(Plate towers)

AKSEL'ROD, Yu.Y.; VASIL'YEV, B.T.; GUROVA, N.M.; RAMM, V.M.; SURKOV, Ye.I.;
TSURIKOV, S.A.

Absorption of sulfuric anhydride in bubble towers with the yield of
oleum. Khim.prom. no.1:39 Ja '64. (MIRA 17:2)

RAMM, V.M.; AKSEL'ROD, Yu.V.

Intensity of heat transmission through a tube wall on sieve
and tubular trays. Khim. prom. no.5:367-371 My '64.

(MIRA 17:9)

AKSEL'ROD, Yu.V.; RAMM, V.M.; SURKOV, Ye.I.

Equilibrium pressure of sulfuric anhydride vapors over oleum.
Zhur. prikl. khim. 37 no.6:1199-1204 Je '64.

(MIRA 18:3)

AKSEL'ROD, Z. M.

Chasovye mekhanizmy; teoriia, rashet i proektirovanie. Moskva, Mashgiz, 1947. 358 p. diagrs.

Bibliography: p. 354-(355)

Clockwork; theory, calculation and designing.

DLC: TS545.A4

SO: Manufacturing and Mechanical Engineering in the Soviet Union, Library of Congress, 1953.

~~AKSEL' ROD, Z. M.~~
~~AKSEL' ROD, Z. M.~~
AKSEL' ROD, Z. M.

Author: Aksel'rod, Z. M.

Title: The applicati n of speed regulators in the construction of various devices.
(Regulatory sklerosti v prâberostromnii.) 260 p.

City: Moscow

Publisher:

~~Publitsizmat~~ State Print ng House of Literature pertaining to "Machine Construction.

Date: 1949

Available: Library of Congress

Source: Monthly List of Russian Accessions, Vol. 3, No. 2, Page 96

AKSEL'ROD, Z. M.

Regulatory skorosti v priborostroenii. Moskva, Mashgiz, 1949. 263 p. illus.

Bibliography: p. [261-262]

Speed governors in instrument construction.

DLC: TJ1055.A38

SO: Manufacturing and Mechanical Engineering in the Soviet Union, Library of Congress, 1953.

