

Fric, V.

Fric, V. Instability of the auxiliary impulse in the switch valve. p. 643.
Haj. A precise differential amplifier. Tr. from the English. p. 643.
Sk, Antimony-lithium photocathode. Tr. from the Russian. p. 644.
2d Exhibition of the Czechoslovak Machinery Industry in Brno.
(To be contd) p. 646.

Vol. 17, no. 11, Nov. 1956
SLABOPROUDY OBZOR
TECHNOLOGY
Czechoslovakia

So. East European Accessions, Vol. 6, May 1957
No. 5

CZECHOSLOVAKIA/Radio Physics - General

I-1

Abs Jour : Ref Zhur - Fizika, No 8, 1958, No 18534

Author : ~~Fric Viktor~~

Inst : Not Given

Title : First International Congress in Paris 1956 on Microwave Tubes

Orig Pub : Slaboproudy obzor, 1957, 18, No 11, 764-769

Abstract : Survey article, devoted to microwave tubes and based on the published materials of the First International Congress in Paris in 1956. Bibliography, 100 titles.

Card : 1/1

83373

2/037/60/000/005/004/056

Evaluation of the Fundamental ^{E192/E382}Methods of Tuning the Magnetrons
from the Point of View of Efficiency and Frequency Stability
they operate with low "parameters".

ASSOCIATION: Výzkumný ústav pro vakuovou elektrotechniku,
Praha (Research Institute for Vacuum
Electrotechnology, Prague) ✓

Card 2/2

Z/039/60/021/08/005/032
E140/E563

AUTHOR: Frič, Viktor

TITLE: Increasing Magnetron Efficiency by Ferrite Isolators

PERIODICAL: Slaboproudý obzor, 1960, Vol 21, No 8, pp 468-473

ABSTRACT: The article examines the theoretical increase of magnetron efficiency resulting from the use of ferrite isolators, which eliminate load variation influence on the magnetron parameters. In a numerical example an increase from 41 to 58 percent was found. There are 9 figures and 9 references, 3 of which are Czech, 1 Soviet and 5 English.

ASSOCIATION: Výzkumný ústav pro vakuovou elektrotechniku
(Research Institute for Vacuum Electrical Engineering)

SUBMITTED: January 29, 1960

Card 1/1

FRIC, Viktor; DOHNALEK, Jarmil; STARY, Zdenek, inz.

Magnetron 60 SA 5l for industrial use. Sbor vak elektrotech
3:36-5l '6l.

1. Vyzkumny ustav pro vakuovou elektrotechniku, Praha.

FRIC, Viktor

Evaluation of principal methods of magnetron tuning from the viewpoint of their efficiency and frequency stability. Sbor vek elektrotech 3:52-61 '61.

1. Vyzkumny ustav pro vakuovou elektrotechniku, Praha.

FRIC, Viktor; STARY, Zdenek, inz.

Contribution to the design of magnetron output transformers.
Sbor vak elektrotech 3:62-73 '61.

27109
Z/039/61/022/008/004/007
D260/D303

9.4/110 (1003, 1105, 1144)

AUTHOR: Frič, Viktor

TITLE: On the significance of a high vacuum in microwave tubes and methods of its production

PERIODICAL: Slaboproudý obzor, v. 22, no. 8, 1961, 476-479

TEXT: The performance, stability and life of microwave tubes depend to a large extent on maintaining a high vacuum in them. Modern evacuation methods and devices permit attaining and maintaining a vacuum better than 10^{-8} - 10^{-9} mm Hg. The article describes the principle and performance of the following devices: 1) The conventional evacuation system consisting of a forepump and a diffusion pump; 2) A US electronic cold-cathode ultra-high vacuum pump; 3) The French PV S 11 electronic heated-cathode vacuum pump; 4) A French miniature heated-cathode vacuum pump. In Czechoslovakia, the katedra elektroniky a vákuovej fyziky Karlovej univerzity (Chair of Electronics and Vacuum Physics, Charles University) has

Card 1/3

27109

Z/039/61/022/008/004/007

D260/D303

On the significance of a high vacuum...

built several modifications of small, glass elements with titanium evaporation designed for producing very high vacua in systems previously evacuated by the conventional forepump-diffusion pump system, which were described by L. Eckertová, L. Kryška, L. Pátý and P. Schürer (Ref. 18: Čerpací elementy s vypařovaným titanem (Pumping Elements with Titanium Evaporation), Čs. čas. fys. 10. 1960, no. 5, 443-447). They operate on the principle of gas gettering by evaporated titanium. In one of these elements, the titanium evaporation takes place in an atmosphere of residual gases partially ionized by the potential between a heated cathode and a titanium rod as an anode, thus increasing the desorption of inert gases. Measurements have shown that residual-gas pressures as low as 4×10^{-8} - 4×10^{-10} can be produced by this element. It is hoped that these elements can also be used for the additional evacuation of smaller microwave tubes. In conclusion it is stated that in addition to their better economy, the main advantage of electronic vacuum pumps is that the pumping process can be interrupted at any time without damaging the tube. There are 4 figures, 1 table and

Card 2/3

On the significance of a high vacuum... ²⁷¹⁰⁹
Z/039/61/022/003/004/007
D260/D303

18 references: 8 Soviet-bloc and 10 non-Soviet-bloc. The references to the four most recent English-language publications read as follows: E. Brown, J.H. Leck, Desorption of Gas in the Cold Cathode Ionisation Gauge, Brit. Journ. of Appl. Phys., 6, 1955, May, 161-164; N.W.W. Smith, Noise Reduction in Microwave Tubes by Getter Ion Pumping, Abstract in Le Vide 15, 1960, no. 85; S. Wagener, The Use of Getters for the Production of Very High Vacua, Vacuum, III, no. 1, January 1953, 11-23; L.D. Hall, Electronic Ultra-High Vacuum Pump, Rev. of Scient. Instr., 29, 1958, no. 5, 367-370. X

ASSOCIATION: Výzkumný ústav vákuové elektroniky, Praha (Research Institute of Vacuum Electronics, Prague)

SUBMITTED: December 7, 1960

Card 3/3

43198

Z/059/62/023/012/003/004
E192/E582AUTHORS: Frič, Viktor and Dohnálek, Jarmil

TITLE: Principles of dielectric heating at microwaves

PERIODICAL: Slaboproudý obzor, v. 23, no. 12, 1962, 691 - 697

TEXT: The heating power produced in a dielectric having a permittivity ϵ and loss factor $\tan \delta$, placed in an electric field

E of frequency f , is proportional to $E^2 f \tan \delta$. The heating of high-loss, high-permittivity materials is thus comparatively efficient, while for materials of low ϵ and low $\tan \delta$ it is necessary to employ high E or f ; however, neither E nor f can be made very high since high E can result in breakdowns of the dielectric and high f can reduce the field penetration depth into the material. Frequencies ranging from 15 Mc/s to microwaves can be used for the purpose of heating but microwaves are advantageous in many applications. Continuously operating magnetrons are particularly suitable as sources of microwave heating energy and 2 special tubes were designed for this purpose at the Research Institute for Vacuum Electrotechnology at Prague. The first magnetron, type 508551, operates at 2575 ± 50 Mc/s and gives a

Card 1/3

Principles of

4/059/62/025/012/005/004
F192/582

continuous power of 200 W. Its supply voltage is 10 kV and anode current 0.4 A; the saturation magnetic field is 1150 G. The other magnetron, type 60S251, also operates at the same frequency and has a coaxial antenna output; its maximum anode voltage is 5.5 kV and current 0.8 A. The magnetic field in the gap is 1150 G and the output of the device is 2 kW; the tube is water-cooled at the rate of 50 - 60 l./h. The resonance system of the device consists of 18 resonators with double coupling straps. The microwave dielectric heating sources of this type can be used for warming-up refrigerated food; a special oven with a waveguide, used for this purpose, is shown. The heaters can also find application in drying grain and other vegetable products, destruction of insects in the grain, pasteurization and sterilization and vulcanization of rubber. A plasma burner operating at 5500 °C for destroying harmful ingredients in the products of internal-combustion engines can be constructed by using the magnetrons. Human operators have to be suitably protected when operating with microwave heaters. The permissible maximum microwave radiation in the USA is 10 mW/cm² while in the Soviet Union it is as low as

✓

Card 2/3

Principles of

Z/039/62/023/012/003/004
E192/E382

10 $\mu\text{W}/\text{cm}^2$ unless the operator is in contact with radiation for less than 20 min when 1 mW/cm^2 is permissible. There are 9 figures and 5 tables.

ASSOCIATION: Výzkumný ústav pro vakuovou elektrotechniku, Praha
(Research Institute for Vacuum Electrotechnology, Prague)

SUBMITTED: May 14, 1962

X

Card 3/3

Z/037/62/000/005-6/045/049
E140/E520

AUTHOR: Frič, V.

TITLE: Electronic limitation of the high-frequency output power of magnetrons

PERIODICAL: Československý časopis pro fysiku, ¹²no.5-6, 1962, 697-709

TEXT: A relation is derived for the stability of the working mode from the conditions of synchronization of the basic components of a high-frequency field and electrons in the neighbourhood of the cathode. The way in which the problem is put shows the influence of the space charge on the upper limit of the magnetic field, at which the magnetron can be operated stably in the π mode. The limiting influence of the space charge and the high-frequency field in the interaction space is included in the common function F , the value of which was determined from an evaluation of the data published on a large number of magnetrons. The conclusions reached can be used with advantage in designing a new magnetron as a criterion of the fundamental possibility of the generation of the required high-frequency output. There are 5 figures.
Card 1/2

Electronic limitation of the ...

Z/037/62/000/005-6/045/049
E140/E520

ASSOCIATION: Vyzkumny ústav pro vakuovou elektrotechniku, Praha
(Research Institute for Vacuum Engineering, Prague)

Card 2/2

45696

Z/039/63/024/001/003/006
E192/E382

9.4x10

AUTHOR: Frič, Viktor

TITLE: Practical use of the criterion of electronic limitation of maximum power output in the design of magnetrons

PERIODICAL: Slaboproudý obzor, v. 24, no. 1, 1963, 14 - 18

TEXT: The author found in an earlier work (Cs. čas. pro fys., 12, 1962, 5-6) that stable operation could be achieved in newly designed types of magnetrons up to a certain value of the magnetic field. There was evidence that the upper boundary of the magnetic field was limited electronically due to the space charge and high-frequency field in the interaction space. An attempt is made in the following to show how this limitation criterion can be used in the design of new magnetrons. It was shown in the earlier work that over the whole operating region the magnetron should meet the following condition: X

$$\frac{U_a}{U_{a_{cr}}} \leq F \frac{N\lambda}{(N-2)\lambda_v} \quad (1)$$

Card 1/4

Practical use of

Z/059/65/024/001/005/006
E192/E382

if it is furnished with resonance systems consisting of identical resonators and:

$$\frac{U_a}{U_{a\pi}} \leq F \frac{2N\lambda_{\pi}}{(N-2)\lambda_v} \quad (2)$$

when the resonators are "staggered". In these equations, U_a is the anode-operating voltage, $U_{a\pi}$ is the threshold voltage for the π -mode, F is a function which expresses the electronic limit for the upper boundary of the magnetic field, N is the number of resonators, λ_{π} is the resonance wavelength of the π -mode and λ_v the resonance wavelength of the neighbouring mode with the nearest phase velocity. The power-limitation criterion is taken into consideration by the following design approach. First, the threshold voltage for the π -mode is plotted as a function of the magnetic field (using the Hartree formulae) and the threshold voltage given by Eq. (1) or (2) is also shown. The maximum value of the anode current and voltage can now be determined for any

Card 2/4

Practical use of

4/059/65/024/001/003/006
E192/E382

value of the magnetic field. The dependence of the anode current on the anode voltage is then calculated for various successive values of ΔU_a . The electronic efficiency is evaluated for every calculated value of the anode current and is plotted as a suitable graph. The high-frequency power generated by the electrons is then calculated for each successive value of the anode voltage and the corresponding anode current. The amplitude of the high-frequency voltage at the anode can be calculated for each successive value U_a . The resulting values of the high-frequency anode voltage can be calculated for radii given by:

$$r_s = \sqrt{\frac{r_k^2}{1 - 1.14 \times 10^{-7} \frac{\omega}{n} \frac{1}{\Pi}}} \quad [\text{cm}; \text{vc}] \quad (6) \quad \checkmark$$

It is now possible to plot a function $U = U_a + U_{vf}$ as a function of the anode voltage U_a or the anode current I_a . Such a graph gives the maximum theoretical anode voltage and current and thus
Card 5/4

Practical use of

Z/059/63/024/001/005/006
E192/E382

permits evaluation of the maximum high-frequency power. A numerical example of using this approach in the design of a 2 kW magnetron is given. There are 6 figures. 4

ASSOCIATION: Vyzkumný ústav pro vakuovou elektrotechniku, Praha
(Research Institute for Vacuum Electrical
Engineering, Prague)

SUBMITTED: June 26, 1962

Card 4/4

FRICH, V. [Fric, V.]

Limitation of the operating parameters of magnetrons determined by the special features of the interaction of electrons with a high-frequency field. Radiotekh. i elektron. 9 no.8:1386-1398 Ag '64. (MIRA 17:10)

1. Issledovatel'skiy institut vakuumnoy elektrotehniki, Praga.

1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020

FRIC, Viktor

Determining the value of the F function limiting the upper
electronic threshold of the magnetic field of magnetrons.
Sbor vak elektrotech 4:16-25 '64.

1. Research Institute of Vacuum Electrical Engineering, Prague.

FRICEK, J.

FRICEK, J. General repairs of tractors with wheels in the district repair shop of machine-tractor stations in Plzen. (To be contd.) p. 11. S. B. Correct standardization of work in the repair shops of machine-tractor stations. p. 15.

Vol. 7, no. 1, Jan. 1957
MECHANISACE ZEMEDLSTVI
AGRICULTURE
Czechoslovakia

So: East European Accession, Vol. 6, No. 5, May 1957

FRICEK, J.

FRICEK, J. General repairs of tractors with wheels in the district repair shop of machine-tractor stations in Plzen. (To be contd.) p. 39.

Vol. 7, no. 2, Jan. 1957
MACHINISACE ZEMEDLSTVI
AGRICULTURE
Czechoslovakia

So: East European Accession, Vol. 6, No. 5, May 1957

FRICH

Category : CZECHOSLOVAKIA / Radio Physics. Generation and Conversion of I-4
Radio-Frequency Oscillations.

Abs Jour : Ref Zhur - Fizika No 3, 1957, No 7255

Author : Frich

Title : Calculation of Fundamental Parameters of the Resonant System
of a Magnetron

Orig Pub : Slaboproudny obror, 1956, 17, No 8, 430-438

Abstract : Relations are derived for the calculation of the fundamental
parameters of the magnetron. A summary of the fundamental rules
that must be observed in the calculation of a new resonant
system of magnetrons is given.

Card : 1/1

- 16 -

FRICH, I., CAND MED SCI, "FORMS AND METHODS OF
TRAINING PHYSICIANS IN THE USSR AND IN CZECHOSLOVAKIA."
LENINGRAD, 1961. (FIRST LENINGRAD MED INST IM ACAD I, P.
PAVLOV, CHAIR OF ORGANIZATION OF PUBLIC HEALTH). (KL,
2-61, 220).

-292-

FRICH, T.

New method of pneumography. Gig. i san. 23 no.5:77-79 My '58

(MIRA 11:6)

1. Iz Kluzhskogo nauchno-issledovatel'skogo gigiyenicheskogo instituta, Rumynskaya Narodnaya Respublika.

(RESPIRATION, physiol.

pneumography, new method (Rus))

SHTRAUS, Kh.; LENGEL, I.; FRICH, T.

Influence of air pollution from cement dust on the body and
public health. Trudy ISGMI no. 56:102-112 '60. (MIRA 14:11)
(RUMANIA--AIR POLLUTION) (RUMANIA--PUBLIC HEALTH)

ACCESSION NR: AP4043672

S/0109/64/009/008/1386/1398

AUTHOR: Frich, V.

TITLE: Limitations of operating parameters of magnetrons imposed by the peculiarities of the interaction of electrons with a high-frequency field

SOURCE: Radiotekhnika i elektronika, v. 9, no. 8, 1964, 1386-1398

TOPIC TAGS: magnetron, magnetron theory, electron interaction, electron field interaction, space charge, space charge distribution

ABSTRACT: This is a continuation of the author's theoretical work whose results were reported before the Second Czechoslovakian Conference on Electronics (V. Frič, Českosl. časop. fys., 1962, 12, 4, 697). The author's formulas for the upper operating limit of a magnetron were reported. In the present article, a more accurate derivation of those formulas, based on the similarity of electron trajectories in static and generating magnetrons in the near-cathode region, is submitted. The magnetron upper operating limit is imposed by the distribution of electrons in the boundary layer of the space-charge cloud; a purely Brillouin

Card 1/2

ACCESSION NR: AP4043672

space-charge distribution is assumed. The function F expressing the operating limit is numerically evaluated from the published data on many magnetrons; this function allows for the effects of the space charge and field asymmetry. The numerical values of the function for multicavity (including the rising-sun type) magnetrons with and without strips are given. These conclusions are also offered: (1) The near-cathode electron trajectories in a generating magnetron are similar to those in a static magnetron; (2) The electron distribution in the space-charge cloud corresponds, in the first approximation, to the Brillouin state; (3) The function F may serve for an approximate determination of the thickness of the transient layer of the space-charge cloud in a generating magnetron. Orig. art. has: 7 figures, 22 formulas, and 1 table.

ASSOCIATION: Issledovatel'skiy institut vakuumnoy elektrotekhniki ,Prague
(Research Institute of Vacuum Electrical Engineering)

SUBMITTED: 25Aug63

ENCL: 00

SUB CODE: EC

NO REF SOV: 003

OTHER: 011

Card 2/2

EAST GERMANY

KILIAS, Rudolf, Dr., of the Institute for Special Zoology and Zoological Museum at Humboldt University (Institut für Spezialzoologie und Zoologisches Museum der Humboldt-Universität) (Director: SENGELAU (initial(s) not given), Professor, Dr.), and EICK, Wolfgang, Dr., of the Office for Veterinary Examination and Animal Hygiene (Veterinäruntersuchungs- und Tiergesundheitsamt) (Director: WOLSECK (initial(s) not given), Ph. D.) in Berlin and Potsdam, respectively.

"Intermediate-Host Snails of Important Domestic Helminths. Part 1: Functions, Description, and Biology of the Intermediate-Host Snails"

Jena, Angewandte Parasitologie, Vol 4, No 2, Jul 1963, pp 85-99.

Abstract: The present knowledge of the functions of intermediate hosts in land- and fresh-water-snails in regard to the native helminths of domestic and other useful animals was reviewed. Data on the morphology, diagnosis, occurrence, distribution, reproduction, and nutrition were given for the following: *Viviparus contectus*, *Valvata piscinalis piscinalis*, *Bithynia tentaculata*, *Bithynia leachi*, *Physa fontinalis*,

1, 2

KAHLICH, R.; FRANEK, J.; FRICOVA, O.

APPROVED FOR RELEASE: 06/13/2000

CIA-RDP86-00513R000513710010-3"

Distribution and activity of β -hemolytic streptococci in newly formed communities. 1. The role of streptococci as the pathogen in acute respiratory diseases. *Cesk. epidem. mikrob. imun.* 12 no.2 81-87 Mr '63.

1. Vojensky ustav hygieny, epidemiologie a mikrobiologie v Praze
(STREPTOCOCCAL INFECTIONS) (RESPIRATORY TRACT INFECTIONS)

FRIDOVÁ, VÁCLAVA
2
Turbidimetric determination of despectified bovine serum
in biological material. Václava Fridová and Tomáš I.
Přítomný (Ústav hematol. krvní transfúze, Prague).
Chem. listy 51, 285-6(1957).-- A modified quant. detn. is
described by direct photometric measurement of turbidity
which arises after beef plasma, despectified according to
Massons (*Lancet* 1946, 2341), has been adjusted to pH 4.2 by
addn. of AcOH buffer. The method requires as little as 0.3
ml. blood. *L. J. Habáček*

PRISTOUPIL, T.I.; FRIČOVÁ, V.

Some changes in the sulfur groups in modified proteins. Cesk. farm.
12 no.3:134-137 Mr '63.

1. Ustav hematologie a krevni transfuse, Praha.
(BLOOD PROTEINS) (SULFUR) (HEAM) (FORMALDEHYDE)
(HYDROGEN PEROXIDE) (CHEMISTRY) (SULFIDES)

CZECHOSLOVAKIA

V. FRICOVA and T. I. PRISTOUPIK, [Affiliation same as above.]

"Enzymatic Decomposition of Modified Bovine Serum Albumin."

Prague, Ceskoslovenska Farmacie, Vol 12, No 4, May 63; pp 191-193.

Abstract [English summary modified]: Trypsin, chymotrypsin and pepsin hydrolysis of specimens of bovine serum albumin, either native or denatured by heat, formalin, oxidation were studied by biuret and ninhydrin methods. Denatured samples decomposed to a higher degree than native ones. Table, 4 graphs; 3 Czech (1 patent) and 3 Western references.

L/1

Simple automatic fraction collector. Chem Listy 58 no. 6:
667-669 Je '64.

1. Institute of Hematology and Blood Transfusion, Prague.

FRICOVSKY, R.

Cementing in spectacle optics. Jemna mech opt 9 no.4:
197-1'8 '64.

FRICSOVSZKY, Gyorgy

How do semiconductors work? Term tud kozl 7 no.11:506-509
N°63.

1. Eotvos Lorand Tudomanyegyetem Atomfizikai Tanszeke,
Budapest.

KIRSCHNER, Istvan; PAPP, Elemer; FRICSOVSZKY, Gyorgy

Physics of supraconductors. Pt.1. Fiz szemle 13 no.10:311-318
0'63

1. Eotvos Lorand Tudomanyegyetem Atomfizikai Tanszeke.

KIRSCHNER, Istvan; PAPP, Elemer; FRICSOVSZKY, Gyorgy

Physics of supraconductors.Pt.2. Fiz szemle 13 no.11:336-349
N '63.

1. Eotvos Lorand Tudomanyegyetem Atomfizikai Tanszeke.

KIRSCHNER, Istvan; PAPP, Elemer; FRICSOVSZKY, Gyorgy

Physics of supraconductors, Pt.3. Fiz szemle 13 no.12:
379-384 D'63.

1. Eotvos Lorand Tudomanyegyetem Atomfizikai Tanszeke.


FRID, A.A.

SUBJECT USSR / PHYSICS
AUTHOR KLJARFEL'D, B.N., FRID, A.A.
TITLE A Filamentlike Anode in a Gas Discharge.
PERIODICAL Zurn.techn.fis, 26, fasc.11, 2541-2547 (1956)
Issued: 12 / 1956

CARD 1 / 2

PA - 1689

Here the experimental investigation of the ignition mechanism of the discharge in a long discharge tube along the axis of which a thin wire is drawn, is described. The application of a potential, which is positive with respect to the cathode, to the filament causes a discharge luminescence on the surface of the filament as well as the instant ignition of the discharge between the main electrodes. In mercury vapors ($p = 0,001$ mm torr in the case of discharge currents of the order from 10^{-5} to 10^{-3} ampères on the filament) a weak luminescence extends over the surface of the filament to the extent of up to 75 cm. However, a reliable discharge is attained only if the discharge tube is not very long. That portion of the filament which is next to the cathode is the anode of the independent discharge. The remaining part of the filament collects the electrons which are propagated from the domain of the independent discharge. These electrons penetrate into the cylindrical field between the walls of the tube and the field, describe several circles round the filament, and then impinge upon the filament. Near the filament the electrons have the highest kinetic energy and ionize the gas intensely. On this occasion a noticeable concentration of electrons and positive ions is brought about in



FRID, A. I
 ca

PROCESSES AND PROPERTIES INDEX

The metabolism of the brain and the humorally active substances of the central nervous system. V. M. Rubel, A. I. Frid and A. N. Kislinskii. *J. Physiol. (U. S. S. R.)* 27, 58-69 (1939); *Chem. Zentr.* 1940, I, 2497; cf. *C. A.* 34, 51701. — Trepanned dogs were subjected to acoustic, alimentary and elec. stimulation, after which the arterial and venous blood (from the sinus sagittalis) were examined to det. the content in residual and lipoid N, the final NH₃ value and the content in NH₃-forming substances (in mg. % N). The absorption spectra in the ultraviolet region were detd. and the physiol. action on isolated frog hearts was studied. The results are discussed at length.

M. G. Moor.

ASB-35A METALLURGICAL LITERATURE CLASSIFICATION

FRID, A. I.

11 H

Ch

Biological action of citral and β -ionone, substances related to vitamin A. M. I. Rokhlina, A. I. Frid, A. I. Kaplan, and E. A. Chkoniya. *Vestnik Oftalmol.* 27, No. 1, 28-30 (1948). -- Citral shows a definite antihistamine action on isolated eye and heart of a frog, guinea pig intestine, rabbit ear, and frog legs. Emulsified frog eyes show pupil dilatation at 1:2000 concn.; a lesser effect is observed at higher or lower concns.; addn. of adrenaline gives a greater effect, while atropine shows a weak effect in combination with citral. The contractile effect of 1:2,000,000 soln. of histamine is completely counteracted by 1:2000 to 1:10,000 soln. of citral. Citral at 1:2000 diln. shows vessel contraction in ear or leg expts; more diln. gives an opposite effect (dilatation). Citral at 1:10,000 concn. removes the constrictor action of adrenaline (1:2,000,000). Citral depressed the heart at 1:10,000 concn. and counteracted 1:2,000,000 soln. of histamine in this respect. Ionone (1:10,000) has a neg. chronotropic and inotropic effect on frog heart action. Citral (0.05 in 1 ml.) removes the histamine induced contraction of isolated intestine. G. M. Kosdapsol

ASW 51.4 METALLOGRAPHIC LITERATURE CLASSIFICATION

EXCERPTA MEDICA SEC. 12 Vol. 12/8 Opth. Aug. 58

FRID, A. I.

1292. THE CONTENT OF HYALURONIC ACID IN THE FLUID OF THE ANTERIOR CHAMBER OF THE EYE IN GLAUCOMA AND CATARACT (Russian text) - Frid A. I. - SBORN. INFORM. - METOD. MATERIAL. INST. 1956, 4(16-18) -

The content of hyaluronic acid in the fluid of the anterior chamber of the eye was determined in patients with glaucoma, using as a control the fluid from the anterior chamber of patients with cataract. The content of hyaluronic acid was determined by the method of nephelometry using a Spekker photoelectric absorption meter. In patients with cataract, the content of hyaluronic acid was on the average 0.052 mg./1 ml. In patients with absolute glaucoma, in both the stage of development and in long-standing conditions, there was an increase in the content of hyaluronic acid (on the average 141.8 mg./0.1 ml.). In early stages of the disease and in secondary glaucoma, no increase in the content of hyaluronic acid in the anterior chamber fluid was observed. The author connects disturbance of the hyaluronic acid enzyme system - hyaluronidase - in glaucoma patients with a diminution in the amount of acetylcholine.

(S)

BERENSHTEYN-KECHNER, R.A.; FRID, A.I.

Role of the central nervous system in the regulation of intraocular pressure in X-ray therapy for glaucoma. Trudy TSentr. nauch.-issl. inst. rentg. 1 rad. 10:357-366 '59. (MIRA 12:9)
(GLAUCOMA) (X RAYS--THERAPEUTIC USE)
(INTRAOCULAR PRESSURE) (NERVOUS SYSTEM)

FRID, A. M.

"Investigation of the Process Governing the Occurrence and Development of Cavitation in Hydroturbines." Cand Tech Sci, Khar'kov Polytechnic Inst imeni Lenin, Min Higher Education USSR, Khar'kov, 1954. (KL, No 2, Jan 55)

Survey of Scientific and Technical Dissertations Defended at USSR Higher Educational Institutions (12)

SO: Sum. No. 556, 24 Jun 55

28(2)

SOV/32-25-5-34/56

AUTHORS: Epshteyn, V. L., Frid, A. M.

TITLE: On the Computation of Statistical Characteristics on Punched Card Computers (O vychislenii statisticheskikh kharakteristik na schetnoperforatsionnykh mashinakh)

PERIODICAL: Zavodskaya Laboratoriya, 1959, Vol 25, Nr 5, pp 613-616 (USSR)

ABSTRACT: The use of punched card computers (PC) in practice is usually limited to assortment and grouping and a compilation of frequency characteristics on the tabulators. The analysis of the mathematical structure of statistical characteristics. (Table) shows that the latter may be divided into two groups with respect to computation: the first group comprises operations, as the summation of a larger number of data, the computation of the sum of products (including the sum of squares) and various operations of grouping; the second group covers division, extraction of roots etc. Thus, the first group is a comprehensive one, whereas the second group comprises operations which are carried out according to data obtained by operations of the first group. On this basis a uniform scheme is worked out for the present case for the purpose of adjusting the tabulator

Card 1/2

SOV/32-25-5-34/56

On the Computation of Statistical Characteristics on Punched Card Computers

T-5, which comprises the entire complex of mass computations in the course of statistical investigations; this is done by the method of series of numbers (Ref 1). Three diagrams are given in a table. There are 1 table and 1 Soviet reference.

ASSOCIATION: Stal'proyekt (Stal'proyekt)

Card 2/2

Frid, A.M.

AID Nr. 982-15 4 June

CAVITATION DAMAGE IN MATERIALS (USSR)

Frid, A. M. Izvestiya vysshikh uchebnykh zavedeniy. Aviatsionnaya tekhnika, no. 1, 1963, 126-130. S/147/63/000/001/014/020

Measurements were made of cavitation damage (weight loss) caused by the impact erosion of a water jet with a velocity of 4 m/sec impinging periodically on aluminum, electrolytic copper, and magnesium specimens which were rotated at a peripheral speed of 45 m/sec in a closed vessel whose air pressure was varied from 760 to 260 mm Hg. It was found that maximum weight loss in each metal occurs at a definite critical air pressure: 630, 525, and 440 mm Hg for aluminum, magnesium, and copper, respectively. Weight loss at critical pressure is 3 to 5 times higher than at atmospheric pressure. Similar results were obtained with aluminum subjected to ultrasound-induced cavitation; a maximum weight loss occurred when the weight of the air dissolved in water (and, consequently, in the microcracks of the specimens) at -50°C was about the same as that of the air dissolved in water at 630 mm Hg and 20°C , which is the point at

Card 1/2

AID Nr. 982-15 4 June

CAVITATION DAMAGE IN MATERIALS [Cont'd]

S/147/63/000/001/014/020

which maximum weight loss occurred with impact-erosion cavitation. The results seem to support the author's hypothesis that cavitation damage of materials is caused by the presence of air-filled microcracks and pores on the surface of the specimen. The water pressed into microcracks at the moment of jet impact is compressed and instantaneously heats the air in the microcracks and pores to a high temperature. Intense corrosion, and, possibly, chemical reactions, and even melting take place on the microcrack walls under high temperature. The pressure drops as the specimen passes the jet; the liquid and highly compressed vapors are ejected from the microcracks of the pores causing intense erosion of microcrack surfaces. The increase in temperature depends on the compression ratio, and the amount of damage depends on the weight of the air in the microfissures. This explains the maxima on weight loss-pressure curves. Generally, cavitation damage depends not only on the hardness and strength of the microscopic volumes of the material, but also on its melting temperature, heat resistance, and high-temperature corrosion resistance.

[MS]

Card 2/2

L 00028-66 EWT(m)/EWP(t)/EWP(b) IJP(c) JD
ACCESSION NR: AP5020312

UR/0186/65/007/004/0496/0498
532.72:546.42:631.4

AUTHOR: Prokhorov, V. M.; Frid, A. S.

TITLE: The effect of salt concentration in soil solutions on the rate of diffusion of microquantities of strontium in the soil

SOURCE: Radiokhimiya, v. 7, no. 4, 1965, 496-498

TOPIC TAGS: soil, diffusion, strontium-90

ABSTRACT: The purpose of this investigation was to measure directly the effect of the composition of the soil solution on the rate of diffusion of radioactive isotopes in the soil. The experiments were conducted with Sr-90 without a carrier. The soil (37 m²/g, specific surface) was wetted with concentrations of CaCl₂ solutions ranging from 3.3 10⁻² to 8.5 g-equiv/l. The soil was moistened to the extent of 30% by weight. To correct for adsorption of Ca⁺⁺ by soil the equilibrium concentration of CaCl₂ was determined by complexometric titration. The diffusion coefficient of strontium-90 as a function of the concentration of Ca⁺⁺ is shown in the figure (Enclosure 01). In the concentration range 4.10⁻³ - 5.8 10⁻¹ M the diffusion coefficient of strontium increases by approximately a factor of 13. From 0.6 to

Card 1/3

L 00028-66

ACCESSION NR: AP5020312

6.6 N the diffusion coefficient remains practically constant. The data presented may be useful in estimating the migration of Sr-90 in soil from radioactive wastes with large salt concentration. The authors wish to express their gratitude to M. K. Mel'nikova for her interest in this work and to A. F. Batygin for his help in carrying out experiments. Orig. art. has: 1 figure and 1 table. 2

ASSOCIATION: none

SUBMITTED: 27Nov64

ENCL: 01

SUB CODE: NP, LS

NO REF SOV: 004

OTHER: 001

Card 2/3

L 00028-66

ACCESSION NR: AP5020312

ENCLOSURE: 01




Fig. 1. Diffusion coefficient of Sr-90 in soil as a function of the concentration of Ca²⁺.
C_{eq} -- concentration of Ca²⁺ in an equilibrium soil solution (g-equiv/l);
N -- total concentration of calcium in soil, recalculated to CaCl₂ (in % of the weight of dry soil).

dg
Card 3/3

PROCESSES AND PROPERTIES INDEX

1ST AND 2ND ORDERS

100 AND 5TH ORDERS

BC

A-1

Detection of small amounts of niobium and tantalum by means of phenylarsinic acid. I. P. ALIMARIN and R. I. FRED (Zavod. Lab., 1937, 6, 823-825).—The powder of mineral is fused with 10 parts of K_2O_2 , and the melt is dissolved in 20% aq. tartaric acid. The solution is saturated with H_2S , excess of which is eliminated from the filtrate. HCl is then added to 3—5x, followed by excess of saturated aq. phenylarsinic acid, when a white ppt. or turbidity is obtained in presence of Nb or Ta ($\pm 2 \mu g.$ of Nb_2O_5 or Ta_2O_5 per ml. of solution). Ti and Zr interfere if present in considerable excess; other elements, except F, do not interfere. R. T.

ASB-ILA METALLURGICAL LITERATURE CLASSIFICATION

GROUPS	1ST AND 2ND ORDERS	ENGLISH	100 AND 5TH ORDERS
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z AA AB AC AD AE AF AG AH AI AJ AK AL AM AN AO AP AQ AR AS AT AU AV AW AX AY AZ	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100	A B C D E F G H I J K L M N O P Q R S T U V W X Y Z AA AB AC AD AE AF AG AH AI AJ AK AL AM AN AO AP AQ AR AS AT AU AV AW AX AY AZ	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

BC

Determination of niobium and tantalum with the aid of phenylarsonic acid. I. P. ALJMARIN and B. I. FINEP (Zavod. Lab., 1938, 7, 913-916).—The mixture, containing 0.1 g. each of Al_2O_3 , Fe_2O_3 , V_2O_5 , U_2O_7 , MnO_2 , Ca_2O_3 , La_2O_3 , and 2-30 mg. of $Nb_2O_5 + Ta_2O_5$, is fused with $K_2S_2O_7$, the melt is dissolved in 150 ml. of π -HCl, and the solution is filtered. Excess of 3% $PhAsO_3H_2$ is added to the filtrate, which is boiled for 1 hr.; on the next day the ppt. of $[M_2O_5(PhAsO_3)_2]H_2$ ($M = Ta, Nb$) is collected, washed with 4% NH_4NO_3 , ignited at 1000° , and weighed as M_2O_5 . The ppt. may contain Ti; if this is present it should be determined colorimetrically, and the corresponding wt. of TiO_2 subtracted from that of M_2O_5 .

R. T.

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

MATERIALS INDEX										CHEMICAL ELEMENTS									
GROUPS										GROUPS									
I										II									
III										IV									
V										VI									
VII										VIII									
IX										X									
XI										XI									
XII										XII									
XIII										XIII									
XIV										XIV									
XV										XV									
XVI										XVI									
XVII										XVII									
XVIII										XVIII									
XIX										XIX									
XX										XX									
XXI										XXI									
XXII										XXII									
XXIII										XXIII									
XXIV										XXIV									
XXV										XXV									
XXVI										XXVI									
XXVII										XXVII									
XXVIII										XXVIII									
XXIX										XXIX									
XXX										XXX									

CA

4

Failure to separate the rare earths electrolytically by use of a mercury cathode. P. Albuin and D. I. Fink. *Zapadnaya Lab.* 8, 498(1930); *Chem. Zentr.* 1930, II, 2789.—Fe is completely sep'd. from rare earths by electrolysis in an acid soln. The rare earths remain in soln. Pt wire was used as anode. Electrolysis was at 2-3 amp., 7 to 8 volts, 1-2 hrs., bath temp. 60-70°. The acid soln. of the rare earths was then analysed with a polarograph with a dropping-Hg electrode. Neither reduction reactions nor amalgam formation was observed. M. Hoesel

ASA-SEA METALLURGICAL LITERATURE CLASSIFICATION

1930-1939

1940-1949

1950-1959

1960-1969

1970-1979

PROCESSES AND PROPERTIES INDEX

7

Ca

Quantitative microchemical analysis of minerals, ores and rocks. V. Colorimetric determination of iron. I. P. Almarin and B. I. Fedt. *Zavodskaya Lab.* 10, 232 (1911); cf. *C. A.* 35, 2812. Dissolve 10-20 mg of mineral or ore powder with 5 ml. of water and 3-4 drops of 18 N H₂SO₄, and add 1 ml. of concd. HF soln. Heat first on a steam bath and then on a sand bath. Fuse the residue with K₂SO₄, dissolve the cold melt in very dd. hot H₂SO₄, add 1 drop HNO₃, and heat for 1 min. For each 0.1 mg. Fe₂O₃ add 3 ml. of 25% sulfosalicylic acid and dropwise 25% NH₄OH until yellow and then 0.5 ml. in excess. Dil. the colored soln. to the mark (1 ml. of colored soln. should contain not over 0.05 mg. Fe₂O₃) and after 5 min. compare in a colorimeter with a standard soln. contg. about 0.02 mg. Fe₂O₃ per ml. In the presence of Mn add 0.2 g. of NH₄OH.HCl before adding the NH₄OH. With rich Mn ores increase the hydroxylamine to 1 g. If the sample contains over 20% Al₂O₃ or MgO use 5 ml. of sulfosalicylic acid.

B. Z. Kamich

ASB-514 METALLURGICAL LITERATURE CLASSIFICATION

1930s 1940s 1950s 1960s 1970s 1980s 1990s

Determination of columbium and tantalum in minerals and ores. I. P. Alimarin and B. I. Fridl. *Trudy Vsesoyuz. Konfederatsii Anal. Khim.* 2, 333-37 (1948).—Good results are obtained in detns. of small quantities of Cb by the

Schoeller method (fuse Cb_2O_5 with K_2SO_4 , dissolve the melt in $H_2C_2H_4O_4$, hydrolyze in 30 ml. of the soln. in the presence of 5 ml. of HNO_3). Errors are introduced by the presence of much Ta. Schoeller's methods for earth acids in the presence of Ti and Zr are satisfactory if considerable quantities of the earth acids are present and if the empirical correction is made to the final wt. of the pentoxides. If the content of the earth acids is approx. 0.1% and considerable quantities of Ti are present, then all 3 of Schoeller's methods give very low or, sometimes, neg. results. Cb and Ta can be sepd. from Ti and Fe by pyrogallic acid; no empirical corrections are necessary. Sepn. of Cb and Ta from Zr by leaching the pyrosulfate melt of the mixt. of oxides with 5% pyrogallic acid in N HCl is more satisfactory than the sepn. from Ti. Even after the 1st sepn. of the mixt. MgO and ZrO_2 , most of the Zr remains in soln. and after the 2nd sepn. the ppt. of the earth acids contains less than a mg. of ZrO_2 . Pptn. of Cb and Ta by acidifying the alk. pyrogallic soln. with HCl is unsatisfactory, because of the formation of $Zr(OH)_2$ on the addn. of excess NH_3 to the pyrogallic acid soln. Cb and Ta can be detd. by benzenearcous acid even in the presence of Al, Fe, U, V, Mn, and the rare earth elements. As a result of expts. an improved method for detg. Cb and Ta was developed. Decomp. the sample with a mixt. of HP and H_2SO_4 , or fuse with K_2SO_4 , and dissolve the melt in 100

ml. of 5% pyrogallic acid. In the presence of large quantities of Ti and Fe the soln. assumes a dark-brown color and a ppt. of Cb and Ta pyrogallate is formed. Add a slight excess of NH_3 to the soln., heat to boiling (the ppt. of the earth acids dissolves), neutralize the hot soln. with HCl, add excess acid to make the soln. approx. N , heat for 30-40 min. to boiling, add macerated filter paper, and let stand for several hrs. Filter, wash with 1% pyrogallol soln. acidic with HCl, and ignite the filter and the ppt. in a porcelain crucible. Fuse the resulting oxides with K_2SO_4 or dissolve in HP and H_2SO_4 , and repeat the sepn. with pyrogallic acid. If the sample contains much Ti, or if a large sample (2.5 g.) is used, a 3rd sepn. is necessary. The filtrates after the 1st sepn. are dark and on the following day a slight ppt. consisting of Ti is formed by the atmospheric oxidation of pyrogallol. The pentoxides obtained are usually contaminated by small quantities of Ti and Fe and, if sepd. with K_2SO_4 , contain nearly all of the H_2SiO_3 , which can be removed by heating the Cb and Ta pyrogallates in a Pt crucible, treating with HP and H_2SO_4 , and dissolving the ppt. in 20 ml. of 10% aq. $H_2C_2H_4O_4$. If Ta predominates in the pentoxide mixt., the soln. of the residue is incomplete, owing to the partial sepn. of $HTaO_3$, which forms turbid or opalescent colloidal solns. In such cases make the soln. alk. with NH_3 , heat to boiling (the soln. becomes clear), acidify with HCl, sat. the soln. with H_2S , and filter the sulfides of the heavy metals and Pt formed. Remove the excess H_2S by boiling, add HCl to bring the soln. to N , heat to boiling, ppt. the Cb and Ta with 30-40 ml. of 3% aq. benzenearcous acid, heat the liquid with the

ASB-51A METALLURGICAL LITERATURE CLASSIFICATION

13000 17100100

140300 *

101003 MEF ONV 300

0111101

13000 17100100

0111101 ONV 300

ppt. on a sand bath until the ppt. coagulates completely, add macerated paper, and let stand overnight. Filter, wash with 4% NH_4NO_3 soln. acidify with HNO_3 , and ignite in porcelain. Remove the adhered alkali metals by moistening the ignited pentoxide with 1-2 ml. of 5% HNO_3 , digest on a water bath for 5-10 min., make alk. with NH_3 , filter through a dense filter, wash with 4% NH_4NO_3 , and ignite the filter with the residue in the same crucible. To convert the results for the content of Ti , fuse the oxides with K_2CO_3 , dissolve the melt in 5% H_2SO_4 , evap. H_2O , transfer the colored soln. to a measuring flask, and det. Ti colorimetrically. Cb and Ta in case-ites can be det. colorimetrically by the Platonov method (C.A. 34, 4814; 32, 2238), which is based on their property of forming red colored compds. with pyrogallol acid in $\text{H}_2\text{C}_2\text{O}_4$ soln. (Ta gives a color in acid soln. only, and Cb in basic soln.). In the presence of large quantities of earth acids, better results are obtained with a combination of the permanganate and pyrogallol method: a single sepn. with tartaric acid, according to Schoeller, and colorimetric detn. of Cb in the Ta ppt. and of Ta in the Cb ppt. Twenty-one references.

W. R. Henn

Trid, B.I.

The use of ordinary analytical balances for quantitative
 microanalysis of minerals. B. I. Frid, *Izvestiya Akad. Nauk
 SSSR Ser. Khim. i Geol. Tekh. Nauk*, No. 1011, 1955, 98-104; *Referat. Zhur., Khim.*, 1956, No. 1011.—
 Method of adjustment, detn. of zero point, sensitivity, pre-
 cision of analytical balances, and the weighing rules for micro-
 analysis are described.
 N. Vasileff

3

1-4E 4j

1/1

PM

FRID, B.I.

USSR/Fitting Out of Laboratories - Instruments.
Their Theory, Construction, and Use.

H-

Abs Jour : Ref Zhur - Khimiya, No 3, 1957, 8713

Author : Frid, B.I.

Inst : A Commission on Analytical Chemistry, Academy of Sciences
USSR

Title : An Electrode for Potentiometric Microtitrations.

Orig Pub : Tr. Komis. po analit. khimii. AN SSSR, 1956, 7, No 10,
170-173.

Abstract : The design of a microelectrode for potentiometric micro-
titrations in which the indicator electrode (IE) and ref-
erence electrode (RE) are mounted together and connected
electrolytically by means of a saturated solution of
Na₂SO₄ or KCl occupying the space between two concentric
glass tubes, the inner of which serves to insulate and
hold the IE, is described. The two glass tubes form a
ground glass joint at the lower end, thus, preventing

Card 1/2

ALIMARIN, Ivan Pavlovich; FRID, Berta Izrailevna; LEONT'YEVA, K.D.,
red.; KOGAN, V.V., tekh. red.

[Quantitative microchemical analysis of minerals and ores;
laboratory manual] Kolichestvennyi mikrokhimicheskii analiz
mineralov i rud; prakticheskoe rukovodstvo. Moskva, Gos.
nauchno-tekhn.izd-vo khim.lit-ry, 1961. 399 p.

(MIRA 15:1)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut mineral'-
nogo syr'ya (for Alimarin, Frid)
(Mineralogical chemistry) (Microchemistry)

FRID, D. I., Candidate Med Sci (diss) -- "The surgical anatomy of the arterial blood supply of the pancreas (Anatomical-experimental investigation)" / Leningrad, 1959. 17 pp (State Order of Lenin Inst for the Advanced Training of Physicians in S. M. Kirov), 250 copies (KL, No 22, 1959, 123)

FRID, D.I.

Arterial blood supply of the pancreas. Sbor. nauch. trud. GIDUV
no. 14:205-215 '58. (MIRA 13:10)

1. Iz kafedry operativnoy khirurgii Gosudarstvennogo instituta
dlya usovershenstvovaniya vrachey (zav. kafedroy prof. A.P.
Nadein) i Pontonoy bol'nitsy Kolpinskogo rayona Leningrada
(glavnyy vrach L.A. Krishtovich).
(PANCREAS—BLOOD SUPPLY)

FRID, D.I.

Capsule of the pancreas and its significance in acute pancreatitis.
Sbor. nauch. trud. GIDUV no. 14:216-219 '58. (MIRA 13:10)

1. Iz kafedry operativnoy khirurgii Gosudarstvennogo instituta
dlya usovershenstvovaniya vrachey (zav. kafedroy prof. A P.
Nadein) i pontonnoy bol'nitsy Kclpinskogo rayona Leningrada.
(PANCREAS—DISEASES)

AND, A. A., NIKOL, YA. S., KASHA, V. M., AND, ...

Apparatus for artificial circulation with automatic electrocardiogram
Installation 171

Novye khirurgicheskie apparaty i instrumenty i opyt ikh primeneniya (New
SURGICAL Equipment and Instruments and Experience in Their Use) NO.1,
Moscow, 1957 A collection of Papers of the Scientific Research Inst.
for Experimental Surgical Equipment and Instruments.

NIERKAI

FRID, Ye. I.

USSR :

Thermal resistivity of $\text{Li}_2\text{O} \cdot \text{Al}_2\text{O}_3 \cdot 4\text{SiO}_2$ ceramic materials.
D. Finkel'shteyn and Ye. I. Frid. Pribory Pirov.
Mineral., Akad. Nauk S.S.S.R. 7, 381-5 (1963).—The
particular case with which β -spodumene is formed below
 600° in the presence of strong mineralizers (e.g. WO_3) or by
hydrothermal methods is striking. To synthesize spodu-
mene, a mix of Li_2CO_3 18.6; kaolin from Prosyanovsk 39.6;
plastic Chasov-Yar clay 16.6; and quartz sand 27.2% was
heated to $1230\text{--}1320^\circ$ for 12 hrs. The cryst. phase, with n
of about 1.516, was β -spodumene contaminated by some
mullite, residual quartz, and glass. The thermal expan-
sion coeff. was 1.23×10^{-5} between 20° and 1000° . The
ceramic properties of β -spodumene were similar to feldspar,
and its melt was highly viscous at 1210° , the thermal ex-
pansion being similar to that of synthetic cordierite (with
 2.2×10^{-5}) if fired at 1420° . The thermal shock (spalling)
resistivity was very high. W. Zitel

Handwritten initials and marks.

FRID, F.P.

507/3409

PHASE I BOOK EXPLOITATION

Moscow. Vsesoyuznyy teploobmennicheskiy institut

Teploobmen pri vysokikh teplovykh nagruzki i druzhnykh metallicheskikh ustroystvakh i obratnykh ustroystvakh (Heat Exchange Under High Thermal Loads and Other Special Conditions) Collection of Articles Moscow, Gosenergoizdat, 1979. 135 p. 4,000 copies printed.

Ed.: G. I. Matveyev, A. A. Armand; Ed. (outside book): I. K. Korikovskiy; Tech.

PURPOSE: The book is intended for personnel of scientific research institutes, planning and design organizations, and for power engineers.

COVERLINE: This collection of 9 articles presents the results of research conducted at the All-Union Heat Engineering Institute. Problems of heat exchange under high pressure and other special conditions are discussed. Attention is devoted to special cases such as heat exchange between a pipe wall and water, including cases of carry-over and film boiling; heat transfer to steam and water under supercritical conditions; heat exchangers from pipe wall to gas under high pressure; and the hydraulic resistance of a heated tube. References are given at the end of each article.

- 2. Dorobchuk, V. Ye., and F. P. Frid. Investigation of Critical Heat Loads 23
- 3. Dorobchuk, V. Ye., V. L. Lal'chuk, and V. V. Modnikova. Heat Emission to Water Under High Pressure 30
- 4. Armand A. A., V. Y. Zheleznyy, and A. S. Kon'kov. Investigation of Heat Emission From Wall to Steam Near the Critical State 41
- 5. Zheleznyy, V. G. Experimental Investigation of the Mechanism of Surface Boiling 51
- 6. Zheleznyy, V. G., and V. L. Lal'chuk. Experimental Investigation of Heat Emission From Tube Wall to Gas at High Temperature 69
- 7. Lal'chuk, V. L., and B. I. Syrovatkin. Experimental Determination of Hydraulic Resistance with Turbulent Flow of Air in a Heated Tube 91
- 8. Dorobchuk, V. Ye., and F. P. Frid. Investigation of Heat Emission in Annular Channels 101
- 9. Armand A. A. Calculation of Transient Processes in Heat Exchangers 113

AVAILABLE: Library of Congress (C3320.M6d)

Card 3/3

B/lep
4-4-80

5

SOV/96-59-9-15/22

AUTHORS: Doroshchuk, V.Ye. (Candidate of Technical Sciences) and
Frid, F.P. (Engineer)

TITLE: The Influence of Throttling the Flow and of Heating a
Length of Pipe on Critical Thermal Loadings

PERIODICAL: Teploenergetika, 1959, Nr 9, pp 74-79 (USSR)

ABSTRACT: A good deal of experimental work has been published on
critical thermal loadings during forced flow of water and
steam/water mixtures, but unfortunately there are
considerable differences between the results of various
authors. Recently workers in the Power Institute of the
Ac. Sc. USSR have published articles in Teploenergetika
and elsewhere in which they point out the important
effects of throttling the flow at the inlet to the
experimental channel and of the heated length of the
experimental pipe. It is claimed that throttling
disturbs the flow, alters the structure of two-phase flow
and causes boiling of the water. Alteration in the
length of pipe heated also alters the structure of flow
in heated and unheated pipes. Therefore, the degree of
stabilisation of flow structure at constant velocity,
pressure and steam content at the point where critical

Card 1/6

SOV/96-59-9-15/22

The Influence of Throttling the Flow and of Heating a Length of Pipe on Critical Thermal Loadings

conditions occur, depends on the distance of this point from the commencement of heating. These views cannot be ignored because they introduce important factors not usually considered. The experimental rig used in the Power Institute of the Ac. Sc. USSR is illustrated diagrammatically in Fig 1 and is briefly described. From consideration of this system it is concluded that one of the heat exchangers is a source of considerable pulsation which might affect the experimental section of the apparatus and the critical thermal loadings. It is accordingly possible that the observed influence of throttling the flow and of the length of heated pipe may be peculiar to the equipment used in the Power Institute. The All-Union Thermo-Technical Institute accordingly investigated the influence of flow pulsation, and of the length of pipe heated, on critical thermal loading. A diagram of their experimental rig is given in Fig 2 and it is briefly described. The experimental procedure and methods of measurement are also recounted. In order to determine the influence of throttling on critical thermal loadings, tests were made with the throttling valve in

Card 2/6

SOV/96-59-9-15/22

The Influence of Throttling the Flow and of Heating a Length of Pipe on Critical Thermal Loadings

different positions, with different rates of flow, and with water heated to different temperatures. The results of the tests are plotted in Fig 3 and they show that turbulence caused by throttling at the inlet has no influence on the critical thermal load. Moreover, the results confirm that any effect of throttling is not due to the flow becoming turbulent. The effect only alters the large pulsations of working fluid leaving the heat exchanger in the Power Institute's equipment. The way in which the pulsations could occur in the heat exchanger is explained. Two series of tests were run to check the explanation; the results, plotted in Fig 4, confirm that pulsations really do reach the measuring section. Unfortunately, low-inertia instruments were not available and the magnitude of the pulsation could only be judged by movements of the manometer needles. The question of the influence of the length of the tube heated is of considerable importance as most laboratory rigs use relatively short tubes whilst long tubes are found in practice. Tests were accordingly made with water and

Card 3/6

SOV/96-59-9-15/22

The Influence of Throttling the Flow and of Heating a Length of Pipe on Critical Thermal Loadings

steam/water mixture on tubes of various lengths at a pressure of 100 atms. To ensure that the installation was similar in other respects the only change made was to make one of the electric contacts moveable. In order to check the rate of flow a cooler, which is not shown in Fig 2, was installed at the outlet from the experimental section in order to condense the steam/water mixture to a single-phase liquid. Two series of tests were run at a pressure of 100 atm; the test conditions are given and the test results are plotted in Figs 5 and 6. They show that the length of tube heated has practically no influence on the critical thermal loading for the ratios of length to diameter investigated. The lack of experimental points on the right-hand side of the graph in Fig 5 results from the fact that critical conditions do not arise at high rates of flow and steam contents around 0.5. Returning again to the experimental results of the Power Institute concerning the influence of the length of tube heated, it is assumed that they reached their conclusion because they disregarded the important pulsations of working substance that occur in their apparatus.

Card 4/6

SOV/96-59-9-15/22

The Influence of Throttling the Flow and of Heating a Length of Pipe on Critical Thermal Loadings

To confirm this the present experiments on tubes of different lengths were repeated with pulsation present. The results are plotted in Fig 7 and Fig 8, where the straight lines correspond to the mean results obtained for tubes of various lengths in tests without pulsation (Figs 5 and 6). The peculiar shape of the curves obtained in the presence of pulsation is explained as being due to differences in the steam content in the water in different parts of the pipe at different times. It is only when conditions are such that steam/water mixture is present throughout the pipe that the curves come into line with those obtained in the absence of pulsation. This confirms that the results attributed by the Power Institute of the Ac. Sc. USSR to other factors are really due to pulsation. The important part played by pulsation flow in governing critical heat transfer has no direct relationship to the selection of permissible heat loadings in vessels containing water under pressure because, in the absence of a steam phase in the first circuit, there is no reason for pulsations to arise. Disturbances of

Card 5/6

SOV/96-59-9-15/22
The Influence of Throttling the Flow and of Heating a Length of
Pipe on Critical Thermal Loadings

flow due to local resistances have much less influence
on critical thermal loadings than pulsations caused by
Card 6/6 steam condensation.

There are 8 figures and 7 Soviet references.

ASSOCIATION: Vsesoyuznyy teplotekhnicheskiy institut
(All-Union Thermo-Technical Institute)

FRID, G.S., kandidat ekonomicheskikh nauk.

Economic problems of contact and nonreactive splitting of fats.
Masl.-shir.prom. 19 no.1:26-28 '54. (MLRA 7:2)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut zhirov.
(Oils and fats)

FRID, G.S.

High-quality products from the processing of cottonseed in screw
presses. Masl.-zhir.prom.21 no.1:35 '56. (MIRA 9:6)
(Cottonseed oil)

FRID, G.S.

Development of the extraction process (J. Amer. Oil Chemists' Sec.,
no.4 1954). Masl.-zhir.prom. 21 no.3:40 '56. (MLRA 9:8)
(Oils and fats)

FRID, G.S.

Prepressing and extraction of cottonseed, technical conditions and characteristics of the finished products (J Amer.Oil Chemists' Soc., no.2 1955). Masl.-shir.prom. 21 no.3:40 '56. (MLRA 9:8)
(Cottonseed oil)

YASNYI, A.M. [deceased]; FRID, G.S.

Fats and oils in capitalist countries. Masl.-zhir.prom.22 no.4:
29-30 '56. (MIRA 9:9)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut zhirov.
(Oils and fats)

FRID, G.S.

AKATOV, S.K.; FRID, G.S., kandidat tekhnicheskikh nauk.

Use and economic effectiveness of lift trucks in loading and unloading.
Masl.-zhir, prom. 23 no.5:32-34 '57. (MLRA 10:5)

1. Leningradskiy mylovarennyy zavod im. Karpova.
(Loading and unloading) (Industrial power trucks)

FRID, G.S., inzh.

From foreign patent literature on oil industries. Masl.-zhir.
prom. 27 no. 4:44-46 Ap '61. (MIRA 14:4)
(Bibliography—Oil industries)

AKATOV, S.K., inzh.; KHARITONOV, A.A., inzh.; LOZNER, G.Ye., inzh.; FRID, G.S.,
inzh.

Economic efficiency of the utilization of carbon dioxide. Masl.-zhir.
prom. 28 no.8:25-26 Ag '62. (MIRA 17:2)

1. Leningradskiy mylovarennyy zavod imeni Karpova.

FRID, G.S., inzh.

Liquid shortenings. Masl.-zhir.prom. 28 no.8:46-47 Ag '62.
(MIRA 17:2)

FRID, G.S., inzh.

From foreign literature on patents in the oils and fats industry.
Masl.-zhir. prom. 28 no.10:42-43 0 '62. (MIRA 16:12)

FRID, G.S., inzh.

From the foreign patent literature of the fats and oils industry.
Masl.-zhir.prom. 29 no.1:44-46 Ja '63. (MIRA 16:2)
(Oils and fats—Patents)

FRID, G.S., inzh.

Review of articles from periodicals concerning the oil and fat
industry. Masl.-zhir. prom. 29 no.3:43-45 Mr '63.

(MIRA 16:4)

(Bibliography--Oils and fats)

FRID, I.A., starshiy prepodavatel'

Application of linear programming in determining the optimum
production program of a spinning and weaving factory. Tekst.prom.
25 no.2:21-26 F '65. (MIRA 18:4)

1. Kafedra vysshey matematiki Moskovskogo tekstil'nogo instituta.

FRID, I. A.

Frid, I. A. On the stability of solutions of a linear differential equation with retardation in the critical case. *Moskov. Gos. Univ. Uč. Zap. 181. Mat. 8* (1956), 73-82. (Russian)

1-F/W

The extension of the Poincaré-Lyapunov stability theory to nonlinear differential-difference equations has been considered by the reviewer [*Ann. of Math.* (2) 50 (1949), 347-355; MR 10, 715] and by E. M. Wright [*Proc. Roy. Soc. Edinburgh. Sect. A.* 63 (1949-50), 18-26; MR 12, 106]. The author considers the problem under the assumption that a finite number of roots of the characteristic equation have real part zero, and the remainder have real parts which are uniformly negative.

R. Bellman (Santa Monica, Calif.)

FRID, I. A.

Anesthesia in radical operations for tumors of the sigmoid and
rectum. Vop. onk. 8 no.2:35-44 '62. (MIRA 15:2)

1. Iz 1-go khirurgicheskogo otdeleniya (zav. - chl.-korr. AMN
SSSR, prof. S. A. Kholdin) i 2-go khirurgicheskogo otdeleniya
(zav. - chl.-korr. AMN SSSR, prof. A. I. Rakov) Instituta
onkologii AMN SSSR (dir. - deystv. chl. AMN SSSR, prof. A. I.
Serebrov)

(ANESTHESIA) (COLON—TUMORS) (RECTUM—TUMORS)

FRID, I.A.: LEBEDEVA, L.V.

Artificial hypotension in the surgery of malignant neoplasms.
Vop. onk. 6 no.3:41-48 Mr '60. (MIRA 14:2)
(HYPOTENSION) (CANCER)

LEBEDEV, L.V.; FRID, I.A.

Experience in the use of controlled hypotension in surgical practice.
Khirurgia 36 no.7:9-17 Je '60. (MIRA 13:12)
(HYPOTENSION) (AUTONOMIC DRUGS)

FRID, I. A.

Artificial hypotension in radical operations for tumors of the sigmoid and rectum. Vop. onk. 8 no.4:30-36 '62. (MIRA 15:4)

1. Iz 1-go khirurgicheskogo otdeleniya (zav. - chl.-korr. AMN SSSR, prof. S. A. Kholdin) i 2-go khirurgicheskogo otdeleniya (zav. - chl.-korr. AMN SSSR, prof. A. I. Rakov) Instituta onkologii AMN SSSR (dir. - deystv. chl. AMN SSSR, prof. A. I. Serebrov)

(RECTUM—TUMORS) (INTESTINES—TUMORS)
(HYPOTENSION)

FRID, I. L.

USSR/Engineering - Tools

Card 1/1

Author : Frid, I. L.
Title : An Attachment for the Simultaneous Cutting of Two Wire Rods
Periodical : Stan. i Instr. Ed. 1, 31, Jan/1954
Abstract : An attachment used on shearing dies for clamping wire rods is described. According to the author this arrangement speeds up the cutting operations of wire rods (up to 100 mm thick) by 80%. Drawings.
Institution :
Submitted :

FRID, I.L., inzh.

Section of the foreman Evgenii Shershnev. Mashinostroitel'
no.1:19-22 N '56. (MIRA 12:1)

1. Zavod imeni Vladimira Il'icha.
(Assembly line methods)

FRID, I. P.; GREBENKOV, A. V.

The MLI, 5 sheet-stamping air hammer. Biul. tekhn.-ekon. inform. Gos.
nauch.-issl. inst. nauch. i tekhn. inform. 16 no. 5:19-20:63.

(Sheet-metal work—Equipment and supplies) (MIRA 16:7)

FRID, I.P.

Introducing the K3537 press. Biul. tekhn.-ekon. inform. Gos.
nauch.-issl. inst. nauch. i tekhn. inform. 18 no.3:27-28
Mr '65. (MIRA 18:5)

FRID, I.P.

Introducing the K'934 horizontal straightening press. Bul.tekh.-
ekon.inform.Gos.nauch.-obshch.inst.nauch. i tekhn.inform. 18 no.4:20-
21 Ap '65. (MIRA 18:6)

POPESKO, Petr[Popesko, Peter]; AKAYEVSKIY, Anatoliy Ivanovich, prof.-doktor [translator]; ERID, K., prof., doktor, retsenzent; KOMAREK, V., dots. doktor, retsenzent; SHUTTA, Yu.[Sutta, J.], dots. doktor, retsenzent; KRIPPEL, Mikulash, doktor, red. izd-va; ELUSKA, Jan, tekhn. red.

[Atlas of the topographical anatomy of farm animals] Atlas topograficheskoi anatomii sel'skokhoziaistvennykh zhiivotnykh. Bratislava, Slovatskoe izd-vo sel'khoz. lit-ry. Vol.2.[Trunk] Tulovishche. 1962. 200 p. (MIRA 16:4)
(Veterinary anatomy--Atlases)

