

82588

S/022/60/013/01/10/010
C 111/ C 333

Depolarization of the Bundle Under Motion in an Inhomogeneous Magnetic Field

The dispersion of angles resulting from the oscillations of the particles is then

$$(5) \Delta\psi' = 2\pi \frac{\Delta\mu}{\mu} \frac{E}{me^2} \frac{2m - n - n^2}{2(1-n)} \frac{\bar{r}^2 - \bar{z}^2}{s^2} \frac{t}{T_0},$$

where $\frac{\Delta\mu}{\mu}$ is the relative deviation of the magnetic moment from the Dirac value.

There are 2 non-Soviet references: 1 Italian and 1 American.

ASSOCIATION: Fizicheskiy institut AN Armyanskoy SSR (Physical Institute AS Armyanskaya SSR)

SUBMITTED: June 28, 1959

Card 2/2

KHEYFETS, S. A., Cand Phys-Math Sci -- "Loss^{ed} of particles in modern circular-orbit accelerators." Mos, 1961 (Inst of Theoretical and Experimental Phys, Acad Sci USSR). (KL, 4-61, 186)

-51-

21.2000

22783

S/057/61/031/005/014/020
B104/B205

AUTHORS: Kheyfets, S. A. and Baryshev, A. I.

TITLE: Transition processes in an accelerating system, caused by injection of particles

PERIODICAL: Zhurnal tekhnicheskoy fiziki, v. 31, no. 5, 1961, 606-612

TEXT: A study has been made of the changes of amplitude, phase, and frequency of the accelerating voltage, which are caused by injection of particles. In doing so, the authors confined themselves to a continuous injection of particles. In this case, the formulas for the transition processes due to a pulsed injection can be derived from the formulas presented here for the transition $\delta \rightarrow \infty$. The variation of load in time is a characteristic feature of continuous injection. The losses suffered by accelerated and slowed down particles in a strongly focusing accelerator are equal. The time dependence of the load is given by $\alpha_n(t) = \alpha_n(1 - \exp(-\delta t))$ (1), and the phase shift caused by the rated current of the accelerator is found to be $\Delta\omega(t) = \Delta\omega(1 - \exp(-\delta t))$ (2).

Card 1/5

Transition processes in an...

22783

S/057/61/031/005/014/020
B104/B205

If the relations $\omega_H = \omega_0 + \Delta\omega$ and $\alpha_H = \alpha_0 + \alpha_n$ are valid (ω_0 and α_0 stand for the frequency and the decrement, respectively, up to injection), the variation of the accelerating voltage can be described by

$$\ddot{u} + 2(\alpha_H - \alpha_0 e^{-\alpha_0 t})\dot{u} + (\omega_H^2 - \alpha_0^2 e^{-2\alpha_0 t})u = \frac{I_0 \omega_0}{C_0} \cos(\omega_0 t + \psi) \left(\dot{u} = \frac{du}{dt} \right), \quad (3)$$

Next, the authors derive the two conjugate complex roots

$$p = \frac{\alpha_H + \sqrt{\alpha_H^2 - \omega_H^2}}{\delta} \approx \frac{\alpha_H + i\omega_H}{\delta}, \quad (10)$$

$$p^* = \frac{\alpha_H - \sqrt{\alpha_H^2 - \omega_H^2}}{\delta} \approx \frac{\alpha_H - i\omega_H}{\delta}; \quad \alpha_H \ll \omega_H, \quad (11)$$

which offer two linearly independent solutions to (3). By variation of parameters one obtains

$$U_{\text{accel.}} = \frac{\omega_0}{C_0} e^{-\alpha_H t} \left\{ \frac{F(\beta; \gamma; -\frac{2\alpha_n}{\delta} e^{-\alpha_0 t}) e^{i\omega_H t}}{\gamma_0} \times \right.$$

$$\left. \times \int_0^t \int_0^t F(\beta; \gamma; -\frac{2\alpha_n}{\delta} e^{-\alpha_0 t}) e^{-\alpha_H t - \frac{2\alpha_n}{\delta}(1-e^{-\alpha_0 t}) - i\omega_H t} \cos(\omega_0 t + \psi) dt + \text{c.c.} \right\}, \quad (12)$$

Card 2/5

22783

S/057/61/031/005/014/020
B104/B205

Transition processes in an...

where ∇_0 is the Wronski equation of (3) at $t = 0$. As a general solution, one obtains

$$u = Ge^{-\gamma t} F\left(\beta; \gamma; -\frac{2\alpha_2}{\delta} e^{-\delta t}\right) + C^* e^{-\gamma^* t} F\left(\beta^*; \gamma^*; -\frac{2\alpha_2^*}{\delta} e^{-\delta t}\right) + u_{\text{particular}}(\beta)$$

Here, C and C^* are arbitrary constants which are to be determined from the initial conditions. It is evident that, if the accelerating system is adjusted to the frequency ω_0 without a load, the initial conditions for $\omega_H/\delta \gg 1$ are given by

$$u|_{t=0} = \frac{I_0}{2C_0\alpha_0} (1 - e^{-\alpha_0 t}) \sin \psi,$$

$$\dot{u}|_{t=0} = \frac{I_0\omega_0}{2C_0\alpha_0} (1 - e^{-\alpha_0 t}) \cos \psi.$$

(B)

Thus, the solution of (3) for $\omega/\delta > 1$ can be represented in the form $u = D(t) \cos[\omega_0 t + \Phi(t)]$ (13), where D is an envelope, and Φ is the phase of the accelerating voltage. If the reduced parameters $l = \alpha_n/\delta$; $m = \alpha_H/\delta$; $n = \Delta\omega/\delta$ are introduced, the two functions can be represented by

$$D(x) = \frac{I_0}{2C_0\alpha_0} e^{-(m+lr-x)} \sqrt{(a_1 + a_2)^2 + (b_1 + b_2)^2}, \quad (14)$$

$$\Phi(x) = \psi + n(x + e^{-x}) - \arctg \frac{b_1 + b_2}{a_1 + a_2}, \quad (15)$$

Card 3/5

22783

S/057/61/031/005/014/020
B104/B205

Transition processes in an...

for which case the notations

$$a_1 = (1 - e^{-x}) e^j \cos n, \quad (16)$$

$$b_1 = (1 - e^{-x}) e^j \sin n, \quad (17)$$

$$a_2 = (m - l) \int_0^x e^{ms + i\tau - s} \cos(nx + ne^{-s}) dx, \quad (18)$$

$$b_2 = (m - l) \int_0^x e^{ms + i\tau - s} \sin(nx + ne^{-s}) dx. \quad (19)$$

are valid. The time dependence of the phase of the voltage acting upon the particles leads to a shift of the voltage frequency by $\Delta\omega(t) = d\varphi/dt$. It can easily be shown that at $x \rightarrow 0$ the functions D , φ , and $\Delta\omega$ tend toward a value that corresponds to the values holding before particle injection. For $x \rightarrow \infty$ these functions tend toward values that correspond to continuous operation with a load. Variations in amplitude, frequency, and phase of the accelerating voltage lead to deviations of the beam parameters from the rated values. These deviations are largely dependent on the current strength of the particles. The frequency

Card 4/5

22783

S/057/61/031/005/014/020
B104/B205

Transition processes in an...

deviation of the accelerating voltage leads to a variation in the radius of the equilibrium orbit of the particles. This may lead to a complete loss of the beam. The frequency shift limits the particle currents if no precautionary measures are taken. Small particle currents do not lead to any significant frequency shifts. These results have been obtained without accounting for the effects of these processes upon the beam. Yu. F. Orlov, A. G. Sal'man, and S. K. Yesin are thanked for valuable comments and their interest in the work, as well as V. S. Pogosyan and B. M. Teryan for numerical computations. V. V. Yekimov is mentioned. There are 5 figures and 1 Soviet-bloc reference.

SUBMITTED: May 16, 1960

Card 5/5

25029

S/057/61/031/007/010/021
B104/B206

24.6730

AUTHORS: Kheyfets, S. A., Orlov, Yu. F., and Gendzhoyan, G. V.
TITLE: Particle losses in an electron accelerator resulting from quantum fluctuations of radiation (phase oscillations)
PERIODICAL: Zhurnal tekhnicheskoy fiziki, v. 31, no. 7, 1961, 824-829
TEXT: The magnetic field of an annular electron accelerator is usually changed according to the relation $H \approx H_0(1 - \cos \omega t)$. Orlov et al. (PTE, no. 5, 17, 1958) showed that for $|\cos \omega t| < 5/6$ and $H < 1.8 H_0$, the mean square amplitude of the phase oscillations may be described by

$$\overline{A^2} = BF_p(\zeta), \quad (1)$$

$$F_p(\zeta) = \zeta^{-1/2} (1 + \zeta)^{-1/2} e^{-(1+\zeta)} \int_0^{\zeta} (1+u)^{-1/2} u^{1/2} e^{(1+u)} du, \quad (2)$$

Card 1/6

Particle losses in an electron ...

25022

S/057/61/031/007/010/021
B104/B206

$\xi = P_r / \dot{\epsilon} = \Delta \xi_{\text{rad}} / U$ is the relation of the emission intensity of electrons in a magnetic field with the energy increment $\dot{\epsilon}$. ξ increases quickly with increasing particle energy. The parameter β depends on the coupling of radial- and phase oscillations, and determines radiation attenuation. In strongly focusing accelerators $\beta = 0$; in weakly focusing ones, $\beta = -\{4(1-n)\}^{-1}$. If in a strongly focusing accelerator, a variation of the magnetic field along the orbits is used to attenuate the radial oscillations, the radiation attenuation can be described by the decrements

$$\gamma_{\phi} \approx 4(1+\beta) \frac{P_r}{\dot{\epsilon}}; \int_0^t \gamma_{\phi} dt' \approx (1+\beta)\zeta, \quad (3)$$

$$A^2 = A_0^2 \exp \left(- \int_0^t \gamma_{\phi} dt' \right). \quad (4)$$

Card 2/6

Particle losses in an electron ...

25029

S/057/61/031/007/010/021:
B104/B206

The parameter B is then

$$B = 0.84 q \alpha \sigma_2 \sigma_3 L^{-1/2} \left(\frac{mc^2}{U} \right)^{1/2} \left(\frac{R}{L} \right)^{1/2}, \quad (5),$$

where L and R are length and curvature radius of the orbit in meters,
 $\sigma_2 = \left\langle \frac{H^2}{H_0^2} \right\rangle$, $\sigma_3 = \left\langle \frac{|H|^3}{H_0^3} \right\rangle$, q the multiplicity of the frequency of the ac-

celeration voltage, α the logarithmic differential quotient of the orbit
 length with respect to the pulse, Φ_s the equilibrium phase (with $\Phi = 0$, the
 voltage of the acceleration field attains a maximum). If the oscillations
 can be assumed as linear, the kinetic equation for the distribution func-
 tion of the amplitudes, which takes account of the stochastic oscillations
 as well as the attenuation of the oscillation, may be brought into the form
 of the equations

$$\frac{\partial \Phi}{\partial x} = \frac{\partial}{\partial x} \left(x \frac{\partial \Phi}{\partial x} + x \Phi \right), \quad (6)$$

Card 3/6

25029

S/057/61/031/007/010/021
B104/B206

Particle losses in an electron ...

where

$$z = \frac{a}{\tau+1}, \quad dx = \frac{d\tau}{\tau+1}, \quad (7)$$

$$a = \frac{A^2}{A_{\text{non}}^2} \exp \int_0^t \gamma dt'; \quad \tau = \frac{A^2}{A_{\text{non}}^2} \exp \int_0^t \gamma dt' \quad (8).$$

If $A_{\text{permissible}}$ is the maximum permissible oscillation amplitude,
 $A_{\text{permissible}}^2 = \Phi_{\text{permissible}}^2 = \Phi^2 / \Omega^2$ (where Ω is the frequency of the phase)
 holds for linear phase oscillations. If $\Phi = C(\cos \Phi_s - \cos \Phi)$ holds for
 nonlinear phase oscillations, $A_{\text{permissible}}^2 = 4(1 - \Phi_s \cot \Phi_s)$ may be written
 down approximately. For the number of particles participating in the
 acceleration up to the "moment" $\zeta \sim 1$, formula

$$n(\zeta) \approx n(0) \exp \left\{ -(1+\beta) \int_{\zeta}^{\zeta} \frac{A_{\text{non}}^2}{A^2} \exp \left(-\frac{A_{\text{non}}^2}{A^2} \right) d\zeta \right\}. \quad (14)$$

Card 4/6

25029

Particle losses in an electron....

S/057/61/031/007/010/021
B104/B206

is given which agrees with that by K. B. Robinson (Intern. Conf. on High-Energy Accel. a. Instr., CERN, p. 293, 1959). Calculation results for $n(\zeta)$, which were made at the Computer Center of the AS Armyanskaya SSR by means of (14), are shown in some diagrams. It may be seen that the quantum-oscillations due to emission begins at $\zeta > 1$ and that the approximation formula

$$n(\zeta) = n(0) \exp \left\{ \int_0^{\zeta} \alpha_0(x') dx' \right\}, \quad (11)$$

can be used for $B_1 \ll 0.3$. The losses strongly depend on B_1 and β . The authors thank the collaborators of the Computer Center, R. A. Aleksandryan, T. M. Ter-Mikayelyan and A. G. Piliposyan for their assistance. There are 7 figures and 11 references: 7 Soviet-bloc and 4 non-Soviet-bloc.

ASSOCIATION: Fizicheskiy institut AN Arm. SSR (Physics Institute, AS Armyanskaya SSR). Vychislitel'nyy tsentr AN Arm. SSR (Com-
Card 5/6

Particle losses in an electron ...

25029

S/057/61/031/007/010/021
B104/B206

puter Center, AS Armyanskaya SSR)

SUBMITTED:

August 31, 1960

Card 6/6

S/056/61/040/002/033/047
B112/B214

AUTHORS: Bayyer, V. N., ~~Kheyfets, S. A.~~

TITLE: Electron-electron scattering at large energies

PERIODICAL: Zhurnal eksperimental'noy i teoreticheskoy fiziki, v. 40,
no. 2, 1961, 613-615

TEXT: An approximate calculation of the electron-electron scattering cross section at high initial energies E and at an angle of scattering $\theta \gg m/E$ is made in the present paper following a method proposed by A. A. Abrikosov (Ref. 3: ZhETF, 30, 96, 386, 1956). In the determination of the cross section by the method of perturbation it is not possible to restrict oneself to the lowest order because the higher approximations contain the high value $e^2 \ln^2(E/m)$. According to a suggestion of Abrikosov, only those terms are taken into account, in which the highest powers of $e^2 \ln^2(E/m)$ appear. For selecting such terms, certain conditions are formulated. If ω is the maximum energy of the emitted photon, the

differential scattering cross section is given by: $d\sigma = d\sigma_0 \exp \left[-\frac{8e^2}{\pi} \ln \frac{E}{\omega} \ln \frac{E}{\omega} \right]$. ✓

Card 1/2

BAYYER, V.N.; KHEYFETS, S.A.

Behavior of the cross section of electromagnetic particle
production at the threshold. Zhur. eksp. i teor. fiz.
40 no.2:715-717 F '61. (MIRA 14:7)
(Particles (Nuclear physics))

35473
S/109/62/007/003/016/029
D256/D302

24.6730

AUTHORS: Baryshev, A.I., and Khayrets, S.A.

TITLE: Influence of a beam in an electron accelerator upon
the accelerating system

PERIODICAL: Radiotekhnika i elektronika, v. 7, no. 3, 1962,
483 - 490

TEXT: The electric field generated by the beam of electrons of modern high-energy accelerators as a rule impedes the acceleration, being shifted in phase against the accelerating voltage and changing the load conditions of the external generator. In certain circumstances the energy output of the generator is transferred to excite undesired harmonic oscillations, increasing considerably the required power output and causing excessive thermal losses in the resonators. The authors investigate the effect of excitations of a cylindrical resonator by a beam of relativistic electrons and examine its influence on the performance of the generator. Formulas expressing the amplitude and the phase of the voltage generated by

Card 1/2

Influence of a beam in an ...

S/109/62/007/003/016/029
D256/D302

the beam are derived, assuming a constant velocity of electrons and uniform density of particles along the bunch, the transverse component of the velocity being neglected. It is shown that a beam of circular cross-section travelling axially along the cylindrical resonator can generate E_{m10} -type oscillations; however, for non-circular cross-section of the beam oscillations with $n \neq 0$ will also occur, mainly with $n = 1$. For the resonant harmonic the maximum of the voltage generated by the beam coincides with the moment when the center of the particle bunch crosses the center of the resonator. Based upon an equivalent diagram the effect on the system of the oscillation generated by the electrons is considered. Formulas for modulation of the external generator are derived expressing the modulus and the phase of the voltage applied across the load necessary to obtain the required accelerating voltage in the presence of the voltage generated by the beam. It is pointed out that the phase oscillations were taken into account. There are 4 figures and 2 Soviet-bloc references.

SUBMITTED: May 15, 1961

Card 2/2

S/057/62/032/008/003/015
B104/B102

24 6742.

AUTHORS: Orlov, Yu. F., and Kheyfets, S. A.

TITLE: Particle losses due to multiple Coulomb scattering in a cyclotron accelerator

PERIODICAL: Zhurnal tekhnicheskoy fiziki, v. 32, no. 8, 1962, 919 - 923.

TEXT: The mean square amplitude of the betatron oscillations produced by multiple Coulomb scattering is

$$A^2 = \frac{B}{\sqrt{x^2 - 1}} \left(\operatorname{arch} x - \operatorname{arch} x_0 - \frac{x}{\sqrt{x^2 - 1}} + \frac{x_0}{\sqrt{x_0^2 - 1}} \right), \quad (12)$$

$$B = \frac{4|\Phi|_{\max}^2 |\Phi|^2}{\pi \omega^2 A_{\text{osc}}^2} \frac{NL^3}{M^2 V} \frac{(Ze^2)^2}{m c^2} L \quad (13)$$

$$2i\omega = \Phi \frac{d\Phi}{d\theta} - \Phi \frac{d\Phi^*}{d\theta}, \quad (14)$$

where $\tilde{\epsilon}$ is the total particle energy, $\tilde{\epsilon}_{\text{inj}}$ the injection energy, L the orbit length, Φ a Floke's function describing the betatron oscillations,

Card 1/2

S/058/63/000/001/023/120
A062/A101

AUTHOR: Orlov, Yu. F., Kheyfets, S. A.

TITLE: Calculation of parameters of a strong focusing accelerator taking into account the stray fields

PERIODICAL: Referativnyy zhurnal, Fizika, no. 1, 1963, 42, abstract 1A404
(In collection: "Elektron. uskoriteli". Tomsk, Tomskiy un-t, 1961, 145 - 148)

TEXT: Calculation of a strong focusing accelerator with a real magnetic field (taking into account the stray fields) is mathematically complicated. Therefore one proceeds by first determining "ideal" accelerator parameters which have then to be recalculated more precisely in conformity with the results of magnetic measurements. For such a recalculation it is suggested to use the perturbation theory by considering the deviations of the field and its gradient from the "ideal" values as small. With the thus improved accuracy the accelerator parameters satisfy the invariability condition of the betatron oscillation frequencies and of the equilibrium orbit. The equations obtained from this condition can

Card 1/2

Calculation of parameters of...

S/058/63/000/001/023/120
A062/A101

be satisfied by a suitable choice of the field index n and of the lengths of the
rectilinear gaps and magnetic sectors.

A. Pateyev

[Abstracter's note: Complete translation]

Card 2/2

BARYSHEV, A.I.; KHEYFETS, S.A.

Effect of the beam of an electron accelerator on its accelerating
system. Radiotekh. i elektron. 7 no.3:483-490 Mr '62. (MIRA 15:2)
(Electron beams)
(Oscillators, Electric)

ORLOV, Yu.F.; KHEYFETS, S.A.

Particle loss due to multiple Coulomb scattering in a cyclotron.
Zhur.tekh.fiz. 32 no.8:919-923 Ag '62. (MIRA 15:8)
(Cyclotron)

KHEYFETS, Semen Abramovich; KHARITONO, V.M., otv. red.; ANDREASYAN,
V.B., red. izd-va; GOROYAN, G.L., tekhn.red.

[The electron synchrotron] Elektronnyi sinkhrotron. Erevan,
Izd-vo AN Arm.SSR, 1963. 185 p. (Akademiia nauk Arm.SSR.
Nauchno-popyliarnaiia seriia, no.3) (MIRA 16:8)
(Synchrotron)

ORLOV, Yu.F.; KHEYFETS, S.A.

Radiation damping of free oscillations. Dokl. AN SSSR 151
no.2:318-319 J1 '63. (MIRA 16:7)

1. Predstavleno akademikom V.I.Vekslerom.
(Quantum electrodynamics)

S/057/63/033/003/010/021
B104/B180

AUTHORS: Baryshev, A. I., and Kheyfets, S. A.

TITLE: Effect of induced voltage on the phase oscillations of the particle bunch in an accelerator

PERIODICAL: Zhurnal tekhnicheskoy fiziki, v. 33, no. 3, 1963, 320-325

TEXT: A particle beam passing through a resonator in an accelerator induces a voltage. The present paper deals with the coupling caused by this voltage between the field oscillations in the resonator and the phase oscillations of the bunch particles. It is shown that if the natural frequency is greater than that of the generator, the frequency and the decrement of the phase oscillations will fall. If the accelerated particle currents are high and the phase constant is low, the longitudinal motion becomes unstable and attenuation changes into anti-attenuation. If $\eta = \Delta\omega/\beta > 0$ frequency and decrement of attenuation rise and the phase oscillations become stable and attenuate more rapidly. Here, β is the attenuation decrement. It is therefore better to choose quite a high equilibrium phase and tune the resonator
Card 1/2

S/057/63/033/003/010/021

Effect of induced voltage on the phase ... B104/B180

to a frequency slightly below that of the external generator. There are 2 figures.

SUBMITTED: March 7, 1962

Card 2/2

ACCESSION NR: AT4014036

S/2918/63/000/000/0496/0507

AUTHOR: Kheyfets, S. A.

TITLE: Progress in the techniques of storage of clashing beams

SOURCE: AN ArmSSR. Fizicheskiy institut. Voprosy* fiziki elementarny*kh chastits, 1963, 496-507

TOPIC TAGS: clashing beams, storage ring, high energy storage ring, beam lifetime, beam size, injection, current limitation, plasmoid interaction, strong focusing

ABSTRACT: The problems arising in the study of the possibility of constructing storage rings for high energies are discussed on the basis of experiments gained with small storage rings (with energy less than 500 MeV in each beam). The reported results pertaining to small storage rings deal with the lifetime of the beam in the ring, the transverse beam dimensions, the attainment of very high

Card 1/2

ACCESSION NR: AT4014036

vacuum, injection, and experiments with clashing beams. The problems specific to large storage rings include limitation of the current due to plasmoid interaction, and strong focusing in large storage rings. The status of several storage rings under construction is discussed, with emphasis on the Italian Adone project. Orig. art. has: 3 figures and 8 formulas.

ASSOCIATION: Fizicheskiy institut AN ArmSSR (Physics Institute, AN ArmSSR)

SUBMITTED: 00

DATE ACQ: 20Feb64

ENCL: 00

SUB CODE: PH

NO REF SOV: 005

OTHER: 004

Card 2/2

KHEYFETS, S.A.; ORLOV, Yu.F.

Theory of radiative damping of radial oscillations of an electron
in a magnetic field. Zhur. eksp. i teor. fiz. 45 no. 4:1225-1229
O '63. (MIRA 16:11)

1. Fizicheskii institut Gosudarstvennogo komiteta po ispol'zova-
niyu atomnoy energii SSSR, Yerevan.

AUTHOR: Kheyfets, S. A.; Yasin, S. K.

Simple method for measuring free transverse oscillation frequencies in a
synchrotron

1965, *Plasma energiya*, v. 18 no. 1, 1965, 6

synchrotron, particle motion, perturbation

An attempt was made to measure particle transverse oscillation frequencies in the equilibrium orbit local, time-independent perturbations. The method developed with the assumption that the particle motion is periodic and the induced local perturbations are small. The method is applicable to the betatron oscillations. (orig. and trans. in Russian)

Card

1/1 50

KHEYFETS, S.B.; ILINICH, B.K., red.; TRUSOV, N.S., tekhn. red.

[Finances of regional service industry and enterprises]
Finansy raionnoi promyshlennosti i predpriatii bytovogo ob-
sluzhivaniia. Moskva, Gosbytizdat, 1963. 129 p.
(MIRA 16:12)

(Service industries--Finance)

KHEYFETS, S.B.

New laboratory equipment for comminution of materials into fine particles. Zav.lab. 27 no.5:610-612 '61. (MIRA 14:5)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut novykh stroitel'nykh materialov.
(Crushing machinery)

AKUNOV, V.I.; KHEYFETS, S.B., inzh., retsenzent; VASILENKO, A.N.,
red.; TAIROVA, A.L., red. izd-va; SMIRNOVA, G.V., tekhn. red.

[Jet mills; elements of theory and design]Struinye mel'nitsy;
elementy teorii i rascheta. Moskva, Mashgiz, 1962. 263 p.

(MIRA 15:10)

(Milling machinery)

KHEYFETS S. G.

PA 10T71

USSR/Steel Alloys
Metallurgy

Apr 1947

"Surface Quality and Fatigue Resistance," S. G.
Kheyfets, 8 pp

"Vestnik Mashino" Vol XXVII, No 4

Mathematical discussion of the effect of cuts and
scratches on the durability of metals, chiefly steel
alloys. Fully illustrated with tables, formulae and
graphs.

10T71

1ST AND 2ND ORDERS										3RD AND 4TH ORDERS									
PROCESSES AND PROPERTIES INDEX																			
B 13 Additional Stresses in Fatigue Test Specimens. (In Russian.) S. G. Kheifets. Zavodskaya Laboratoriya (Factory Laboratory), v. 14, June 1948, p. 742-748. Heat developed during operation of the cantilever fatigue-test machine, caused by irregularity of the test specimens, results in additional stresses which change the true fatigue strength of the material. Methods of calculation of such stresses are indicated.																			
ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION										E-2000-1000-1000									
10000 10000 10000 10000 10000 10000 10000 10000 10000 10000										10000 10000 10000 10000 10000 10000 10000 10000 10000 10000									

KHEYFETZ, S. G.

PA. 37/49T82

USSR/Engineering
Stress Analysis

Sep 48

"The Effect of Size on the Limits of Durability,"
S. G. Kheyfetz, Cand Tech Sci, TsNIITMASH, 3 $\frac{1}{2}$ pp

"Vest Mashinostroy" Vol XXVIII, No 9

Describes experiments to ascertain influence of
size of specimen on results obtained from fatigue-
testing machines, with four sketches.

PMB

37/49T82

KHEYFETS, S. G.

"Effect of size of specimen on fatigue strength," Investigation of the Fatigue Strength of Structural Steels, 120 p., Published by Mashgiz, 1949.

KHEYFETS, S.G.

KHEYFETZ, S.G.

"Calculation of the Permissible Tolerances of Ring Shaped Specimens Used for Relaxation Tests"--pp. 89-94

A paper contained in the symposium "A New Method of Investigation of Relaxation and Creep of Metals," edited by I.A. Odling, Mashgiz, 1949

KHEYFETS, S. G.

"Methods for Studying the Fatigue Strength of Steel Under Bending by Asymmetrical Cycles," pp. 134-146 of the book "Studies on the Strength of Steel," Mashgiz, 1951

Translation W-23621, 21 Aug 52

"Selection of Testing Machine Parameters and Permissible Beats of Specimens in Fatigue Testing," pp 178-195 from the above book.

KUDRYAVTSEV, I.V., kandidat tekhnicheskikh nauk, redaktor; SAVERIN, M.M., kandidat tekhnicheskikh nauk; ZAVARTSEVA, V.M., inzhener; SAVKO, L.I., inzhener; KOBRIN, M.M., inzhener; VIDMAN, D.N.; PROSVIRIN, V.I., doktor tekhnicheskikh nauk; MORGUNOVA, N.N., inzhener; ~~KHEIFETS, S.G., kandidat tekhnicheskikh nauk; BRUMBERG, R.M., inzhener.~~

[Studies in the strenth of steel] Issledovaniia prochnosti stali. Moskva, Gos. nauchno-tekhn. izd-vo mashinostroitel'noi lit-ry. Vol. 40. 255 p. 1951
(MLRA 6:5)

1. TSentral'nyy nauchno-issledovatel'skiy institut tekhnologii i mashinostroyeniya Ministerstva tyazhelogo mashinostroyeniya SSSR.

(Steel--testing)

1951

REPRINTS S. G.

Selections of the characteristic parameters of the test machines and the permissible parasitic oscillations of the specimens in endurance (fatigue) tests. - pp. 178 - 195

A paper contained in the symposium "Research Work on the Strength of Steel", edited by I. V. Kudryatseva, Mashgiz, 1951.

KHEDZETZ S. G.

Methods of investigation of the fatigue strength of steel in the case of bending stresses following a non-symmetrical cycle.- pp. 134 - 144.

A paper contained in the symposium "Research Work on the Strength of Steel", edited by I. V. Kudryatseva, Mashgiz, 1951.

VOLYNSKIY, S.L., inzh.; GORYUNOV, P.I., inzh.; ZELLER, Yu.G., inzh.;
Kheyfets, S.I., inzh.

Redesigning the N-11 automatic oscillograph. Elek. sta. 29
no. 11:85-86 N '58. (MIRA 11:12)
(Oscillograph)

LIEGOBER, M.B., insh.; KHEYFETS, S.I., insh.

Synchroniser with permanent time lead in the automatic reclosing
circuit. Elek. sta. 30 no.2:83-84 P '59. (MIRA 12:3)
(Electric power distribution--Equipment and supplies)
(Electric circuit breakers)

KHEYFETS, S.I., inzh.

Registering device with magnetic memory. Elek. sta. 34 no.8:
62-64 Ag '63. (MIRA 16:11)

PAVLOV, I.Ya., master; KHEYFETS, S.Kh., inzhener.

Improved, safe lubricator. Energetik 1 no.2:17 J1 '53. (MLRA 6:8)
(Lubrication and lubricants)

KHEYFETS, S. KH. ENG.

Fuel

Mechanization of auxiliary processes in unloading fuel. Rab. energ. 3 No. 2, 1953.

9. Monthly List of Russian Accessions, Library of Congress, June 1953. Unclassified.

LUR'YE, Z.S., inzh.; KHEYFETS, S.Kh., inzh.; GUR'YEV, D.P., inzh.

Collapse of caked layers in fuel bunkers. Elek.sta. 32
no.8:25-28 Ag '61.

(MIRA 14:10)

(Electric power plants) (Coaling-stations)

KHEYFETS, S.Kh.
ZAPOL'SKIY, M.V.

"PK-2 and PK-2 m. electric caterpillar crane." P.I. Il'in, S.Kh. Kheifets. Reviewed by M.V. Zapol'skii. Torf.prom. 31 no. 7:30 '54.

(MLRA 7:11)

(Cranes, derricks, etc.) (Il'in, P.I.) (Kheifets, S.Kh.)

GUTMAN, A.A., polkovnik med.sluzhby., KHEYFETS, S.L., mayor med.sluzhby

Expanded consultations within the hospital. Voen.-med.shur.
no.11:72-73 N'56 (MIRA 12:1)
(DIAGNOSIS)

KHEYFETS, S.L. (Leningrad)

Treatment of acute bronchitis. Sov. med. 24 no. 10:137-138 0 '60.
(MIRA 13:12)

(BRONCHITIS)

KHEYFETS, S.L. (Leningrad)

Pulmonary cancer in patients with tuberculosis; according to material from a district clinic. Klin.med. 39 no.4:87-91 '61.

(MIRA 14:4)

1. Iz protivotuberkuleznogo dispansera No.12 (Otktyabr'skogo rayona Leningrada (glavnyy vrach A.I. Leporskaya).

(TUBERCULOSIS) (LUNGS—CANCER)

KHEYFETS, S.L. (Leningrad)

Interrelationship of cancer and tuberculosis of the lungs.
Klin.med. 40 no.6:39-42 Je '62. (MIRA 15:9)

1. Iz protivotuberkuleznogo dispansera No.12 (glavnyy vrach
G.G. Yuzhina) i onkologicheskogo punkta (zav. B.S. Vitkin)
Okt'yabr'skogo rayona Leningrada.
(TUBERCULOSIS) (LUNGS--CANCER)

KHEYFETS, S.L. (Leningrad)

Case of poisoning in argon-arc welding. Gig. truda i prof. zab.
7 no.3:49-50 Mr'63 (MIRA 17:1)

1. Leningradskaya poliklinika No.45.

KHEIFETS, S.M.

PROCESSES AND PRIORITIES INDEX

The use of phosphatized castor oil in the fat-liquoring of chrome leather. S. M. Kheifets and S. A. Grevnin. *Azbestovo-Oberaznyy Proizv.* S. S. R. 14, 704-05(1935).

Gradual introduction at 70° of 30% of a 73% H₃PO₄ (d. 1.67) during 24 hrs. into castor oil gave a product of acid no. 282 and d. 1.050, contg. 72.5% fat acids. An emulsion was prepd. by adding 200 g. of 25% NH₃ to 1 kg. of the product. After neutralization, the acid no. was 41.2, org. P₂O₅ 2.70%, and total combined P₂O₅ 3.68%. Fat-liquoring with this prepn. has no advantage compared to other customary fat-liquoring methods. The expts. are described.

A. A. Bochtlingk

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

KEYWORDS										PROCESS AND PROPERTIES INDEX									
ca 9. Manufacture of shuttle leather belts in the plant "Kominarn" in 1944. S. M. Kheifets and N. N. Korshunov. <i>Koskovskaya Obozreniya</i> Prom. 14, 398-400 (1938).—The following operations were introduced to produce higher grade shuttle leather belts: Soaking, straining, unhairing, washing, fleshing, cleaning, cutting, weighing, washing, pickling, tanning, washing, neutralizing, washing, straining, greasing, suspending, resting, suspending, hot fat liquoring, resting in piles, drying on frames, cutting to strips, pumicing and sorting. Details of chemicals used and other mfg. conditions are described. A. A. Bochtlink.										29									
ASB-51A METALLURGICAL LITERATURE CLASSIFICATION																			
10000 10000 10000 10000 10000 10000 10000 10000 10000 10000										10000 10000 10000 10000 10000 10000 10000 10000 10000 10000									

KHEIFETS, S. M.

Imperviousness to water and thickness of the varnish film on chrome-tanned leather. S. M. Kheifets and M. I. Kutovskii. *Kozhennye Oshchimaia Prom.* (U. S. S. R.) 10, No. 7, 41-3 (1967); *Chemie & Industrie* 39, 993. — A satisfactory imperviousness to water is obtained with a varnish of the following composition: 10% casein 1.83 kg., blood 1.10 kg., milk 0.34 kg., glycerol 0.01 kg., alizarin oil 0.00 kg., 12% formaldehyde 7.0%, to a total vol. of 12 l. Variations in the imperviousness to water are generally due to insufficient viscosity of the casein soln., which should be 2.5° Engler at 40°. To render the film finer, the above mixt. should be passed through a colloid mill.

A. D. B. — Continuation

ASAC-SLA METALLURGICAL LITERATURE CLASSIFICATION

1ST AND 2ND DIGITS										3RD AND 4TH DIGITS									
PROCESS AND PROPERTIES INDEX																			
KEYFEET, S.H. CA Maped cooking and salting of wet salted shins. S. M. Kheifets, I. O. Meetrovich and S. A. Greynin. Koshvenno-Oshvennoye. <i>Proiz.</i> S. S. R. 17, No. 1, 45-7 (1937). Lowering the Na₂S content to 1 g. per l. causes a smaller area of the finished material. An increase up to 4 g. per l. in 12 hrs. increases the area by 0.0%, while an increase up to 8 g. per l. increases the area by 2.6%. The expts. are described in detail. A. A. Boeshling																			
ASM-AIA METALLURGICAL LITERATURE CLASSIFICATION 1931 STYRENE 1931 STYRENE 1931 STYRENE 1931 STYRENE																			

KHEYFETS, S.N. (Ussuriysk)

Diagnosis and treatment of female sterility. Akush. i gin. no.1:
18-23 '63. (MIRA 17:6)

KHEYFETS, S.N., kand. med. nauk (Ussuriysk)

Cervical pregnancy. Akush. i gin. 39 no.3:129 My-Je'63
(MIRA 17:2)

KHEYFETS, S.N.

Subcutaneous emphysema in labor. Akush. 1 gin. 33 no.6:88-89 N-D '57
(PUERPERIUM, compl. (MIRA 11:3)

emphysema, subcutaneous)
(EMPHYSEMA, etiol. and pathogen.
subcutaneous in puerperium)

KHEYFETS, S.N.

Paracervical anesthesia in artificial abortion. Sov.med. 24
no.3:130-132 Mr '60. (MIRA 14:3)
(ABORTION) (ANESTHESIA IN OBSTETRICS)

KHEYFETS, S. N.

Cand Med Sci - (diss) "Functional infertility of women in normally passable Fallopeat tubes." Khabarovsk, 1961. 23 pp; (Khabarovsk State Med Inst); 250 copies; price not given; (KL, 7-61 sup, 263)

KHEIFETS, S.N.

Clinical diagnostic significance of mucus crystallization from
the cervical canal. Akush. i gin. no. 6875-80 '60.

(MIRA 14:1)

(UTERUS)

KHEYFETS, S.N., kand.med. nauk

Sterile marriages. Sovet. med. 27 no.9:92-96 S'63 (MIRA 17:2)

KHEYFETS, S.N., kand. med. nauk (Ussuriysk)

Postpartum pituitary insufficiency (Sheehan's syndrome). Akush, i gin.
40 no.4:135-137 J1-Ag '64. (MIRA 18:4)

KHEYFETS S. YE

HA 151T84

USSR/Medicine - Tuberculosis, Larynx Jul/Aug 49
Vitamin D2

"Case of Tubercular Lupus Vulgaris of the Larynx
Treated with Vitamin D2," S. Ye. Kheyfets, Hosp of
Stupino, Moscow Oblast, 1 p

"Vest Oto-Rino-Laringol" No 4

Primary tubercular lupus vulgaris of the larynx with-
out simultaneous affection of the skin or other
regions of the respiratory passages is very rare.
In 720 cases Voznesenskiy found only one primary case
and 16 cases without simultaneous skin affection.
Case cited is interesting not only because of its

151T84

USSR/Medicine - Tuberculosis, Larynx Jul/Aug 49
(Contd)

rarity but because it was cured by Vitamin D2 alone.
Chief Physician, Hosp of Stupino: I. M. Kosov.

151T84

KHEYFETS, V., inzh. (Arkhangel'sk)

Preventing oil discharge in Li-2 airplanes. Grazhd.av. 12
no.8:18 Ag '55. (MIRA 15:8)
(Airplanes--Lubrication)

KHEIFETS, V. A.										PROCESSES AND PROPERTIES INDEX										13									
Recovery of Copper from Scrap of Brass-Plated Iron. V. A. Heifets (<i>Zhurnal Prikladnoi Khimii</i> (J. Applied Chem.), 1933, 6, 653-664; <i>C. Abs.</i>, 1934, 28, 3986).—(In Russian, with German summary.) As soon as the copper has been anodically dissolved, the underlying iron is covered with an amorphous film of oxides on electrolysis in a neutral $\text{Cu}(\text{NO}_3)_2$ solution. These oxides make the iron passive but raise the potential to +2.12 v. The passive action of the layer is independent of the current density, and it decreases with the increase in the temperature and becomes stable at 65° C. The joule heat increases to such an extent at a current density in excess of 4 amp./dm.² that the solution heats very rapidly. The resistance of the solution has its minimum at a concentration of 1.0M $\text{Cu}(\text{NO}_3)_2$. The energy consumption per ton of cathode copper produced is proportional to the current density, and the proportionality factor is below one. The resistance of the solution is independent of the cation; a decrease in the Cu^{++} and increase in the Zn^{++} does not cause any change in voltage of the cell. The success of the process depends entirely on a proper concentration of Cu^{++} (minimum 35-45 gm./litre). 1 kg./litre of copper may be precipitated from an original copper concentration of 160 gm./litre. The spent electrolyte can be regenerated as follows: by diluting the electrolyte in special purification tanks the iron is entirely precipitated through hydrolysis; the copper is then precipitated as $\text{Cu}(\text{OH})_2$ by addition of ZnO.—S. G.																													
ASH-15A METALLURGICAL LITERATURE CLASSIFICATION																													
REGIONAL SYMBOLS										COLLISIONS										REGIONAL SYMBOLS									
1 2 3 4 5 6 7 8 9 10										11 12 13 14 15 16 17 18 19 20										21 22 23 24 25 26 27 28 29 30									

GANICHEV, I.A., inzh.; MESHCHERYAKOV, A.N., inzh.; KHEYFETS, V.B.

New methods of making antiseepage curtains. Gidr.stroi.31 no.2:14-18
P '61. (MIRA 14:3)

(Soil percolation) (Grouting)

SHARF, V.Z.; FREYDLIN, L.Kh.; OPARINA, G.K.; KHEXFETS, V.I.; BYCHKOVA, M.K.; KOPYLEVICH, G.M.; YAKUBENOK, V.V.

Production of isoprene from formaldehyde and isobutylene via 3-methyl-1,3-butanediol. Izv. AN SSSR. Ser. khim. no.9:1663-1665 '65. (MIRA 18:9)

1. Institut organicheskoy khimii im. N.D. Zelinskogo AN SSSR i Opytno-konstruktorskoye byuro sinteticheskikh produktov Priokskogo soveta narodnogo khozyaystva, Tula.

KHEYFETS, V.L.; STRIZHEVSKIY, I.I.

Container method for the hermetically sealed transportation of
calcium carbide. Khim.prom. no.1:71-72 Ja '63. (MIRA 16:3)
(Calcium carbide--Transportation)

REMEN', T.F.; KHEYFETS, V.L.; VAYSBURD, S.Ye.

Activity of sulfur in binary systems Fe - S, Co - S, Ni - S.
Zhur.prikl.khim. 36 no.1:218-220 Ja '63. (MIRA 16:5)
(Alloys) (Sulfur) (Electromotive force)

1ST AND 2ND ORDERS										3RD AND 4TH ORDERS									
PROCESSING AND PROPERTIES INDEX																			
<i>m</i> <i>6</i> *Electrodeposition of Tin. V. L. Khavits and Ya. V. Valner (Sobolevskaya Leningradskogo Instituta Metallov (Engl. Central Inst. Metals, Leningrad), 1934, (10), 165-180; <i>C. Ab.</i>, 1935, 22, 3007).—[In Russian, with German summary.] A study was made of 3 types of electrolytic tin baths: cyanide, oxalate, and a sulphate bath containing sulphonic acids. It was found that in the cyanide and oxalate baths a passivity of the anode occurs, resulting in a change in the tin concentration of the bath during electrolysis. The sulphate bath does not undergo any changes and also has a better throwing power. It was definitely established that the addition of cresolsulphonic acid and glue to an electrolytic tin bath prevents change in the composition of the bath, gives good throwing power, and permits the use of a high current density.—S. (i).																			
ASD-5LA METALLURGICAL LITERATURE CLASSIFICATION										ECONOMY INDEX									
RESEARCH DIVISION RESEARCH DIVISION RESEARCH DIVISION										RESEARCH DIVISION RESEARCH DIVISION RESEARCH DIVISION									

Microfilm card with perforated edges. The card contains the following text:

KHIMFETIS, V.L.

Electrochemical deposition of binary alloys (brass).
V. A. Sukhodolov, V. L. Kheifets and I. N. Chapurskii.
Repts. Central Inst. Metals (Leningrad) No. 17, 200 15
(in German 216)(1934). -- Deposition of brass from a bath
consisting of a soln. of $ZnSO_4 \cdot 7H_2O$, $CuSO_4 \cdot 5H_2O$, tartaric
acid and $NaOH$ in H_2O was studied. A brass anode and
an Fe cathode were used. Results show possibility of
obtaining a good deposit (0.01 mm. thick) from such a
bath. S. L. Madorsky

ASH-SLA METALLURGICAL LITERATURE CLASSIFICATION

4

PROCESSES AND PROPERTIES OF

Protective action of cathodic polarization. V. I. Kheifets and B. M. Idel'chik. *Korrosivn. i Porboz. i Nel.* No. 1, 35-40 (1938); *Khim. Referat. Zhur.* 1, No. 11-12, 107-8 (1938).—In every process of the contact of metal with electrolyte there are surface regions in which there are more active, energetic ions that pass more easily into solution. In these places a deficiency of electrons, in the neighboring places (inactive) an excess of electrons is created. Regions of the first type act as anodes; those of the second type as cathodes, on which H is evolved. The protective η , d , is greater in the presence of O than in its absence. For Fe and Zn the c. d. does not depend on the partial pressure of O. For Fe it is higher than the c. d. calcd. from the soln. velocity, while for Zn it is lower. The protective c. d. increases with the concn. of acid, but it is higher in HCl than in H_2SO_4 solns. with the same pH. An explanation of these factors is based on the mechanism, and on the different character of corrosion depending on the nature of the medium and the metal: (1) acid- O_2 . (a) $2M^{++}$ (ion in lattice) + O_2 + $4E^-$ + $2H_2O$ = $2M(OH)_2$; (b) $2M(OH)_2$ + $4H^+$ $\rightarrow$ $2M^{++}$ (ion in soln.) + $4H_2O$; (2) acid- H_2 . (a) $2H^+$ + $2E^-$ = $2H_2$; $2H_2$ $\rightarrow$ H_2 ; (b) M^{++} (ion in the double layer) $\rightarrow$ M^{++} (ion in soln.). (3) pure O_2 . (a) $4H^+$ + O_2 + $4E^-$ = $2H_2O$; (b) M^{++} (ion in the double layer) $\rightarrow$ M^{++} (ion in soln.). In all cases the protective c. d. depends on the first stage of the soln. process. The same holds true for pairs of 2 metals. The more basic metal will be more decomposed. If the noble metal possesses a smaller overvoltage of H. As a result of this, H. will be evolved on the less-active regions of the noble metal. In the pair Fe-Sn in a HCl soln., Sn will be the anode owing to the slow discharge of H_2 on Sn.

W. R. Henn

W. R. HENRY

CP

9

Stability of some metallic coatings. V. I. Kheifets and
 1. N. Chapurskii. *Korrosiya i Bor'ba s Nel* 4, No. 1,
 64-7(1938); *Khim. Referat. Zhur.* 1, No. 10, 84(1938). —
 In double-layer coatings (Cu undercoating and Sn upper
 layer) on Fe plate in running sea water the no. of corrosion
 points on Fe increased during the first 3-5 hrs., then be-
 came const. They appear only at pores in the coating.
 The no. of the pores decreases linearly with the thickness
 of the Cu and the Sn layers. With a preliminary boiling
 of Fe in oil at 150-200° no corrosion was observed under
 analogous conditions. Zn coatings are resistant to cor-
 4 rosion on immersion in still sea water, but not to alternate
 action of air and water. Resistance increases with the
 thickness of the Zn layer. In running sea water the cor-
 rosion velocity of the coatings is greater than in still water.
 Cd coating in still sea water has the same effect as Zn
 coatings. Alternate action of air and sea water causes an
 5 oxide film to be formed which protects the coatings from
 further changes. In running sea water there are also
 formed local corrosion spots (besides the complete oxide
 film) in which a further corrosion of Cd takes place. No
 rusting of Fe was observed during 30 days of the investiga-
 tion. W. R. Henn

ASH-SLA METALLURGICAL LITERATURE CLASSIFICATION

REGIONAL SYMBLITH

147082 44

147082 44 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

[illegible]

fer of the electron from the electrode to the
relatively more rapid rise in overvoltage indicated a more
complex reaction. These observations were consistent with
previously reported results in the lower pH range.

C. H. Dickinson

KHEYFETS, I. L.

USSR

The dependence of the overvoltage of electrode reactions on current density, with consideration of concentration polarization. V. I. Kheifets, M. I. Falshtein, and E. L. Shtrom (A. A. Zhukov State Univ., Leningrad). *Trudy Sovetskoye Elektrokhim., Akad. Nauk S.S.S.R., Otdel. Khim. Nauk* 1950, 202-11 (1953). For the case in which concn. changes at the electrode surface, $dE/d \log i$, is a function of the changes in activity of oxidized (or reduced) substances taking part in the electrode reaction, E , is the electrode potential at c.d. i . Polarization curves are given for the cathodic reduction of O on a rotating smooth Pt electrode in the following solus. (slopes in parenthesis): 0.1N KCl (0.122), 0.1N KBr (0.139), 0.1N KI (0.142), 0.1N KOH (0.058), 0.1N KCl + 0.05N KOH (0.058), 0.1N KBr + 0.05N KOH (0.067), 0.1N KI + 0.05N KOH (0.075), 0.1N HCl (varies with c.d.), 0.1N H₂SO₄ (varies with c.d.). The slopes for the neutral and alk. solus. indicate that O is reduced in one step without the intermediate formation of H₂O₂. O₂ is adsorbed on the surface and dissov. into atoms. The direct participation of H⁺ in the electrode reaction is indicated by the dependence of the slope on pH. For solus. of alkali hydroxide the activity of OH⁻ is practically equal to the mean activity of the dissolved alkali. Detailed interpretation of data for the acid solus. is not possible in the absence of well-defined slopes. Effects of anion adsorption are noted. R. D. Misch

Guinean State U. and Inst. Market Abolition Ind.

KHEYFETS, V. L.

TA 255T19

USSR/Chemistry - Metallurgy, Refining 11 Jan 53
of Metals

"The Effect of Temperature on the Regularity of
Joint Separation of Ions During Electrolytic
Refining of Metals," A. L. Rotinyan, V. L. Kheyfets,
Ye. S. Kozin, O. I. Kalganova

DAN SSSR, Vol 88, No 2, pp 301-304

The effect of temp on the contamination of Ni
cathodes with admixts of Cu, Zn, Pb, Co, and Mn
was studied under various conditions. In the first
and second cases the rate of sepn of admixt on the

255T19

cathode is limited by diffusion, and the rate of
sepn of the base metal, by diffusion or delayed
discharge. In the third case, the rate of sepn
of the admixt and the base metal is detd by de-
layed discharge. In the fourth case, the rate
of sepn o. admixt is limited by delayed dis-
charge, and that of the base metal, by diffusion
Presented by Acad A. N. Frumkin 11 Nov 52.

255T19

"APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8

APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8"

KHEYFETS, V.L.; REYSHAKHRIT, L.S.

Regularities in the simultaneous discharge of nickel and hydrogen ions. Part 1. Effect of Ph on current distribution between nickel and hydrogen. Uch.sap.Len.um.169:173-188 '53. (MLRA 9:6)
(Nickel) (Hydrogen) (Electrolysis)

KHRYZHEV, V.L.; AVDEYEV, D.K.; REYSHAKHRIT, L.S.; STROKAN, B.V., otvetstvennyy redaktor; MEL'NIKOVA, G.G., redaktor; GLAZUNOV, F.D., tekhnicheskiiy redaktor.

[Practical work in theoretical electrochemistry] Praktikum po teoreticheskoi elektrokhemii. Leningrad, Izd-vo Leningradskogo universiteta, 1954. 235 p.
(Electrochemistry) (MLRA 8:2)

USSR/Chemistry - Isobaric Potential Calculations

Card : 1/1

Authors : Kheyfets, V. L., and Rotinyan, A. L.

Title : ~~Isobaric Potentials of the Formation of Hardly Soluble Hydroxides and Basic Salts and pH Solutions, which Are in Equilibrium with the Solid Phase.~~
Isobaric Potentials of the Formation of Hardly Soluble Hydroxides and Basic Salts and pH Solutions, which Are in Equilibrium with the Solid Phase.

Periodical : Zhur. Ob. Khim, 24, Ed. 6, 930 -936, June 1954

Abstract : The possibility for the calculation of standard isobaric potentials in the formation of basic salts and pure hydrates is shown by measuring the pH of solutions, which are in equilibrium with the solid phase of basic salts or pure hydrate. Experiments showed that basic salts form in almost all cases at greater concentrations. Pure hydrates form only in the case of zinc at small basic concentrations of its ions. Standard isobaric potentials were computed for reaction of formation of basic salts of many metals. Eighteen references. Tables, graphs.

Institution : The Leningrad Technological Institute, Leningrad

Submitted : December 24, 1953

USSR/ Chemistry Analysis methods

Card : 1/1 Pub. 151 - 5/33

Authors : Rotinyan, A. L., Kheyfets, V. L., Kozich, E. S., and Kalnina, E. N.

Title : Composition of almost insoluble Ni-compounds deposited by alkali in a sulfate solution and standard isobaric potentials of their formation

Periodical : Zhur. ob. khim. 24/8, 1294 - 1302, August 1954

Abstract : The compositions of almost insoluble Ni-salts formed during the reaction of NiSO_4 solutions with alkali solutions, were determined by analyzing the pH - lg α $\pm$ curves. The results obtained were re-checked by analyzing the electro-conductivity curves of mother liquors during the deposition of the basic Ni-salts with alkali. The standard isobaric formation potentials of these compounds and the standard isobaric addition potential of Ni-sulfate to nickelous hydroxide, resulting in the formation of $3\text{NiSO}_4 \cdot 4\text{Ni}(\text{OH})_2$, were calculated. Twelve references: 9 USSR; 2 USA and 1 Czech (1936 - 1954). Table; graphs.

Institution :

Submitted : March 19, 1954

KHEYFETS, V. L.

USSR/Chemistry

Card 1/1 : Pub. 151 - 2/42

Authors : Kheyfets, V. L.; Rotinyan, A. L.; Kozich, E. S.; and Kalnina, E. N.

Title : Composition of hardly-soluble compounds separated out by alkali from Ni-salt solutions in the presence of boric acid

Periodical : Zhur. ob. khim. 24/9, 1486-1490, Sep 1954

Abstract : During the separation of Ni from mixed nickel sulfate and boric acid solutions, by means of alkali, the composition of the solid phase at the beginning of its formation was investigated by the potentiometric titration method. The composition of the solid phase, which was found to be in equilibrium with the solution, is described. Standard isobaric potentials of the formation of nickel diborate from ions and from nickelous hydroxide and boric acid, were computed. The effect of 500 temperature on the change in composition of the forming solid phase, is explained. Six USSR references (1950-1954). Tables; graphs.

Institution : ...

Submitted : March 19, 1954

KHEYFETS, V.L.

ROTINYAN, A.L.; KHEYFETS, V.L.

Simultaneous discharge of simple cations. TSvet.met. 27 no.2:24-33
Mr-Ap '54. (MIRA 10:10)

(Electrometallurgy)

KHEFFETS, V. L.

Influence of Surface Adsorption on the Hydrogenation of Hydrogen on Platinum

The influence of the adsorption of organic substances on the hydrogenation of hydrogen on platinum was studied. The rate of hydrogenation of hydrogen on platinum was measured in 0.1 M HCl and 0.1 M NaOH solutions with addition of organic substances. The results of the measurements are compared with the values of adsorption of organic substances on platinum determined by other methods.

The results of the measurements agree with the values of adsorption of organic substances on platinum determined by other methods. The rate of hydrogenation of hydrogen on platinum was measured in 0.1 M HCl and 0.1 M NaOH solutions with addition of organic substances. The results of the measurements are compared with the values of adsorption of organic substances on platinum determined by other methods. The results of the measurements agree with the values of adsorption of organic substances on platinum determined by other methods.

to the heterogeneity of the Pt surface and of the H₂ gas.

KHEIFETS, V. L.

4

CH Cathode-film acidity during the electrolysis of aqueous
solutions. V. L. Kheifets, A. L. Rotinyan, and T. M.
Ovchinnikova, *J. Appl. Chem. U.S.S.R.* 28, 457-60
(1955) (Engl. translation).—See C.A. 49, 15501h.
B. M. B. (2) *RA*

"APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8

Signature of [illegible]

[illegible]

APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8"

18(5)

SOV/112-59-3-5731

Translation from: Referativnyy zhurnal. Elektrotehnika, 1959, Nr 3, p 212 (USSR)

AUTHOR: Rotinyan, A. L., and Kheyfets, V. L.

TITLE: Producing a Very Pure Cathode Nickel
(Polucheniye osobo chistogo katodnogo nikelya)

PERIODICAL: Materialy Soveshchaniya po vopr. intensiv. i usoversh. dobychi i
tekhnol. pererabotki medno-nikelevykh i nikelovykh rud. 1956, M., Profizdat,
1957, pp 195-203

ABSTRACT: A method developed in the Gipronikel' Institute is suggested for
collective deep purification of nickel electrolyte from a number of impurities.
The method is based on the fact that during electrolysis, as a result of a joint
discharge, the impurities are included in the cathode deposit, and their content
in the electrolyte (both absolute and relative concentrations as compared to Ni
concentration) is considerably reduced. (Translator's note: the meaning of
the Russian original is not clear.) Processing conditions can be selected for

Card 1/2

SOV/112-59-3-5731

Producing a Very Pure Cathode Nickel

maximum productivity. Practical realization of the method is considered, as well as tests at the Yuzhural'nikel' and Severonikel' Combines. It is mentioned that the electrochemical purification can be used successfully for electro-winning of other high-purity metals.

I. L. G.

Card 2/2

"APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8

KHEFFETS, V. L.

APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8"

KHEYFETS, V. L.


✓ The effect of surface-active additives on the overvoltage of oxygen evolution on smooth platinum. V. L. Kheyfets and I. Ya. Rivlin. *Zhur. Priklad. Khim.* 29, 69-73 (1956); cf. *C.A.* 50, 7025d. — The effect of additives on the overvoltage of O evolution on smooth Pt anodes was studied in 0.5 molar H_2SO_4 to which were added satd. solns. of nonylic, caprylic, and heptylic acids (0.0014, 0.0046, and 0.02M, resp.) and 0.005N thiourea. The values of ϕ and $d \log I_0/d\phi$ (c.d. 10 ma./sq. cm.) of solns. without additives and with the additives in the order given were: —, 0.37; 0.058, 0.067; 0.089, 0.083; 0.118, 0.133; and 0.403, 0.171. In solns. with additives the $\log I_0$ vs. ϕ curves exhibited a bend at ϕ , below which there was an appreciable deviation of I obtained galvanometrically and by the vol. of O evolved. The presence of H_2SO_4 in all solns. with additives was detected analytically. Thus, even in dil. H_2SO_4 (0.5 molar), the reaction $2HSO_4^- \rightarrow 2e^- + H_2SO_4$ took place (at $\phi = 2.05-2.35$ v., H scale). However, at higher values of ϕ depolarization occurred and the current efficiency of O evolution increased from 81.2 to 83.3% as I increased from 5.30 to 42.10 ma./sq. cm. The displacement of the rising part of the capacitance C of the double elec. layer vs. ϕ indicated that complete desorption did not occur (cf. *C.A.* 49, 11400a) and that the additives were adsorbed with their pos. ends toward the metal. The absence of peaks on the C vs. ϕ curves was attributed to the masking effect of H evolution. Both series of curves, $\log I_0$ vs. ϕ and C vs. ϕ proved the postulate that O evolution was detd. by the rates of the reactions $H_2O \rightarrow 2e^- + O_{ads}$ or $2H^+ + O_{ads} \rightarrow H_2O$ + H_2O .

APPROVED FOR RELEASE: 09/17/2001 CIA-RDP86-00513R000722010010-8

KM R

"APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8



APPROVED FOR RELEASE: 09/17/2001

CIA-RDP86-00513R000722010010-8"

KHEYFETS, V.L.; ANTONOVSKAYA, Ye.I.

Ferrocyanide electrolytes for gold plating. Zhur. prikl. khim. 29
no.4:595-600 Ap '56. (MIRA 9:11)
(Gold plating)(Ferrocyanides)