

KUNSTETTER, S.

The geometry of helicoid surfaces. p. 417

MECHANIK Warszawa, Poland Vol. 32, no.8, Aug. 1959

Monthly List of East European Accessions (EEAI) LC, Vol. 9, no. 2
Feb. 1960
Uncl.

KUNSTETTER, Stanislaw, doc.mgr inz.

Contemporary methods of calculation of the forces of the metal
cutting process. Mechanik 36 no.1:17-21 '63.

1. Politechnika, Warszawa.

KUNSTLER, F.

Examination of the motion of the bobbin on the Schonherr B0 wool power loom. II. p. 305. Magyar Textiltechnika. Budapest. No. 8, Aug. 1955.

Source: East European Accessions List, (EEAL), Lc, Vol. r, No. 2, Feb. 1956

KUNSTLER, F.

Examination of the motion of the bobbin of the schenherr BO wool power loom.
(To be contd.) p. 272. KOHASZATI LOFAK (Magyar Banaszati es Kohaszati
Egyesulet) Budapest. Vol. 10, No. 4, Jan, 1955

SOURCE: East European Accessions List (EEAL) Library of Congress
Vol. 5, No. 6, June 1956

KUNSTMAN, Halina
GELBER, Jerzy; KUNSTMAN, Halina; SWIERCZEWSKI, Stanislaw

Types of Corynebacterium observed in the Szczecin region during
1952-54. Med. dosw. mikrob. 7 no.1:59-63 1955.

1. Z Wojewodziej Stacji Sanitarno-Epidemiologicznej w Szczecinie
i z Oddzialu Dzieciacego Zakaznego Woj. Szpitala Specjalistycznego
w Szczecinie.

(CORYNEBACTERIUM,
types of strains isolated in Poland)

KUNSTMAN, V.G.

Reproducibility of the magnetic field distribution in
electromagnetic analyzers. Elektrofiz. app. no. 2:80-89 164.
(MIR-1873)

L 39635-66 ENT. 1 171117 CD-2

ACC NR: AP6002884

SOURCE CODE: UR/0286/65/000/024/0041/0041

AUTHOR: Kunstman, V. G.; Tsvetkov, V. N.

ORG: none

TITLE: Device for measuring the strength of magnetic fields, Class 21, no. 176977

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 24, 1965, 41


TOPIC TAGS: magnetic field, magnetic field intensity, nonhomogeneous magnetic field, magnetic field measurement, measurement, measuring apparatus, nuclear magnetic resonance

ABSTRACT: The device for measuring the strength of magnetic fields, based on the utilization of the nuclear magnetic resonance phenomenon, consisting of a transmitter with a high-frequency coil, an ampoule with working substance and modulator coil located in the measured magnetic field, a generator, a wide-band amplifier, a detector, a low-frequency amplifier, and an oscillograph, is characterized by the fact that resonance amplifiers connected in parallel and tuned to the first, second and third harmonic of the nuclear magnetic resonance signal are included between the low-frequency amplifier and the oscillograph. These features are incorporated in the design in order to facilitate the search for the nuclear magnetic resonance signal in fields of relatively high nonhomogeneity and to increase the signal to noise ratio.

Cord 1/2

L 39635-66

ACC NR: AP6002884



1. high-frequency transmitter coil, 2. ampoule with working substance, 3. modulator coil, 4. capacitor, 5. generator, 6. wide-band amplifier, 7. detector, 8. reference frequency amplifier, 9 - 11. resonance amplifiers, 12. oscillograph

SUB CODE: 14,20/

SUBM DATE: 25Jun64/

Card 2/2MLP

L 01978-67

ACC NRI AP6030151

SOURCE CODE: UR/0120/66/000/004/0166/0168

AUTHOR: Kunstman, V. G.; Tsvetkov, V. N.

ORG: none

TITLE: Magnetic field intensity meter with automatic self-adjustment to the measured field *9m*

SOURCE: Pribery i tekhnika eksperimenta, no. 4, 1966, 166-168

TOPIC TAGS: magnetic field intensity, magnetic field measurement, weak magnetic field, magnetic field measuring device, *electronic test equipment*

ABSTRACT: A magnetic field intensity meter which uses the phenomenon of proton resonance in automatically adjusting to and following the field being measured has been developed. The device consists of two units: a high frequency unit with sensors and an autodyne circuit, and a control unit with low frequency circuit components. The device is designed for the 1—16 Koe (4—70 Mc) range. By using the automatically adjusting frequency autodyne, the frequency deviation from the resonance value of the field due to various destabilizing factors is reduced by a factor of 30. With an inhomogeneity of the measured magnetic field 10^{-3} cm^{-1} , the deviation of the frequency resonance value does not exceed 10^{-5} Orig. art. has: 1 figure. [KM]

SUB CODE: 09/ SUBM DATE: 11Aug65/ ORIG REF: 002/ OTH REF: 001/

Card 1/1 *tbl*

UDC: 621.317.44

KUNSTOVNY, P.

A cobweb steel construction of the Svarox type. p. 182. (Pozemni Stavby.
Vol. 5, No. 4, Apr 1957, Praha, Czechoslovakia)

SO: Monthly List of East European Accessions (EEAL) LC, Vol. 6, No. 8, Aug 1957. Uncl.

KUNSTVEZEL, Algemeene

X.15, Jan. 1954.

Refuadonia

859. MINERAL FIBRE INSULATING MATERIAL. Algemeene Kunstvezel
Maatschappij, O.V., Fleming, W.L. and McPHAIL, H. (German P. 811,689/1951;
 abstr. in Chem. Abstr., 1953, vol. 47, 7756). Insulating sheets are
 prepared by coating mineral fibres with an aromatic-petroleum-extract
 binder. Thus, 50 parts by weight of petroleum extract of an approximate
 specific gravity of 1.02 and a softening point of 378, 6 parts milk casein,
 1.5 parts ammonia, and 20 parts water are used. The casein is dissolved
 in the ammoniacal water and placed in a mixer with a stirrer. The
 petroleum extract is heated to 120° and slowly added. The mixture which
 thickens after cooling, is sprayed on to the mineral fibres. C.A.

16-11-54
 mld

KUNSTYR, I.; POSPISIL, J.

Penetration of *Serratia marcescens* from the intestine into the organism of irradiated dogs. *Folia microbiol.* 7 no.1:83-87 '62.

1. Veterinary Research Unit, Prague.
(*SERRATIA MARCESCENS* infect) (INTESTINES microbiol)
(RADIATION INJURY exper)

KUNSTYR, Ivo

Salmonella infections in dogs. Cesk. epidem. 11 no.3:157-159 My '62.

1. Veterinarni vyzkumne stredisko, Praha.

(SALMONELLA INFECTIONS veterinary)
(DOGS dis)

HUNGARY / Chemical Technology. Chemical Products and H
Their Applications. Binding Substances. Concrete
and Other Silicate Building Materials.

Abs Jour: Ref Zhur-Khimiya, 1959, No 4, 12654.

Author : Kunszt, Gyorgy.

Inst : Not given.

Title : Bauxite as a Filler for Concretes Used for Radia-
tion Protection.

Orig Pub: Epitoanyag, 1958, 10, No 1-2, 23-27.

Abstract: The great content in bauxite (3) of hydrate water
(12-20%) permits making a proposal for its possible
use instead of limonite in concretes used for
radiation protection. By taking into account the
fact that the neutron capture cross-section is
limited by the content of hydrogen in concrete,
a conclusion can be drawn as to the necessity for

Card 1/2

53

HUNGARY / Chemical Technology. Chemical Products and H
Their Applications. Binding Substances. Concrete
and Other Silicate Building Materials.

Abs Jour: Ref Zhur-Khimiya, 1959, No 4, 12654.

Abstract: using B in which the content of hydrate water that
enters into a unit of volume is greater than in
limonite. Adding a small quantity of scrap metal
to the concrete mixture can compensate for an
insufficiency of B. Bib. 7 titles. -- D. Pyush-
peki.

Card 2/2

KUNSZT, Gyorgy, dr.

Fourth Scientific Session of architectural researchers. Epites szemle 8 no. 2:38-45 '64.

1. Epitesugyi Miniszterium Muszaki Fejlesztési Foszaltalyanak osztalyvezetoje.

KUNSZT, György, inz. dipl.

Designing and testing concretes in high water content for
the construction of protection walls against ionizing radiation.
Inst tech budow biul inf no.11:16-24 '62.

KUNSZT, Gyorgy

Effect of external factors on the steam-strengthened concrete.
Epitoanyag 14 no.11:393-396 N '62.

KUNSZT, Gyorgy, dr.

On the development of the work of the research institutes of the Ministry of Construction. Epites szemle 7 no.3:65-70 '63.

1. Epitesugyi Miniszterium Muszaki Fejlesztési Foosztalyanak osztalyvezetoje.

KUNSZT, Gyorgy, dr., a muszaki tudományok kandidátusa

Experiments with heavy concrete prepared with bauxite aggregate
used for radiation shielding. Magy ep ipar 12 no.6:265-270 '63.

KUNSZT, Gyorgy, dr.

"Concrete and reinforced concrete works" by Levi, Rabinovics,
Szavalov. Reviewed by Gyorgy Kunszt. Epitoanyag 16 no.7:275
Jl '64.

1ST AND 2ND CIPHERS		PROCESSING AND PRESENTATION	
1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18	19	20
21	22	23	24
25	26	27	28
29	30	31	32
33	34	35	36
37	38	39	40
41	42	43	44
45	46	47	48
49	50	51	52
53	54	55	56
57	58	59	60
61	62	63	64
65	66	67	68
69	70	71	72
73	74	75	76
77	78	79	80
81	82	83	84
85	86	87	88
89	90	91	92
93	94	95	96
97	98	99	100

14

CA
KUNSZT J

Medical evaluation of mineral waters. Janos Kunzt
Hidrológiai Közlemények 14, 27-40 (1934). Mineral waters
are classified as (1) alk., contg. per kg. more than 0.1 g. NaHCO₃, (2) calcium, contg. more than 0.1 g. Ca ion, (3) iron-contg., with at least 0.01 g. Fe⁺⁺, which should represent at least 1.0 equiv. %; (4) Glauber salt waters, contg. an av. of Na₂SO₄ sufficient to lower the f. p. 0.50°, (5) bitter, contg. a like amt. of MgSO₄, (6) NaCl-contg. waters with at least 0.5 g. NaCl, (7) iodic, contg. at least 0.001 g. I ion, (8) arsenical, contg. at least 0.001 g. As ion, (9) Ra-contg., with at least 3-4 Mache units of Ra or 10⁻⁸ mg. Ra, and (10) simple mineral waters under the above mentioned limits but having heating effects due, e. g., to temp., free CO₂ or S contg. gases. S. S. de L.

12

ADV. SER. METEOROLOGICAL LITERATURE CLASSIFICATION

12

KUNSZT, JANOS, ed.

Furdosok kezikonyve. Irtak: Banfai Ivan (et al.) Budapest, Hungary.
Medicina, 1957. 212 p.

Monthly List of East European Accessions (EEAI), LC, Vol. 8, no. 11, November 1959,
Uncl.

KUNTER, G.

Urgent problems in the situation of the working class in West
Germany. Sots. trud. no.8:31-38 Ag '58. (MIRA 11:9)

1.Drezdenskiy nauchno-issledovatel'skiy institut ekonomiki i okhrany
truda.

(Germany, West--Economic conditions)

RUSSIA, I. O.

Sliding contact of electric machinery.

Moskva, Redatsionno-izdatel'skii otel TSBTI, 1948. 55 p. (49-29776)

TK2821.K8

KUNTS, I. S.

PA 22/49T21

USSR/Electricity
Bibliography

Oct 48

"New Dissertations Submitted at the All-Union
Electrotechnical Institute Imeni Lenin," I. S.
Kunts, Cand Tech Sci, 1 p

"Elektrichestvo" No 10

Summarizes seven dissertations for degree of
candidate of technical sciences.

FDB

22/49T21

USSR/Engineering
Publications

Scientists

Jun 49

"Dissertations at the All-Union Electrical Engineering Institute Imeni Lenth," I. S. Kunts, Cand Tech Sci, 1 p

"Elektrichestvo" No 6

Annotations on seven dissertations for degree of candidate of technical sciences include: S. I. Dzhenchel'skaya's "High-Polymeric Compounds as Gas-Generating Materials," I. A. Poltavev's "Testing Arbitrary Extinction of a Gas Discharge," and

54/40755

Jun 49

USSR/Engineering (Contd)

S. A. Yamanov's "Dependence of Dielectric Losses Upon the Chemical Composition of High-Polymeric Organic Compounds."

KUNTS, I. S.

54/40755

POBEGAYLO, V.M., mladshiy nauchnyy sotrudnik; GLUKHEN'KIY, V.T., mladshiy
nauchnyy sotrudnik; KUNTS, S.A., ordinator

Chloromycetin emulsion for treating streptoderma. Vest.ven. i derm.
30 no.4:52 J1-Ag '56. (MLPA 9:10)

1. Iz L'vovskogo kozhno-venerologicheskogo instituta.
(CHLOROMYCETIN) (SKIN--DISEASES)

Kunts, V.V.

USSR/Physics - Nuclear momenta

Card 1/1 Pub. 118 - 2/3

Authors : Kyul'ls, Ye. F.; Kunts, V. V.; and Khartman, V. G.

Title : Table of nuclear momenta

Periodical : Usp. fiz. nauk 55/4, 537-593, Apr 1955

Abstract : A table of nuclear momenta with the indication of a method and the precision of measurement is presented. The data are taken from the data given in "Physical Abstracts" published prior to September 1954. In the reference list, all work on the determination of nuclear momenta is given. The work is in Russian.

Institution :

Submitted :

CZECHOSLOVAKIA

DIEPOLD, F., KUNTSCHER, V., VLK, J; Physiological Institute,
Medical Faculty, Charles University (Fysiologicky Ustav Lk. Fak.
KU) Plzen.

"Further Information on the Influence of Food Administration
on Acetylcholine Changes in the Walls of the Digestive Tract of
White Rats."

Prague, Ceskoslovenska Fysiologie, Vol 15, No 2, Feb 66, p 91

Abstract: One hour after the administration of food cholin-
esterase activity of the stomach walls is much higher than during
starvation. 4 - 6 hours following feeding the acetylcholine
content in duodenum walls is substantially higher than during
starvation. There is a smaller difference in the walls of the
ileum. 2 Western, 3 Czech references. Submitted at "16 Days
of Physiology" at Kosice, 30 Sep 65.

1/1

- 132 -

USSR / Cultivated Plants. Plants for Technical Use. M
Oil Plants. Sugar Plants.

Abs Jour : Ref Zhur - Biologiya, No 6, 1959, No. 25001

Author : Kuntse, A.

Inst : Moscow Agricultural Academy im. K. A.
Timiryazeva

Title : New Methods for the Cultivation of the
Sugar Beet

Orig Pub : Sb. stud. nauchno-issled. rabot. Mosk. s.-kh.
akad. im. K. A. Timiryazeva, 1957 (1958),
vyp 7, 87-92

Abstract : On the Ulatso-Lyulinets Experimental Selection
Station (UkSSR) in 1955, effectiveness of
various methods of sowing the sugar beet
was investigated at length- and crosswise
cultivation. Planning, conditions and

Card 1/2

89515

53630

S/079/61/031/002/008/019
B118/B208

AUTHORS: Petrov, K. A., Neymysheva, A. A., Fomenko, M. G.,
Chernushevich, L. M., and Kuntsevich, A. D.

TITLE: Reaction of N-chloroimides of carboxylic acids with trialkyl-,
halogen-, and cyano phosphites

PERIODICAL: Zhurnal obshchey khimii, v. 31, no.2, 1961, 516-522


TEXT: The authors studied the reaction of N-chloroimides of esters of acetic and carboxylic acids with trialkyl-, halogen-, and cyano phosphites. Contrary to the vigorously reacting sulfene chlorides, chloroamines, and alkyl hypochlorites, the reaction of N-chloroethyl acetimide with triethyl phosphite proceeds smoothly and with little heat evolution. Separation of ethyl chloride occurs only on prolonged heating at 60-70°C. This reaction probably takes place in two stages:

Card 1/4

89515

S/079/61/031/002/008/019
B118/B208

Reaction of N-chloroimides ...




The free phosphonium compound was not obtained. Chloroimides of carboxylic acid esters react more vigorously with phosphites; main products are the esters of dialkoxy-methylenamide of phosphoric acid. The chloroamides react with dialkyl chloro and dialkyl fluoro phosphites, alkyl dichloro and alkyl di-fluoro phosphites in a similar manner, giving the corresponding halogen amidophosphates in yields of between 27.5 and 70.5%.

Card 2/4

89515

S/079/61/031/002/008/019
B118/B208

Reaction of N-chloroimides ...



Dialkyl fluoro phosphites give with chloroimides rather stable phosphonium compounds. Prolonged heating of the phosphonium compounds reduces the yield of fluoro phosphates; the reaction mixture was, therefore, distilled in vacuum after heating for 1-2 hr at 40-50°C. The fluoro amidophosphates are thermostable and are slowly hydrolyzed with water. When treating difluoro amidophosphates with aqueous alkali lyes at low temperatures, only one fluorine atom is hydrolyzed. On the action of a calculated quantity of sodium alcoholate in the solvent, only one fluorine atom is substituted by the alkoxy radical. Chloro amidophosphates are not thermostable, contrary to fluoro amidophosphates, distill only in high vacuum, and are easily hydrolyzable even at room temperature. When treating chloro amidophosphates with potassium cyanate in water at 5°C, the cyano group is substituted for chlorine, in addition to hydrolysis; in this way, the ethyl ester of

Card 3/4

89515

S/079/61/031/002/008/019
B118/B208

Reaction of N-chloroimides ...

diethoxy-methylenamide of cyano phosphoric acid results in a 20% yield. By reacting chloroimides with cyano phosphites, cyano amidophosphates are obtained according to Arbuzov's rearrangement (Ref. 2) in yields between 30 and 50%. Dialkoxy-methylenamides of dicyano phosphoric acid are unstable and decompose with separation of gaseous products. There are 1 table and 4 references: 2 Soviet-bloc.

SUBMITTED: February 15, 1960

Card 4/4

1ST AND 2ND ORDERS																										3RD AND 4TH ORDERS																									
PROCESSES AND PROPERTIES INDEX																																																			
KUNTSEVICH, A. N.																																																			
Ca																																																			
The hormone content of fetal fluid. A. N. Kuntsevich. <i>Abstrakter i Ginek.</i> 1946, No. 1, 20 R. - Comparison of hormone content in blood, urine, and spinal fluid of women in late pregnancy with that of the fetal fluid showed that the latter contains much less folliculin and prolactin than are contained in the former fluids. Thus, only 333 mouse units per l. of folliculin and 118 mouse units per l. of prolactin were found, while prolactin was not found at all, apparently because of impermeability of the membrane to the latter hormone. G. M. Kosolapoff																																																			
ASB-52A METALLURGICAL LITERATURE CLASSIFICATION																																																			

L 00038-66 EWT(m)/EWP(t)/EWP(b) IJP(c) JD/JG
 ACCESSION NR: AP5023710

UR/0075/65/020/008/0802/0804
 543.70

AUTHOR: Onosova, S. P.; Kuntsevich, G. K.

TITLE: Spectrophotometric study of the reaction of scandium ions with pyrocatechol violet

SOURCE: Zhurnal analiticheskoy khimii, v. 20, no. 8, 1965, 802-804

TOPIC TAGS: scandium, scandium compound, spectrophotometric analysis, dye chemical

ABSTRACT: Scandium and pyrocatechol violet form a blue complex of anionic character at a 1:1 molar ratio. The absorption maximum of the complex is reached at pH 5 ($\lambda = 590 \text{ m}\mu$) and remains constant with rising pH. The optimum pH range selected was 5.0-5.7; it was produced with urotropine and acetate buffer solutions. The average value of the molar extinction coefficient ϵ is $(1.73 \pm 0.13) 10^4$. For a complete color development, a twofold excess of the reagent is sufficient. A linear dependence of the optical density of the colored solution on the scandium concentration is observed up to 60 μg per 25 ml of solution. Complex-forming ions such as citrate, tartrate, oxalate, acetate, etc., and ions of thorium, aluminum,

Card 1/2

L 00038-66

ACCESSION NR: AP5023710

iron, copper, etc. interfere with the color development. A procedure for the determination of scandium in the absence of interfering ions is given. Orig. art. has: 5 figures.

ASSOCIATION: Ural'skiy politekhnicheskiy institut im. S. M. Kirova, Sverdlovsk
(Ural Polytechnic Institute)

SUBMITTED: 08May64

ENCL: 00

SUB CODE: QC, OP

NO REF SOV: 003

OTHER: 000

Card 2/2

ADAMOVICH, V.I.; KUNTSEVICH, I.M.; FISHER, I.Z.

Short-range order near an excited molecule in a liquid. Zhur.
fiz. khim. 37 no.11:2568-2570 N'63. (MIRA 17:2)

1. KUNTSEVICH, I.
2. USSR (600)
4. Climbing Plants
7. Use of liana for city landscaping. Ahil. -kom, khoz. 2 no. 9, 1952

9. Monthly List of Russian Accessions, Library of Congress, January 1953. Unclassified.

KUNTSEVICH, I. P.

GROKHOL'SKAYA, V.S., kandidat sel'skokhozyystvennykh nauk; KUNTSEVICH, I.P.,
kandidat tekhnicheskikh nauk.

Transplanting large bare-root trees. Gor.khoz.Mosk. 31 no.6:31-32
Je '57. (MIRA 10:7)

(Moscow--Tree planting)

KUNTSEVICH, I.P., kand. tekhn. nauk.

Let's use climbing plants to make our city more beautiful. Gor. khoz.
Mosk. 32 no.3:18-19 Mr '58. (MIRA 11:3)
(Moscow--Climbing plants)

KUNTSEVICH, I., starshiy nauchnyy sotrudnik, kand.tekhn.nauk

Special workers for landscaping cities. Zhil.-kom. khoz. 10 no.11:
13-14 '60. (MIRA 13:11)

1. Akademiya kommunal'nogo khozyaystva.
(Landscape gardening)

KUNTSEVICH, Iosif Porfir'yevich, kand. tekhn. nauk; TER-MKRTICHAN,
Ashot Khristoforovich, inzh.; SHMELEV, G.M., red.; SMIRNOVA,
R.N., red.izd-va; KHENOKH, E.M., tekhn. red.

[Machines and implements for establishing and maintaining green-
belts and parks; an album] Mashiny i orudiia dlia zelenogo stroi-
tel'stva i khoziaistva; al'bom. Moskva, 1962. 144 p.

(MIRA 16:1)

1. Akademiya kommunal'nogo khozyaystva.
(Landscape gardening---Equipment and supplies)

KUNTSEVICH, I.P., kand. tekhn. nauk; SIMONYAN, A.A., kand. tekhn. nauk;
BATURIN, T.F., inzh.

Garden and park machinery and devices. Nov. tekhn. zhil.-kom. khoz.:
Blagoustr. gor. [no.1]:12-25 '61. (MIRA 18:5)

GRINGAUZ, M.Ya.; KUNTSEVICH, M.A.

Study of the permeability of the skin by means of radioactive isotopes
Report no.1. Sbor.nauch.rab.Bel.nauch.-issl.kozhno-ven.inst. 6:38-47
'59. (MIRA 13:11)

(SKIN)

(ISOTOPES--PHYSIOLOGICAL EFFECT)

GRINGAUZ, M.Ya.; KUNTSEVICH, M.A.

Study of the permeability of the skin by means of radioactive isotopes.
Report No.2. Sbor.nauch.rab.Bel.nauch.-issl.kozhno-ven.inst. 6:91-
101 '59. (MIRA 13:11)

(SKIN)

(ISOTOPES--PHYSIOLOGICAL EFFECT)

SOSNOVSKIY, A.T., kand.med.nauk; KUNTSALVICH, M.A., nauchnyy sotrudnik;
KASPEROVICH, N.K.

Transplantation of bone marrow in radiation sickness in animals.
Zdrav.Bel. 7 no.8:35-36 Ag '61. (MIRA 15:2)

1. Iz kafedry kozhvenbolezney Minskogo meditsinskogo instituta i
Belorusskogo kozhveninstituta (dir. - akademik A.M. ISSIK A.Ya.
Prokopchuk), (MARROW TRANSPLANTATION) (RADIATION SICKNESS)

PERYSHKIN, G.A.; KUNTSEVICH, N.M.

Spillways of fishponds. Dokl. AN BSSR 9 no.10:680-682 0 '65.
(MIRA 18:12)

1. Belorusskiy politekhnicheskiy institut. Submitted May 18,
1965.

KUNTSEVICH, O.Y., kandidat tekhnicheskikh nauk.

Loess as a concrete additive for hydraulic structures. Izv. VNIIG
no.45:115-122 '51. (MLRA 10:3)
(Concrete) (Loess)

Use of basalt as raw material for the production locally of

KUNTSEVICH, O.V.; ALEKSANDROV, P.Ye.; RATINOV, V.B.; ROSENBERG, T.I.;
BOGAUTDINOVA, G.G.

Theory of setting of gypsum cements. Dokl.AN SSSR 104 no.4:587-
588 O '55. (MIRA 9:2)

1.Vsesoyuznyy nauchno-issledovatel'skiy institut zhelezobetonnykh
izdeliy i nerudnykh materialov i Leningradskiy institut inzhene-
rov zheleznodorozhnogo transporta imeni V.N.Obratzsova. Predsta-
vleno akademikom P.A.Rebinderem.
(Gypsum)

ROSSINSKIY, Ye. Ye., kandidat tekhnicheskikh nauk; KUNTSEVICH, O. V.,
kandidat tekhnicheskikh nauk

Investigation of mortars and concretes for mixed cements obtained
by grinding basalt and portland cement together. Sbor. LIZHT
no. 148:134-148 '55. (MLRA 8:10)

(Cement)

SOV/124-57-9-11132

Translation from: Referativnyy zhurnal. Mekhanika, 1957, Nr 9, p 173 (USSR)

AUTHORS: Kuntsevich, O. V., Aleksandrov, P. Ye.

TITLE: The Effect of the Dissolution of the Cement Component of a Concrete by Running Water on the Freezing Stability of the Concrete (Vliyaniye rastvoreniya tsementnogo kamnya protochnymi vodami na morozostoykost' betona)

PERIODICAL: V sb.: 15-ya nauchn. konferentsiya Leningr, inzh.-stroit in-ta. Leningrad, 1957, pp 427-428

ABSTRACT: Bibliographic entry

Card 1/1

KUNTSEVICH, O.V.
IOKHEL'SON, Ya.Ye., kand.tekhn.nauk; KUNTSEVICH, O.V., kand.tekhn.nauk.

Technical problems in making high-strength, rapid-
hardening concrete. Bet. 1 zhel. -bet. no.8:325-329 Ag '57.
(MIRA 10:10)

(Concrete)

SATALKIN, A.V.; KUNTSEVICH, O.V.

Some problems in the technology of silicalcite materials. Silikaty
no.1:100-106 '59. (MIRA 13:2)
(Building materials)

SATALKIN, A.V., prof.; KUMTSEVICH, O.V., dots.; ALEKSANDROV, P.Ye., inzh.;
SOKOLOVSKIY, V.I., inzh.

Using high-strength lime-quartz materials in subway construction. Transp.stroi. 9 no.2:43-45 F '59. (MIRA 12:5)
(Leningrad--Subways) (Silicates)

PAROV, V.P. [doc-566], prof.; KONTSEVICH, O.V., kand.techn.nauk

Principles of silicate technology. Spor. LITZHT no.157:3-3 '58.
(MIRA 12:11)

(Building materials)

ELIZAVICH, O.V., head. to the. main, dots.; SAKALIN, A.V., doctor to the.
head, prof.

Autoclave-hardened concrete made with silicalcite cements. Spor.
LIIZHT no.157:2-14 '59. (MIRA 12:11)
(Concrete) (Cement)

KUMTSOVICH, O.V., head of the group, dots.; KOKOROV, P.G., assistant

Physical and chemical properties of pressed silicalcites and certain
silicalcite products. Sborn. bilzhim no.157:34-41 '59. (MIRA 10:11)
(Building materials)

ALEKSANDROV, P.Ye., inzh.; KUNTSEVICH, O.V., kand.tekhn.nauk, dotsent

The problem of corrosion of the reinforcement in concrete with
additions of salt. Sbor. trud. LIIZHT no.174:177-184 '60.

(MIRA 15:11)

(Concrete reinforcement--Corrosion)

KUNTSEVICH, O.V., kand.tekhn.nauk, dotsent; ALEKSANDROV, P.Ye., inzh.

The effect of surface-active substances on cement stone, mortar
and concrete. Sbor. trud. LII ZHT no.174:185-200 '60. (MIRA 15:11)
(Surface-active agents)
(Frost resistant concrete)

KUNTSEVICH, O.V., kand. tekhn. nauk. dotsent

Data on the thermal analysis of hardened cement made with lime-
quartz cement. Sbor. trud. LIIZHT no.200:78-88 '62.

(MIRA 16:7)

(Cement—Testing)

KUNTSEVICH, O.V.; ALEKSANDROV, P.Ye.

Effect of the composition of concrete on its resistance to
frost. Sber. trud. LITZHT no.192:91-109 '62. (MIRA 16:9)

RUSSIAN / 520124. 3.
USSR/Chemical Technology. Chemical Products and Their Application -- Silicates.
Glass. Ceramics. Binders, I-9

Abst Journal: Referat Zhur - Khimiya, No 2, 1957, 5283

Author: Aleksandrov, P., Bogautdinova, G., Kuntsevich, S., Ratinov, V.,
Rozenberg, T., Stalikova, G.

Institution: All-Union Scientific Research Institute of Reinforced Concrete,
Leningrad Institute of Railroad Transport

Title: New Testing Methods for Building and Molding Gypsum

Original

Publication: Stroit. materialy, izdeliya i konstruktsii, 1956, No 5, 31-33

Abstract: Work conducted by VNIIZhelezobeton and the Leningrad Institute of Railroad Transport, has shown that termination of the processes of hydration and crystallization of gypsum coincide in time. The hardening process is divided into two periods: end of the first is determined, not accurately, by means of the needle of Vick, as "termination of setting," and the end of the second (13-17 minutes) is the "end of crystallization." It is appropriate to evaluate the kinetics of hardening (setting time, end of crystallization) from the value of exothermy or volumetric changes.

Card 1/1

VAKSER, I.I.; STUBAYLO, G.D.; CHISTOVA, V.A.; KRYUCHKOV, G.R.,
dots., nauchnyy red.; KUNTSEVICH, S., otv. za vypusk;
STERZHANOV, P., tekhn. red.

[Public health in the White Russian S.S.R. for forty years
(1919-1958); an index to the literature] Zdravookhranenie
Belurusskoi SSR za sorok let, 1919-1958; ukazatel' litera-
tury. Minsk, 1961. 500 p. (MIRA 16:7)

1. Minsk. Respublikanskaya gosudarstvennaya nauchnaya
meditsinskaya biblioteka.

(WHITE RUSSIA—PUBLIC HEALTH—BIBLIOGRAPHY)

(BIBLIOGRAPHY—WHITE RUSSIA—PUBLIC HEALTH)

BELOV, N.V.; KUNTSEVICH, T.S.; NERONOVA, N.N.

Shubnikov groups (of antisymmetry) for infinite bilateral bands.
Kristallografiia 7 no.5:805-808 S-O '62. (MIRA 15:12)

1. Institut kristallografi AN SSSR.
(Crystallography)

BELOV, N.V.; NERONOVA, N.N.; KUNTSEVICH, T.S.

Drawings showing crystal structures in Shubnikov antisymmetry groups. Kristallografiia 9 no.2:147-154 Mr-Ap'64. (MIRA 17:5)

1. Institut kristallografi AN SSSR.

CHERNYSH, A.; YANKOVSKIY, L.; KUNTSEVICH, V.; SVETAL'SKIY, B.

Automatic control of motorship engine operations. Rech.
transp. 22 no.9:27-28 S '63. (MIRA 16:10)

USENKO, Vladimir Andreyevich, prof., doktor tekhn. nauk; ZABELOTSKIY, Lazar' Markovich, kand. tekhn. nauk; KUNTSEVICH, V.A., inzh., retsenzent; ZVEZDKINA, Ye.V., inzh., retsenzent; ILRAGIMOV, S.S., kand. tekhn. nauk, retsenzent; SHTEYNGART, M.D., red.; BATYREVA, G.G., tekhn. red.

[Silk technology] Tekhnologiya shelka. Pod red. V.A.Usenko.
Moskva, Izd-vo nauchno-tekhn. lit-ry RSFSR. Pt.2. [Silk spinning] Shelkopriadenie. 1961. 343 p. (MIRA 15:2)
(Silk) (Spinning)

KUDOKOTSEV, V.P.; KUNTSEVICH, V.A.

Stimulation of the restorative processes by the method of
trypsin and calcium chloride treatment of the surgical wound
following amputation of external organs in mammals. Biul.
eksp. biol. i med. 60 no.9:106-109 S '65. (MIRA 18:10)

1. Biologicheskii fakul'tet Khar'kovskogo universiteta.

KUNTSEVICH, V.M.

Calculating the dynamic braking of asynchronous motors of automatic-control systems used in mine hoisting machines. Avtomatyka no.2:21-24 (MLRA 9:10) '56.

1. Institut gornichoi spravi imeni M.M.Fedorova Akademii nauk URSS.
(Automatic control) (Mine hoisting) (Electric motors, Induction)

KUNTSEVICH, V.M.

Analog-to-digital converters (Review) [with summaries in Russian
and English]. Avtomatyka no.2:70-87 '57. (MLRA 10:8)

1. Institut elektrotekhniki Akademii nauk URSR.
(Electronic digital computers)

Kuntsevich, V.M.
KUNTSEVICH, V.M.; AKININ, P.I.

Approximate methods for determining the frequency and amplitude of hunting in optimizing controllers [with summaries in Russian and English]. Avtomatyka no.3:56-69 '57. (MIRA 10:10)

1. Institut elektrotehniki Akademii nauk URSS (for Kuntsevich).
2. Kiivs'kiy ordena Lenina politekhnichnyi institut (for Akinin).
(Servomechanisms)

KUNTSEVICH, V. M.: Master Tech Sci (diss) -- "Investigation of systems of regulating inertial production processes". Kiev, 1958. 18 pp (Min Higher Educ Ukr SSR, Kiev Order of Lenin Polytech Inst) (KL, No 12, 1959, 129)

AUTHOR: Kuntsevich, V.M.

102-58-1-5/12

TITLE: ~~The Use of Perturbation Control in Optimizing Control~~
Systems (Pro vykorystannya regulyuvannya po zburyuyuchikh
vplyvakh (kompaunduvannya) v systemakh ekstremal'nogo
regulyuvannya)

PERIODICAL: Avtomatika (Kiyev), 1958, Nr 1, pp 50 -- 55 (Ukrainian SSR)

ABSTRACT: Linear and slightly non-linear peak-holding control systems can often be rendered much less sensitive to perturbations by employing perturbation control; this type of control supplements ordinary proportional deviation control and can also be used with peak-holding (extremal) controls. The transients to be expected in a particular system (maintenance of maximum load torque in an asynchronous motor) are illustrated for cases where combined (derivative and proportional) perturbation control is used and when a simple linear proportional perturbation control loop is closed or open. It is shown that the first is much the most effective method. There are 4 Soviet references and 3 figures.

ASSOCIATION: Instytut elektrotekhniky AN URSS (Institute of Electrical Engineering, Ac.Sc. Ukrainian SSR)

SUBMITTED: September 26, 1957
Card 1/1

AUTHOR: V.M. Kantsyach.

SOV/102-58-2-5. 0

TITLE: An approximate frequency method of studying peak-holding sampled-data control systems. (Nablyzhenyy chastotnyy metod doslidzhennya ekstremal'nykh system impul'snogo rehulyuvannya)

PERIODICAL: Avtomatyka, 1958, No.2. pp 48-64 (USSR)

ABSTRACT: After a short general review of the difficulties of analysing such systems, particularly if nonlinear links are present, detailed consideration is given in section 1 to the structural diagram of stepping type peak-holding control systems (Fig.1b; Fig.1a. is a very generalized structural diagram). The time between samplings is assumed much larger than the duration of the transients. Units 3. and 4. are memory units (stores) which record the previous value of the controlled co-ordinate and 5 is a summator; 6 is a sampler; 7 is the effector motor, operated by the sign of the difference between the current and previous values. A backlash of 2Δ is assumed in 6. The reader is referred to ref.(1) for a detailed treatment of such systems. The equations for the system are then given (eqs. (1) - (5)). Systems which oscillate (hunt) about the peak are assumed, in relation to Fig.2 (open-loop system). The second section deals with the self-oscillation frequency and frequency characteristics of

* Paper presented at the seminary on the theory of automatic regulation, Kiev, 1957.
Card 1/3

SOV/102-58-2-5/10

An approximate frequency method of studying peak-holding sampled-data control systems.

the system. Equations (8) and (8a) relate to the input and output of the nonlinear link; only the steady state is considered, and the pulse sequence is expanded as a Fourier series (eq. (9)). Equations (10) give the amplitude of the fundamental (approximately), provided all transients die away in between samplings; otherwise large errors result. The bodegraphs of Fig. 3. are then introduced. Some detailed cases are then considered, in case 1 eq. (3) is replaced by (12). Fig. 4. gives the frequency curves implied by eqs. (14) and (15). The potman interval between samplings is then considered, in relation to Fig. 4., and stepping regulators are shown to provide better control than continuous-acting ones, particularly for controlled objects of high inertia. Fig. 5. illustrates the variations in the optimum sampling frequency, oscillation amplitude etc. It is stated (but not proved) that it is easy to incorporate the third harmonic term also. Section 3 then deals with ways of improving the response of stepping-type peak-holding systems. It is shown that one can reduce the search loss by Tsypkin's continuous correction method (ref. (2)) without having to increase the gain. Fig. 6. represents a system in which the feed-back of the sign of any change via link 8 involves a lag (direct simple feedback produces no improvement); detailed consideration is given to Fig. 7. The Fourier expansion, neglecting all harmonics, is applied as

Card 2/3

An approximate frequency method of studying peak-holding sampled-
data control systems.

before (eq. (18)), and the development is as before, eq. (21) gives
the amplitude of the oscillation in the feed-back link. Fig.9. deals
with the choice of feedback parameters to give a present oscillation
amplitude. The paper contains 22 numbered equations, 9 figures, and
14 references, 9 of which are Soviet and 2 Ukrainian.

ASSOCIATION: Instytut Elektrotekhniki AN URSR (Institute of Electrical Engineering
Ac. Sc. Ukrainian SSR)

SUBMITTED: September 15, 1957.

1. Data--Analysis 2. Control systems--Analysis 3. Control systems
--Equipment

Card 3/3

SOV/102-58-3-2/10

AUTHORS: Kryzhanovs'kyy, O.M. (Krizhanovskiy, O.M.) and Kuntsevich, V.M. (Kuntsevich, V.M.)

TITLE: Analysis of Extremal Control Systems from the Transients which Occur in Them (Analiz system ekstremal'nogo regulirovaniya za dopomohoyu doslidzhennya perekhidnykh protsesiv u nykh).

PERIODICAL: Avtomatika (Kyiv). 1958, Nr.3, pp.23-43 (USSR)

ABSTRACT: Extremal systems with only one maximum are considered. The transients occurring when the system passes instantaneously from the characteristic 1 of Fig.2a to characteristic 2 are considered. The actual change is assumed small, so the shapes of the curves can be approximated by parabolas. The extremal systems shown structurally in Fig.2 are then considered. The servomotor, linear link in the controlled object, nonlinear extremal characteristic (2 of Fig.1) and direct sensing link are represented by equations (1) - (4), where the α 's are constants and dots denote time derivatives. The system is assumed at rest at A of Fig.1 before perturbation; Eq.(5) is derived in the usual way and the analysis follows the standard course. The result is to

Card 1/4

SOV/102-58-3-2/10

Analysis of Extremal Control Systems from the Transients which Occur in Them.

reduce the equations to a linear differential equation. Relay control systems are studied by phase - plane methods in para.2; Eq.(9) replaces Eq.(4). Fig.3 shows the phase trajectories corresponding to Eqs.(12a) and (12b). An extremal system of control law described by Eq.(13) is then considered; Δ is the width of the hysteresis loop shown by a two-position polarized relay. Fig.4 shows the phase trajectories; Eq.(12a) applies to the right of line EFGH, Eq.(12b) to the left of it. The system of Fig.2b of control law Eq.(14) is now considered; its phase trajectories (Fig.5) show that it cannot work. Fig.6 is now considered (this has direct feedback of $\dot{x}$). The control law is Eq.(15); Fig.7a shows the phase trajectories, etc. If x is not readily obtained for this purpose, the linear part of the circuit of the controlled object may be altered; the effect of this becomes smaller as the hysteresis loop of the lower relay in Fig.6 becomes wider; a time delay in the top relay is only required. Figs.2c and 2d show possible ways of deriving x if x is not directly accessible.

Card 2/4

SOV/102-58-3-2/10

Analysis of Extremal Control Systems from the Transients which Occur in Them.

Various methods of improving the transient behaviour are discussed in para.3; a new way involving introducing terms containing $\dot{x}$ into the control law is proposed (this involves no special technical difficulties). Eq.(22) now replaces Eq.(4); this is briefly discussed. The control law of Eq.(24) is now introduced (Fig.8a is a system following this law; the other sections of Fig.8 relate to Eqs.(31), (32) and (32a) respectively, which are also control laws. Fig.9 shows the phase trajectories corresponding to Eq.(24), and Fig.10 those for Eq.(27); Fig.11 similarly relates to Eqs.(32) and (32a). Eqs.(36) relate to the transients corresponding to Eq.(31). An object with a characteristic which can be approximated by sections of straight lines is considered in para.4; the treatment uses the results of the earlier sections. Fig.12a relates to the control law of Eq.(43), with the characteristic approximated as in Eq.(39); Fig.12b does the same for the control law of Eq.(32). Para.5 deals with transients in extremal control systems using the Krylov-Boglyubov method for nonlinear

Card 3/4

SOV/102-58-3-2/10

Analysis of Extremal Control Systems from the Transients which Occur in Them.

differential equations. Fig.13 relates to the control law of Eq.(32); the full line is derived from Eqs.(65) and (66), which are approximate and the broken one from Eqs.(37a) and (37b). Para.6 deals briefly with approximating an unsymmetrical extremal characteristic by a cubic, i.e. by Eq.(69). There are 13 figures and 18 references, of which 12 are Soviet and 6 English.

ASSOCIATION: Instytut hirnychoy spravy im. M.M. Fedorova AN URSSR
(Institute of Mining Inspectorate im. M.M. Fedorov,
Academy of Sciences, Ukr.SSR); Instytut elektrotekhniky
AN URSSR (Institute of Electrical Engineering, Academy of
Sciences, Ukr.SSR).

SUBMITTED: April 15, 1958.

Card 4/4

SOV/24-59-3-6/33

AUTHORS: Kryzhanovskiy, O. M. and Kuntsevich, V. M. (Kiyev)

TITLE: Transients in Peak-Holding Control Systems.

PERIODICAL: Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh nauk, Energetika i avtomatika, 1959, Nr 3, pp 32-42 (USSR)

ABSTRACT: The paper presented by the authors in Avtomatika, 1958, Nr 3 (Ref 12) is reproduced in slightly condensed form (it now contains only 9 figures, but the equations have all been numbered and amount to 56). There are 13 references, 4 of which are English and the rest Soviet.

SUBMITTED: February 23, 1959.

Card 1/1

S/194/61/000/002/011/039
D216/D302

16.8000

AUTHOR: Kuntsevich, V.M.

TITLE: A study of extremal sampled data control systems
with pulse and digital elements

PERIODICAL: Referativnyy zhurnal. Avtomatika i radioelektronika,
no. 2, 1961, 32, abstract 2 V245 (V sb. Teoriya i
primeneniye diskretn. avtomat. sistem, M., AN SSSR,
1960, 425-445)

TEXT: A study of transient oscillation around the position of the
extremum in an extremal system ~~SC~~ (ES). Transients in a relay con-
tinuous ES are analyzed in the phase plane. The shape of oscilla-
tions of the controlled quantity in the sampled data ES differs
little for given settings from that of oscillations in continuous
systems. Circuits of sampled data ES of control are given and
oscillating states of their operation are analyzed. A description
is given of an extremum regulator of the sampled data type with
digital computing arrangements. 24 references.
Card 1/1

✓B

69809

16,9500

S/024/60/000/01/011/028

E081/E335

AUTHOR: Kuntsevich, V.M. (Kiyev)

TITLE: A Peak-holding Control System⁹ Subject to a Random Input

PERIODICAL: Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh nauk, Energetika i avtomatika, 1960, Nr 1, pp 90-101 (USSR)

ABSTRACT: The paper presents a summary of three papers by Ivakhnenko and Kuntsevich in Avtomatika (Ukrainian) in 1958 and 1959. The system is one in which a small-amplitude harmonic perturbation is used (in conjunction with a phase-sensitive detector) to establish the size and sense of the deviation from the peak. The essential features of the random quantities A_n and B_n are indicated by Eq (1.13) (in each case the mathematical expectation is zero). The stability in the open-loop state is examined; the error is presented as a function of signal-to-noise ratio (Figure 3). The second section deals with a similar system, which has two harmonic perturbations differing in frequency (and two phase-sensitive detectors). The stability of that system is examined similarly for a system whose

Card1/2

69809

S/024/60/000/01/011/028

A Peak-holding Control System Subject to a Random Input

perturbations have frequencies in the ratio 1:2. The third section deals with the stability in the closed-loop state; here the discussion is less rigorous. The last section presents a simple example. There are 5 figures and 13 references, 12 of which are Soviet and 1 is English.

SUBMITTED: October 2, 1959

✓

Card 2/2

KUNTSEVICH, V.M.

S/102/60/000/02/04/005
C111/C222

9.4310

AUTHORS: Vasil'yev, V.I., and Kuntsevich, V.M. (Kyyiv)

TITLE: Contactless Synchronous Relay Type Detector for Infra-low
Frequencies 250 ✓

PERIODICAL: Avtomatika, 1960, No.2, pp. 73-75

TEXT: The present paper contains a description of a contactless synchronous detector with transistors projected in the Laboratory of Automatic Control of the Institute of Electrical Engineering of the Academy of Sciences Ukr.SSR. The detector shall be used for extremal systems. The connection between the input magnitude and output magnitude is the same as for contact circuits. Triodes of the type P6A are used. Experiments have shown that only triodes with equal characteristics shall be used. There are 4 figures.

SUBMITTED: January 15, 1960

Card 1/1

KUNTSEVICH, V.M.



3/102/60/000/002/007/008/21
D251/D304

AUTHORS: Zeydel', K.H. (L'viv), and Kuntsevich, V.M. (Kyiv)

TITLE: The use of an extremal regulator for the automatic dosage of lime in chemical water-purifiers

PERIODICAL: Avtomatyka, no. 2, 1960, 76-80

TEXT: The authors propose a new principle for automatic lime regulation which they claim will guarantee an optimum liming regime with variable hardness of the water. The principle is based on the automatic maintenance of minimum electrical conductivity in the water with the help of an extremal regulator using a conductometric sensor. The theoretical bases of the method are the chemical reactions



Card 1/2

S/102/60/000/002/007/008/XX
D251/D304

The use of an extremal ...

in direct proportion to the number of OH^- and Ca^{++} ions, hence minimum conductivity implies maximum precipitation. There are two basic schemes of regulation. In the first the extremal regulator is applied to the direct variation in the loss of lime. This scheme has certain faults which, the authors claim, are avoided in the combination-type scheme. This latter scheme is illustrated in a figure. The authors claim that with this combination-type apparatus a liming regime close to the optimum may be maintained. Engineer B.K. Svetal'skiy and Senior Mechanic V.V. Korochinskiy participated in work on the regulator. There are 4 figures

Fig. 1. Schematic diagram of the regulator.

Fig. 2. ...

81283

13.2000

S/102/60/000/003/004/006

G 111/ C 333

AUTHORS: Kuntsevych, V. M., Vasyl'yev, V. J. (Kyyiv)

TITLE: New Schemes of Extremum Controllers of the Step Type

PERIODICAL: Avtomatika, 1960, No. 3, pp. 31-37

TEXT: This paper present a description of two schemes of extremum controllers of the step type developed in the automatic control laboratory of the Instytut elektrotekhniki AN URSR (Institute of Electrical Engineering of the Academy of Sciences of the Ukrainian SSR). Without differing from the existing extremum controllers by the law of regulation which is utilized, the new controller schemes differ advantageously from them constructively, inasmuch as their contact elements are almost completely replaced by contactless elements in order to raise the reliability of operation. ✓

The controller schemes described in this paper are designed chiefly for controlling objects to be regulated with great inertia and (or) with great delay. The control period of the controllers may be gradually altered from 0 to 8 or 9 minutes.

The first of the described controllers is a controller of the relay type having a law of regulation

Card 1/3

84283

S/102/60/000/003/004/006

C 111/ C 333

New Schemes of Extremum Controllers of the Step Type

$$(1) \begin{cases} u = a_0 \operatorname{sign} (\bar{\varphi}_n - \bar{\varphi}_{n-1}) u_{n-1} & \text{for } nT \leq t \leq (n + \gamma)T \\ u = 0 & \text{for } (n + \gamma)T \leq t \leq (n + 1)T, \end{cases}$$

where $\gamma = \text{const}$ is the impulse width, T control period, φ_n , φ_{n-1} values of the controlled variable averaged over T taken at the origin of the $n - 1$ and n periods of the control, u voltage of the impulse element, while in the second extremum controller latitude-impulse modulation - law of regulation (1),

$$(3a) \gamma \approx \gamma_0 + a |\bar{\varphi}_n - \bar{\varphi}_{n-1}| \quad \text{for } \operatorname{sgn} u_n = \operatorname{sgn} u_{n-1}$$

and

$$(3b) \gamma = \gamma_0 \quad \text{for } \operatorname{sgn} u_n \neq \operatorname{sgn} u_{n-1}$$

where $\gamma_0 = \text{const}$ - is used for improving the quality of the control process.

The described controllers ensure the required change of sign of the regulating effect with a change in voltage u_φ proportional to the extremum index by ~ 0.15 v (with change in u_φ ranging from 0 to 5 v).

Card 2/3

01:23

S/102/60/000/003/004/006

O 111/ O 333

New Schemes of Extremum Controllers of the Step Type

B. K. Svetal's'kyy, engineer is mentioned in the paper.

There are 5 figures, and 2 Soviet references.

SUBMITTED: April 20, 1960

X

Card 3/3

KUNTSEVICH, V.M.

S/102/60/000/004/002/006
D251/D304

16.8000

AUTHORS: Kostyuk, V.I., Kuntsevych, V.M., and Mandrovs'kyi-
Sokolov, B.Yu.

TITLE: On the work of S. Chang "Application of the z-trans-
formation method for optimization of self-adjusting
systems"

PERIODICAL: Avtomatyka, no. 4, 1960, 14 - 31

TEXT: An outline is given of the above-named work of S. Chang
(Ref. 1: AIEE Conference Paper, NCP, 59-1296) in which two kinds
of systems are considered: The derivative sensing system and the
alternate biasing system. The authors consider Chang's work in re-
lation to other investigators, in particular V.V. Kazakevich (Ref.
24: Sistemy ekstremal'nogo regulirovaniya i nekotoryye sposoby ulu-
chsheniya ikh kachestva (Systems of Extremal Control and Some Me-
thods of Improving Their Properties) sb. Avtomaticheskoye upravle-
niye i vychislitel'naya tekhnika, pod. red. V.V. Solodognikova, Ma-
shgiz, 1958) and O.M. Kryzhanovs'kyi and V.Ya. Soltyk (Ref. 22: Av-
Card 1/3

S/102/60/000/004/002/006
D251/D304

On the work of S. Chang ...

tomatyka, no. 4, 1960). The author state that the results of Chang and Kryzhanovs'kyy and Soltyk, despite different methods of approach, are of the same form. Attention is drawn to the resemblance between block-diagrams of the two methods and the fact that both recommend the derivative sensing system with a weighted sum of all previously measured values of the figure of merit (cost function). It is shown that these systems give an advantage in noise stability only in the case of slowly-changing perturbances. The authors state that there is no practical difficulty in constructing Chang's schemes in practice, but that certain of his basic statements and assumptions need further clarification. There are 11 figures, 4 tables and 24 references: 7 Soviet-bloc and 17 non Soviet-bloc. The 4 most recent references to the English-language publications read as follows: T.P. Goodman, R.H. Hillsley, Continuous self-measurement of characteristics of systems with random inputs. A step towards self-optimizing control, ASME Paper, 58-1RD-5, 1958; G.W. Anderson, J.A. Aseftine, A.R. Mancini, C.W. Sature. A self adjusting system for optimum dynamic performance, IRE National Convention Record, Part 4, 1958; J.E. Bertram, Control by stochastic adjust

Card 2/3

On the work of S. Chang ...

S/102/60/000/004/002/006
D251/D304

ment, AIEE Winter meeting, Conference Paper, Febr. 1959. R. Staf-
fin, Executive--Controlled adaptive systems, AIEE Winter Meeting,
Conference Paper, Febr. 1959.

SUBMITTED: May 20, 1960

✓
B

Card 3/3

KUNTSEVICH, V.M. (Kiyev)

Concerning the theory of experimental step-by-step systems.
Izv. AN SSSR. Otd. tekhn. nauk. Energ. i avtom. no. 5: 68-76 S-O
'60. (MIRA 13:11)
(Automatic control)

85056

S/024/60/000/005/002/017

E140/E435

16.9500 (1024, 1031, 1344)

AUTHOR: Kuntsevich, V.M. (Kiyev)

TITLE: Certain Problems in the Theory of Stepping Extremum Regulators

PERIODICAL: Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh nauk, Energetika i avtomatika, 1960, No.5, pp.77-86

TEXT: Although the study of extremum regulators with continuously shifting point of extremum is at least as important as the investigation of such systems with impulse disturbances, there are as yet no rigorous investigations of such systems with stepping structures. This article considers transient processes in such systems of various types and considers questions of improving their quality. It is assumed that all computations required in the system are carried out instantaneously. It is also assumed in the present work that the systems investigated have constant control period T . The problem is first solved for an extremum point which is displaced by an impulse disturbance remaining fixed after the disturbance and then this restriction is lifted. The equation of the closed-loop control system is found in the form of a linear second-order finite-difference equation. According to the

Card 1/3

X

85056

S/024/60/000/005/002/017

E140/E435

Certain Problems in the Theory of Stepping Extremum Regulators

character of the roots the system should arrive at the point of extremum, perhaps carrying out a damped oscillation. It was assumed that the computer built into the system can divide. Further, a variant is discussed in which division is not required. The author mentions his previous work (Ref.10) describing a transistor realization of such a machine operating reliably. It is pointed out that these systems may be improved by using pulse-width modulation. This permits a simple control circuit without division and obtaining transients close to those in the linear case. In another paper by the same author (Ref.5) an extremum control using continuously acting circuits was described using a corrective network introducing the first difference of the x-coordinate into the linear system. For systems containing non-linear circuits with extremum characteristics and a linear circuit with high inertia, an improvement may be obtained by introducing an additional term proportional to the second difference of the extremum position. With an extremum position varying continuously at constant velocity, the variation of the controller output compensating this will take place at the same velocity but with a velocity error. This is

Card 2/3

✓X