

MALININ, Yu.S., kand.tekhn.nauk; MAYANTS, M.M., inzh.

Calorimeter or conductometer for studying the hydration process of
cement during heat and moisture treatment. Trudy NIITs cement
no.17:45-52 '62. (MIRA 16:5)

(Cement--Testing)

MALININ, Yu.S., kand.tekhn.nauk; KLISHANIS, N.D., inzh.

Study of the hydration process of tricalcium silicate. Trudy
NIITSement no.17:53-63 '62. (MIRA 16:5)
(Calcium silicates)

ROYAK, S.M., dotsent, kand.tekhn.nauk; MALININ, Yu.S., kand.tekhn.nauk;
MAYANTS, M.M., inzh.

Study of the hydration process of tricalcium silicate during heat
and moisture treatment. Trudy NIITsSement no.17:64-75 '62.
(MIRA 16:5)

(Calcium silicates)

BUDNIKOV, P.P., akademik; ROYAK, S.M.; MALININ, Yu.S.; MAYANTS, M.M.

Hydration kinetics of Portland cement clinker minerals in hydro-thermal treatment. Dokl. AN SSSR 148 no.1:91-94 Ja '63.

(MIRA 16:2)

1. Vsesoyuznyy gosudarstvennyy nauchno-issledovatel'skiy institut tsementnoy promyshlennosti. 2. AN UkrSSR (for Budnikov).
- (Portland cement) (Hydration)

5/020/63^{hh560}/148/001/018/032
B101/B186

70

AUTHORS: Budnikov, P. P., Academician AS UkrSSR, Royak, S. M.,
Malinin, Yu. S., Mayants, M. M.

TITLE: Study of the kinetics of hydration of Portland cement
clinker minerals in hydrothermal processing

PERIODICAL: Akademiya nauk SSSR. Doklady, v. 148, no. 1, 1963, 91-94

TEXT: The degree of hydration of $2\text{CaO}\cdot\text{SiO}_2$, $3\text{CaO}\cdot\text{SiO}_2$, $3\text{CaO}\cdot\text{Al}_2\text{O}_3$, and
 $4\text{CaO}\cdot\text{Al}_2\text{O}_3\cdot\text{Fe}_2\text{O}_3$ was calculated from the content of non-hydrated phase
determined by x-ray diffraction analysis: $L = 100 - A/100 + mA$, where L
is the degree of hydration, A the content of non-hydrated phase, and m
the stoichiometric coefficient for the water content of the fully
hydrated material. The empirical equation $L = K \log \tau - B$ was found,
where τ is the time, K a factor depending on temperature and other
experimental conditions, and B a constant proportional to the induction
period of hydration. The equation describes the hydration of the
principal amount (20-80%) of the individual compounds investigated, and

Card 1/2

Study of the kinetics of ...

S/020/63/148/001/018/032
B101/B186

their mixtures and the alite phase of Portland cement. Its use simplifies the study of cement hydration. Further investigations are being carried out for combined setting, i.e., short-termed hydrothermal processing and subsequent setting at room temperature. There are 4 figures and 3 tables. The most important English-language reference is: S. Brunauer, L. Copeland, R.H. Bragg, J. Phys. Chem., 60, no. 1, 112 (1956). ✓

ASSOCIATION: Vsesoyuznyy gosudarstvennyy nauchno-issledovatel'skiy institut tsementnoy promyshlennosti (All-Union State Scientific Research Institute of the Cement Industry)

SUBMITTED: September 11, 1962

Card 2/2

BUDNIKOV, P.P., akademik; ROYAK, S.M.; MAYANTS, M.M.; MALININ, Yu.S.

Occurrence of an intermediate phase during the hydration of tricalcium
silicate subjected to hydrothermal treatment. Dokl. AN SSSR 150
no.1:136-139 My '63. (MIRA 16:6)

1. AN UkrSSR i chlen-korrespondent AN SSSR (for Budnikov).
(Calcium silicates) (Hydration)

L 36940-66 EWT(m)/EWP(w)/T/EWP(t)/ETI/EWP(k) IJP(c) JD/HW/WB

ACC NR: AP6019713

SOURCE CODE: UR/0128/66/000/006/0003/0005

AUTHOR: Korolev, V. M. (Candidate of technical sciences); Kolobashkin, B. M. (Candidate of technical sciences); Zhmurina, Yu. A. (Engineer); Maslov, A. D. (Engineer); Malinina, A. D. (Technician); Kuyanov, M. M. (Technician)

ORG: none

TITLE: High-strength stainless steel VNL-1

SOURCE: Liteynoye proizvodstvo, no. 6, 1966, 3-5

TOPIC TAGS: stainless steel, high strength steel, austenitic martensite steel, precipitation hardenable steel/VNL-1 *stainless steel*

ABSTRACT: A new austenitic-martensitic cast stainless steel designated VNL-1 has been developed. The steel contains 0.08% max C, 0.9% max Mn, 0.75% max Si, 14.07—14.60% Cr, 6.45—7.50% Ni, 0.68—0.83% Mo, 0.016—0.018% S, and 0.028—0.30% P. At room temperature the steel has a tensile strength of 111—123 kg/mm², a yield strength of 84—93 kg/mm², an elongation of 11.8—19.0%, a reduction of area of 37—45%, and a notch toughness of 5—8 mkg/cm². The corresponding figures for -196C are 161—180 kg/mm², 107—147 kg/mm², 9—16%, 14—21%, and 4—7%. At 500C the steel has a tensile strength of 65—80 kg/mm², an elongation of 8—10%, and a reduction of area of 20—40%. In cyclic tests under a stress of 77.5—88 kg/mm², the steel withstood

Card 1/2

UDC: 621.74:669.15-194.55

L 36940-66

ACC NR: AP6019713

6000—14000 cycles at a frequency of 8 cycles/min. Under axial stresses, the steel has a fairly low notch sensitivity. The steel can be successfully welded with argon-shielded arc in either the as-cast or heat-treated conditions. Fully heat-treated welds have a strength of over 90 kg/mm² and a satisfactory notch toughness in the range -196C to 20C. The corrosion resistance in SO₂ and in sea water of VNL-1 is equivalent to that of E1696 and 268L steels. The steel is used for investment castings into ceramic molds. Orig. art. has: 7 figures and 4 tables. [FM]

SUB CODE: 11/ SUBM DATE: none/ ORIG REF: 002/ ATD PRESS: 5039

Card 212 *11/*

MALININA, A. I.

Finkel'shteyn, M. Z., K. F. Zhigach, Ye. M. Mogilevskiy, T. A. Tibilova, and
A. I. Malinina. "Carboxymethyl Ethers of Cellulose and Their Use in Industry"

Problems of Petroleum Production and Petroleum Engineering, Moscow, Neftyanoy
institut, Gostptekhnizdat, 1957, 393pp. (Trudy vyp. 20)
This book is a collection of articles written by professors and faculty members
of the Petroleum Inst. im I. M. Gubkin.

FINKEL'SHTEYN, M.Z., kand.tekhn.nauk; ZHIGACH, K.F., prof., doktor khimicheskikh nauk; MOGILEVSKIY, Ye.M., kand.tekhn.nauk; TIBILOVA, T.A., inzh., MALININA, A.I.

Carboxymethyl ethers of cellulose and their use in the national economy. Trudy MNI no.20:67-92 '57. (MIRA 13:5)
(Cellulose)

5(1,3) SOV/26-123-2-22/50
AUTHORS: Zhigach, K. F., Finkel'shteyn, M. Z., Timokhin, I. M.,
Malinina, A. I.

TITLE: Production of Carboxy-Methyl Cellulose Fractions and Investi-
gation of Its Physical and Chemical Properties (Polucheniye i
issledovaniye fiziko-khimicheskikh svoystv fraktsiy
karboksimetiltseilyulyozy)

PERIODICAL: Doklady Akademii nauk SSSR, 1958, Vol 123, Nr 2, pp 289-291
(USSR)

ABSTRACT: This water soluble sodium salt of the cellulose carboxy-methyl
ester (CMC) has found widespread use in the last years as a
stabilizer, emulsifier, active addition to synthetic deter-
gents, as a glue etc. (Refs 1,2). CMC is a complex polydisperse
product consisting of various fractions that differ from each
other by their chemical composition (Ref 3) and their physical
and chemical properties. CMC can be produced with different
values of the esterification and polymerization. Therefore not
every CMC type is suited for the purpose. Only single types
can be practically used in the one or other branch of industry:
this must be determined in every single case. The connection

Card 1/4

SOV/20-123-2-22/50

Production of Carboxy-Methyl Cellulose Fractions and Investigation of Its Physical and Chemical Properties

between the chemical composition of the CMC samples and their properties and behaviour has remained unexplained until now. These samples almost ever contain a certain amount of small fibers that are difficult to solve and are capable of swelling, the so-called gel-like phase, the content of which can influence in a high degree the properties (especially the rheological properties, Ref 4) of CMC solutions. For these reasons the authors wanted to close this gap. Four samples of CMC were chosen as objects: a) That used for stabilizing loam solutions in drilling (Refs 2,5), b) That serving for the stabilization of silicate salt solutions when drilling into water-endangered and easily sliding soft rocks (Ref 2), and as a glue (Ref 6). c) German samples of the type VHR, d) A special CMC preparation of low viscosity. Besides its fractionation by means of methanol or acetone samples a - c are separated into the gel- and sol-like phases by centrifuging. I The viscosity, II the stabilizing effect were determined of the fractions obtained. The viscosity of the aqueous solutions of CMC above 0.1% does not obey the Newton law. In the 0.05% solutions investigated

Card 2/4

SOV/20-123-2-22/50

Production of Carboxy-Methyl Cellulose Fractions and Investigation of Its
Physical and Chemical Properties

the viscosity anomaly was almost completely lacking. The stabilizing effect of the CMC fractions was determined by the filtration analysis with a pressure drop of 1 atmosphere absolute pressure. Table 1 gives the results. As may be seen, the fractionation tends to show a heterogeneity of the CMC with respect to the degree of polymerization and esterification. The properties of the fractions change according to rules with the order of the isolation of the latter: lower polymerized fractions are esterified in a higher degree. The fractions produced by precipitation are not of equal value with respect to their stabilizing properties. It was also shown that the gel-like phase has only a weak stabilization and effect. Besides the degree of polymerization and esterification this must be taken into account. The ratio of the gel- and sol-like phase is not only important when used as a stabilizer of loam solutions. The gel-like phase is the most effective when using it as a glue. There are 1 table and 7 references, 4 of which are Soviet.

Card 3/4

SOV/20-123-2-22/50
Production of Carboxy-Methyl Cellulose Fractions and Investigation of Its
Physical and Chemical Properties

ASSOCIATION: Moskovskiy neftyanoy institut im. I. M. Gubkina (Moscow
Petroleum Institute imeni I. M. Gubkin)

PRESENTED: July 3, 1958, by A. V. Topchiyev, Academician

SUBMITTED: July 1, 1958

Card 4/4

5(3),17(3)

AUTHORS:

Zhigach, K. F., Finkel'shteyn, M. Z.,
Timokhin, I. M., Malinina, A. I.

SOV/20-123-3-25/54

TITLE:

Carboxy-Methyl Cellulose Preparations for Blood-Substituting
Solutions (Polucheniye preparatov karboksimetilttsellyulozy dlya
krovezameshchayushchikh rastvorov)

PERIODICAL: Doklady Akademii nauk SSSR, 1958, Vol 123, Nr 3, pp 471-474
(USSR)

ABSTRACT:

The sodium salt of the compound under review (Na-CMC) does not considerably change the blood composition if used as a plasma substitute in animals (Ref 1), even not in considerable excess. Na-CMC, however, was negatively characterized since it causes hypertension on intravenous injection. It was useful to try the synthesis of such preparations which also would yield good results with regard to their hemodynamic properties. CMC preparations can be produced with different polymerization degree (PD) and esterification degree (ED). This work was initiated by the institute mentioned in the "Association" together with Tsentral'nyy institut gematologii i perelivaniya krovi = TsOLIPK (Central Institute of Hematology and Blood Transfusion) in 1953.

Card 1/4

Carboxy-Methyl Cellulose Preparations for
Blood-Substituting Solutions

SOV/20-123-3-25/54

CMC preparations with different PD- and ED-values were obtained by esterification of pulverized alkali cellulose with sodium monochlorine acetate. The quantity of the esterifying agent depends on the PD of the original alkali cellulose. Table 1 shows that, at the same ratio of the reagents, with a lesser PD of alkali cellulose higher EDs are attained. The desired ED can be obtained by a limitation of the sodium monochlorine acetate consumption, as this reduces the PD of the initial cellulose. For the synthesis of blood-substituting solutions only chemically pure CMC preparations can be used. An instruction for the purification is given. In order to obtain a complete solubility the ED of CMC must be high; values of 70-85 do not influence the blood-substituting properties of CMC (Ref 5). From among the CMC preparations tested (PD of 240 up to 58) those with values between 70 and 100 were the most efficient ones (3% aqueous solutions with a viscosity 3.5 - 5.0 centipoises; contrary to Ref 6). The desired preparations with a low PD can be obtained by a) destruction of the initial cellulose and alkaline cellulose, respectively, or b) by additional splitting of finished CMC preparations. Only the mode b) can be recommended.

Card 2/4

Carboxy-Methyl Cellulose Preparations for
Blood-Substituting Solutions

SOV/20-123-3-25/54

In order to accelerate the destruction process of the alkali cellulose that requires a lot of time, by atmospheric oxygen (Table 2), hydrogen peroxide is added to the mercerization bath or to the alkali cellulose during the pulverization. The results of the experiments are given in table 3. Small quantities H_2O_2 (up to 1.5%) do not influence the blood-substituting properties of CMC. Large amounts, if added directly to alkali cellulose, turn CMC preparations toxic, and animals are killed if they are intravenously injected. The increase in the toxic effect cannot be explained by a modification of the average chemical composition. Most probably it is a consequence of the unequal destruction process as well as of the agglomeration of a certain quantity of highly oxidized cellulose by which CMC preparations become toxic. For this reason, H_2O_2 must be used very carefully for the above-mentioned purpose. For the purpose of reducing of the PD below 100 the finished product was hydrolytically cleft with aqueous HCl solution at 65-70°. The duration of this process depends on the initial PD of CMC preparations. Good

Card 3/4

Carboxy-Methyl Cellulose Preparations for
Blood-Substituting Solutions

SOV/20-123-3-25/54

results were yielded with CMC preparations of a relatively low molecular weight (PD about 130). The investigations performed suggest new ways of synthesizing Na-CMC preparations with blood-substituting properties. There are 5 tables and 9 references, 6 of which are Soviet.

ASSOCIATION: Moskovskiy neftyanoy institut im. I. M. Gubkina
(Moscow Petroleum Institute imeni I. M. Gubkin)

PRESENTED: July 3, 1958, by A. V. Topchiyev, Academician

SUBMITTED: July 1, 1958

Card 4/4

FINKEL'SHTEYN, M.Z.; TIMOKHIN, I.M.; MOGILEVSKIY, Ye.M.; MALININA, A.I.

Obtaining sodium chloroacetate for the production of
carboxymethyl ethers of cellulose. Izv.vys.ucheb.zav. nef't' i
gaz 2 no.12:43-47 '59. (MIRA 13:5)

1. Moskovskiy institut nef'tikhimicheskoy i gazovoy promyshlennosti
imeni akademika I.M. Gubkina.
(Cellulose) (Acetic acid) (Oil well drilling fluids)

DKHARIYAL, Ch.D.; ZHIGACH, K.F.; MALININA, A.I.; TIMOKHIN, I.M.;
FINKEL'SHTEYN, M.Z.

Effect of production techniques of carboxymethylcellulose
on its etherification and solubility in water. Izv.vys.ucheb.
zav.; nef't' i gaz 5 no.2:29-34 '62. (MIRA 15:7)

1. Moskovskiy institut nef'tekhimicheskoy i gazovoy
promyshlennosti imeni akademika I.M. Gubkina.
(Cellulose)

FINKEL'SHTEYN, M.Z.; TIMOKHIN, I.M.; SATIMBAYEV, R.S.; PODLEGAYEV, I.P.;
MALININA, A.I.

Using low-viscosity preparations of carboxymethylcellulose
for stabilizing weighted clay muds. Izv.vys.ucheb.zav.; neft'
i gaz 5 no.4:25-27 '62. (MIRA 16:1)

1. Moskovskiy institut neftekhimicheskoy i gazovoy promyshlen-
nosti imeni akademika I.M.Gubkina, Namanganskiy zavod
iskusstvennogo volpkna. (Cellulose) (Oil well drilling fluids)

DKHARIYAL, Ch.D.; MALININA, A.I.; TIMOKHIN, I.M.; FINKEL'SHTEYN, M.Z.

Effect of some factors on the reaction rate of carboxymethylation of cellulose and the homogeneity of carboxymethylcellulose. Zhur. prikl. khim. 36 no.11:2513-2517 N '63.
(MIRA 17:1.

1. Moskovskiy institut neftekhimicheskoy i gazovoy promyshlennosti imeni I.M. Gubkina.

DKHARIYAL, Ch.D.; ZHIGACH, K.F.; MALININA, A.I.; TIMOKHIN, I.M.;
FINKEL'SHTEYN, M.Z.

Factors influencing the effectiveness of cellulose
carboxymethylation. Zhur.prikl.khim. 37 no. 5; 1099-1105
My '64. (MIRA 17:7)

1. Moskovskiy institut neftekhimicheskoy i gazovoy
promyshlennosti imeni I.M.Gubkina.

L 08460-67 EWP(j)/EWP(k)/EWP(m) IJP(c) RM
ACC NR: AP6030903 (A,N) SOURCE CODE: UR/0080/66/039/008/1849/1852

AUTHOR: Dzhariyal, Ch. D.; Malinina, A. I.; Timokhin, I. M.; Finkel'shteyn, M. Z. 24

ORG: Moscow Institute of the Petrochemical and Gas Industry imeni I. M. Gubkin
(Moskovskiy institut neftekhimicheskoy i gazovoy promyshlennosti) B

TITLE: Effect of the conditions of preparation of carboxymethylcellulose (CMC) on the degree of its polymerization

SOURCE: Zhurnal prikladnoy khimii, v. 39, no. 8, 1966, 1849-1852

TOPIC TAGS: cellulose, polymer degradation, polymerization degree

ABSTRACT: A study of the effect of the mercerization temperature showed that as the latter rises, the degree of polymerization of carboxymethylcellulose (CMC) diminishes. This is attributed to the high rate of degradation of cellulose during its mercerization at higher temperatures. In the process of carboxymethylation of cellulose, a rise in the reaction temperature to 80°C reduces the degradation of the CMC obtained. At 95°, however, the degradation is more pronounced. The degree of polymerization of CMC decreases very appreciably with rising content of free NaOH in the reaction mixture. It does not change with changing cellulose/ClCH₂COOH ratio and changes only slightly with the water/cellulose ratio. Ultrasonic waves (19.45 kc) had no effect on the polymerization. It is shown that the degree of polymerization of CMC can be determined in unpurified preparations, since the impurities they contain do not have any

Card 1/2

UDC: 547.458.81+541.64

L 08460-67

ACC NR: AP6030903

appreciable effect on the concentration of the low-molecular electrolyte in a 1.5
N NaOH solution. Orig. art. has: 8 tables.

SUB CODE: 07/ SUBM DATE: 06Jul64/ ORIG REF: 002/ OTH REF: 001

FINKEL'SHTEYN, M.Z.; DKHARIYAL, Ch.D.; TIMOKHIN, I.M.; MALININA, A.I.

Effect of successive additions of reagents and the degree of polymerization of cellulose on the degree of esterification and solubility of carboxymethylcellulose in water. Izv. vys. ucheb. zav.; nef't' i gaz 5 no.11:31-34 '62.

(MIRA 17:6)

1. Moskovskiy institut neftekhimicheskoy i gazovoy promyshlennosti imeni akademika I.M. Gubkina.

ORLOV, Vladimir Ivanovich; MALININA, G., red.

[A treatise on inspiration which gives birth to great
inventions] Traktat o vdokhnove'e rozhdaushchem velikie
izobreteniia. Moskva, Izd-vo "Znanie," 1964. 349 p.
(MIRA 17:6)

GALKO, N.V.; KURNOSOVA, L.M.; MALININA, G.P.

Results of the study of the safety and immunological effectiveness of simultaneous vaccinations with live vaccines against poliomyelitis and mumps. Trudy Len.inst.epid.i mikrobiol. 22: 66-93 '61. (MIRA 16:2)

1. Iz virusologicheskoy laboratorii Leningradskogo instituta epidemiologii i mikrobiologii imeni Pastera i otdela virusologii Instituta epidemiologii i mikrobiologii AMN SSSR (zav. - chlen-korrespondent AMN SSSR prof. A.A. Smorodintsev).
(POLIOMYELITIS---VACCINATION)
(MUMPS---PREVENTIVE INOCULATION)

Heat-treatment of chromium and tungsten magnet steels. V. A. Erakhtin and K. Mahovina. *Stal* 9, No. 4 5, 63-6 (1939).—Magnetic properties of steels contg. (1) C 0.90-1.10 and Cr 2.90-3.80% and (2) C 0.68-0.78, W 5.0 6.0 and Cr 0.3-0.5% which have been annealed for machining can be restored by heating to a high temp., about 1025° for (1) and 1200° for (2), for 5 min. to dissolve the carbides, cooling in air, annealing at 600° to ppt. carbides at the optimum degree of dispersion and quenching in oil from 850°.

H. W. Rathmann

ASME-STEEL METALLURGICAL LITERATURE CLASSIFICATION

MALININA, K. A.

MALININA, K. A. "Isothermic Transformation of P9 Austenitic Steel."
Min Higher Education USSR. Moscow Order of Labor
Red Banner Inst of Steel imeni I. V. Stalin.
Moscow, 1950. (Dissertation for the Degree of
Candidate in Sciences)
TECHNICAL

So: Knizhaya Letopis', No. 17, 1956.

MALININA, K. F.

GULYAEV, A. P.; MALININA, K. A.

8
1-4E2C

Isothermal transformation of austenite in high-speed steel
A. P. Gulyaev and K. A. Malinina. Metalloved. i Obrabotka
Metallov, 1956, No. 12, 3-8. An exper. study was made of steel
R64C0.9, Cr 4.3, W 9, V 2.3%. The types of heat-treat-
ments used were: (a) austenitizing at 900° followed by iso-
thermal transformation for 6 hrs. at 750° to 100°; (b) the
same except 1220° austenitizing; (c) 1220° austenitizing;
cooled to 20° and isothermally transformed at 700° to 100°;
(d) the same as c except cooled to -78°; (e) the same as
c except held 30 min. at 560° before isothermal transforma-
tion at 500° to 100°; (f) the same as c except the time was 1
hr.; (g) the same as c except the time was 5 hrs. The amt. of
austenite and its compn. after austenitizing at 900° and at
1220° was: 900°, 87%_W, 2.0, Cr 2.0, V 0.3%; 1220°,
96%_W, 7.4, Cr 4.2, V 1.4%. The amt. of martensite after
austenitizing at 1220° and cooling to 20° and to -78° was:
20°, 60%_W, -78°, 76%_W. The amt. carbide phases at the be-
ginning of isothermal transformation for various treatments
were: c 4.0; e 4.4; f 4.8; g 5.8%. The amt. of isothermal
transformation was detd. by magnetic measurements.
Temp.-time-transformation (TTT) diagrams were con-
structed for primary austenite produced at 900°, primary
austenite produced at 1220°, retained austenite, and tem-
pered retained austenite. Diagrams were also given show-
ing the phase compn. and the hardness after 6-hr. transfor-
mation. The TTT diagrams for primary austenite showed
zones corresponding to pearlite, bainite, and martensite.
The diagrams for retained austenite lacked the bainitic and
martensitic zones and showed a faster pearlite reaction the
larger the amt. of martensite. The diagrams for tempered

1/2

GULYAEV, A.F.; MALININA, K.A.

retained austenite showed bainitic and martensitic zones. On the basis of the expd. results recommendations were made for improving various heat-treatments of this steel. For annealing after hot-working: 1 hr. at 750°, air cool. For annealing after welding: hot welded parts held at 750° for 6 hrs., cooled to 500°, and then air cooled. For step quenching: 5- to 10-min. treatment in a bath at 250 to 600°. For bainitic treatment: quench to 300° and hold for 3 hrs., temper at 500° for 1 hr., cool to 250° and hold for 5 hrs., cool to room temp., and then repeatedly temper for 1 hr. at 500°.

A. G. Guy

8
14E2C

2/2

RS any

MALINDA, K.A.

Sensitivity of micrometers and experimental errors in the study of phase transformations. *K. A. Malinda*

Phys. Lett. 22, 812-14 (1954). -- Readings of 3 modifications of an autometer were compared with respect to the amount of residual gas found in a high speed steel. A close agreement was recorded, though the results reported differ from those obtained by the ballistic method. *J. D. G.*

*A-U Sci Res Instrument Inst.
MS 2 IP*

MALININA, K. ^{A.} kandidat tekhnicheskikh nauk.

Sixth conference of laboratory workers employed by instrument making plants. Zav.lab.22 no.11:1394-1395 '56. (MLBA 10:2)

1. Vsesoyuznyy nauchno-issledovatel'skiy instrumental'nyy institut.
(Scientific apparatus and instruments)

MALININA, K.A.; SMOL'NIKOV, Ye.A.; SUYETOV, A.P.; BADAYEVA, A.A.; LUNEVA, Z.S.; KUKOLEV, V.V.; SOKOLOVSKAYA, V.V.; LEBEDEVA, Ye.A.; UVAROVA, A.F., tekhn.red.

[Technological operations in the manufacture of metal-cutting tools; instructions] Tekhnologiya izgotovleniya metallorezhnykh instrumentov; rukovodiashchie materialy. Moskva, Gos. nauchno-tekhn.izd-vo mashinostroit.lit-ry. No.7. [Heat treatment] Termicheskaya obrabotka. 1960. 127 p.

(MIRA 13:6)

1. Vsesoyuznyy nauchno-issledovatel'skiy instrumental'nyy institut.
 2. Termicheskaya laboratoriya Vsesoyuznogo nauchno-issledovatel'skogo instrumental'nogo instituta (for all, except Uvarova).
- (Metal-cutting tools) (Metals--Heat treatment)

ATTENTION

TO: [illegible]

FROM: [illegible]

SUBJECT: [illegible]

Card 1

Short Time Temperature of the ...

...

... dependent ...
...
...
...
...

...
...
...

...
...

...
...

...
...

...
...

...
...

...
...

...
...

...
...

...
...


Chart: Time Temperature

(subjected to a temperature of 100°C for 1 hour)
 temperature of the sample at the end of the heating
 (3) duration of the heating process (minutes)
 (4) duration of the cooling process (minutes)
 (5) duration of the holding process (minutes)
 (6) duration of the cooling process (minutes)
 heating arrangement, of temperature rate, of constant
 temperature and of the duration of the heating
 holding; (7) internal temperature of the sample
 tools used, temperature of the sample (if the
 is permitted). Comparison of the results of the
 Union Scientific Research Test Institute (VNIIT) with
 different plants, in order to find the time of the
 tempered in the different plants, in order to find
 lower (depending on the type of the sample)
 these temperatures, in order to find the time of the
 in the different plants. Results of the tests
 after various temperatures, in order to find the
 There are 3 different types of samples, in order to find

Card: 4

Short Time Tempering of Heat-Treated Al-3%Cu

Fig. 5. Heat-treated
of RO steel: (1) sample
tempering at 200°C. 1 hr;
(2) sample temper-
ing at 200°C. 1 hr;
(3) sample temper-
ing at 200°C. 1 hr;
(4) sample temper-
ing at 200°C. 1 hr.



1. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 2. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 3. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 4. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 5. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 6. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 7. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 8. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 9. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$
 10. $\text{H}_2\text{O} + \text{H}_2\text{O} \rightleftharpoons \text{H}_3\text{O}^+ + \text{OH}^-$

2011

GULYAYEV, A.P., doktor tekhn. nauk, prof.; MALININA, K.A., kand. tekhn. nauk; SAVERINA, S.M., inzh.; YAKOVLEVA, V.I., red.; UVOROVA, A.F., tekhn. red.

[Tool steels, properties and heat treatment; manual] Instrumental'nye stali, svoistva i termicheskaya obrabotka; spravochnik. Moskva, Gos. nauchno-tekhn. izd-vo mashinostroit. lit-ry, 1961. 205 p. (MIRA 14:8)

1. Moscow. Vsesoyuznyy nauchno-issledovatel'skiy instrumental'nyy institut.

(Tool steel)

MALININA, K.A.

Recrystallization of austenite in rapid steel following hot plastic deformation. Metalloved. i term. obr. mat. no. 5:15-17 My '64. (MIRA 17:6)

1. Vsesoyuznyy nauchno-issledovatel'skiy instrumental'nyy institut.

KURDINA, A.A.; MALININA, K.N.

Tertian malaria with prolonged incubation time in migrants
from the south. Med.paraz. i paraz.bol.24 no.3:220-223 J1-S
'55. (MLRA 8:12)

1. Iz Leningradskoy gorodskoy protivomalyariynoy stantsii
(zav.stantissey, R.M.Soboleva)
(MALARIA, epidemiology,
in Russia, tertian malaria in migrants from
southern Russia)

Malinina, K. N.
ZAPOL'SKAYA, A. N.; KURDINA, A. A.; MALININA, K. N.; PANFEROVA, Ye. A.

Relation of dysentery to hymenolepiasis. Med. parazit. i parazit. bol.
24 no.4:308-310 O-D '55. (MLRA 9:1)

1. Iz Leningradskoy protivomalyariynoy stantsii (zav. R. M. Soboleva)
(TAPEWORM INFECTION, in infant and child,
hymenolepiasis, relation to dysentery)
(DYSENTERY, in infant and child,
relation to hymenolepiasis)

MALININA, K. N.

KURDINA, A.A., MALININA, K.N., PANFEROVA, Ye.A.

The problem of the relation of dysentery to giardiasis helminth infections. Med.paraz. i paraz. bol. 27 no.2:183-188 Mr-Apr '58
(MIRA 11:5)

1. Iz parazitologicheskogo otdela Leningradskoy gorodskoy sanitarno-epidemiologicheskoy stantsii (glavnyy vrach N.G. Grigor'yeva, zav. otdelom R.M. Soboleva).

(DYSENTERY, complications
giardiasis or helminth infect., interrelation (Rus))
(GIARDIASIS, complications
dysentery, interrelation (Rus))
(HELMINTH INFECTIONS, complications
dysentery, interrelation (Rus))

Ref No L A

USSR/Chemical Technology - Chemical Products and Their
Application. Ceramics. Glass. Binders. Concrete.

H-7

Abs Jour : Referat Zhur - Khimiya, No 1, 1958, 2074

Author : Mironov S.A., Astreyeva O.M., Malinina L.A.

Inst : -

Title : Interaction of Minerals of Tricalcium Aluminate and
Tetracalcium Aluminoferrite with Finely Ground Quartz Sand
During Autoclaving.

Orig Pub : Tsement, 1957, No 2, 9-13

Abstract : A study of interaction of quartz sand and synthesized
 C_3A and C_4AF under conditions of autoclaving for 4 and
24 hours at pressures of 8, 12 and 16 atmospheres gau-
ge pressure. It was found that the strength of samples
prepared from pure C_3A and subjected to autoclaving, is
very low, which is attributed to the formation of tri-
calcium hydroaluminate of cubic form. The strength of
samples made from pure C_4AF is high; the products of

Card 1/2

USSR/Chemical Technology - Chemical Products and Their
Application. Ceramics. Glass. Binders. Concrete.

H-7

Abs Jour : Referat Zhur - Khimiya, No 1, 1958, 2074

hardening of C_4AF are the hexahydrate of iron hydroaluminate, a considerable amount of Ca hydroxide and Fe hydroxide. On addition of ground sand to the C_3A strength of the samples is increased considerably; in the experiments that are described a strength of up to 200 kg/cm^2 was attained. On addition of ground sand to C_4AF strength of the samples is decreased, which is due, apparently, to the fact that the main portion of the sand constitutes a lean addition, while the strength of the new formations is lower in this instance. It is pointed out that it is advantageous to utilize sandy portland cement, having as a base alite-alumoferrite clinker, in the manufacture of autoclaved articles; on steaming of the articles at atmospheric pressure the same clinker is recommended but with a substitution of finely ground active additives, in lieu of the sand.

Card 2/2

187

AUTHOR: Malinina, L.A., Ingenieur.


TITLE: On the composition of Portland Cement and the "optimum" pressure of steam for concrete components subjected to autoclave treatment. (O sostave Portlandtsementa i optimal'nom davlenii para pri avtoklavnoi obrabotke betonnykh izdelii).

PERIODICAL: "Beton i Zhelezobeton" (Concrete and Reinforced Concrete), 1957, No.2, pp.65-68 (U.S.S.R.)

ABSTRACT: This autoclave method accelerates the process of hardening and saves Portland cement (up to 50%) by the addition of finely ground sand. The selection of the type of Portland cement and optimum steam pressure are claimed to be very important. Investigations carried out by Professor S. A. Mironov of the NIITS are explained as follows: Clinker substances (C_3S , C_2S , C_3A and C_4AF) and also quartz sand were obtained synthetically and ground to pass a mesh with 4.900 squares/cm². Test results show that the high strength of the samples, after autoclave treatment, is developed in samples prepared from C_4AF and that samples made from C_3A possess no measureable strength. The addition of finely ground sand results in increased strength of the product due to the presence of hydrosilicates. Products based on C_3A are of average strength and products based on C_4AF

On the composition of Portland Cement and the "optimum"¹⁸⁷ pressure of steam for concrete components subjected to autoclave treatment. (Cont.)

are the weakest. All the clinker materials react chemically in the autoclave with the finely ground quartz sand, the addition of the latter inducing more complete hydration of all the clinker particles and thus considerably increasing the strength of the products. The largest quantity of quartz sand combines with C_2S , a slightly smaller quantity with C_3S ; this results in the formation of calcium hydrosilicate of considerable strength. C_3A and C_4AF also react with certain quantities of quartz sand⁴ forming:



The author recommends the introduction of this autoclave method in all new factories for precast concrete products. The products should be cured under pressure (8 to 12 ats). There are 2 graphs, 2 tables and 2 references, one of which is Russian.

KALININA, L. A., Cand Tech Sci -- (diss) "Study of the cement composition and steam pressure for concretes of autoclave solidification." Mos, 1958. 19 pp. (Acad of ^{Construction} ~~Build~~ and Architect^{ure} USSR, Sci Research Inst of Concrete and Reinforced Concrete NIIMB), 120 copies. (KL, 9-58, 118)

- 80 -

MIRONOV, S.A., prof., doktor tekhn.nauk; BUZHEVICH, G.A., kand.tekhn.nauk;
KRASNYI, I.M., kand.tekhn.nauk; MALININA, L.A., kand.tekhn.nauk;
KHAVIN, B.N., red.izd-va; BOROVNEV, N.K., tekhn.red.

[Instruction on autoclave hardening of concrete products made with
solid and porous aggregates] Instruktسيا po avtoklavnoi obra-
botke izdelii iz betonov na plotnykh i poristykh zapolniteliakh.
Moskva, Gos.izd-vo lit-ry po stroit., arkhitekt. i stroit.materialam,
1959. 25 p.

(MIRA 12:11)

1. Akademiya stroitel'stva i arkhitektury SSSR. Nauchno-issledo-
vatel'skiy institut betona i zhelezobetona, Perovo. 2. Laboratoriya
yacheistykh i legkikh betonov i uskorenogo tverdeniya betona Nauchno-
issledovatel'skogo instituta betona i zhelezobetona Akademii stroitel'-
stva i arkhitektury SSSR (for all except Khavin, Borovnev).

(Autoclaves)

(Concrete products)

MIRONOV, S.A., prof.; MALININA, L.A., kand.tekhn.nauk

Investigating the modulus of elasticity in autoclave-hardened
concretes. Trudy NIIZHB no.11:175-185 '59.

(MIRA 13:6)

(Concrete--Testing)

MIRONOV, Sergey Andreyevich, doktor tekhn. nauk, prof.; MALININA,
Larisa Alekseyevna, kand. tekhn. nauk; GLEZAROVA, I.L.,
red. izd-va; TEMKINA, Ye.L., tekhn. red.

[Accelerating the hardening of concrete; steaming concrete
under factory conditions] Uskorenie tverdeniia betona;
proparivanie betona v zavodskikh usloviakh. Moskva,
Gos. izd-vo lit-ry po stroit., arkhitekt. i stroit. materialam,
1961. 222 p.

(Concrete)

(MIRA 15:2)

MALININA, L.A., kand.tekhn.nauk

Frost resistance and spontaneous deformations in autoclave concretes
made with dense and porous aggregates. Bet. i zhe1.-bet. no.1:33-35
Ja '61. (M.I.A 14:2)

(Frost resistant concrete)

MIRCNOV, S.A., prof.; MALININA, L.A., kand.tekhn.nauk; FEDOROV, V.A., inzh.

Strength increase and linear deformations of concrete during
steaming. Bet. i zhel.-bet. no.4:170-174 Ap '61.

(MIRA 14:6)

1. Chlen-korrespondent Akademii stroitel'stva i
arkhitektury SSSR (for Mironov).
(Reinforced concrete)

MALININA, L., kand, tekhn. nauk

How to choose a steaming system. Stroitel' no. 5: 28-29 My '61.

(MIRA 14:6)

(Precast concrete)

S/081/62/000/007/077/07
B'50/B'01

AUTHORS: Mironov, S. A., Sizov, V. N., Malinina, L. A., Khvorost-
yanskiy, V. F.

TITLE: Investigation of the composition and processes of heat
treatment of highly stable mortars and fine-grained concretes
for prestressed reinforced concrete panels

PERIODICAL: Referativnyy zhurnal Khimiya, no. 2, 1962 391 - 392.
abstract 2K354 (Tr. N. i. in-ta betona i zhelezobetona Akad
strava i arkhitekt. SSSR, no. 20, 1962 52 - 69)

TEXT. The fundamental technological factors are considered for obtaining
the requisite strength of vibrated and rolled concrete for prestressed and
reinforced panels. To obtain a strength of 300 - 400 kg/cm² with preheating
for 2 to 4 hours at 100°C it is essential to apply fresh high-quality low
aluminate alite cements containing C₃S ≥ 55% and C₃A ≤ 6-8% with a specific
surface of 3500 - 4000 cm²/g. It is necessary to use classified sand,
eliminating particles less than 0.6 mm and to introduce instead parts of
sand (25-50%) of granitic rubbles with grains of 10 to 15 mm in size. The
Card /2

Investigation of the composition ..

S/081/62/000/002/077/10"
B-50/B-10"

reduction of B/U (V/Ts) to ensure a sufficiently satisfactory depositing of the concrete mix makes it possible to obtain fine-grained concrete of great strength immediately after short-duration preheating. Keeping the freshly prepared mix for 2/3 of an hour before pouring into the mold can also increase the strength of the vibrated and rolled panels. It is advantageous to stir the concrete mix in vibratory mixers or in crushers. Heat treatment at 100°C should be carried out for 3 - 4 hours with the surface covered to prevent loss of moisture. When testing for resistance to frost, samples of the cement-sand mortar, preheated for 2 hours at 100°C were kept for 100 cycles of freezing and thawing without any substantial loss of weight.

[Abstracter's note: Complete translation.]

Card 2/2

MALININA, L.A., kand.tekhn.nauk; FEDOROV, V.A., ~~inzh.~~

Deformations of concretes in the process of steaming and during
further storage provided with air-drying. Izv.ASiA 4 no.1:
90-97 '62. (MIRA 15:11)

(Concrete)

MIRONOV, S.A., doktor tekhn. nauk, prof.; MALININA, L.A., kand. tekhn. nauk; FEDOROV, V.A., inzh.; KAYSER, L.A., inzh.; KRONGAUZ, S.D., kand. tekhn. nauk; PANFILOVA, L.I., kand. tekhn. nauk; SEMENOV, L.A., doktor tekhn. nauk, prof.; PODUROVSKIY, N.I., kand. tekhn. nauk; VINNITSKIY, A.M., kand. tekhn. nauk; KLIMOVA, G.D., red. izd-va; SHEVCHENKO, T.N., tekhn. red.

[Instructions on curing concrete and reinforced concrete products at plants and building sites] Instruktsiia po preparivaniu betonnykh i zhelezobetonnykh izdelii na zavodakh i poligonakh. Moskva, Gosstroizdat, 1962. 33 p. (MIRA 15:12)

1. Akademiya stroitel'stva i arkhitektury SSSR. Institut betona i zhelezobetona, Perovo. 2. Chlen-korrespondent Akademii stroitel'stva i arkhitektury SSSR (for Mironov).
(Precast concrete--Curing) (Autoclaves)

S/081/62/000/022/053/088
B180/B186

AUTHORS: Mironov, S. A., Malinina, L. A.

TITLE: Chemical additives to accelerate concrete setting

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 22, 1962, 365, abstract
22K363 (Stavba, v. 9, no. 2, 1962, 41-44 [Slovak])

TEXT: A study was made of the effect of the following additions on the setting rate of concrete made with cement type 500: CaCl_2 , NaCl , NaNO_3 , K_2CO_3 , $\text{Al}_2(\text{SO}_4)_3$, $\text{Al}_2(\text{SO}_4)_3 + \text{CaCl}_2$, AlCl_3 , $\text{Na}_2\text{S}_2\text{O}_3$. Whatever the consistency of the concrete mixture, the composition of the cement or the conditions of setting, the most satisfactory additions were CaCl_2 and NaCl in the amount of $\sim 1\%$ (by weight of the cement). Chemical additions combined simultaneously with steaming produced the strongest concrete.
[Abstracter's note: Complete translation.]

Card 1/1

MIRONOV, S.A., prof.; MALININA, L.A., kand.tekhn.nauk; KOROLEVA, O.Ye., inzh.

Effect of the duration of curing on concrete strength. Bet.1
zhel.-bet. 9 no.5:196-199 My '63. (MIRA 16:6)
(Precast concrete--Curing)

MIRONOV, S.A., doktor tekhn. nauk, prof.; MALININA, L.A., kand. tekhn.
nauk; FEDOROV, V.A., inzh.

Physicomechanical properties of concrete with compact and
porous aggregates subjected to autoclave treatment. Trudy
NIIZHB no.32:88-109 '63. (MIRA 17:1)

MIRONOV, S.A., doktor tekhn. nauk, prof.; MALININA, L.A., kand. tekhn. nauk; LIFANOV, I.I., inzh.; MALINSKIY, Ye.N., inzh.

Dilatometric studies of structures of cement mortars subjected to various heat treatments. Trudy NIIZHB no.32:66-76 '63. (MIRA 17:1)

MIRONOV, S.A., prof., doktor tekhn. nauk, MALININA, L.A., kand. tekhn.
nauk; MALINIKIY, Ye.N., inzh.

Method of determining deformations of various concretes in
the process of autoclaving. Stroim. mat. 10 no.6:35-40 Fe '64.
(MIRA 17 10)

MIKONOV, S.A., doktor tekhn. nauk, prof.; MALININA, L.A., kandyd.
tekhn. nauk; KHVOROSTYANSKIY, V.F., inzh.; KUZNETSOVA, M.Ye.,
inzh.; KUZNETSOVA, M.N., red.

[Methods for the rapid heat treatment of concrete and
prospects for using them in the production of precast
concrete] Metody kratkovremennoi teplovoi obrabotki beto-
tona i perspektivy ikh primeneniia pri proizvodstve ob-
nogo zhelezobetona. Moskva, Stroiizdat, 1964. 120 s.

MILONOV, Sergey Andreyevich, doktor tekhn. nauk, prof.; MALININA,
Larisa Alekseyevna, kand. tekhn. nauk

[Acceleration of the hardening of concrete] Uskorenie
tverdeniia betona. Izd. 2., ispr. 1. Moskva, Stroi-
izdat, 1964. 347 p. (MIRA 17:7)

MIRONOV, S.A., doktor tekhn. nauk; MALININA, L.A., kand. tekhn. nauk;
MALINSKIY, Ye.N., inzh.

Role of the excess pressure of air-steam medium in the process
of thermal treatment of building materials. Stroi. mat. 11
no. 12:8-11 D '65. (MIRA 18:12)

BRONSHTEYN, R.M.; GORYUNOVA, V.G.; STERLIN, I.I.; MALININA, L.I.; IVANOVA, A.S.

Rapid complexometric (trilonometric) methods for determining the
zinc, magnesium, and calcium content of paint materials. Lakokras.
mat. i ikh prim. no.2:42-44 '60. (MIRA 14:4)
(Paint materials) (Zinc--Analysis)
(Magnesium--Analysis) (Calcium--Analysis)

PUGACHEV, A.G., kand. med. nauk; KRIZOVSKAYA, N.I.; MALININA, L.I.

Clinical Xray data in incomplete intestinal version. Pedia-
triia 42 no.3:25-30 Mr'63 (MIRA 17:2)

1. Iz khirurgicheskogo otdeleniya (zav. - kand. med. nauk A.G. Pugachev; nauchnyy konsul'tant - prof. S. Ya. Doletskiy) Instituta pediatrii (dir. M. Ya. Studenikin) AMN SSSR i Det-skoy gorodskoy klinicheskoy bol'nitsy No.13 imeni N.F. Filatova (glavnyy vrach L.A.Vorokhobov), Moskva.

ARENDET, A.A., prof.; ARTARYAN, A.A., kand. med. nauk; BAIROV, G.A., prof.;
VOLKOV, M.V., prof.; VARSHAVSKAYA, D.Ya., kand. med. nauk;
VOROKHOBOV, L.A.; GENEL'LOV, A.I., kand. med. nauk;
DANIYEL'BEK, K.V., kand. med. nauk; LENZHAVIN, V.M., kand.
med. nauk; DOLETSKIY, S.Ya., prof.; YERMOLIN, V.N.; ZATSEPIN,
S.T., kand. med. nauk; ZVYAGINTSEV, A.Ye., dots.; ISAKOV, Yu.F.,
doktor med. nauk; KOZYREV, V.A., kand. med. nauk; KONOVALOV,
A.N.; KORNYSANSKIY, G.P., prof.; KLIMANSKIY, V.A., kand. med.
nauk; KLIMKOVICH, I.G., dots.; KONENASHIN, N.I., kand. med.
nauk; LEVINA, O.Ya., kand. med. nauk; LENYUSHKIN, A.I., kand.
med. nauk; LEYBZON, N.D., doktor med. nauk; MALININA, L.I.,
doktor med. nauk; MAREYEVA, T.G., kandidat meditsinskikh
nauk; NERSESYANTS, S.I., kand. med. nauk; OVCHINNIKOV, A.A.;
OGLEZNEV, K.Ya., kand. med. nauk; ROSTOTSKAYA, V.I., kand.
med. nauk; STEPANOV, E.A., kand. med. nauk; EPSHTEYN, P.V.;
OSTROVERKHOV, G.Ye., prof., glav. red.; DOMBROVSKAYA, Yu.F.,
prof., otv. red.

[Multivolume manual on pediatrics] Mnogotomnoe rukovodstvo po
pediatrii. Moskva, Meditsina. Vol. 9. [Pediatric surgery] Khir-
urgiya detskogo vozrasta. Red. toma S.I.A. Doletskii. 1964. 654 p.

(MIRA 17:9)
1. Deystvitel'nyy chlen AMN SSSR (for Dombrovskaya). 2. Chlen-
korrespondent AMN SSSR (for Bairov, Volkov).

DATE / 11 :
 ABS. JOUR. : RZhBiol., No. 1959, No. 10354
 AUTHOR :
 INST. :
 TITLE :

RIG. PUB. :

STRACT : arid conditions. The best varieties of watermelons for Priaral'skaya semi-desert are: Melitopol'skiy, Semipalatinskiy belokrylyy, Sol'-Ilatskiy, Belosemyonko and others. The best period for sowing is April, beginning of May. The feeding area for watermelons under the conditions of Priaral'ye is 3-4 meters. -- V. D. Latkin-
 -Gurkov

CARD: 2/2

MALININA, M.I.

Adaptation features and properties of watermelons in dry farming.
Trudy po prikl. bot.; gen. i sel. 32 no.3:219-222 '59.

(MIRA 14:5)

(Melons) (Plants, Effect of aridity on)
(Adaptation (Biology))

MALININA, M. I., CAND AGR SCI, "CHARACTERISTICS OF
GROWTH AND DEVELOPMENT OF WATERMELONS IN THE NON-IRRI-
GATED AREA OF THE SEMIDESERT REGION OF WESTERN KAZAKHSTAN."
LENINGRAD-PUSHKIN, 1960. (MIN OF AGR RSFSR, LENINGRAD AGR
INST). (KL, 3-61, 226).

IVANOVA, Z.B.; DOBACOV, N.S.; MALININA, M.S.; POTASHEN, A.A.

A new preparation for the moist eradication of insects in grain elevators. Seleksiya i Semenovodstvo 17, No.6,51-3 '50. (MLRa 3:5) (CA 47 no.17:3958 '53)

USSR / General and Special Zoology. Insects

P

Abs Jour: Ref Zhur-Biol., No 1, 1958, 2361

Author : Yefremova N. I. and Malinina M. S.

Inst :

Title : The Preparation NIUIF-100 for the Disinfection of Warehouses.

Orig Pub: Zashchita rast. ot vredit. i bolezney, 1956, No 3, 28-29

Abstract: The following pests were destroyed by the emulsions of NIUIF-100: the granary Curculionidae and the peas Bruchidae, in 3 days and 3 nights, by a concentration of 0.001-0.01%; the rice Curculionidae, in 2-6 days and nights, by a concentration of 0.025-0.01%; mites, in 7 days and 7 nights, by a concentration of 0.005-0.01%; scarabs of the small Tenebrionidae, in 9 days and 9 nights, by a concentration of 0.01-9.06%.

Card 1/2

MALININA, M.S., starshiy nauchnyy sotrudnik

Spray disinfection of grain storages. Zashch. rast. ot vred.
1 bol. 3 no.4:30 J1-Ag '58. (MIRA 11:9)

1. Moskovskaya stantsiya zashchity rasteniy.
(Insecticides) (Grain--Storage)

IVANOVA, Z.V., kand.sel'skokhoz.nauk; MALININA, M.S., starshiy nauchnyy
sotrudnik

Prepare storages to receive new crops. Zashch.rast.ot vred.1
bol. 5 no.7:32-34 J1 '60. (MIRA 16:1)
(Granaries--Disinfection)

S.117/60/000/012/015/022
AOO4/AOO1

AUTHORS: Malinina, N., Molodkina, M., Datskiy, M., Filippov, G.

TITLE: Cement Models for the Manufacture of Dies

PERIODICAL: Mashinostroitel', 1960, No. 12, p. 36

TEXT: Generally the complex profile of the working surface of forging dies for blades is machined on copying milling machines according to wooden model templets. These models lose their geometrical shape rather quick because of temperature fluctuations and the effects of air moisture in the storing rooms. Instead of having model sets for forging dies made of wood, the manufacture of which takes a model maker of the 6th grade some seven days, the Leningradskiy metallicheskiy zavod (Leningrad Metallicheskiy Plant) produces these models from cement. The templets used for the cement-model making serve also for the checking of the die shape during the milling operation and fitting work. At the beginning a frame work is manufactured from templets, distance sleeves and gaging pins. Braces are mounted on the sides of the framework, tightened by wedges and cramps. Then diluted construction gypsum is filled into the framework, the side walls of which are removed after the solidification of the gypsum. The profile of the die

Card 1/2

Cement Models for the Manufacture of Dies

S/117/60/000/012/015/022
A004/A001

model is then shaped subsequently between every pair of neighboring templets, the surplus gypsum being cut away flush with the templet profile. Those parts of the profile for which the framework does not provide a templet is done by surface gaging. The ready gypsum mold is covered with a thin nitro-lacquer coating and greased with stearin diluted with kerosene in order to prevent the gypsum from sticking to the cement. Side walls are mounted to the ready mold and the cement is poured in. The process of the cement model setting takes 3-4 days. The cast cement model-templet has a smoother and better surface than the wooden ones, while its manufacture costs by 2-2.5 times less than that of wooden model-templets. There are 4 figures.

✓

Card 2/2

STRELETSKIY, D.N., kand.tekhn.nauk; MALININA, N.G., inzh.

"Economics of steel elements" by IA. M. Likhtarnikov. Reviewed
by D.N.Streletskii, N.G.Malinina. Prom. stroi. 40 [1.e. 41.]
no.3:55-56 Mr '63. (MIRA 16:3)
(Steel, Structural)

MALININA, N.G., inzh.

Setting labor standards for preparing welded structural
elements of aluminum alloys. Avtom. svar. 17 no.11:45-71
N '64 (MIRA 18:1)

1. NII montazhspestry.

MALININA, N.V., kand.med.nauk (Leningrad)

Urinary excretion of neutral 17-ketosteroids in dysentery. Vrach.
delo no.10:127-128 O '62. (MIRA 15:10)

1. Kafedra infektsionnykh bolezney (zav. - prof. P.I.Strelov)
Instituta usovershenstvovaniya vrachey, Leningrad.
(STEROIDS) (DYSENTERY)

MALININA, N. YE.

PA 50145

USSR/Geophysics
Magnetic Fields - Earth

Jan 1947

"Magnetic Field of West Siberia," N. Ye. Malinina,
Inst Terrestrial Magnetism, 18 pp

"Izv Akad Nauk SSSR. Ser Geograf i Geofiz" Vol XL,
No 1

Regional magnetic anomalies of the territories of
West Siberia mapped and published for first time.
Maps made without use of the results of detailed
magnetic surveys carried out by number of organiza-
tions, chiefly by the West Siberian Expedition of
the State-Union Geophysical Trust, due to the war

50145

USSR/Geophysics (Contd)

Jan 1947

and the necessity of rapid work. Maps may be used
to solve general questions of geologic structure in
West Siberia, and to plan geophysics and geologic
prospecting work. Future mapping will use more
complete data then available. Submitted by Acade-
mician L. S. Leybenzon.

50145

3(6)

PHASE I BOOK EXPLOITATION

SOV/2770

Malinina, Natal'ya Yevgen'yevna

Magnitnoye pole zemli (The Earth's Magnetic Field) Moscow, Svyaz'izdat, 1959.
39 p. (Series: Lektsii po tekhnike svyazi) 8,300 copies printed.

Sponsoring Agency: Ministerstvo svyazi SSSR. Tekhnicheskoye upravleniye.

Resp. Ed.: Yu. D. Kalinin; Ed.: V.I. Bashchuk Tech. Ed.: S.F. Karabilova

PURPOSE: This booklet is intended for the general reader interested in earth science. It will be of interest to communications and other specialists concerned with the effects¹ of terrestrial magnetism.

COVERAGE: This booklet discusses questions in terrestrial magnetism and the Earth's magnetic field. The importance of such studies to geologists in the matter of prospecting mineral deposits is noted. Studies were carried out by magnetic stations under the direction of IZMIR (Institute for the

Card 1/3

SOV/2770

The Earth's Magnetic Field

Study of Terrestrial Magnetism, Ionosphere, and Radio Wave Propagation). No personalities are mentioned. There are 8 Soviet references.

TABLE OF CONTENTS:

Foreword	2
Introduction	3
The Earth's Permanent Magnetic Field and Its Secular Variations	6
Elements of terrestrial magnetism	6
Magnetic surveys	8
Secular variations	16
Graphic representation of the Earth's magnetic field	19
Structure of the Earth's magnetic field. Magnetic anomalies	23
Hypotheses on the origin of the Earth's permanent magnetic field	26

Card 2/3

SOV/2770

The Earth's Magnetic Field	27
The Earth's Variable Magnetic Field	27
Components of the Earth's variable magnetic field	29
Magnetic activity	33
Solar-diurnal geomagnetic variations	
Magnetic storms	40

Bibliography

AVAILABLE: Library of Congress

MM/gap
12-21-59

Card 3/3

MALININA, O.V.

L.I.Voinov, physician and humanist; from unpublished material.
Khirurgiia 35 no.8:138-139 Ag '59. (MIRA 13:12)
(VOINOV, L.I.)

MALININ, Olga Vasil'yevna; SEMEN V. Ye.F., red.

Leonid Ivanovich Voinov. Leningrad. Meditsina, 1965. 49 p.
(MIRA 18:6)

MAVINKIN, B. A.

Work experience of the Kostrom cattle breeding farms.
Moskva, Izd. gazety "Sotsialisticheskoe zemledelie," 1945. 12 p. (V samosnch' preisedate-
liu kolkhozov.)

DA

MAININA, P. A.

561

kolkhoz "12 Oktyabr'". Kosrrom. rayon
kosrrom. obl. M., Goskul'tprosvetizdat, 1954. 63 s' 4 l. ill.
22 sm. (B-chka "v pomoshch' Lektoru" No 21). 36.000 ekz.
1 r. 25 k.- 54-54741 p 338.1k + 636.2.083 sr (47.35)

SO: Knizhnaya Letopis, Vol. 1, 1955

MALININA, P., Geroy Sotsialisticheskogo Truda

Soviet women are active builders of communism. Voen.znan.
36 no.3:2 Mr '60. (MIRA 13:3)

1. Predsedatel' kolkhoza "XII Oktyabr'."
(Women and socialism)

MALININA, Praskov'ya Andreyevna, Geroy Sotsialisticheskogo Truda, laureat
Stalinskoy premii; LEONOVA, T.S., red.; RAKITIN, I.T., tekhn. red.

[Upswing; about the "12th of October" Collective Farm] Vzlet; o
kolkhoze "12-i Oktiabr'." Moskva, Izd-vo "Znanie," 1961. 29 p.
(Vsesoiuznoe obshchestvo po rasprostraneniю politicheskikh i
nauchnykh znaniy. Ser.5, no.17) (MIRA 14:9)
(Kostroma Province—Collective farms)

MALININA, P., Geroy Sotsialisticheskogo Truda

Let's build three-row livestock barns. Sel'. stroi. 15 no. 2:4-5
F '61. (MIRA 14:5)

1. Predsedatel' kolkhoza "XII Oktyabr'" Kostromskogo rayona,
Kostromskoy oblasti.

(Barns)

PRUDNIKOV, G.; GORSHKOV, A., Geory Sotsialisticheskogo Truda;
MALININA, P., Geory Sotsialisticheskogo Truda; SEMENOV, I.,
Geory Sotsialisticheskogo Truda; KHALYAVIN, S.; BELOUSOV, D.;
MORYGANOV, A.N., kand. sel'khoz. nauk; ULIN, I.I., red.;
LEVINA, L.G., tekhn. red.

[Know how to use every hectare of land] Umelo ispol'zovat'
kazhdyi gektar zemli. Moskva, Izd-vo MSKh RSFSR, 1962. 52 p.
(MIRA 15:9)

1. Predsedatel' kolkhoza "Pervoye maya" Kaluzhskoy oblasti
(for Prudnikov).
2. Predsedatel' kolkhoza "Bol'shevik"
Vladimirovskoy oblasti (for Gorshkov).
3. Predsedatel' kol-
khoza "12-y Oktyabr'" Kostromskoy oblasti (for Malinina).
4. Predsedatel' kolkhoza "Novaya zhizn'" Tul'skoy oblasti
(for Semenov).
5. Predsedatel' kolkhoza "Kommunar" Bryanskoy
oblasti (for Khalyavin).
6. Sekretar' partiynogo komiteta
kolkhoza "Put' Lenina" Bryanskoy oblasti (for Belousov).
7. Zaveduyushchiy otdelom Moskovskogo instituta sel'skogo
khozyaystva (for Moryganov).

(Agriculture)

MaLININA, R.

Characteristics and parameters of amplifier vacuum-tubes. *Kinomekhanik* no.
5:35-39 My '53.

(MLRA 6:6)

(Amplifiers, Vacuum-tube)

5(2)

SOV/32-25-9-5/53

AUTHORS: Yakovlev, P. Ya., Razumova, G. P., Malinina, R. D.

TITLE: Polarographic Determination of Impurities in Steel on Nickel Basis by Means of a Co-precipitation With Methyl Violet

PERIODICAL: Zavodskaya laboratoriya, 1959, Vol 25, Nr 9, pp 1039-1041 (USSR)

ABSTRACT: A method for the quantitative co-precipitation of impurities with methyl violet (I) (of the triphenylmethane series, recommended by V. I. Kuznetsov (Refs 1-3)) and a subsequent polarographic determination of zinc, cadmium, lead, and bismuth was elaborated. This method is based upon a simultaneous precipitation of zinc thiocyanate of the iodides of cadmium, lead and bismuth. The experiments showed that zinc with (I) is precipitated quantitatively in the presence of thiocyanate and that for bismuth, satisfying results are also obtained with a precipitation in the presence of potassium iodide (II) and ammonium thiocyanate (III) (Table 1, results for Bi and Cd). Lead is precipitated quantitatively in form of methyl violet salt in the presence of iodides. (I), (II), and (III) were ad-

Card 1/2

SOV/32-25-9-5/53

Polarographic Determination of Impurities in Steel on Nickel Basis by Means of a Co-precipitation With Methyl Violet

ded in the ratio 1 : 10 : 10 for the joint precipitation of the impurities. The analysis is concluded by polarographing on a self-recording integral-differential TsLA polarograph with an electrolyzer of the system Gintsvetmet. The accuracy of the method was tested by a determination of impurities added in definite quantities to the solution of the alloy (Table 2), and the determination error was ascertained to amount to 10 to 15% relatively. The course of an analysis is given. There are 2 tables and 6 Soviet references.

ASSOCIATION: Tsentral'nyy nauchno-issledovatel'skiy institut chernoy metallurgii (Central Scientific Research Institute of Ferrous Metallurgy)

Card 2/2

31729

S/081/61/000/021/030/094
B101/B147

55300

AUTHORS: Fedorov, A. A., Ozerskaya, F. A., Malinina, R. D., Sokolova, Z. M., Linkova, F. V.

TITLE: Determination of manganese, iron, nickel, and lead contents in pure electrolytic chromium

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 21, 1961, 112, abstract 21D113 (Sb. tr. Tsentr. n.-i. in-t chernoy metallurgii, no. 19, 1960, 7 - 21)

TEXT: Methods for determining Mn, Fe, Ni, and Pb in highly pure electrolytic chromium have been developed. Mn determination is based on removing Cr from perchloro acid solution as CrO_2Cl_2 and photometrically determining the violet color of MnO_4^- forming after oxidation of manganese by means of periodate. 0.5 g (0.02 - 0.04% Mn) or 1g (0.001 - 0.02% Mn) of chromium is dissolved in 30 milliliters (ml) of concentrated HCl and 30 ml of HClO_4 (specific gravity 1.67). The solution is evaporated, concentrated HCl is added, and the substance is heated until the
Card 1/3