

BECHUSOVA, Ye.M.; PAVLENKO, N.K.; POZDNYAKOVA, I.I.

Optical investigation of complex formation in the systems  
 $GdCl_2 - KCl - H_2O$ ,  $GdCl_2 - KBr - H_2O$  and  $GdCl_2 - GfCl - H_2O$ .  
Nauch. zhhegod. Khim. fak. Od. un. no. 3:15-22, 1961.  
(MIRA 17:8)

POZIGUN, A.I.; ANUFRIYEVA, T.F.

Bonding refraction of POTASSIUM tetraoxalocadmiate. Nauch.  
azhegod. Khim. fak. Od. un. no. 2346-49 '61. (MIRA 17.8)



025 10 11 5 9

21  
Photoelectric properties of granular silver sulfide films.  
1957  
M. J. Beck  
M. J. Beck

Pozigun, E.A.

3580. Use of certain colorless organic compounds for the detection of the ferricyanide ion. E. A. Pozigun. *Trudy Odesk. Univ. Ser. Khim.* 1957, 1958, 148 (5), 75-76; *Ref. Zhur., Khim.* 1957, Abstr. No. 23,495.—The conditions are studied for the detection of  $[Fe(CN)_6]^{3-}$  by the formation of colored compounds with 1- and 2-naphthylamine (I and II), 1- and 2-naphthol (III and IV), catechol (V) and quinol (VI), and also the influence of a series of cations and anions on the indicated reactions. The limits of detection in  $\mu g$  for I, II, III, IV, V and VI, respectively, are 2, 2, 0.6, 2, 2 and 20, at limiting dilutions of 1 in  $1 \times 10^4$ ,  $1 \times 10^4$ ,  $3 \times 10^3$ ,  $2.6 \times 10^3$ ,  $1 \times 10^4$  and  $1 \times 10^4$ . C. D. Kopsin

0  
 7 F.H.  
 11  
 RM

UL'YANOV, I.A., inzh.; SOLDATENKOV, A.P., inzh.; EMITRIYEV, V.K.,  
inzh.; MASHIN, M.G., inzh.; POZIGUN, L.V., inzh.;  
DUKTOVSKAYA, O.A., inzh.; CHEKUNOV, I.H., inzh.; LICKEROVICH,  
Ye.F., inzh.; KAPITONOVA, Z.I., inzh.; LEVITSKIY, Ya.B., otv.  
red.; ROMANOVA, L.A., red. izd-va; OVSEYENKO, V.G., tekhn.red.

[Coals of the U.S.S.R.] Ugli SSSR; spravochnik. Moskva, Gos  
gortekhnizdat, 1962. 318 p. (MIRA 15:11)  
(Coal)

PHASE I BOOK EXPLOITATION 807/52L

Academika mna BSSR. Mozhdvedostremny komitet po provedeniyu Mezhdunarodnogo geofizicheskogo goda. V. razdel programy MOU: Ionosfera.

Issledovaniya neodnorodnostey i ionosfer (Investigations of Inhomogeneities in the Ionosphere) Moscow, Izd-vo AN BSSR, 1960. 96 p. 2,000 copies printed. (Series: Izv. Sbornik statey, No. 4)

Resp. Eds. Yu.Y. Kubnerovskiy and S.F. Mirkotau, Candidate of Physics and Mathematics/ Ed.: Ye.P. Shubnikov, Tech. Ed.: O.M. Gus'kov.

PURPOSE: This publication is intended for geophysicists. It will be of particular interest to researchers specializing in studies of the structure of the ionosphere and its effect on radio wave propagation

CONTENTS: This collection of articles on the properties of ionospheric inhomogeneities was published by the IOY Committee of the AS USSR, as the fourth serial contribution to the fifth section of the IOY program (the ionosphere). Individual articles deal with various types of ionospheric inhomogeneities and their drifts, a study of the state of polarization, and a method of correlation analysis of the measurements of inhomogeneities and drifts in the ionosphere. No generalities are mentioned. References follow individual articles. A brief English abstract is appended to each article.

TABLE OF CONTENTS:

Foreword	5
Gusev, V.D., and S.F. Mirkotau. Correlation Analysis Applied to Media With Three-Dimensional Characteristics	7
Mirkotau, S.F. Three-Dimensional Characteristics of the Inhomogeneities in the Ionosphere	20
Smirnovskiy, D.F., and Yu.V. Kosharevskiy. Displacement of Disturbances in the F <sub>2</sub> Layer	38
Kosharevskiy, Ya.F., and Ye.S. Zayarnaya. Anisotropy of the Form of Small-Scale Inhomogeneities and Their Movement in the F <sub>2</sub> Layer	43
Mirkotau, S.F., Yu.V. Kosharevskiy, and V.D. Gusev. The Movement of Different Scale Inhomogeneities in the Ionosphere	57
Polizum, V.I. The Drift of Ionospheric Inhomogeneities According to Observations in Rostov-on-Don	70
Isakurov, V.D., and E.S. Farkifirovskiy. Drift of Small-Scale Inhomogeneities in the Ionosphere (According to Measurements in Irkutsk)	73
Farkov, V.A. The Measurement of Drifts in the Ionosphere With Simultaneous Investigation of the State of Polarization	85
Klyamovskiy, M.P. Criteria for the Applicability of Correlation Analysis	92

AVAILABLE: Library of Congress

Card 3/3

37/500/005  
7-3-61

6

28426

S/169/61/000/007/095/104

A006/A101

9.9/00

AUTHOR: Pozigun, V.L.

TITLE: Drift of heterogeneities in the ionosphere from observations carried out in Rostov-on-Don

PERIODICAL: Referativnyy zhurnal. Geofizika, no. 7, 1961, 41, abstract 7G286 (V sb. "Issled. neodnorodnostey v ionosfere, no. 4", Moscow, AN SSSR, 1960, 70 - 74, English summary)

TEXT: The author describes a device for the investigation of drift of small-scale heterogeneities. The results of observations of drifts in layers E and F2 of the ionosphere were, basically, processed by the method of similar fadings and only individual records by the method of correlation analysis. Data are presented on motions in layers E and F2 showing that there are cases when both layers of the ionosphere are moving jointly. H

[Abstracter's note: Complete translation]

Card 1/1



L 53762-65 EWT(1)/EWG(v)/FCC/EEC-4/EEC(t)/EMA(h) Po-4/Pe-5/Pq-4/Pae-2/  
Feb/Fi-4 GW

ACCESSION NR: AP5014122

UR/0203/65/005/003/0576/0578  
550.388.2

AUTHOR: Pozigun, V. L.

40  
39  
B

TITLE: Heterogeneous regions in the ionospheric E-layer

SOURCE: Geomagnetizm i aeronomiya, v. 5, no. 3, 1965, 576-578

TOPIC TAGS: ionospheric heterogeneity, median method

ABSTRACT: The study of heterogeneities in the ionospheric E-layer is based on drift measurements made between 1958 and 1960. The evaluation of reflected impulses was made by means of a parameter  $\beta$  which characterizes the pollution of the ionosphere by heterogeneities in the reflecting regions. Impulse attenuations of reflections from the E-layer were processed. In the daytime, frequencies of 2.0 to 2.9 Mc were used, and at night for reflections from the Es-layer, frequencies of  $2.2 \pm 0.2$  Mc were taken. The seasonal rate of the parameter  $\beta$  was determined by the method of median values. Maximum  $\beta$  values were obtained in March, April, May, and October; they were near zero in December and January. The diurnal rate of  $\beta$  values differed from month to month. In spring and autumn the maximum value was at sunrise and sunset, while in summer no significant maximum appeared. Histograms were drawn which characterized the  $\beta$  values for the E- and Es-layers. Values of the

Card 1/2

L 53762-65

ACCESSION NR: AP5014122

E-layer show a normal distribution rate. Values of various types of E<sub>s</sub>-layer differ from each other. The summer months without distinctly expressed maxima characterize a turbid ionosphere rich in heterogeneities. Orig. art. has: 1 table and 2 figures. [EG]

ASSOCIATION: Rostovskiy-na-Donu gosudarstvennyy universitet (Rostov-on-Don State University)

SUBMITTED: 30Oct64

ENCL: 00

SUB CODE: ES

NO REF SOV: 004

OTHER: 001

ATD PRESS: 4019

Card 2/2

L 38555-65 EWT(1)/EWG(v)/EWC(t)/EEC-h/EEC(t)/EWA(h) Pe-5/Po-h/Pq-h/Pae-2/Peb/Pi-h  
RB/GN-2  
ACCESSION NR: AT5009255 S/2831/64/G00/013/0122/0128

AUTHOR: Pozigun, V. L.

TITLE: Results of investigations of horizontal motions of small heterogeneities

SOURCE: AN SSSR. Mezhdudevdomstvennyy geofizicheskiy komitet. V razdel programy MGG: Ionosfera. Sbornik statey, no. 13, 1964, 122-128

TOPIC TAGS: wave fading, ionospheric heterogeneity, vertical sounding, histogram, direction dispersion, probable velocity

ABSTRACT: The influence of the lower layer on fadings of reflected waves from the upper layer was studied by comparing drifts of ionospheric heterogeneities in the E- and F2-layers. Observational data of vertical soundings during 24 hr from September 1958 to September 1961 on the frequency of  $2.2 \pm 0.2$  Mc for the E-layer were used. The differences in drift velocities and directions in the E- and F2-layers were compared. The comparison indicates that the drift

Card 1/2

L 38555-65

ACCESSION NR: AT5009255

velocities in the F2-layer are greater than those in the E-layer. Directions of motion lasting for a brief instant in the F2- and E-layers are independent of each other. Direction histograms indicate that, in general, drifts move to the west. Individual layers have other seasonal drift directions. The F2-layer has a pronounced easterly drift in spring and fall. The E<sub>s</sub>-layer is characterized by a great number of drift directions, but the predominant direction is west. Drift is to the north in spring and to the south in summer. The probable velocities of ionospheric heterogeneities vary from 10 to 160 m/sec in the E-layer and from 10 to 240 m/sec in the E<sub>s</sub>- and F2-layers. Velocities of drifts also change seasonally. Orig. art. has: 4 figures and 1 table. [EG]

ASSOCIATION: none

SUBMITTED: 00

ENCL: 00

SUB CODE: ES

NO REF SOV: 004

OTHER: 001

ATD PRESS: 3225

Card 2/2

DEMIDOV, K.K.; POZIGUN, Ye.A.

Effect of desensitizers on the photoelectrochemical effect of silver  
bromide. Zhur. nauch. i prikl. fot. i kin. 6 no. 3:161-163 My '61.  
(MIRA 14:5)

1. Nauchno-issledovatel'skiy institut fiziki Gosudarstvennogo  
universiteta im. I.I. Mechnikova, Odessa.  
(Photographic emulsions) (Silver bromide)

DEMIDOV, K.K.; POZIGUN, Ye.A. [Pozihun, K.A.]

Photoelectrochemical properties of thallium halides in the  
presence of desensitizers. Ukr.fiz.zhur. 4 no.6:789-792 N-D  
'59. (MIRA 14:10)

1. Odesskiy gosudarstvennyy universitet im. I.I.Mechnikova.  
(Thallium halides---Electric properties)

04.2700

S/058/62/000/005/091/119  
AG61/A1G1

AUTHORS: Demidov, K. K., Pozigun, Ye. A., Prokopovich, L. P.

TITLE: A study of the thermoelectric properties of silver and thallium haloids in the presence of desensitizers

PERIODICAL: Referativnyy zhurnal, Fizika, no. 5, 1962, 33, abstract 5E262  
("Nauchn. yezhegodnik. Odessk. un-t. Fiz.-matem. fak. i N.-i. in-t fiz.", no. 2, Odessa, 1961, 180-182)

✓B

TEXT: The temperature dependence of the thermo-emf and the electrical conductivity of AgBr and TlBr specimens was examined in the presence of desensitizers. Tablets were pressed from the material obtained by interaction of Ag or Tl nitrate solutions with KBr. The apparatus used for measuring the thermo-emf in a wide temperature range is described. Conductivity and thermo-emf were higher in desensitized specimens than in non-desensitized ones. The specimens possessed hole conductivity. Evidently, the desensitizer plays the role of an acceptor impurity in the materials under consideration.

[Abstracter's note: Complete translation]

L. Berger'

Card 1/1

POZIK, L.N.; TENENBAUM, I.M.

~~A~~ special apparatus for the rapie Y-ray analysis of run-of-mine  
ores. Atom.energ. 3 no.7:28-35 J1 '57. (MLRA 10:7)  
(Ores--Sampling and estimation) (Gamma rays)



POZIN, A. A.

POZIN, A. A. -- "Principles of Design and Construction of Suction Hoses."  
Sub 31 Mar 52, Moscow Inst of Fine Chemical Technology and Lebedev  
(Dissertation for the Degree of Candidate in Technical Sciences).

SO: Vechernaya Moskva, January-December 1952

77-101, A E.

CHELYUK, A.P.; SOKOLOVSKAYA, F.M.; POZIN, A.A.; KHODOSH, S.I., redaktor;  
LUR'YE, M.S., tekhnicheskij redaktor

[Manufacture of driving belts, conveyor belts and hoses] Proizvod-  
stvo privodnykh remnei, transportnykh lent i rukavov. Moskva, Gos.  
nauchno-tekhn. izd-vo khimicheskoi lit-ry, 1954. 244 p. (MLRA 8:3)  
(Hose) (Belts and belting)

POZIN, A A.

879. Hydraulic characteristics of suction hose.  
A. A. POZIN and V. A. LEPKOV. *Trudy Nauchno-  
Tekhn. Inst. Fizik. Mosk., 1956, No. 2, 75-102*  
Hoses of various structures and dimensions with open  
and enclosed wire windings are investigated for loss  
of pressure and coefficient of resistance to flow over  
a wide range of Reynolds numbers. GGH21.34

Pozin, A. A.

11 15 11

~~V. Aqueous lubricant for rubber molding dies. E. D. Glinka, T. I. Kuchinskaya, A. A. Pozin, M. D. Nudakov, and V. G. Epshtein. U.S.S.R. 109,133, Dec. 25, 1957. The die lubricant contains surface-active substances, such as alkali salts of fatty acids, as well as substances which increase the viscosity, e.g. glycol and carboxymethylcellulose. M. Hosh.~~

REF: 4E2c(j)/4E4j/  
4E2b

pf 03 JAB

reinforcement  
 A A Fozia ~~and~~ ~~with~~ styrene resins with  
 100% V. A. 200. It contains styrene resins with  
 for mixes based on various synthetic or semi-synthetic  
 light weight, soft and porous materials, *eg* for  
 foams, sponges, foams, electrical insulation, and  
 using chemical apparatus for reinforcement of  
 leathers, and for leather substitutes. The *part* of up  
 to 40 parts by weight to 100 of BKS 56 gives soft  
 which are designated by the letters BSS followed by  
 the percentage figure of styrene, gives leather-like  
 There are  
 182D21M021 61"

*POZIN, A.A.*

NUSINOV, M.D.; PAVLOV, V.P.; POZIN, A.A.; EPSHTEYN, V.G.; KUKHTENKOVA, T.I.

Mechanical properties of rubber mixtures and peculiarities of their  
flow through slit passages. Kauch. i rez. 16 no.8:24-27 Ag '57.  
(MIRA 10:11)

1. Nauchno-issledovatel'skiy institut rezinovykh i lateksnykh izdeliy.  
(Elastomers--Testing) (Rheology)

SOV/138.-58-6-4/25

AUTHORS: Makeyeva, A.R., Romyantseva, N.P., and Pozin, A.A.

TITLE: On Reducing the Time of Vulcanisation of Butyl Rubber Mixtures (O sokrushchenii prodolzhitel'nosti vulkanizatsii smesey iz butilkauchuka)

PERIODICAL: Kauchuk i Rezina, 1958, Nr 6, pp 14 - 16 (USSR)

ABSTRACT: Butyl rubber is a copolymer of isobutylene containing 1 - 3% isoprene. The low degree of unsaturation determines to a large extent the properties of butyl rubber and of its vulcanisates (Ref 1), as well as its stability towards the action of ozone (Ref 4). Butyl rubber vulcanisates possess great strength. Various uses of butyl rubber in the West are enumerated (Refs 5 - 8). The time required for vulcanising butyl rubber mixtures can be shortened by increasing the temperature of vulcanisation, and by using ultra-accelerators. Experiments were carried out in hydraulic presses at 142°, 151°, 160° and 180°C, and butyl rubber with 1.4 - 2.2% unsaturation was compared with butyl rubber of  $1 \pm 0.2\%$  unsaturation. Experimental results are given in Tables 1 and 2. Fig 1 shows the changes in the equilibrium modulus of butyl

Card 1/2

SOV/1383-58-6-4/25

On Reducing the Time of Vulcanisation of Butyl Rubber Mixtures  
rubber vulcanisates with varying degree of unsaturation,  
which were vulcanised at 142°C, and Fig 2 the same vul-  
canisates which were vulcanised at 142°C for 50 minutes.  
The properties of butyl rubber vulcanisates vulcanised at  
142° and 160°C are given in Table 3. Rubbers, filled  
with carbon black and vulcanised in presses, show  
slightly less tensile strength and relative elongation  
when the degree of unsaturation is increased from 1%  
to 2%.  
There are 3 figures, 2 tables and 9 references (6 Soviet,  
3 English)

ASSOCIATION: Nauchno-issledovatel'skiy institut rezinovykh i  
lateksnykh izdeliy (Research Institute for Rubber and  
Latex Articles)

1. Butyl rubber--Vulcanization
2. Time--Applications

Card 2/2



SOV/138-58-9-7/11

AUTHORS:

Makeyeva, A. R; Pozin, A. A; Yeganova, Ye. S; Baksat, O. V.  
Zel'dich, E. I.

TITLE:

Possibility of Using SKP Rubber for Manufacturing Rubber Boots (O vozmozhnosti primeneniya kauchuka SKP dlya izgotovleniya rezinovy obuvi)

PERIODICAL:

Kauchuk i Rezina, 1958, Nr 9, pp 25 - 27 (USSR)

ABSTRACT:

The output of rubber shoes is to be increased three to four times by the end of 1965 according to the directives of the May Conference of the Central Committee of the KPSS. The authors tested the properties of standard SKP mixtures containing atomised carbon black and mixtures and compositions prepared under laboratory and industrial conditions in the factory "Krasnyy bogatyr". The composition of the two mixtures is given. The plasticity of standard mixtures containing channel black practically did not change after heating for 90 minutes (Fig.1). Mixtures containing atomised carbon black showed considerable lower plasticity after heating for 40 - 50 minutes. SKP mixtures prepared under industrial conditions could not be tested because they show great tendency to scorching. This disappeared when 2 - 3% of

Card 1/2

SOV/138-58-9.7/11  
Possibility of Using SKP Rubber for Manufacturing Rubber Boots

zinc benzoate was added to the mixtures (Figs. 2 - 3)  
The addition of this substance does not affect the  
properties of the vulcanisates (Tables 1 and 2). Prop-  
erties of vulcanisates made from SKP and SKB rubber  
are compared (Tables 2 - 4). The physico-mechanical  
characteristics of boots made from SKP rubber, when  
zinc benzoate was added, were slightly better than those  
made from SKB rubber. There are 4 Tables, 3 Figures  
and 3 Soviet References.

ASSOCIATION: Zavod "Krasnyy bogatyr" i Nauchno-issledovatel'skiy  
institut rezinovykh i lateksnykh izdeliy ("Krasnyy bogatyr"  
Factory and the Scientific Institute for Rubber and Latex  
Articles)

Card 2/2

SOV/32-24-7-56/65

AUTHORS: Pozin, A. A., Izrayelit, G. Sh. (deceased), Musinov, M. D.

TITLE: An Apparatus for Estimating the Deformability of Rubber Mixtures  
(Pribor dlya otsenki deformiruyemosti rezinovykh smesey)

PERIODICAL: Zavodskaya Laboratoriya, 1958, Vol.24, Nr 7, pp. 901 - 901  
(USSR)

ABSTRACT: The present methods for the investigation of the deformability do not correspond to the actual conditions of industrial processes. Therefore an apparatus was constructed which does not have these disadvantages. It is based on the consistometer according to Heppler (Geppler) which is used with an ultra-thermostat maintaining automatically the temperature with an accuracy of  $\pm 0,025^{\circ}$  within the range of from 1 to  $100^{\circ}$ . The sample itself represents a model press mold with the rubber mixture put into the press as a sample of a certain size; then it is deformed at a constant specific pressure. The sample is brought to the temperature desired within five minutes before the pressure sets in; in the determination the data on the shrinkage of the sample indicated by an instrument are read every five seconds within the first minute, and then every

Card 1/2

SOV/32-24-7-56 '65

An Apparatus for Estimating the Deformability of Rubber Mixtures

thirty seconds. The results of this experiment are graphically represented as function of the piston travel vs. the time of observation. The values obtained from observations at a distance of 5 sec ( $T_5$ ) may be taken as criterion of the flowing. The diagram of every rubber mixture is determined according to the data obtained from five samples; the error increases with the "flow rate", however, it is not greater than  $\pm 6,5\%$  as a maximum. The plotting of the flow curve can be automatized by simple adaptations. There are 2 figures.

ASSOCIATION: Nauchno-issledovatel'skiy institut rezinovykh i lateksnykh izdeliy (Scientific Research Institute for Rubber and Latex Products)

Card 2/2

Pozin, A. A.

SOV/13-59-3-15/16

**AUTHOR:** Khabarov, V.P.  
**TITLE:** Industrial and Technical Conference in the Factory "Krasny Trugol'nik" (Proizvodstvenno-tekhnicheskaya konferentsiya na zavode "Krasny trugol'nik")

**PERIODICAL:** Nauchuk i izv. 1959, Nr 3, pp 61 - 62 (USSR)  
**ABSTRACT:** This conference was held from 18th to 21st February, 1959 in Leningrad. It was attended by representatives from the factory "Krasny Trugol'nik" (the Tomsk Factory for Rubber Footwear), the factory "Mator", the Chernovyy and Ruzhichan factories, Nauchno-issledovatel'skiy institut khimicheskoy i lateksykh izdeliy (Research Institute for Rubber and Latex Articles, NIIR), the Gosudarstvennyy komitet Sovetskoy ministroy SSSR po khimii (State Committee of the Soviet of Ministers of the USSR for Chemistry), Upravleniye khimicheskoy promyshlennosti Leningradskoy Soveta narodnogo khozyaystva (Administration of the Leningrad Council of National

Card 1/3

Economy). Gosplan of the USSR, Gosstatstatvnyy institut (State Statistical Agency), primarily by the rubber industry (Leningradskiy khimiko-ekonomichekii institut (Leningrad Engineering-Economics Institute) and Vsesoyuznaya Borgovaya palata (All Union Board of Trade). The following papers were read: 1) by the Chief Engineer of the factory "Krasny Trugol'nik", A.G. Savazon on "The Results of Fulfilling the Resolutions of the 1953 Industrial and Technical Conference and Problems of Development of the Factory During the Period 1959 to 1965". The lecturer pointed out that during 1958 the plant had started using the vulcanizing apparatus AGV-01, and that considerable automation of the plant had been carried out during the same year. 2) by the chief of the Technical Laboratory for Rubber Footwear of the Research Institute for Rubber and Latex Articles, A.A. Pozin, Candidate of Technical Sciences, on "Mechanizing and Modernizing the Rubber Footwear Industry." 3) The head of a department

Card 2/3

of the Gosplan, USSR, G.V. Grigor'yan on "The Seven Year Plan of the Development of the Rubber Footwear Industry in the USSR". 4) A report on the work of the workshop Nr 6 in the factory "Krasny Trugol'nik". 5) The chairman of the All-Union Board of Trade, I.I. Ayzenberg on "Superior Quality Footwear Produced by Factory Firms". The Conference gave a high evaluation of the work of the lecturers. It is recommended that the results of the conference should be introduced and the quality of rubber footwear improved.

Card 3/3

POZIN, A.A.; TOKAREVA, T.Ye.; KOCHKIN, K.I.; PYATETSKAYA-SHAPIRO, I.P.

Mechanized method for the manufacture of warm rubber boots. Kauch.  
i rez. 24 no.4:32-35 Ap '65. (MIRA 18:5)

1. Nauchno-issledovatel'skiy institut razinovykh i lateksnykh  
izdeliy.

POZIN, A.A.; ZAKLYAKOVA, A.V.

Use of granular rubber mixtures for the manufacture of rubber footwear with textile fabric uppers. Kauch. i rez. 23 no. 3: 33-37 Mr '64. (MIRA 17:5)

1. Nauchno-issledovatel'skiy institut rezinovykh i lateksnykh izdeliy.

POZIN, A.A., kand.tekhn.nauk; TSURKAN, V.P., inzh.

Dimension conformity of rubber galoshes and boots to leather  
footwear. Kozh.-obuv.prom. 4 no.1:18-19 Ja '62. (MIRA 15:3)  
(Boots and shoes, Rubber) (Shoe manufacture)



NUSINOV, M.D.; POZIN, A.A.; MAYZEL', M.M.

Response to remarks concerning the articles of M.D. Nusinov,  
A.A. Pozin, M.M. Maizel; published in the no.2, 1961 issue of  
the journal. Izv.vys.ucheb.zav.; tekhn.leg.prom. no.5:124-129  
'61. (MIRA 14:12)

(Rubber machinery)

S/138/60/000/000/000/015  
A051/A029

AUTHORS: Musinov, M.D.; Ivanov, B.I.; Mazina, G.R.; Chernaya, V.V.; Rozin,  
A.A.

TITLE: The Application of Electric Contact Transmitters for Measuring Large  
Deformations of Latex Films

PERIODICAL: Kauchuk i Rezina, 1960, No. 8, pp. 35 -37

TEXT: Latex balloons widely used in atmosphere probing frequently undergo premature deformations when being elevated to a given height, probably due to an uneven distribution of the deformations at different areas of their surfaces. The investigation of the deformations in the different areas of the latex balloon was undertaken, adopting experimental conditions close to those encountered in the performance of the balloons, i.e., low temperatures and electrical discharges. The authors overcame the usual difficulties of measuring deformations of large magnitudes, especially under the given conditions of low temperature and of curved object, by using transmitters of the electric contact type in a thermobaric-chamber. Measurements were made at different parts of the surface of the balloon (in the equatorial and meridional directions). The rheochord transmitter could not be used in view of the changing temperature. The transmitter showings were recorded on

S/138/60/000/000/009/015  
A051/A029

The Application of Electric Contact Transmitters for Measuring Large Deformations of Latex Films

a photographic tape at a distance, using a magnetic-electrical oscillograph of the  $\mu$ MO-2 (MFC-2) type. Figure 1 is a diagram of the electric contact transmitter used by the authors, and Figure 2 is a circuit diagram of the transmitter's construction. The transmitter has the following design: Two supporting prisms (2) of 5x 5x 5 mm made of plexiglas are fastened onto the balloon surface (1), using compensation latex films (3). The No. 88 glue is used for fastening the prisms and the latex films to the balloon's surface. The prisms serve as contacts for connecting the outlets which join the transmitter to the electrical measuring circuit. The compensation films prevent the occurrence of local voltages concentrating in the balloon's film during expansion, due to its slight thickness. The thickness of the film was 0.10 - 0.15 mm at the beginning of the measurements and a few microns at the final point. The experiments were carried out only 24 hours after the transmitters were attached to the surface of the balloon to ensure satisfactory adhesion. Manganin was used as the material for the contact wire due to its low temperature coefficient. The distance between the supporting prisms, when fastened to the balloon's surface, was 25 mm. A description is given of the design

S/137/60/000/008/108/111  
A051/A029

The Application of Electric Contact Transmitters for Measuring Large Deformations of Latex Films

of the current recorders, situated in the supporting prisms. As the balloon expands, the supporting prisms move on opposite directions and cause periodic connecting and disconnecting of the circuit in the transmitter and a corresponding jump of the current in the electrical circuit. A visual check is made by counting the number of tubes which light up connected in series with the oscillograph's vibrator. Figure 3 is a typical oscillogram of the transmitter's showings. The accuracy of the counting would depend on the accuracy of division of the contact wire into various sections. Figure 3 shows that the rate of deformation is variable at different periods of time. This fact is taken into account when studying the kinetics of the film's deformation under conditions close to real ones. The authors conclude that their method is useful in measuring large deformations, such as 500 - 600%, of non-metal materials (rubber, latex films, plastics, etc.). It is especially useful in measuring at distances under conditions similar to actual performance. There are 3 figures and 5 references: 4 Soviet and 1 English.

ASSOCIATION: Nauchno-issledovatel'skiy institut rezinovykh i lateksnykh izdeliy  
(Scientific Research Institute of Rubber and Latex Articles)

NUSINOV, M.D.; IVANOV, B.I.; MAZINA, G.R.; CHERNAYA, V.V.; POZIN, A.A.

Use of electric-contact strain gauges for measuring large  
deformations of latex films. Kauch.i rez. 19 no.8:35-37  
Ag '60. (MIRA 13:9)

1. Nauchno-issledovatel'skiy institut rezinovykh i lateksnykh  
izdelyi.  
(Strain gauges) (Deformations (Mechanics)) (Latex)

NUSINOV, M.D.; POZIN, A.A.; OSPOVAT, R.I.; IL'IN, N.S.

Relation between the filling of a rubber mixture, based on butadiene-styrene rubber, and its viscoplastic characteristics. *Kauch.i rez.* 19  
no.5:21-23 My '60. (MIRA 13:7)

1. Nauchno-issledovatel'skiy institut rezinovykh i lateksnykh  
izdelyi i Moskovskiy institut tonkoy khimicheskoy tekhnologii im.  
M.V.Lomonosova.

(Rubber, Synthetic)  
(Fillers)

84294

15.9300 2109 1526 14174

S/138/60/000/005/006/012  
A051/A029

AUTHORS: Nusinov, M.D., Pozin, A.A., Ospovat, R.I., Il'in, N.S. <sup>15</sup>

TITLE: On the Relationship Between the Filling of a CKE (SKB)-Based Rubber Mixture and its Elastic-Viscous Characteristics

PERIODICAL: Kauchuk i Rezina, 1960, No. 5, pp. 21 - 23

TEXT: Carbon black and the softener have the greatest effect on the elastic-viscous characteristics of a rubber mixture due to the higher specific gravity in the volumetric or weight content of the mixture. It was shown (Refs. 1 and 2) that an increase in the degree of filling of the rubber mixture with carbon black decreases the plastic properties of the mixture, and an increase in the softener content leads to an increase in these properties. The changes of each characteristic at different degrees of filling with carbon black and softeners are observed. The behavior of the mixtures in deformations can be predicted based on the data of the changes. The laboratory method for the observations is described (Ref. 4). The total deformation obtained in the testing can be divided into elastic and viscous components, from which the elastic or the viscous properties

Card 1/3

84294

S/138/60/000/005/006/012  
A051/A029

On the Relationship Between the Filling of a CKE(SKB)-Based Rubber Mixture and its Elastic-Viscous Characteristics

can be determined (Ref. 5). Figure 1 is the graphical outline of the experiment. The formulae which were used for the computations are given (Formulae 1 - 7). A highly-filled commercial mixture with a SKB-60 base was chosen as the object of the investigation. As a result of the experimental data obtained several conclusions were drawn: with an increase in the carbon black dosage the characteristic indices increase and with an increase in the softener dosage they decrease. The intensity of the change of the various characteristics varies with an increase in the degree of filling in the mixtures. The plastic viscosity  $\eta_2$  and the standard of instantaneous elasticity  $G_2$  change most significantly. Both are associated with the intermolecular interaction. The characteristics of the lagging elastic deformation change only slightly in this case. Since the lagging elastic deformation is determined mostly by the elastic properties of the rubber molecule and the individual links and an increase in the degree of filling does not change the rubber substance itself, the value of the characteristic of the lagging elastic deformation changes with it. This fact can be utilized in developing a new method of high-speed control of

Card 2/3



84294

S/138/60/000/005/006/012  
AO51/A029

On the Relationship Between the Filling of aCKE(SKB)-Based Rubber Mixture and its Elastic-Viscous Characteristics

the technological properties under industrial conditions, viz. the control of the G2 standard by ultrasound. On the other hand, with an increase in the degree of the filling with active gaseous carbon black, the standard increases significantly, and the viscosity of the lagging elasticity increases correspondingly. Similar results were obtained for rubber mixtures based on various rubbers (Refs. 7 and 8). In this case the presence of an interaction (in the non-vulcanized state) between the filler and the rubber substance is assumed, which leads to an increase in the numeric values of the characteristics of "high-elastic" deformation. There are 4 sets of figures and 8 references: 6 Soviet, 1 English and 1 German.

ASSOCIATION: Nauchno-issledovatel'skiy institut rezinovykhi lateksnykh izdeliy i Moskovskiy institut tonkoy khimicheskoy tekhnologii im. M.V. Lomonosova (Scientific Research Institute of Rubber and Latex Products and the Moscow Institute of Fine Chemical Technology imeni M.V. Lomonosov)

Card 3/3

S/138/59/000/011/007/011  
A051/A029

AUTHORS: Nusinov, M. D.; Pozin, A. A.; Gal'chenko, G. I.

TITLE: The Determination of Some Mechanical Characteristics of Rubber Mixtures, Using the Rotational Elastoviscosimeter ✓

PERIODICAL: Kauchuk i Rezina, 1959, No. 11, pp. 35-39.

TEXT: An instrument and method for determining the mechanical properties of rubber mixtures under conditions of a uniform shear at various temperatures and three conditions of deformation were developed. The mechanical properties of each type of deformation were determined by applying the linear theory of deformation and, in particular, the method of the mechanical moduli (Refs. 1-3). Formula 1 is the equation for the sum deformation, consisting of the elastic instantaneous deformation, the elastic-delayed deformation and the plastic deformation. In addition to the general linear theory, the authors also make use of the model method, according to Refs. 4-9, with the general equation given in Formula 2. Figure 2 shows the relationship of the sum deformation to the time element, in the case of the shear deformation modulus. Formulae 5-7 are the equations of the component

Card 1/4

S/138/59/000/011/007/011  
A051/A029

The Determination of Some Mechanical Characteristics of Rubber Mixtures,  
Using the Rotational Elastoviscosimeter

types of deformation, listed above, respectively. The authors use these formulae and Figure 2 to determine the mechanical characteristics of the material, which are:  $G_1$  - the shear modulus of the delayed elasticity, in dyne/cm<sup>2</sup>,  $G_2$  - the instantaneous elastic shear modulus, in dyne/cm<sup>2</sup>,  $\eta_1$  - the viscosity of the delayed elasticity, in dyne·sec/cm<sup>2</sup>,  $\eta_2$  - the plastic viscosity, in dyne·sec/cm<sup>2</sup>,  $t$  - the time of the tension action (deformation), in sec. It is simplest to use the conditions of constant tension for determining the mechanical properties of the rubber. It is also stated that the given Formulae (No. 1-7) are only valid at constant temperatures. Formula 8 is given for calculating the temperature dependence of the plastic viscosity. Formula 9 shows that with an increase in the temperature the plastic viscosity of the material decreases. The experimental methods are outlined in detail and a photographic illustration of the instrument used is given in Figure 3 with a diagrammatic sketch of its component parts. Each part is described in detail and the functioning principle of the instrument is explained. The tests are conducted at constant temperature, determined by an ultrathermostat. The computed results

Card 2/4

S/138/59/000/011/007/011  
A051/A029The Determination of Some Mechanical Characteristics of Rubber Mixtures,  
Using the Rotational Elastoviscosimeter

along the two branches were found to coincide completely. The following high-filled rubber mixtures were tested (in weight parts): CKB-60 (SKB-60) 125 lamp carbon black, 25 vaseline oil; KCC-30A (SKS-30A) 180 jet carbon black, 90 polydienes; CKH (SKI)<sup>117</sup> 117 jet carbon black, 40.0 vaseline oil. Sulfur was excluded to eliminate the effect of the scorching in the mixtures. As a result of the experimental procedure it was shown that there is a relationship between the elastic-viscous characteristics for the three rubber mixtures and the value of the shear tension within a range of  $0.0785 \cdot 10^6 - 0.238 \cdot 10^6$  dyne/cm<sup>2</sup> at a temperature of 70°C. This indicates that in the test range of deformation and shear tensions the tested rubber mixtures are linear elastic-viscous materials, the behavior of which can be simulated by using a four-element mechanical model. It was also found that for the SKB-60-based rubber mixture the plastic viscosity coefficient  $\eta_2$  and the shear modulus of the delayed-elastic shear  $G_1$  decrease with an increase in the temperature. There are 2 diagrams, 1 oscillogram, 5 graphs, 1 table, 9 formulas and 15 references: 12 Soviet, 2 English, 1 French.

Card 3/4

S/138/59/000/011/007/011  
A051/A029

The Determination of Some Mechanical Characteristics of Rubber Mixtures,  
Using the Rotational Elastoviscosimeter

ASSOCIATION: Nauchno-issledovatel'skiy institut rezinovoy i lateksnykh  
izdeliy (Scientific Research Institute of the Rubber and  
Latex Products Industry)



Card 4/4

S/138/59/000/0:2/005/006

AUTHORS: Mikhlin, E. D., Poretskaya, L. I., Pozin, A. A., Artem'yeva,  
V. P., Gal'braykh, I. Ye., Shcherbakova, L. F., Nikiforova,  
T. F.

TITLE: A Method for the Determination of the Tendency for Pore  
Formation in Rubber Mixtures During Vulcanization <sup>15</sup>

PERIODICAL: Kauchuk i Rezina, 1959, No. 12, pp. 23-28

TEXT: The authors stress the importance of controlling the rubber mixtures during vulcanization to avoid swelling and the formation of pores and to ensure the production of monolithic rubber articles. The presence of gases and steam due to moisture and the wrong composition of the rubber mixture can be harmful in this connection. Other causes of pore formations are listed. The gasometric method for moisture-determination is quoted (Ref. 1). The duration of this method, viz. 40 minutes for each determination, renders it unpractical for industrial purposes. The degree of porosity is determined by the specific gravity method (Ref. 2). However, the specific gravity changes during vulcanization, particularly if pore formations occur. The ratio of the specific gravities of the vulcanizate

Card 1/4

S/138/59/000/012/005/006

A Method for the Determination of the Tendency for Pore Formation in Rubber Mixtures During Vulcanization

and the rubber mixture is given in Formula 1. The relation between the moisture of the rubber mixture, the K value, i.e., the above-mentioned ratio, and the porosity of the vulcanizate was studied. The experimental procedure is outlined. The value of K was computed according to experimental data. Fig. 1 shows the instrument used for the determination of the specific gravity. The formula for the determination of the specific gravity before heating is given in Formula 2 and for determination after heating in Formula 3. The values of K obtained are listed in Table 1. The Authors used the gasometric method for determining the moisture in the rubber mixtures. Fig. 2 shows the relationship between the value of K and the moisture content of the initial rubber mixture according to the composition No. 151. The relationship which is obtained is explained by the fact that during the heating and vulcanization under relatively hard conditions (temperature 170-180°C) part of the moisture contained in the rubber mixture volatilizes. A special method was applied to the determination of the moisture content and the dependence of the porosity on the K value and the moisture content in the case of press-molded galoshes at the "Krasnyy Treugol'nik" plant. It was applied in production to the control of rubber

Card 2/4

S/138/59/000/012/005/006

## A Method for the Determination of the Tendency for Pore Formation in Rubber Mixtures During Vulcanization

mixtures used in the manufacture of these overshoes, which, in turn, were vulcanized at atmospheric pressure and also in the manufacture of heels for shaped boots. As many as 89 rubber mixtures were tested in the plant and the results of the K values obtained are listed in Table 4. It can be seen from the table that in order to obtain monolithic overshoes vulcanized at atmospheric pressure the rubber mixtures must be characterized by a value of  $K \gg 0.985$ . The processing of rubber by the "straining" method causes an increase in the K value by 15 to 17%, both in industry and under laboratory conditions. Other tests were carried out for the K determination of rubber mixtures used in the manufacture of boot heels. The results are given in Table 6. A linear relationship exists between K and the monolithic structure of the boot heels manufactured by molding according to modern standard industrial procedures. The authors conclude that they were able to develop a qualitative method for the determination of the tendency of rubber mixtures for pore formation during vulcanization, and that this tendency is characterized by the value of K, which, in turn, depends on the moisture of the rubber mixture. The method recommended was tested in industry on CKB -60 (SKB-60), and CKC -30 (SKS-30) rubber-based materials and was found

Card 3/4



S/138/59/000/012/005/006

A Method for the Determination of the Tendency for Pore Formation in Rubber Mixtures During Vulcanization

to be applicable to the control of rubber mixtures. The admissible minimum value of K can be made part of the technological regulations, since it is one of the indices characterizing the quality of rubber mixtures. The numerical value of this figure depends on the composition, processing conditions and vulcanization of the rubber mixtures and is selected each time according to the composition of the rubber mixture used and applicable to the specific production conditions. There are 6 tables, 2 figures and 6 references: 5 Soviet and 1 English. ✓

ASSOCIATION: Nuachno-issledovatel'skiy institut rezinovykh i lateksnykh izdeliy i zavod "Krasnyy treugol'nik (Scientific-Research Institute of Rubber and Latex Articles and the "Krasnyy Treugol'nik" Plant)

Card 4/4

PLOTKINA, M.; POZIN, B.

Methodology for planning labor productivity in the glass industry.  
Biul.nauch. inform.: trud i zar. plata 5 no.3:3-7 '62.

(MIRA 15:3)

(Glass manufacture--Labor productivity)

PLOTKINA, M.A.; POZIN, B.L.

Efficiently use window and polished glass in the national  
economy. Stek. i ker. 21 no.1:37-40 Ja '64. (MIRA 17:8)

PLOTKINA, M.A.; POZIN, B.L.

Ways to lower the net cost of window and polished glass in 1961-  
1963. Stek.i ker. 18 no.9:40-42 S :61. (MIRA 14:10)  
(Glass manufacture--Costs)

KAV'YAROV, I.S.; POZIN, B.M.; SAMATOV, Yu.P.

Standardization of wheeled and crawler industrial tractors. Trakt. i  
sel'khoz mash. no.7:3-5 J1 '65. (MIRA 18:7)

1. Chelyabinskiy traktorny zavod.

YEGOROV, Yu.D., inzh.; MAGARILLO, B.L., inzh.; POZIN, B.M., inzh.

Concerning the operation of tractors with mounted equipment.  
Trakt. i sel'khoz mash. 32 no.10:7-10 0 '62. (MIRA 15:9)

1. Chelyabinskiy traktorny zavod..  
(Tractors)

SAYAPIN, V.I., kand.tekhn.nauk; POZIN, B.M., inzh.

Resistance of crawler tractors to turning. Trakt.i sel'khoz mash.  
31 no.8:10-12 Ag '61. (MIRA 14:7)

1. Chelyabinskiy politekhnicheskii institut (for Sayapin).
2. Chelyabinskiy traktorny zavod (for Pozin).  
(Crawler tractors)

KAV'YAROV, I.S., inzh.; POZIN, B.M., inzh.

Determining the efficient speed range for industrial tractors.  
Trakt. i sel'khoz mash. 31 no.11:9-11 N '61. (MIRA 14:12)

1. Chelyabinskiy traktorny zavod.  
(Tractors--Speed)



POZIN, L., vedushchiy konstruktor

Design of ships taking into account their repair. Mor.flot 23  
no.2:30-31 F '63. (MIRA 16:2)  
(Shipbuilding) (Ships--Maintenance and repair)

ANUFRIYEV, L.N., kand.tekhn.nauk (Orel); POZIN, G.M., inzh. (Orel)

Method of calculating the temperature of nonheated greenhouses.  
Vod.1 san.tekh. no.12:3-7 D '65. (MIRA 19:1)

FOZIN, L.M.; ALIBITS, I.M.; GRAD, N.M.; VLASOVA, A.I.

Hardening of unsaturated polyesters in the presence of metallic  
zinc. Zhur.prikl.khim. 38 no.3:702-709 Mr 165. (MIRA 18:11)

1. Submitted Febr. 25, 1964.

L 52304-65 ENI(m)/EWP(j) Pc-4 RM

ACCESSION NR: AP5008819

S/0080/65/038/003/0708/0709

AUTHOR: Pozin, L. M.; Al'shits, I. M.; Grad, N. M.; Vlasova, A. I. 17/2

TITLE: Setting of unsaturated polyesters in the presence of metallic zinc

SOURCE: Zhurnal prikladnoy khimii, v. 38, no. 3, 1965, 708-709

TOPIC TAGS: polyester plastic, resin, metallic zinc, catalyst

ABSTRACT: The effect of metallic zinc powder on toughening and other physical-chemical properties of PN-3<sup>15</sup> polyester resin was studied. The rate of resin toughening is directly proportional to zinc concentration in the resin. A similar correlation with zinc content exists for resin hardness and bending strength. It is assumed that zinc reacts with free oxygenated groups of the polyester resin according to:  $2 \text{ } \nu\text{COOH} + \text{Zn} + (\text{ } \nu\text{COO})_2\text{Zn} + 2\text{H}$ . Combination of two carboxy groups contributes to the resin toughness and the liberated hydrogen atoms serve as polymerization initiators which results in acceleration of the setting process. Polyester-zinc compositions are likely to find ample practical application. Orig. art. has: 2 formulas and 1 table.

Card 1/2

L 52304-65

0

ACCESSION NR: AP5008819

ASSOCIATION: none

SUBMITTED: 25Feb64

ENCL: 00

SUB CODE: MT

NO REF SOV: 001

OTHER: 005

LL  
Card 2/2

KAPYRIN, Yu.V.; TREBIN, G.F.; POZIN, L.Z.

Using temperature effects in investigating the wells of the  
Romashkino field. Neft. khoz. 42 no. 3:26-32 Mr '64.  
(MIRA 17:7)

DAKHNOV, V.N.; KOBRANOVA, V.N.; PECHERNIKOV, V.F.; BENDEL'SHTEYN; B.Yu.;  
KHOLIN, A.I.; POZIN, L.Z.; D'YAKONOV, D.I.; LATYSHEVA, M.G.;  
LOBRYNIN, V.M.; LARIONOV, V.V.; NEYMAN, Ya.A.; LEBBEDEV, A.P.

Terminology and symbols used in applied geophysics. Prikl. geofiz.  
no.27:223-235 '60. (MIRA 13:12)  
(Prospecting--Geophysical methods)

16,5600

80855  
S/055/60/000/02/01/009

AUTHOR: Poznyak, E.G.

TITLE: Examples of Regular Metrics on the Sphere and in a Circle non-Realizable in the Class of Twice Continuously Differentiable Surfaces

PERIODICAL: Vestnik Moskovskogo universiteta. Seriya I, matematika, mekhanika, 1960, No. 2, pp. 3-5

TEXT: It is shown that on the sphere and in a circle regular metrics can be prescribed which are not realizable in the class of twice continuously differentiable surfaces in the three-dimensional Euclidean space. The metric is constructed as follows: One constructs a closed surface  $S$  homeomorphic to the sphere, with a conic point. This surface has a regular inner metric in the neighborhood of every point. Then it is shown that there exists no closed surface of the class  $C^2$  which is isometric to the surface  $S$ . The regular metric of  $S$  is transferred to the sphere in a natural manner. From the consideration it follows that the metric obtained on the sphere is not realizable in the class of twice continuously differentiable surfaces. There is 1 non-Soviet reference.

ASSOCIATION: Kafedra matematiki fizicheskogo fakul'teta (Department of Mathematics of the Physical Faculty)

SUBMITTED: May 16, 1959  
Card 1/1



80867

S/055/60/000/03/02/010

16,5000

AUTHOR: ~~Poznyak, E.G.~~

TITLE: Soft Closed Polyhedra

PERIODICAL: Vestnik Moskovskogo universiteta. Seriya I, matematika, mekhanika, 1960, No. 3, pp. 14-17

TEXT: The author considers the set of polyhedra with a given number of corners, edges and face sides. The conditions that a polyhedron of this set is rigid, lead to a system of equations which has just as many equations as unknowns. To the trivial vanishing solution of the system there correspond rigid polyhedra. To a non-vanishing solution there correspond soft polyhedra. Since a solution different from zero is only possible for a vanishing determinant and the latter one represents an algebraic surface to which there correspond only discretely distributed soft polyhedra, it follows that the measure of the subset of the soft polyhedra equals zero while the subset of the rigid polyhedra has a positive measure.

ASSOCIATION: Kafedra matematiki fizicheskogo fakul'teta (Department of Mathematics of the Physical Faculty)

SUBMITTED: May 16, 1959

Card 1/1

LOZNER, G.Ye.; BUKHARIN, V.V., spetsred.; PRASS, B.Yu., vedushchiy  
red.

[Assembly, adjustment, and operation of units employed in the  
continuous manufacture of soap in a vacuum; operating experience  
of the Karpov Leningrad soap factory] Montazh, naladka i eksplu-  
atatsia ustanovok nepreryvnogo proizvodstva myla pod vakuumom;  
opyt Leningradskogo mylovarennogo zavoda im. Karpova. Moskva,  
GOSINTI, 1959. 37 p. (MIRA 13:6)  
(Leningrad--Soap industry)

NUSINOV, M.D., inzh.; POZIN, A.A., kand. tekhn. nauk; MAYZEL', M.M., doktor tekhn. nauk, prof.

Filling of ring press molds with a rubber mixture under constant and variable high pressure. Izv. vys. ucheb. zav.; tekhn. leg. prom. no.4:69-84 '59. (MIRA 13:2)

1. Moskovskiy tekhnologicheskii institut legkoy promyshlennosti, Rekomendovana kafedroy oborudovaniya i avtomatizatsii tekhnologicheskikh protsessov.

(Rubber)

PLOTKINA, M.; POZIN, B.

Hidden potentialities for the increase of labor productivity  
in the production of construction glass. Sots. trud. 6 no.5:58-  
60 My '61. (MIRA 14:6)

(Glass manufacture)  
(Labor productivity)

15(2)

AUTHORS:

Plotkina, M. A., Pozin, B. L.

SOV/72-59-11-12/1

TITLE:

On the Method of Analyzing the Productivity of Glass Industry

PERIODICAL:

Steklo i keramika, 1959, Nr 11, pp 41-42 (USSR)

ABSTRACT:

The method of determining the productivity on the basis of the calculation of the gross production per worker gives a distorted picture of the actual quality of the workers, which the authors demonstrate by means of examples. Under the production conditions prevailing in many Soviet glassworks in which a number of subsidiary activities are carried out, it would be more exact to calculate the work input per unit of production. The Proektiro-konstruktorskoye byuro Instituta stekla (Planning and Designing Office of the Glass Institute) has been dealing with this problem since 1958 and has so far investigated the following plants: Krasnousol'skiy, "Velikiy Oktyabr'", Gomel', Ivot, Konstantinovskiy "Avtosteklo", and Ashkhabad. This work is carried out by Engineers Pozin, Tsibul'skaya, Dobroserdova, Chernyak, Ponomarev, Filyukina. The working method consists in preparing an index card for each course of production. The individual operations are entered on these cards. On the basis of these index cards, a master chart of

Card 1/2

On the Method of Analyzing the Productivity of  
Glass Industry

SOV/72-59-11-12/10

the general work input per final-production unit is drawn up. In this way, it becomes possible to compare the productivity of domestic glassworks with that of foreign glass factories. The table gives, as an example, the data obtained in two works in which production is organized along different lines. By means of an analysis of the productivity of individual works it is possible to take measures for the rationalization of working processes. There is 1 table.

Card 2/2

POZIN, B.L.

Improve calculations of plate glass costs. Stek. i ker. 14 29-31  
My '57. (MLRA 10:6)

1. Proyektno-konstruktorskoye byuro Instituta stekla.  
(Plate glass--Costs)

*B.M. POZIN*  
POZIN, B.M.

Economic efficiency of the removal of hydrogen sulfide from  
coke-oven gas. Koks i khim. no.12:49-50 '57. (MIRA 11:1)

1. Giprogazochistka.

(Coke-oven gas)  
(Hydrogen sulfide)



*Pozin, B. M.*

68-12-21/25

AUTHOR: Pozin, B.M.

TITLE: On the Problem of the Economy of Purification of Coke Oven Gas from Hydrogen Sulphide (K voprosu ob ekonomike ochistki koksovogo gaza ot serovodoroda)

PERIODICAL: Koks i Khimiya, 1957, no.12, pp. 49 - 50 (USSR)

ABSTRACT: This is a criticism of the paper by M.S. Litvinenko and O.P. Vaysberg (Koks i Khimiya, 1957, No.5). The present author criticises costs calculation used in the original paper and concludes that the matter of economy of vacuum carbonate and arsenical methods of gas purification should be widely discussed in the journal, Koks i Khimiya, so that objective conclusions can be reached.

ASSOCIATION: Giprogazoochistka

AVAILABLE: Library of Congress

Card 1/1

Pozin, I.P.

PH

Analysis of the processes of dust removal in a foam scrubber. M. E. Pozin, I. P. Mukhlenov, and V. Ya. Demshin (Lensovet Technol. Inst., Leningrad). *Zhur. Priklad. Khim.* 28, 1116-20(1955); cf. *C.A.* 50, 3876g.—Two alternatives suggest themselves to account for the fact that in foam dust collectors the proportion of dust with larger particle diam.  $\delta$  is larger in the  $H_2O$  passing through the plate (a) than in the  $H_2O$  (foam) passing over the wier (b). That it is not caused by normal settling during the period of retention in the collector is shown by expts. with pure air bubbling through a  $H_2O$ -dust suspension; the particle distribution in both streams remains the same. The second alternative, that classification occurs under the plate by inertia effects of the plate, was tested by a careful material balance of the respective streams and the detn. of the size distribution in a and b. The fractional dust removal  $\sigma_f$  is smaller in a than in b and does not exceed 80% in the former even with the coarser particles,  $\delta = 60 \mu$ . This is accounted by the fact that the free area of the plate is 16.85% so that less than 83.35% of the gas stream is affected by the inertia forces of the plate. This also accounts for the fact that  $\sigma_f$  of hydrophobic dusts is smaller in a and is affected by the  $\delta$ , and by  $\delta$  of the particles to a greater extent than hydrophilic dusts; for  $\delta < 5 \mu$  there is no difference between the 2 dusts.

I. Bencowitz

(2)

GRUZ, R.I.; VANSHEYDT, A.A.; KRYUCHKOV, F.A.; POZIN, L.M.; KANEVSKAYA, N.V.

Interaction of alcohols and amines with NN'-methylenediacylamide and  
with cyclic NN'N"-trimethylenetriacylamide. Zhur.prikl.khim. 36  
no.6:1307-1314 Je '63. (MIRA 16:8)  
(Alcohols) (Amines) (Acrylamide)

A L 10194-66 EWT(m)/EWP(j)/T RM

ACC NR: AP5028545

SOURCE CODE: UR/0286/65/000/020/0161/0161

AUTHORS: Al'shits, I. M.; Grad, N. M.; Pozin, L. M.; Mikhaylova, I. A.

41  
44,55  
44,55  
44,55  
41  
B

ORG: none

TITLE: Method for obtaining unsaturated polyester resins. Class 39, No. 151815

15, 44, 55

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 20, 1965, 161

TOPIC TAGS: polymer, polyester, polymerization, reducing agent, sulfur compound, redox reaction

ABSTRACT: This Author Certificate presents a method for obtaining unsaturated polyester resins at room temperature with the aid of a redox system. The latter consists of a peroxide of isopropylbenzene and a sulfur-containing compound. To decrease explosion hazards and toxicity, thiourea is used as the sulfur-containing compound. The thiourea is introduced into the resin in the form of a glycerin solution.

SUB CODE: 11,07 SUBM DATE: 12Feb62

Card 1/1

POZIN, L.M.; KHEYFETS, V.L.

Amperometric study of the kinetics of the reaction of potassium persulfate with ferrous sulfate. Zhur.prikl. khim. 38 no.11:2469-2472 N '65.

(MIRA 18:12)

1. Submitted March 15, 1965.

POZIN, L.Ya.

Reducing the number of final documents for new ships being built.  
Sudostroenie 29 no.5:45 My '63. (MIRA 16:9)  
(Shipbuilding)

ISLII, Leonid Iosifovich; PISHKO, V.M., doktor geol.-min. nauk,  
prof., red.; PISHIK, Ye.G., ved. red.

[Differential thermometry of gas and oil wells] Differentsial-  
naya termometriia gazovykh i neflianykh skvazhin. Moskva,  
MIRA, 1964. 113 p. (MIRA 1964)

DAKHNOV, V.N., doktor geol.-miner. nauk; KHOLIN, A.I., kand. geol.-  
miner.nauk; PESTRIKOV, A.S.; GALUZO, Yu.V.; AFRIKYAN, AN.;  
YUDKEVICH, R.V.; POPOV, V.K.; POZIN, L.Z.; LARIONOV, V.V.;  
VENDEL'SHTEYN, B.Yu.; GORBUNOVA, V.I.; DZYURAK, M.D.; YEVDOKIMOVA,  
V.A.; ZHOKHOVA, R.G.; LATYSHEVA, M.G.; MAREN'KO, N.N.; MANCHEVA,  
N.V.; MOROZOVICH, Ya.R.; OREKHOVSKAYA, Ye.P.; POKLONOV, M.S.;  
ROMANOVA, T.F.; SEVOST'YANOV, M.M.; TANASEVICH, N.I.; FARMANOVA,  
N.V.; FEDOROVICH, G.P.; SHCHERBININ, V.A.; ELLANSKIY, M.M.;  
YANUSH, Ye.F.; YUNGANS, S.M., ved. red.; YAKOVLEVA, Z.I., tekhn.  
red.

[Using methods of field geophysics in studying gas-bearing re-  
servoirs]Primenenie metodov promyslovoi geofiziki pri izuchenii ga-  
zonosnykh kollektorov. Moskva, Gostoptekhizdat, 1962. 279 p.

(MIRA 16:2)

(Gas, Natural--Geology)

(Prospecting--Geophysical methods)



POZIN, L.Z.

Investigating wells with a gradient thermometer. Razved.i prom.  
no.32:42-52 '59. (MIRA 13:4)  
(Oil well logging) (Rocks--Thermal properties)

POZIN, M., kandidat ekonomicheskikh nauk.

Fuller use of ice cream plant production capacity. Khol.tekh. 30 no.2:  
53-56 Ap-Je '53. (MLRA 6:7)  
(Ice cream industry)

FISHKIN, A.; POZIN, M.

Improve work planning indexes of technical shops of cold storage plants.  
Khol.tekh. 13 no.3:55-59 J1-S '53. (MIRA 6:11)  
(Cold storage)

POZIN, M.

Tekhnologiya Mineralnykh Solei (Technology of Mineral Salts)

688 p. 3.00

SO: Four Continent Book List, April 1954

POZIN, M., kandidat ekonomicheskikh nauk.

Organizing loading work in cold storage plants and centralized  
feeding of goods to the distribution network. Khol.tekh. 31 no.4:  
44-48 O-D '54. (MIRA 8:1)  
(Cold storage) (Loading and unloading)

GELLER, I.; POZIN, M.

Increased use of refrigeration and problems of economic research.  
Khol.tekh.32 no.2:46-49 Ap-Je '55. (MIRA 8:10)  
(Refrigeration and refrigerating machinery)

POZIN, M., kandidat ekonomicheskikh nauk.

Potential increase of labor productivity in making ice cream.  
Khol.tekh.33 no.1:57-61 Ja Mr '56. (MIRA 9:7)  
(Ice cream industry)

POZIN, M., kandidat ekonomicheskikh nauk.

Potentialities for lowering the cost of food preservation in cold  
storage. Khol.tekh.33 no.3:44-49 J1-S '56. (MIRA 9:10)  
(Cold storage--Costs)



~~POZIN, M.~~  
POZIN, M., kand.ekon.nauk

~~Important problems in the manufacture of ice [with summary in  
English]. Khol. tekhn. 35 no.1:57-60 Ja-F '58. (MIRA 11:2)  
(Ice manufacture)~~

GELLER, I.; POZIN, M.

Refrigeration in the U.S.S.R. [with summary in English]. Khol. tekhn.  
35 no.4:16-21 J1-Ag '58. (MIRA 11:10)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut kholodil'noy  
promyshlennosti.

(Refrigeration and refrigerating machinery)

POZIN, M., kand. ekon. nauk

Mechanization of loading in refrigerators. Sov. torz. no. 1:21-  
25 Ja '59. (MIRA 12:2)  
(Cold storage) (Loading and unloading)

AUTHOR: M. Pozin, Candidate of Economic Sciences SCV/66-59-1-4/32

TITLE: To Improve the Method of Determining the Required Cold Storage Capacity (Uovershenstvovat' metodiku opredeleniya potrebnoy kholodil'noy yemkosti)

PERIODICAL: Kholodil'naya tekhnika, 1959,<sup>34</sup> Nr 1, pp 18-21 (USSR)

ABSTRACT: Depending upon the nature and purpose of refrigeration establishments, these can be divided into 2 groups: productional (refrigerating plants), intended for thermal processing of perishable food (cooling, freezing), and distributing (cold storage houses), intended for storage of perishable food products. This classification is not absolute, as in many cases the functions of production and distribution overlap. The capacity of a refrigerating plant is determined by the importance of the local food trade and the amount of reserves to be stored during the period of maximum production. To make full use of a refrigerating plant, it should be calculated or balanced in such a way that during off-season it can be used as distributing cold storage house. As such it handles three kinds of stocks - permanent, seasonal and current. Seasonal stock can be for production (like meat for sausage making) or for consumption. Though the two kinds may be stored together,

Card 1/3

SOV/86-52-1-4/32

To Improve the Method of Determining the Required Cold Storage Capacity

the space they require must be calculated separately. Current stocks are composed of such items which remain in storage only a few days, and usually do not take more than 10 - 15% of the storage space. Since the capacity of a refrigerating plant or a cold storage house depends upon the reserves it must take care of, it is important to investigate and analyze the factors which enter into making up the volume of these reserves. The question of expedient planning and locating of refrigeration establishments in the USSR is of utmost importance at present, because they must be economically justified and must pay off; as refrigerating plants they must be located near the center of cattle breeding, of growing fruit and vegetables, of processing fish, etc; as cold storage houses they must be located near the centers of distribution. The respective planning must consider all viewpoints and conditions which vary with each economic district. Designing and state planning bureaus such as the Gipromyaso, Giproryba, Giprokholod, Giprotorg, should pay attention to the improved method of calculating cold storage space, while projects should only be approved, if their economic justification is confirmed. In designing

Card 2/3

SOV/66-59-1-4/32

To Improve the Method of Determining the Required Cold Storage Capacity

cold storage establishments provision must be made for possible extensions.

ASSOCIATION: Vsesoyuznyy nauchno issledovatel'skiy institut kholodil'noy promyshlennosti (All-Union Scientific Research Institute of Refrigeration Industry)

Card 3/3

L 63833-65 EWT(m)/EWP(t)/EWP(b) IJP(c) JD

ACCESSION NR: AP5020231

UR/0069/65/027/004/0593/05972/  
541.18.046.8

20  
B

AUTHORS: Pozin, M. Ye.; Kopylev, B. A.; Yefremov, I. F.; Varshavskiy, V. I.;  
Markovich, A. G.

TITLE: Coagulation processes in the manufacture of superphosphates

SOURCE: Kolloidnyy zhurnal, v. 27, no. 4, 1965, 593-597

27

TOPIC TAGS: superphosphate, phosphorus compound, fertilizer, potassium compound, calcium sulfate

ABSTRACT: The mechanism of potassium sulfate deposition on apatite granules in the manufacture of superphosphates was investigated to determine the effect of the particle size on this process. The electrokinetic potentials of apatite and other minerals in the superphosphate pulp were established. Test specimens consisted of a standard apatite concentrate with 39.5% of  $P_2O_5$  and a reactive sulfuric acid (100 g apatite and 70 g  $H_2PO_4$  monohydrate). The experimental process is briefly described. The ability of calcium sulfate crystals to become attached to apatite grains is determined mainly by their size. Crystals smaller than 10-15  $\mu$  show a very strong adhesion; crystals larger than 30-40  $\mu$  do not adhere

Card 1/2

L 63833-65

ACCESSION NR: AP5020231

and form no slime coatings which retard the decomposition reaction. The deposition is a result of the adagulation process under the effect of the Van der Waals forces at lowering of the energy barriers. The electrokinetic potentials of apatite and other minerals were measured by the electro-osmotic method at 20C. In phosphoric acid, the electrokinetic potential of apatite has a high absolute value; in sulfuric acid its potentials are low. The potential of anhydrite and gypsum is near zero at all the phosphoric and sulfuric acid concentrations. In distilled water and in dilute solutions of phosphoric and sulfuric acids, apatite and aegirite have a slight negative potential which becomes positive over the acid concentration range of  $10^{-2}$  -  $10^{-1}$  N. It was established that the formation of slime coating may be avoided by choosing conditions ensuring the formation of calcium sulfate crystals larger than 20-30  $\mu$  or by controlling the charges of the interacting particles. Orig. art. has: 1 figure and 1 table.

ASSOCIATION: Leningradskiy tekhnologicheskii institut im. Lensoveta (Leningrad Engineering Institute)

SUBMITTED: 09Mar64

ENCL: 00

SUB CODE: GC, IC

NO REF SOV: 009

OTHER: 003

Card 2/2 *flh*



POKH, N.Y.; KOPYEV, S.V.; KOPYEV, N.R.

Solubility in the system  $\text{NH}_4\text{ClO}_4 - \text{H}_2\text{O} - \text{H}_2\text{O}_2$  -  $\text{H}_2\text{O}$  -  $\text{H}_2\text{O}_2$  -  $\text{H}_2\text{O}$   
prikl. khim. 57 no.11s.341-342 (1984) (USSR 1984)

1. Leningradskiy tekhnicheskiy institut khim. tekhnol.

Pozin, M. Kh.

~~Fertilizer. M. Kh. Pozin, M. A. Kopylov, and E. I. Varshavskii. U.S.S.R. 107,487, Sept. 25, 1957. The acid phosphate-gypsum pulp, obtained in the H<sub>2</sub>SO<sub>4</sub>-extra. of natural phosphates, is treated with a limestone or Ca(OH)<sub>2</sub> suspension. The mixed ppt. thus obtained is sepd. into a concd. fertilizer and gypsum by flotation in the presence of a collector such as the reagent IM-11 or oleic acid.~~

M. Hosh

3

11

VASIL'YEVA, Nadezhda Grigor'yevna; POZIN, M.M., kand. ekon. nauk,  
nauchnyy red.; KAPLUN, M.S., red.; MAMONTOVA, N.N., tekhn.  
red.

[Economic effectiveness of the automation of ammonia refri-  
gerating units] Ekonomicheskaya effektivnost' avtomatizatsii  
ammiachnykh kholodil'nykh ustanovok; nauchnoe soobshchenie.  
Moskva, Gostorgizdat, 1962. 13 p. (MIRA 15:8)  
(Refrigeration and refrigerating machinery)  
(Automatic control)

BILLIK, Abram Markovich; POZIN, Mark Markovich, kand. ekon. nauk; LOVIKOV, Petr Fedorovich; KAMENITSER, S.Ye., prof., doktor ekon. nauk, retsenzent; MOROZOV, M.V., kand. ekon. nauk, retsenzent; VESHKOV, Yu.K., kand. ekon. nauk, red.; MASLOVA, Ye.F., red.; BRODSKIY, M.P., tekhn. red.

[Organization and planning in refrigeration enterprises] Organizatsiia i planirovanie kholodil'nykh predpriatii. Moskva, Gos. izd-vo torg. lit-ry, 1961. 276 p. (MIRA 14:10)  
(Refrigeration and refrigerating machinery)