

YUPKO, L.D.; BALON, I.D.; KAYSTRO, N.P.; LITVINENKO, V.I.; ONOPRIYENKO, V.P.,
kand. tekhn. nauk; ROMANENKO, N.T.; TULUYEVSKAYA, T.A.

Arrangement of additional tuyeres, and their effect on blast
furnace performance. Sbor. trud. UNIIM no.9:71-98 '64

(MIRA 18:1)

SECRET [Illegible text]

[Illegible text]

[Illegible text]

[Illegible text]

ACCESSION NR: AT4010700

S/2601/63/000/017/0209/0210

AUTHOR: Kocherzhynakly, Yu. A.; Kobzenko, G. P.; Pan, V. M.; Sviridanko, V. R.;
Yupko, L. M.

TITLE: Calibration of the VR-5/20 thermocouple according to critical points up to
3000C. Determination of the melting points of vanadium and niobium of high purity

SOURCE: AN UkrRSR. Instytut metalofizyky. Sbornik nauchnykh trudov, no. 17.
1963. Voprosy fiziki metallov i metallovedeniya, 209-210

TOPIC TAGS: thermocouple, VR-5/20 thermocouple, thermocouple calibration,
vanadium, niobium, vanadium melting point, niobium melting point, tungsten rhenium
alloy

ABSTRACT: After calibration studies using the melting points of silver, gold,
iron, nickel, palladium, platinum, chromium, molybdenum, and tantalum had shown
that the VR-5/20 thermocouple (consisting of electrodes made of tungsten alloys
containing 5 and 20% rhenium, respectively) could be used for the accurate de-
termination of temperatures up to 3000C, the authors applied the technique of
V. S. Mikheyev to the determination of the melting points of vanadium (1950C)
and niobium (2520C). "In conclusion, the authors would like to thank A. M.
Gurevich and Ye. I. Pavlova for making the thermocouple available." Orig. art.
Card 1/2

ACCESSION NR: AT4010700

has: 1 figure and 1 table.

ASSOCIATION: Instytut metalofizyki AN UkrRSR (Metallophysics Institute, AN UkrRSR)

SUBMITTED: 00

DATE ACQ: 31Jan64

ENCL: 00

SUB CODE: ML

NO REF SOV: 003

OTHER: 001

Card 2/2

SVECHNIKOV, V.N.; KOCHERZHINSKIY, Yg.A.; YUPKO, L.M.

Chromium - silicon diagram. Stor.nauch.trud. Inst. metallofiz. AN
URSR no.19:212-218 '64. (MIRA 18:5)

calibration

ABSTRACT: On the basis of the tungsten - rhenium phase diagram, distinguish three types of thermocouples which can be prepared in this system: (1) thermocouples from two solid solutions such as VR-0/100, (2) thermocouples from the pure components (VR-0/100), and (3) thermocouples from pure tungsten and a solid solution of rhenium in tungsten with a certain rhenium content (they are used for the measurement of the highest temperatures, 3100-3200C, and are designated VR-0/3, VR-0/5, and VR-0/8).

Card 1/2

L 23620-65

ACCESSION NR: AT5002785

calibration graph (thermo-emf versus temperature) of one of the
the latter type, the VR-5/20, which they plotted on the basis of
points of pure metals and transition points of iron in the process
heating. The VR-5/20 thermocouple may be used to measure temperatures
3000C and has a satisfactory sensitivity. "The authors express their grati-
tude to A. M. Gurevich, B. K. Denishevskiy, and Ye. I. Pavlov for the
couples supplied for the study." Orig. art. has: 1 figure.

ASSOCIATION: None

SUBMITTED: 05Aug64

ENCL: 00

NO REF SOV: 005

OTHER: 001

VR-3 12
VR-20 14
VR-8 18
VR-100 18

Card 2/2

ml
Card 3/3

ACC NR: AT6036277

SOURCE CODE: UR/0000/66/000/000/0053/0055

AUTHOR: Svechnikov, V. N.; Kocherzhinskiy, Yu. A.; Yupko, L. M.

ORG: Institute of Physics of Metals, AN UkrSSR (Institut metallofiziki, AN UkrSSR)

TITLE: Phase diagram of the $CrSi_2$ - $MoSi_2$ system

SOURCE: AN UkrSSR. ²⁷⁻¹²⁷Struktura metallicheskih splavov (Structure of metal alloys).
Kiev, Izd-vo Naukova dumka, 1966, 53-55 ₁₈

TOPIC TAGS: chromium disilicide alloy, molybdenum disilicide containing alloy,
silicon, alloy phase diagram

ABSTRACT: A series of 43 chromium disilicide-molybdenum disilicide alloys have been investigated. The alloys were melted from sintered molybdenum, electrolytic chromium, and commercial or semiconducting silicon. Twenty-one of the alloys contained semiconducting silicon. On the basis of the data obtained by various methods of physicochemical analysis, a phase diagram of $CrSi_2$ - $MoSi_2$ system was plotted.

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R001963130002-6"

Card 1/2

ACC. NO. AT6036277




Fig. 1. Phase diagram of the MoSi₂-CrSi₂ system

ture of 1525 ± 25C. The existence of a double-phase region, between 40.5% and 70% of MoSi₂ has been confirmed. Orig. art. has: 3 figures.

SUB CODE: 07,11,20/ SUBM DATE: 22May65/ ORIG REF: 003/ OTH REF: 001/

ATD PRESS: 5106

Card 2/2

- YUPKO, V.L.

AID Nr. 983-5 5 June

ELECTRIC AND THERMOELECTRIC PROPERTIES OF SILICIDES OF
TRANSITION METALS (USSR)Neshpor, V. S., and V. L. Yupko. Poroshkovaya metallurgiya, no. 2,
Mar-Apr 1963, 55-59. S/226/63/000/002/008/014

The temperature dependence of electric resistivity (in the 20-1000°C range) and of the Seebeck emf (in the 20-600°C range) of silicides of V (15.9, 25.2, and 51.5% Si), Mn (33.4, 23.0, and 51.0% Si), and Fe (14.2, 33.1, and 50.8% Si) and of Co_3Si (13.1% Si), CoSi_2 (48.9% Si), Ni_3Si (13.5% Si), Ni_2Si (19.1% Si), ZrSi_2 (38.5% Si), TiSi_2 (23.9% Si), Re_3Si , and ReSi , has been studied at the Institute of Powder Metallurgy and Special Alloys of the Ukrainian Academy of Sciences. Silicides were obtained by the synthesis of components; the sintered specimens were prepared by hot compacting. Microscopic examination and the x-ray diffraction patterns showed the silicides to have a single-phase structure, except for Co_3Si , Ni_3Si , Ni_2Si , and Re_3Si , which had inclusions of a second phase concentrated along grain boundaries. The nature of the temperature dependence of the electric resistivity of MnSi_2 , Mn_5Si_3 , and ReSi showed these silicides to be semiconductors. The Fe_3Si and Co_3Si appeared to be ferromagnetic semimetals. The temperature dependence of the electric resistivity of all other silicides studied

Card 1/2

AID Nr. 983-5 5 June

ELECTRIC AND THERMOELECTRIC PROPERTIES [Cont'd]

S/226/63/000/002/008/014

was characteristic for metallic conductors; the increase of resistivity with temperature was linear in V_3Si , Ni_2Si , and $CoSi_2$, but nonlinear in all other silicides. The absolute magnitude of thermal emf and its temperature dependence for most silicides studied were characteristic for compounds with metallic conductivity. In general, the temperature dependence of thermal emf was nonlinear and had maxima, which indicates the presence of positive and negative current carriers. The temperature dependence of thermal emf in $FeSi_2$, $MnSi_2$, and $ReSi_2$ was characteristic for doped semiconductors. In general, with increasing relative content of Si in the intermediate phases of Me-Si systems, the absolute values of thermal emf increased and the nature of their temperature dependence became more complex. This probably was caused by an increasing share of covalent bond in silicides and by their electron energy spectrum becoming more complex with increasing Si content. For Re_3Si the thermal emf in the entire range of temperatures tested was found to be zero, which makes this silicide a prospective material for high-temperature thermocouples. [MS]

Card 2/2

L 9909-03

EMT(q)/EMT(e)/BDS--AFFTC--JD

ACCESSION NR: AP3002705

AUTHOR: Neshpor, V. S.; Yapko, V. L.

TITLE: Investigation of preparation conditions of barium disilicide

SOURCE: Zhurnal prikladnoy khimii v. 36, no. 11

TOPIC TAGS: alkaline earth silicides, barium silicide, preparation, semiconductor, refractory, BaSi, Arceol, expansion coefficient, thermal conductivity

ABSTRACT. The preparation and physical properties of barium disilicide have been studied because of its semiconductor properties. It is prepared in a vacuum at 1300-1420C by reduction of barium silicide. Analysis indicated that at 1420C the composition is stoichiometric; at higher temperatures sublimation occurs. X-ray analysis showed that line positions are in agreement with the BaSi sub 2 crystalline structure. Unpublished.

Cont 1/2

L 9914-63
ACCESSION NR: AP3002705

to the crystalline structure of BaSO_4 and BaCO_3 .
Compact specimens, obtained in an argon atmosphere,
black with a metallic lustre. Metallography shows
a composition primarily of BaSO_4 and BaCO_3 .
 $\rho = 4.5 \text{ g/cm}^3$ (BaSO_4 sup 2). $\mu = 0.0001 \text{ cm}^2/\text{V} \cdot \text{sec}$.
 $\tau = 10^{-10} \text{ sec}$, and the thermal expansion coefficient is
 $20 \times 10^{-6} \text{ /}^\circ\text{C}$ and $10 \times 10^{-6} \text{ /}^\circ\text{C}$ at 20°C and 100°C .
 Ca^{2+} (sup 2) (ca. 10%). From measurements
temperature dependence at $20-100^\circ\text{C}$, it was found
semiconductor with a resistivity of $10^4 \text{ } \Omega \cdot \text{cm}$.
from impurity to intrinsic production with E_g
 E_g determined from a plot of the temperature
found to be 0.48 eV. Absolute thermoelectric power is
Microvolts / $^\circ\text{C}$ at room temperature. In view of
possible refractory, semiconducting material, it was
measured only at 1000°C and found to be $10^{-4} \text{ V/}^\circ\text{C}$.
Thermal conductivity constant of $2 \times 10^{-4} \text{ W/cm}^2 \cdot \text{K}$.

Figures are in parentheses.
A.S. DALLA
SYNTHESIS
SIR GORE
Card 2/2

L 16904-65 EWP(a)/EWT(m)/EPT*(n)-2/EPR/EWP(t)/EWP(b)
AFMD(t)/AEDG(b)/AFWL/AS(m)-2/ESD/ASD(a)-5/ESD(tp)/E
AT/WH
ACCESSION NR: AP6047387

AUTHORS: Andreyeva, T. V.; Barantseva, I. G.; Daniluk, Ya.

TITLE: Study of some physical properties of aluminum nitride

SOURCE: Teplotfizika vy'sokikh temperatur, v. 2, no. 5, 1967

TOPIC TAGS: aluminum nitride, specific electrical resistivity, thermal expansion coefficient, dielectric constant, thermocouple, dilatometer/ OMP OK9 pyrometer, HDM 4 resistor

ABSTRACT: The temperature dependence of specific electrical resistivity, coefficient of thermal conductivity, coefficient of thermal expansion

~~ABSTRACT: The temperature dependence of specific electrical resistance, coefficient of thermal conductivity, coefficient of thermal expansion, dielectric constant, and the dielectric loss of~~
have been investigated. The measurements were made on samples of porosity of 10-20%, obtained by cold pressing and subsequent sintering in a sphere of nitrogen at 2173K. The specific electrical resistance measurements were made in a temperature range of 300-1573K on specimens 12-15 mm high, using an MOM-4 apparatus. The temperatures were measured by platinum-platinum-rhodium thermocouples. The specific resistance decreases monotonically from 2.25×10^{11} at 673K to 1×10^7 at 1573K.
Cont 1/2

L 16904-65

ACCESSION NR: AP4047587

The thermal conductivity was measured in the range of 300-1000°K. At low temperatures the method described by V. S. Neshpor and I. G. Pustovalov (Zh. No. 1, 1953) was used, and for high temperatures the method of Pustovalov (Zavodskaya laboratoriya, No. 9, 1951, 1957) was used. The thermal conductivity was measured by a pyrometer of the type OMP-019. A non-linear temperature dependence of the thermal conductivity was observed in this regime. The frequency dependence of the dielectric constant and the dielectric loss angle were measured in the range of 100 kilocycles to 26 megacycles. The dielectric constant dropped sharply at about 300 kilocycles, and thereafter increased very slowly with frequency. The coefficient of thermal expansion was measured in the range of 300-1000°K by a quartz dilatometer. The mean value of this coefficient was $10^{-6}/^{\circ}\text{C}$. The specimens were prepared by Yu. B. Barin.

10 /C. The specimens were prepared by Yu. D. Repkin. See also
and 1 table.

ASSOCIATION: Institut problem materialovedeniya, Akademii Nauk
of Materials Research Problems, Academy of Sciences (USSR)

SUBMITTED: 15May64

SUB CODE: MM

NO REF SOL: 012

Card 2/2

AUTHOR: Malarenko, G. N. (Moscow)

ORG: Institute of Materials Science Problems, Academy of Sciences
Institut problem materialovedeniya, Akademii Nauk (USSR)

TOPIC: Electrical properties; Semiconductors

The article describes the results of an investigation of the
temperature dependence of the electrical conductivity of
single crystals of germanium. The investigation was carried out
in the temperature range 4.2-300 K. It is shown that the
conductivity increases with increasing temperature and that
the temperature dependence of the conductivity is characterized
by a minimum at approximately 100 K. The results are compared
with the data of other authors and the theoretical curves
calculated for a semiconductor with a band gap.

ACCNRE: AI 8927335

...ions were measured and plotted against the ...
model is proposed for LaO_2 ...
...ion, four metal atoms and ...
... atoms participate in ...
... atoms are free and participate ...
... is the strongest one in rare earth d. ...
metallic bond. Orig. art. has: 2 figures and 3 tables

SUBJECT: IC, GC / SUBM DATE: 1985/01/01

L 31877-66 EWI(1)/EWI(m)/ETC(f)/ENP(o)/ENP(t)/EII IJP(o) WRI/JD/JG/GD/AT/WH
ACC NR: AT6013558 SOURCE CODE: UR/0000/65/000/000/0199/0204

AUTHOR: Paderno, Yu. B.; Barantseva, I. G.; Yupko, V. L.

ORG: Institute of Materials Science Problems, AN UkrSSR (Institut problem materialovedeniya AN UkrSSR)

TITLE: Determination of thermal conductivity and electrical resistance of ZrC, HfC, NbC, and TaC at high temperatures

SOURCE: AN UkrSSR. Institut problem materialovedeniya. Vysokotemperaturnyye neorganicheskiye soyedineniya (High temperature inorganic compounds). Kiev, Naukova dumka, 1965, 199-204

TOPIC TAGS: zirconium, hafnium, niobium, tantalum, carbide

ABSTRACT: The thermal conductivity and the electrical resistance of ZrC, HfC, NbC, and TaC were determined in the 1370°-3270°K range. The measurements were made with an apparatus shown in figure 1. The samples were 8 mm in diameter and 15-18 mm in length. The hole depths were 3.5-3.7 and 1.8-2.0 mm, their diameter was 0.9 mm, the distance separating them was approximately 5 mm, and the distance between the potential zones was 7-7.5 mm. The coefficient of thermal conductivity (λ) was calculated from the formula

$$\lambda = \frac{IU}{4\pi\Delta T l} \cdot \frac{r_a^2 - r_b^2}{R^2}$$

Card 1/2

L 31877-66

ACC NR: AT6013558

0

where I is the current in the sample, U is the potential difference on the sample portion of l in length, R is the sample radius, l is distance between potential zones used in potential difference determination, r_a and r_b are radii, $\Delta T = T_b - T_a$ is the temperature difference. The electrical resistance ρ was calculated from the formula

$$\rho = \frac{U}{I} \cdot \frac{\pi R^3}{l}$$

The carbide samples composition is shown in a table. Orig. art. has: 4 figures, 2 tables, 2 formulas.




Fig. 1. 1--electrical lead; 2--vacuum valve; 3--vacuum tubes; 4--leak; 5--chamber housing; 6--front cap-flange; 7--visier; 8--visier glass protection plate; 9--sample.

a--water; b--to prevacuum and diffusion pump; c--to prevacuum line

SUB CODE: 11, '07/

SUBM DATE: 03Jul65/

ORIG REF: 008/

OTH REF: 007

Card 2/2

PB

L 32675-66 EWT(1)/EWT(m)/EWT(t)/ETI 10P(c) 00/ww,cs,ss

ACC NR: AT6013567

(A)

SOURCE CODE: UR/0000/65/000/000/0293/0286

AUTHOR: Paderno, Yu. B.; Dudnik, Ye. M.; Andreyeva, T. V.; Barantseva, I. G.; Yupko, V. L.ORG: Institute of Material Science Problems, AN UkrSSR (Institut problem materialovedeniya AN UkrSSR) ⁵¹TITLE: Measurement of the thermal expansion coefficients of ZrC, HfC, NbC, and TaC at high temperatures

SOURCE: AN UkrSSR. Institut problem materialovedeniya. Vysokotemperaturnyye neorganicheskiye soyedineniya (High temperature inorganic compounds). Kiev, Naukova dumka, 1965, 293-298

TOPIC TAGS: zirconium carbide, hafnium compound, tantalum compound, niobium compound, heat expansion, ~~zirconium carbide~~ CARBIDEABSTRACT: The thermal expansion of ²zirconium, ²⁷hafnium, ²⁷niobium, and ²⁷tantalum carbides was studied in the 1370°-3170°K range. The object of the work was to fill a gap in the literature. The thermal expansion was measured in a vacuum chamber (10^{-2} mm Hg) in which carbide samples (8 mm in diameter and 15-18 mm in length) were heated electrically. The carbide samples were prepared by hot-pressing technique and the temperature was measured with an OPN-19 micropyrometer. The individual carbide samples had the

Card 1/2

L 32675-66

ACC NR: AT6013567

following porosities: ZrC--19 to 24%, HfC--22 to 28%, NbC--13 to 18%, and TaC--27%.
The dependence of the relative thermal expansion ($\Delta L/L$) of the carbide samples upon
temperature is graphed. A table gives the average values of the thermal expansion co-
efficients (α) for various carbides. Orig. art. has: 2 figures, 2 tables.

SUB CODE: 07,11/ SUBM DATE: 03Jul65/ OTH REF: 003

Card 2/2

BLG

L 32053-66, EWP(e)/EWT(m)/EWP(t)/ETI IJP(c) JD/JG/AT/WH

ACC NR: AP6013341

(A)

SOURCE CODE: UR/0363/66/002/004/0626/0629

AUTHOR: Paderno, Yu. B.; Yupko, V.L.; Rud', B.M.; Makarenko, G.N.

48
B

ORG: Institute of Materials Science Problems, Academy of Sciences UkrSSR (Institut problem materialovedeniya Akademii nauk Ukr SSR)

TITLE: Physical properties of certain rare earth dicarbides

SOURCE: AN SSSR. Izvestiya. Neorganicheskiy materialy, v. 2, no. 4, 1966, 626-629

TOPIC TAGS: rare earth metal, carbide, electric property, Hall constant, thermoelectromotive force

ABSTRACT: The temperature dependence of the electrical resistance in the 20 — 1300C temperature range, the coefficient of absolute thermoemf, the Hall coefficient at room temperature, and the melting point were measured on the same samples of Y, La, Ce, Pr, and Nd dicarbides. From these measurements, the charge carrier concentrations and mobilities were calculated. An anomalous temperature dependence of the electrical resistance was observed around 1000C. The high effective carrier concentration in CeC₂ as compared to the other dicarbides studied is explained on the basis of the electronic

Card 1/2

UDC: 546.65'261

L 32053-66

ACC NR: AP6013341

structure of the rare earth atoms and the magnetic susceptibility of the dicarbides. The low effective carrier concentration in the case of YC_2 is due to a change in bond character in the C_2 complex, this being supported by data on the hydrolysis of YC_2 . Orig. art. has: 1 figure and 2 tables.

SUB CODE: 11 / SUBM DATE: 28May65 / ORIG REF: 012 / OTH REF: 008

Card 2/2 *oo*

ACC NR: AP7008531

SOURCE CODE: UR/0363/67/003/002/0395/0397

AUTHOR: Paderno, Yu. B.; Yupko, V. L.; Rud', B. M.; Kvas, O. F.;
Makarenko, G. N.ORG: Institute of Material Science Problems, AN UkrSSR (Institute
problem materialovedeniye AN UkrSSR)

TITLE: Electrophysical properties of Gd, Tb, Dy, Er, Tu dicarbides

SOURCE: AN SSSR. Izvestiya. Neorganicheskiye materialy, v. 3, no. 2,
1967, 395-397TOPIC TAGS: gadolinium ~~dicarbide~~, terbium ~~dicarbide~~, dysprosium
~~dicarbide~~, erbium ~~dicarbide~~, thulium ~~dicarbide~~, dicarbide ~~dicarbide~~,
carbide, resistivity, Hall effect, carrier densityABSTRACT: The results are presented of an experimental determination
of the electrophysical properties of Gd, Tb, Dy, Er, and Tu dicarbides.
Initial powder carbides were obtained by the reduction of metal oxides
with carbon in vacuum at 1800°C for 25-60 min. The carbide powders were
compacted and sintered in argon at 1700-1800°C for 15 min under a
pressure of 100 kg/cm²; the porosity of sintered compacts was 5-13%;
finished specimens were annealed at 1650°C for 8 hr. It was found that
carbide resistivity changed from 30 μohm.c. for GdC₂ to 515 μohm.cm for

Card 1/2

UDC: 546.65'261:541.12.03

ACC NR: AF7C08531

TuC₂; the coefficient of emf from $-5.95 \mu\text{v}/^\circ\text{C}$ for ErC₂ to $-7.75 \mu\text{v}/^\circ\text{C}$ for TbC₂; Hall effect from $-2.55 \text{ cm}^3/\text{coul}$ for TbC₂ to $+136 \text{ cm}^3/\text{coul}$ for TuC₂; effective carrier concentration from 0.018 el/atom M for TuC₂ to 1.04 el/atom M for TbC₂; and mobility from $6.75 \text{ cm}^2/\text{v. sec}$ for ErC₂ to $19.6 \text{ cm}^2/\text{v. sec}$ for TuC₂. Melting points ranged from 2180°C for TuC₂ to 2280°C for ErC₂. Orig. art. has: 1 figure and 2 tables. [TD]

SUB CODE: 11/ SUBM DATE: 13Jan66/ ORIG REF: 009/ OTH REF: 008

Card 2/2

ACC NR: AP7008532

SOURCE CODE: UR/0363/67/003/002/0398/0400

AUTHOR: Paderno, Yu. B.; Yupko, V. I.

ORG: Institute of Materials Science Problems, Academy of Sciences, UkrSSR (Institut problem materialovodeniya Akademii nauk UkrSSR)

TITLE: Nature of the change of the effective concentration of current carriers in a series of rare earth dicarbides

SOURCE: AN SSSR, Izvestiya. Neorganicheskiye materialy, v. 3, no. 2, 1967, 398-400

TOPIC TAGS: carbide, rare earth compound, carrier density, electron structure, transition probability

ABSTRACT: An attempt is made to provide a qualitative explanation for the variation in the experimental values of the effective concentration of carriers n^* in a series of rare earth dicarbides from the standpoint of the probability of appearance of d states in the metal atoms and the energetic stability of the f energy states of rare earth atoms for given degrees of their filling. The qualitative dependence of the appearance of the f-d state, n_{fd} , in the series of rare earth metals is given in Fig. 1. This dependence is shown to be very similar to the nature of the change in the experimental values of n^* (see Table 1). This similarity indirectly confirms an earlier hypothesis that the conduction in these rare earth dicarbides is accomplished mainly with 5d electrons. The change in n^* and resistivity of the corresponding

Card 1/2

UDC: 546.65'261:541.12.03

ACC NR: AP7008532

hexaborides is also discussed. Orig. art. has: 1 figure and 2 tables.

Fig. 1




Table 1. Effective carrier concentration n^* and parameter $\delta = R/e^2$ of rare earth dicarbides

Phase	LaC ₂	CeC ₂	PrC ₂	NdC ₂	GdC ₂	TbC ₂	DyC ₂	ErC ₂	TmC ₂
$n^*, \text{el/cm}^3$	0.63	1.08	0.55	0.68	0.89	1.04	0.86	0.79	$1.8 \cdot 10^{-1}$
$\delta \cdot 10^{-2}, \text{cm}^2/\text{V}^2 \cdot \text{sec}^2$	-15.5	-4.9	-22.1	-13.9	-23.0	-12.3	-18.4	-14.4	-1.8

SUB CODE: 07/ SUEM DATE: 13Jan66/ ORIG REF: 010/ OTH REF: 007

Card 2/2

YUR, N. V.

YUR, N. V.: "Best cultivation of pines on the Boyar Teaching and Experimental Leskhoz." Kiev, 1955. Min Higher Education Ukrainian SSR. Ukrainian Order of Labor Red Banner Agricultural Academy. (Dissertation for the Degree of Candidate of Agricultural Sciences)

SO: Knizhnaya Letopis' No. 47, 19 November 1955. Moscow.

YURALYAVICHUS, B. Yu. Cand Tech Sci -- (diss) "Study of the
Operating Parts of Machines for the ^{Sowing} Planting and ^{Care} Cultivation of
Vegetable Crops ^{under} ~~in the~~ Conditions of the Lithuanian SSR."
Kaunas, 1957. 20 pp with diagrams, 22 cm. (Lithuanian
Agricultural Academy), 100 copies (KL, 18-57, 96)

YURA

POLAND / General Biology. Individual Development.

B-4

Abs Jour : Ref Zhur - Biol., No 2, 1958, No 4918

Author : Yura

Inst : Not given

Title : Controversy on Entoderm in Insects

Orig Pub : Kosmos (Polska), 1956, A5, No 4, 493-500

Abstract : A review of the literature on the controversial question of sources of formation of the middle intestine (MI) in insects. Dorn (1866), Byuchli (1870), Maier (1876), Tikhomirov (1879) and others maintained that insect MI develops from yolk cells, the aggregate of which they accepted as entoderm. Kovalevskiy (1871) and Grassi (1884) maintained that MI is formed from the lower embryo layer, the separation of which Kovalevskiy compared with gastrulation. Vytlachil (1884),

Card : 1/4

POLAND / General Biology. Individual Development. APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R001963130002-6

Abs Jour : Ref Zhur - Biol., No 2, 1958, No 4918

: Fel'tskov (1889) and Geimons (1895) came to the conclusion that MI develops from ectoderm (from stomodeal and proctodeal cavities) and that the entoderm serves to form vitellophages. Chuprova (1906) agreed with Geimons, while Esherikh (1900), Noak (1901), Shvangart (1904) and especially Nusbaum and Fulinskiy (1906) sided with a somewhat modified point of view of Kovalevskiy. During the next 50 years the discussion on this theme continued; the appearance of contradictory observations is explained by technical difficulties, an uncertain terminology, and different interpretation of similar facts. Thus, according to Tikhomirov the MI in *Calandra granaria* forms from yolk cells; according to Inkman (1933) from the lower layer, but according to Sheinert (1933) from the cells of the anterior and middle intestines. The author considers a number of theories which attempted to resolve the

Card : 2/4

YURA, ANATOLIY TERENT'YEVICH.

PHASE I BOOK EXPLOITATION SOV/3735

Hurlyev, Dmytro Stepanovych, and A.T. Yura

Dovidnyk po elektronnykh pryladakh (Reference Book on Electronic Devices) Kyiv, Derzh. vyd-vo tekhn. lit-ry, 1959. 344 p. 10,000 copies printed.

Ed.: Yu.E. Korsak; Tech. Ed.: K. Husarov.

PURPOSE: This reference book is intended primarily for radio amateurs interested in the construction, adjustment, and maintenance of various radio and television equipment. It may also be of interest to the general reader.

COVERAGE: The book gives information on characteristics, electric data, typical diagrams, and applications of the most common electron tubes used in amateur radio. Some data on semiconductors (transistors) are also given. No personalities are mentioned. There are no references.

TABLE OF CONTENTS:

Card 1/14

Reference Book (Cont.)

SOV/3735

GENERAL INFORMATION

Basic Tube Parameters	5
Diodes	7
Triodes	8
Beam tetrodes	8
Pentodes	9
Converters and heterodynes	12
Cathode-ray tubes	12
Barretters	13
Voltage regulators	13
Semiconductor devices	14
Some recommendations for the construction of radio equipment	17

ELECTRONIC AND SEMICONDUCTOR DEVICES

Receiving and Amplifying Tubes	19
0.6Zh6B (audio-frequency pentode)	19
0.6P2B (audio-frequency pentode)	21
1 A1P (heptode-converter)	24

Card 2/14

Reference Book (Cont.)

SOV/3735

1A2P (heptode-converter)	28
1B1P (diode-pentode)	29
1B2P (diode-pentode)	34
1Zh18B (sharp-cutoff radio-frequency pentode)	36
1K1P (remote-cutoff radio-frequency pentode)	38
1K2P (remote-cutoff radio-frequency pentode)	41
1N3S (output twin triode)	42
1P2B (audio-frequency output pentode)	44
1P3B (audio-frequency output pentode)	47
1Ts1S (high-voltage rectifier)	49
1Ts7S (high-voltage rectifier)	51
1Ts11P (high-voltage rectifier)	52
2Zh15B (sharp-cutoff radio-frequency pentode)	53
2P1P (output beam tetrode)	55
2P2P (output beam tetrode)	60
2Ts2S (high-voltage rectifier)	61
5Ts3S (full-wave high-voltage rectifier)	63
5Ts4S (full-wave high-voltage rectifier)	65
6A2P (heptode converter)	66
6A7 (heptode converter)	68

Card 3/14

Reference Book (Cont.)

SOV/3735

6B2P (remote-cutoff radio-frequency diode-pentode)	73
6B3S (twin diode-pentode)	75
6G2 (twin diode-triode)	81
6G3P (triple diode-triode with separate cathodes)	84
6G7 (twin diode-triode)	86
6Ye1P1 (cathode-ray tuning indicator)	89
6Zh1B (sharp-cutoff radio-frequency pentode)	93
6Zh2B (sharp-cutoff radio-frequency pentode)	95
6Zh1P (sharp-cutoff radio-frequency pentode)	97
6Zh2P (sharp-cutoff radio-frequency pentode)	99
6Zh3 (sharp-cutoff radio-frequency pentode)	102
6Zh3P (radio-frequency tetrode with pentode characteristic)	105
6Zh4 (sharp-cutoff radio-frequency pentode)	108
6Zh4P (sharp-cutoff radio-frequency pentode)	112
6Zh5P (sharp-cutoff radio-frequency beam tetrode)	114
6Zh7 (sharp-cutoff radio-frequency pentode)	116
6Zh8 (sharp-cutoff radio-frequency pentode)	120
6Zh9P (sharp-cutoff radio-frequency pentode)	124
6Zh11P (sharp-cutoff radio-frequency pentode)	126

Card 4/14

Reference Book (Cont.)

80V/3735

6I1P (triode-heptode)	127
6K1P (remote-cutoff radio-frequency pentode)	130
6K3 (remote-cutoff radio-frequency pentode)	133
6K4 (remote-cutoff radio-frequency pentode)	136
6K4P (remote-cutoff radio-frequency pentode)	139
6K7 (remote-cutoff radio-frequency pentode)	140
6N1P (twin triode with separate cathodes)	142
6N2P (twin triode with separate cathodes)	144
6N3P (twin triode with separate cathodes)	146
6N5P (twin triode with separate cathodes)	149
6N6P (twin triode with separate cathodes)	153
6N7S (twin triode with common cathode)	155
6N8S (twin triode with separate cathodes)	158
6N9S (twin triode with separate cathodes)	163
6N14P (twin triode with separate cathodes)	167
6N15P (radio-frequency twin triode with common cathode)	169
6P1P (output beam power triode)	172
6P3S (output beam power tetrode)	175
6P6S (output beam power tetrode)	182

Card 5/14

Reference Book (Cont.)

SOV/3735

6P7S (output beam power tetrode)	186
6P9 (wide-band output power pentode)	188
6P13S (output beam power tetrode)	194
6P14P (output beam power tetrode)	196
6P15P (wide-band output beam power tetrode)	199
6S1P (triode)	200
6S2P (triode)	203
6S2S (triode)	204
6S3B (triode)	207
6S3P (low-hum radio-frequency triode)	209
6S5S (triode)	210
6S6B (triode)	214
6S7B (triode)	216
6P1P (triode-pentode)	218
6Kn2P (twin diode with separate cathodes)	221
6Kn6S (twin diode with separate cathodes)	223
6Kn7B (twin diode)	226
6Ts4P (full-wave high-voltage rectifier)	227
6Ts5S (full-wave high-voltage rectifier)	229
6Ts10P (full-wave high-voltage rectifier)	231

Card 6/14

Reference Book (Cont.)

SOV/3735

6E5P (radio-frequency tetrode)	232
Oscillator Tubes	
G-807 (oscillator beam tetrode)	235
GU-13 (oscillator beam tetrode)	237
GU-15 (oscillator beam tetrode)	239
GU-29 (oscillator beam twin tetrode)	241
GU-32 (oscillator beam twin tetrode)	243
GU-50 (oscillator beam tetrode)	245
GU-80 (oscillator pentode)	248
Oscilloscope Tubes and Television Picture Tubes	
5L038 (cathode-ray tube)	250
8L029 (cathode-ray tube)	252
10LK2B (projector kinescope)	254
13L036 (cathode-ray tube with luminance delay)	255
13L037 (cathode-ray tube)	258
18LK2B (kinescope)	260
18LK5B (kinescope with ion trap)	262
23LK2B (kinescope)	263

Card 7/14

Reference Book (Cont.)

SOV/3735

31LK2B (kinescope with ion trap)	265
35LK2B (kinescope with rectangular screen)	266
40LK1B (kinescope with round screen)	268
43LK2B (kinescope with rectangular screen)	269
43LK3B (kinescope with rectangular screen)	271
53LK2B (kinescope with rectangular screen)	272
53LK3B (kinescope with rectangular screen)	273
Voltage Regulators	
SG1P	275
SG2P	276
SG2S	277
SG3S	278
SG4S	279
SG5B	280
Barretters	281
Silicon Diodes	
DK-V1 (receiving diode)	283
Card 8/14	

Reference Book (Cont.)

SOV/3735

DK-V2 (receiving diode with increased sensitivity)	283
DK-V3 (receiving diode)	284
DK-V4 (receiving diode with increased sensitivity)	285
DK-V5 (low-resistance receiving diode)	285
DK-V6 (high-resistance receiving diode)	286
DK-V7 (receiving diode)	287
DK-I1 (measuring diode)	287
DK-I2 (measuring diode)	288
DK-S1 (mixer diode)	288
DK-S2 (mixer diode with increased sensitivity)	289
DK-S3 (mixer diode)	290
Germanium Mixer Diodes	
DG-S1 (mixer diode)	291
DG-S2 (mixer diode of increased sensitivity)	292
DG-S3 (mixer diode)	293
DG-S4 (mixer diode of increased sensitivity)	293
DGTs Type Point-Contact Germanium Diodes	
DG-Ts1	294

Card 9/14

Reference Book (Cont.)

30V/3735

DG-Ts2	295
DG-Ts4	296
DG-Ts5	296
DG-Ts6	297
DG-Ts7	297
DG-Ts8	298
DG-Ts12	298
DG-Ts13	299
DG-Ts14	299

D2 Type Point-Contact Germanium Rectifier Diodes

D2A	300
D2B	300
D2V	301
D2G	301
D2D	301
D2Ye	302
D2Zh	302

Card 10/14

Reference Book (Cont.)

SOV/3735

Junction Germanium Diodes for Rectifying Alternating Current

DG-Ts21.D7A	303
DG-Ts22.D7B	304
DG-Ts23.D7V	304
DG-Ts24.D7G	304
DG-Ts25.D7D	305
DG-Ts26.D7Ye	305
DG-Ts27.D7Zh	305

Point-Contact Germanium Triodes

S1A.S3A	306
S1B.S3B	307
S1V.S3V	308
S1G.S3G	308
S1D.S3D	309
S1Ye.S3Ye	310
S2A.S4A	311
S2B.S4B	311
S2V.S4V	312
S2G.S4G	313

Card 11/14

Reference Book (Cont.)

SOV/3735

P1 Type Junction Germanium Voltage-Amplifier Triodes

P1A	314
P1B	315
P1V	316
P1G	316
P1D	317
P1Ye	318
P1Zh	319
P1I	319

P2 Type Junction Germanium Audio-Power-Amplifier Triodes

P2A	321
P2B	321

P3 Type Junction Germanium Audio-Power Amplifier Triodes

P3A	323
P3B	323
P3V	324

P4 Type Junction Germanium Audio-Power-Amplifier Triodes

Card 12/14

Reference Book (Cont.)

SOV/3735

Audio-Power Amplifier Triodes

P4A	325
P4B	326
P4V	327
P4G	328
P4D	328

P5 Type Junction Germanium Voltage-Amplifier Triodes

P5A	329
P5B	330
P5V	331
P5G	331
P5D	332

P6 Type Junction Germanium Voltage-Amplifier Triodes

P6A	333
P6B	334
P6V	335
P6G	336
P6D	337

Card 13/14

Reference Book (Cont.)

SOV/3735

P7 Type Junction Germanium Triode	338
P13 Type Junction Germanium Triodes	
P13	339
P13A	340
P13B	340
P14 Type Junction Germanium Triode	341
P15 Type Junction Germanium Triode	341

AVAILABLE: Library of Congress

Card 14/14

JP/jb
6-9-60

YURA, R., kand.istor.nauk

Let's survey an ancient town. Znan. ta pratsia no. 12:18-19 D '60.
(MIRA 14:4)

(Voinskaya greblya—Antiquities)

SHOVKOPLYAS, I.G. [Shovkopliias, I.H.]; YURA, R.O. [Iura, R.O.]

"When and how Kiev was founded" by M. IU. Eraicheva'kyi.
Reviewed by I.H. Shovkopliias, R.O. Iura. Dop. AN URSR no.3:
418-420 '64. (MIRA 17:5)

L 8001-66

ACC NR: AT5027854

SOURCE CODE: CZ/2503/63

AUTHOR: Jura, S. - Jura, S.

ORG: Research Institute of Mathematical Machines, Prague (Výzkumný ústav matematických strojů)

TITLE: Electrostatic start-stop systems of tape transport

SOURCE: Československá akademie věd. Vyzkumný ústav matematických strojů. Zprávy o výzkumu, no. 11, 1965, 85-106

TOPIC TAGS: magnetic tape, punched paper tape, tape transport, electrostatics

ABSTRACT: This paper is a continuation of the author's work published earlier (Strojník Stroje na zpracování informací, 1964) and discusses the principle of electrostatic start-stop systems and brakes for both punched and magnetic tapes. The paper describes a start-stop system (USA patent 3,057,529 Tape transport apparatus, October 1962, Vol. 783, Number 2, p. 420) as well as an application is drawn to the advantageous utilization of the electrostatic force. It presents a derivation of relations for the acceleration of the tape during starting or stopping, on the basis of which the starting and stopping

Card 1/2

L 0291-66

ACC NR: AT5027854

determined. He discusses also controlled supply sources for these items. The article concludes with a discussion of the various benefits, a list of advantages and shortcomings of the existing devices, and 15 figures.

SUB CODE: EE, IE, DP / SUBM DATE: 16Dec63

Card 2/2

KUTIL, I.; KURACHKA, F.; SHIMEK, I.

Use of polyelectrolytes for the recovery of gold from waste waters.
Zhur.prikl.khim. 34 no.11:2430-2435 N '61. (MIRA 15:1)

1. Gosudarstvennyy institut blagorodnykh metallov, Praga i
Issledovatel'skiy institut sinteticheskikh smol i lakov, Pardubitse.
(Waste products) (Gold)

KALABUKHOV, N.P.; YURACHKOVSKIY, P.A.

Ultraviolet absorption spectra of X-rayed KCl crystals. Opt.
i spektr. 7 no.4:523-524 Ap '62. (MIRA 15:5)
(Potassium chloride crystals) (X rays)
(Spectrum, Ultraviolet)

L 19477-63 EWT(1)/BDS AFFTC/ASD/IJP(C)

ACCESSION NR: AT3002219

S/2941/63/001/000/0190/0193

X B

AUTHORS: Kalabukhov, N. P.; Yurachkovskiy, P. A.

TITLE: Effect of hardening on absorption spectra of x-rayed KCl crystals

SOURCE: Optika i spektroskopiya; sbornik statey. v. 1: Lyuminestsentsiya. Moscow, Izd-vo AN SSSR, 1963, 190-193

TOPIC TAGS: temperature hardening, absorption spectra, coloration, V-band

ABSTRACT: The authors have traced the effects of hardening on the absorption spectra after x-ray excitation. They also studied the characteristics of the resulting photochemical transformations in color centers. It is shown that in addition to the enhancement in coloration intensity, x-ray excitation entails a change in the V-absorption band. On the hardened crystal the V_2 -band ($\lambda_m = 232\mu$) shows a much sharper resolution than the V_3 -band ($\lambda_m = 215\mu$). The authors contend that this phenomenon could be explained qualitatively by the Varli model for V-centers (Dzh. Varli. Sb. Tsentry* okraski, IL, M., 305, 1958). According to the Varli assumption the V_2 - and V_3 - centers are formed by the double ionization of the negative halogen ions. Furthermore, it is shown that the number of V-

Card 1/2

L 19477-63

ACCESSION NR: AT3002219

centers compared to the quantity of F-centers, created by x-rays or F-irradiation of the x-rayed crystal, are less in the hardened KCl crystals (quenched in water after heating to 500 below melting point) than in the specimen prepared by slow cooling (0.7C per min. in the furnace). In the irradiation process with light in the F-band the increase of R-bands is more strongly apparent in the hardened crystal. Orig. art. has: 3 figures.

ASSOCIATION: none

SUBMITTED: 09Apr62

DATE ACQ: 19May63

ENCL: 00

SUB CODE: PH

NO REF SOV: 001

OTHER: 003

Card 2/2

BOGDANOVICH, A.S.; SIKORSKIY, Yu.A.; YURACHKOVSKIY, P.A.

Effect of thermal treatment and plastic deformation on the dielectric losses of $KCl \cdot CaCl_2$ crystals. Fiz. tver. tela 5 no.12:3524-3528 D '63.
(MIRA 17:2)

1. Kiyevskiy politekhnicheskiy institut.

YURACHKOVSKIY, V.K.

More about the technical, industrial, and financial plan of a
sugar factory. Sakh.prom. 34 no.7:49 J1 '60. (MIRA 13:7)

1. Khmel'nitskiy sakhsvetlotrest.
(Sugar industry)

24.7000

24.3439

37223
S/051/62/012/004/010/015
E039/E485

AUTHORS: Kalabukhov, N.P., Yurachkovskiy, P.A.

TITLE: On the ultraviolet absorption of X-rayed KCl crystals

PERIODICAL: Optika i spektroskopiya, v.12, no.4, 1962, 523-524

TEXT: Samples prepared from specially purified crystals of KCl and X-rayed at room temperature for 1 hour (50 kV, 9 mA, copper anode) were used for this investigation. Absorption spectra were also measured at room temperature of a CФ-4 (SF-4) type spectrophotometer. The characteristic V_3 (218 mmk) band was observed and a relatively weak band with a maximum at about 260 mmk. There is also a strong F band at about 550 mmk and a weak M band at about 830 mmk. The absence of the V_2 bands was unexpected and is usually characteristic of crystals containing a significant concentration of Ca, Sr or Ba. It is not thought that the 260 mmk band depends on any new type of V-centre. The experiments of Dorendorf showed that for X-rayed crystals of KCl there is a V_4 absorption band with a maximum at about 255 mmk at -180°C. Calculations on the possible temperature displacement of the absorption bands show that the 260 mmk band

Card 1/2

On the ultraviolet ...

S/051/62/012/004/010/015
E039/E485

observed at room temperature is not the same as the V_4 band and is stable in sufficiently pure crystals not containing V_2 -centres. Varley's model for V-centres agrees well with the simultaneous occurrence of V_3 and V_4 -centres. The V_3 -centre is a neutral halide atom substituted for an alkali metal ion, which is displaced from its normal position at the internode forming a V_4 -centre. There is 1 figure. ✓

SUBMITTED: August 24, 1961

Card 2/2

L 15566-66 SWP(d)/EWK(1)/EFF(n)-1/1 IUP(0) JA 1/1

ACC NR: AF3304406

AUTHOR: Yurachkovskiy, E. A., Kitenko, E. I.

DR: none

TITLE: Effect of temperature on the formation of F_2 -centers

SOURCE: Zhurnal fizicheskoy khimii, Vol. 44, No. 1, 1970, p. 100-101

TOPIC TAGS: potassium chloride, calcium chloride, low temperature effect

ABSTRACT: KCl-CaCl₂ crystals were irradiated with UV light for F_2 -centers. The crystals were grown from solutions of pure salts. The salt contained traces of impurities. The crystals were irradiated in sodium vapor at 2200 K. The absorption spectra were measured. The formation of F_2 -centers was studied. It was noted in darkness that the absorption spectrum of the crystal was a pure F_2 -center with a small amount of F_2 -center. The absorption spectra were measured at different temperatures. The absorption spectra were measured at different temperatures. The absorption spectra were measured at different temperatures.

Card 1/3

2

UDC: 535.34 : 548.0

APPROVED FOR RELEASE: 03/15/2001

2 19900000

ACC NR: AP6000006

specimen was irradiated simultaneously with F₁ and F₂ bands at 210°K. A weak Z₁-band is formed at 210°K even with simultaneous irradiation by F₁-light. However, F₁-irradiation alone does not form a Z₁-band. This shows that the Z₁-band is formed with considerable efficiency at temperatures above 250°K. Curves for absorption of the function of temperature for the case of F-irradiation show that the peak for the Z₁-band decreases at 210°K.

Page 2/4

L 15566-66

ACC NR: AP6004406

This document contains information that is classified as secret and is intended for the eyes of authorized personnel only. It is to be controlled and its distribution is to be limited to those personnel who have a valid need to know. It is to be stored in a secure location and its use is to be restricted to the purposes for which it was prepared. It is to be destroyed when it is no longer needed and its destruction is to be reported to the appropriate authority.

SECRET - SECURITY INFORMATION - UNCLASSIFIED

Card 3/3

L 45587-66 EWT(m)/T/ENP(t)/ETI IJP(c) JD/JG
ACC NR: AP6028714

SOURCE CODE: UR/0185/66/011/008/0917/0918

AUTHOR: Bohdanovych, A. S.; Ivzhenko, M. A.; Koval'ov, V. K.; Sykors'kyi, Yu. A.;
Yurachkiv's'kyi, P. O.; Bryhynets', V. P.

ORG: Kiev Polytechnical Institute (Kyyivs'kyi politekhnichnyi instytut)

40
39
B

TITLE: Dislocations and V-centers in KCl crystals

SOURCE: Ukrayins'kyi fizychnyy zhurnal, v. 11, no. 8, 1966, 917-918

TOPIC TAGS: potassium chloride, crystal lattice dislocation, x-ray coloring, color center, crystal absorption spectrum

ABSTRACT: This article endeavors to explain the role of dislocations in creating V-centers in KCl crystals subjected to x-rays at room temperatures. Four crystals of "pure" KCl grown from a melt by the Kyropoulos method (two each with dislocation density of $5 \cdot 10^6$ and $5 \cdot 10^4 \text{ cm}^{-2}$) were colored by x-rays at room temperature and their absorption spectra were then photospectrometrically measured. Comparison of graphs plotted from the results of "hard" and "soft" coloring showed that (1), other coloring conditions being equal, the crystals with more dislocations chiefly formed V_3 -centers (218 m μ), while those with fewer dislocations gave only V_2 -centers (230 m μ), and (2) the spectral makeup of V-absorption does not

Card 1/2

L 45587-66

ACC NR: AP6028714

depend on "hardness" of crystal coloration, not only refuting the view that "hard" and "soft" x-rays create V₃- and V₂-centers, respectively, but also suggesting that V₃-centers are defects formed either in or near the dislocations themselves, while V₂-centers form in the lattice far from them and require lattice vacancies. Further studies showed that the preceding assumption is true and that the V₂- to V₃-center ratio is stipulated by dislocation density and the number of "frozen" thermal vacancies in the crystal. In conclusion the authors thank Prof. M. P. Kalabukhov for interest in the work and useful discussions. Orig. art. has: 2 figures. [26]

SUB CODE: 20/ SUBM DATE: 05Mar66/ ORIG REF: 002/ OTH REF: 007 / ATD PRESS: 5082

Card

2/2

pla

YURAGHKOVSKIY, V.K.

Planning and accounting of labor productivity in the sugar industry.
Sakh.prom. 35 no.7:58-59 JI '61. (MIRA 14:7)

1. Khmel'nitskiy sakharotrest.
(Labor productivity) (Sugar industry)

CZECHOSLOVAKIA/Organic Chemistry. Synthetic Organic Chemistry. G-2

Abs Jour: Ref Zhur-Khim., No 24, 1958, 81508.

Author : Yuracka F., Zvonar V.

Inst :

Title : Synthesis of Organic Peroxides.

Orig Pub: Chem. prumysl. 1957, 7, No 4, 192.

Abstract: It is possible to have explosions during the preparation of peroxides according to Zwakha's method (Ref. Zhur-Khimiya, 1958, 61842). The danger of explosion can be eliminated by adding dimethyl-dibutyl phthalate (I) or tricresyl phosphate to the reaction mixture. Thus, a phlegmatized peroxide is obtained in liquid form or as a paste, which is used in polymerizations; for instance a 50% solution of $\text{CH}_3\text{COCCOC}_6\text{H}_5$ or the peroxide

Card : 1/2

CZECHOSLOVAKIA/Organic Chemistry. Synthetic Organic Chemistry. G-2

Abs Jour: Ref Zhur-Khim., No 24, 1958, 81508.

of methylethyl ketone in I, a 66% paste of the
peroxide bis (1-oxycyclohexyl) in I.

Card : 2/2

YURAN, V.

Transforming of conjugate projections and their application for the mechanization of the designing of the axonometric and perspective representations of objects. In Russian.

P. 191. (ZINATNISKIE RAKST. UCHENYE ZAPISKE) (Riga, Latvia) Vol. 10, 1957

SO: Monthly Index of East European Accession (EEAI) LC Vol. 7, No. 5, 1958

SOV/44-58-4-3200

Translation from: Referativnyy zhurnal, Matematika, 1958,
Nr 4, p 121 (USSR)

AUTHOR: Yuran, V. Yu.

TITLE: A Transformation of Conjugate Projections and Their
Application for the Mechanization of Construction of
Axonometric and Perspective Representations of Objects
(Preobrazovaniye sopryazhennykh proyektsey i ikh
primeneniye dlya mekhanizatsii postroyeniya aksonometri-
cheskikh i perspektivnykh izobrazheniy ob"yektov)

PERIODICAL: Zinatn. raksti. Latv. univ., Uch. zap. Latv. un-ta,
1957, Nr 10, pp 191-214

ABSTRACT: The work is divided into two parts. In the first part a
study is made of two methods of transforming conjugate projections
The combination of a perspective and orthogonal projection of
objects on the projecting plane is called a conjugate projection.

Card 1/2

SOV/44-58-4-3200

A Transformation of Conjugate Projections (Cont.)

Such a transformation simplifies the solution both for position and metric problems. The second part deals with a method of supplementary projection. It is applied in the solution of problems on intersection. Its essence is the fact that given objects are projected in a parallel manner on the projecting plane in such a direction that a parallel projection of the unknown elements is obtained, and then their conjugate projections. In the second part are given the geometric foundations and kinematic scheme of a device (axo-perspective-graph) by means of which are constructed perspective and axonometric representations of objects by their orthogonal projections and projections with numerical references. The construction of the device is based on a simple system of constructing visual representations derived on the basis of conjugate projections. Constructions of perspectives on vertical and inclined planes and also special forms of oblique and orthogonal axonometry are examined.

V.N. Zhuravleva

Card 2/2

YURAN, V. Yu. Cand Tech Sci -- (diss) "Transformation of ^{conjugated} ~~orthogonal~~ projections
and their utilization for the mechanization of construction of perspective
and axonometric ^{representations} ~~pictures~~ of objects." Len, 1958. 12 pp with ^{drawings} ~~diagrams~~
(Min of Higher Education USSR. Len Order of Labor Red Banner Construction
Engineering Inst), 150 copies (KL, 52-58, 104)

YURANEK, Yu. [Juraneck, J.]

Test operations in Czechoslovakia using a moving inter-
reservoir combustion source. Neft. khoz. 43 no.2:74-75 (MIRA 18:4)
F '65.

YURANOV, A. P.

A manual on swine diseases, 1st and 2nd editions. (?1920's or 1930's or later)

Is used as a current (1947) textbook for veterinary and zootechnical specialists as well as for directors of state farms (sovkhozes), presidents of agricultural artels, and others.

Veterinariya, Vol. 24, No. 12, Dec 1947 pp 13-15

YURAEV, A.P.

Viroscopic examination in foot-and-mouth disease in cattle.
Veterinaria 35 no.10:69-71 O '58. (MIRA 11:10)

1. Institut epidemiologii i mikrobiologii imeni Gamaleya.
(Foot-and-mouth disease) (Microscopy--Technique)

153-58-1-6/29

AUTHORS: Komissarova, L. N., Plyushchev, V. Ye., Yuranova, L. I.

TITLE: An Investigation of the Thermal Stability of Zirconium-Sulfate-Tetrahydrate (Izucheniye termicheskoy ustoychivosti tetragidrata sul'fata tsirkoniya)

PERIODICAL: Izvestiya vysshikh uchebnykh zavedeniy. Khimiya i khimicheskaya tekhnologiya, 1958, Nr 1, pp. 37 -42 (USSR)

ABSTRACT: The above-mentioned sulfate-tetrahydrate is of great importance amongst the other zirconium-sulfates. Its method of production is given and the crystalline form is mentioned from publications (Reference 1). A survey of the publications on the problem referred to in the title, is given. Details on the condition of the material used for the tests and on the methods applied, are given in the experimental part. The results are summarized in tables 1 and 2. A thermogram covering the range between 20°C and 1100°C is given in figure 1. It shows 3 clear endothermic effects: the two first one between 130° and 215°C, which correspond to the separation of the water of crystallization; the 3rd effect (700 to 740°C) characterizes a complete decay of the sulfate with the separation of SO₃.

Card 1/3

An Investigation of the Thermal Stability of Zirconium-Sulfate-Tetrahydrate
153-58-1-6/29

(Figure 2). This figure shows the curve of the change of weight of the tetrahydrate which confirms and accurately defines the destructive character of this salt. The results of investigation of the dehydration- and decomposition- processes obtained by the methods described here, are compared in table 3.

Conclusions: 1) The last mentioned processes of dehydration and decomposition of zirconium-sulfate-tetrahydrate were investigated by means of a) Heating in air up to the attaining of a constant weight at various temperatures, b) Pyrometer by N. S. Kurnakov, and c) a continuous balance. 2) According to the velocity of heating, the dehydration of the tetrahydrate takes place either in 2 or 3 stages. In all cases, 3 water molecules within the range of 100 to 160°C are cracked at a time. One water molecule, on the other hand, is retained more vigorously and escapes slowly at graduate heating; at 190° to 215°C half of the quantity of the water gets lost up to the complete dehydration taking place at 300 to 340°C. 3) The decomposition of the zirconium sulfate is accompanied

Card 2/3

An Investigation of the Thermal Stability of Zirconium-Sulfate-Tetrahydrate
153-58-1-6/29

by an escape of SO_3 and is gradually completed between 450 to 800°C. 4) The special solidity of the bond of water molecule points to the fact that the properties of tetrahydrate are more correctly expressed by the coordination-formula $H_2ZrO(SO_4)_2 \cdot 3H_2O$. There are 2 figures, 3 tables, and 8 references, 6 of which are Soviet.

ASSOCIATION: Moskovskiy institut tonkoy khimicheskoy tekhnologii im. M. V. Lomonosova. Kafedra tekhnologii redkikh i rasseyannykh elementov (Moscow Institute for Fine Chemical Technology imeni M. V. Lomonosov, Professorial Chair for Rare and Dispersed Elements)

SUBMITTED: September 16, 1957

Card 3/3

89961

S/063/60/005/003/005/011/XX

A051/A029

5. 2200 1043, 1273, 1228

AUTHORS: Yuranova, L.I., Komissarova, L.N., Plyushchev, V.Ye.

TITLE: On the Formation of Hexahydrates of Zirconium and Hafnium Oxynitrates

PERIODICAL: Zhurnal Vsesoyuznogo Khimicheskogo Obshchestva im. D.I. Mendeleeva, 1960, Vol. 5, No. 3, p. 346

TEXT: The authors recently conducted a study on a new method for synthesizing $ZrO(NO_3)_2 \cdot 2H_2O$ and a similar compound of Hafnium, i.e., the dihydrates of zirconium and hafnium oxynitrates. It is possible to obtain individual zirconium and hafnium oxynitrates free of admixtures of any other nitrates. The results could be successfully reproduced several times. Numerous experiments showed that both substances crystallize in a wide range of HNO_3 concentrations and of the zirconium and hafnium concentration, as well as under various temperature conditions. While studying the system

Card 1/4

89961

S/063/60/005/003/005/011/XX
A051/A029On the Formation of Hexahydrates of Zirconium and Hafnium Oxynitrates X

$ZrO_2 \cdot N_2O_5 \cdot H_2O$ at $25^\circ C$ by the physico-chemical method of analysis, the existence of another compound was established, viz., the hexahydrate of zirconium oxynitrate with the composition: $ZrO(NO_3)_2 \cdot 6H_2O$. The compound crystallizes from solutions containing from 21.35 weight % ZrO_2 and 1.93 weight % of N_2O_5 to 4.50 weight % of ZrO_2 and 40.00 weight % of N_2O_5 . The hexahydrate of hafnium oxynitrate can be formed in the same way. The formation of the latter two compounds also takes place when a small excess of $ZrO(NO_3)_2 \cdot 2H_2O$ and $HfO(NO_3)_2 \cdot 2H_2O$ is introduced into a saturated solution of these compounds, or by mixing the dihydrate of zirconium and hafnium oxynitrates with a given amount of water, which is insufficient for the complete dissolution of the initial salts (the molecular ratio of the water and the dihydrates changed from 2:1 to 8:1). In the first case, the crystallization of the hexahydrates, carried out in glass containers for studying the solubility, continued for 8-10 hours in the entire volume of the solution, so that a completely solidified mass was obtained, which was

Card 2/4

89961

S/063/60/005/003/005/011/IX
A051/A029

On the Formation of Hexahydrates of Zirconium and Hafnium Oxynitrates

difficult to crush and which resembled magnesium cement. In the second case mixtures were obtained in the form of a gruel, which after a certain time hardened into a non-transparent, white, enamel-like mass. The obtained preparations were thoroughly ground, dried in air to a constant weight and were analyzed for MeO_2 , N_2O_5 , and H_2O content. The MeO_2 content was determined by calcinating the corresponding hydrates to MeO_2 at 900°C . The Devard method was used for determining N_2O_5 . The amount of water was calculated from the difference. The results of the analysis are given in the table and represent the average values of 5 determinations. It is pointed out that in repeated experiments the results were systematically and favorably reproduced. Thus, the composition of the obtained compounds is expressed by: $\text{ZrO}(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$ and $\text{HfO}(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$. X-ray findings were also obtained, which confirmed the formation of new phases. The hexahydrates were found to be well soluble in water and stable in air. Their densities at 20°C were estimated pycnographically and found to be 2.08 ± 0.02 and 2.66 ± 0.02 , respectively. There is 1 table and 3 non-Soviet references. ✓

Card 3/4

89961

S/053/60/005/003/005/011/XX
A051/A029

On the Formation of Hexahydrates of Zirconium and Hafnium Oxynitrates

ASSOCIATION: Moskovskiy institut tonkoy khimicheskoy tekhnologii im.
M.V. Lomonosova (Moscow Institute of Fine Technology, im.
M.V. Lomonosov)

SUBMITTED: December 29, 1959

Tables:

Preparation	Content, weight %			Molar ratio $\text{MeO}_2:\text{N}_2\text{O}_5:\text{H}_2\text{O}$
	MeO_2	N_2O_5	H_2O	
zirconium nitrate	36.30	31.85	31.85	1.0:1.02:6.1
hafnium nitrate	50.00	25.11	24.89	1.0:0.98:5.9

Card 4/4

S/020/61/136/002/020/034
B016/B060

AUTHORS: Komissarova, L. N., Yuranova, L. I., and Plyushchev, V. Ye.

TITLE: Synthesis and Thermal Stability of Dihydrates of Oxy-nitrates of Zirconium and Hafnium

PERIODICAL: Doklady Akademii nauk SSSR, 1961, Vol. 136, No. 2, pp. 350-353

TEXT: A study has been made of the synthesis of zirconium and hafnium oxy-nitrate dihydrates and their thermal stability. While data available in the literature on the former dihydrate are insufficient and contradictory, the latter is as yet undescribed. Zirconium (hafnium-) oxy-chloride octohydrate, which contains a constant amount of crystal water, has proved to be the only usable initial substance for the synthesis of these compounds. A weighed-in portion of these salts was treated with 100% HNO_3 ($\text{MeO}_2 : \text{HNO}_2 = 1 : 3$ to $1 : 6$). $1 : 4.5$ was found as the optimum ratio. Air was blown through the solutions until the yellow color disappeared, and at 60°C they were vaporized. On the basis of the analysis,

Card 1/2

Synthesis and Thermal Stability of Dihydrates
of Oxy-nitrates of Zirconium and Hafnium

S/020/61/136/002/020/034
B016/B060

the following formulas are ascribed to the compounds synthesized:
 $ZrO(NO_3)_2 \cdot 2H_2O$ and $HfO(NO_3)_2 \cdot 2H_2O$. They are white crystalline substances.

The data obtained for equilibrium displayed certain differences between the zirconium and hafnium compounds regarding the stability and decomposition on heat treatment. They are, however, both thermally unstable and decompose completely at 400°C, when monoclinic ZrO_2 results from

zirconium oxy-nitrate dihydrate with a 54.1% loss of weight. The hafnium compound displays a greater thermal stability, especially the monohydrate forming in between. Both substances decompose stepwise (the stages are less marked in the zirconium compound). There are 2 figures, 2 tables, and 9 non-Soviet references: 3 French, 1 British, and 4 German.

ASSOCIATION: Moskovskiy institut tonkoy khimicheskoy tekhnologii im. M. V. Lomonosova (Moscow Institute of Fine Chemical Technology imeni M. V. Lomonosov)

PRESENTED: June 24, 1960, by V. I. Spitsyn, Academician

SUBMITTED: June 22, 1960

Card 2/2

29018

5.2100

S/O20/61/140/004/019/023
B106/B110

AUTHORS: Yuranova, L. I., Komissarova, L. N., and Plyushchev, V. Ye.

TITLE: New data on the behavior of zirconium and hafnium oxynitrates in aqueous solutions and organic solvents

PERIODICAL: Akademiya nauk SSSR. Doklady, v. 140, no. 4, 1961, 855-858

TEXT: Almost all studies described in the literature with regard to the chemistry of zirconium nitrate solutions concerned microquantities of zirconium and highly diluted solutions (Ref. 3: V. I. Paramonova, ZhNKh, 1, 1905 (1956); Refs. 4-6, see below). In practice, the behavior of zirconium and hafnium oxynitrates in more concentrated solutions is interesting, particularly when studying extraction methods for separating zirconium from hafnium. Therefore, the authors investigated the dependence of pH value, specific electrical conductivity, density, and viscosity of zirconium and hafnium oxynitrate solutions on the concentrations of these compound in aqueous solutions. Moreover, the solubility of oxynitrates in organic solvents was studied. The compounds $ZrO(NO_3)_2 \cdot 2H_2O$, $ZrO(NO_3)_2 \cdot 6H_2O$, and $HfO(NO_3)_2 \cdot 2H_2O$, $HfO(NO_3)_2 \cdot 6H_2O$ were

Card 1/82

X

29018

S/020/61/140/004/019/023

B106/B110

New data on the behavior of ...

tested. Figs. 1 and 2 show results obtained for pH value and specific electrical conductivity of aqueous solutions of these compounds. Since the hydrolysis of oxynitrates decreases with increasing concentration, the decrease of the pH value is only due to the increasing absolute quantity of dissolved salts. Hydrolysis of zirconium and hafnium oxynitrates in aqueous solutions was found to depend on time. The state of equilibrium is attained only two weeks after the solutions have been prepared. A rise in temperature effects stronger hydrolysis. As expected, oxynitrates of hafnium proved to be stronger bases than those of zirconium. The density and viscosity values measured for aqueous solutions of the

oxynitrates concerned are shown in Figs. 3 and 4. 15 organic compounds of different classes were selected to study the solubility of zirconium and hafnium oxynitrates in organic solvents. Measurements were made at 20 and 30°C; temperature fluctuations were $\pm 0.1^\circ$. In all cases, solution equilibrium was established only after a week. Results are shown in Table 5. It is evident that zirconium and hafnium oxynitrates dissolve only slightly, or not at all, in slightly polar or nonpolar organic solvents. The compounds studied are insoluble in acetophenone, dibutyl and benzyl ethers, chloroform, carbon tetrachloride, and dichloro ethane. The solubility of oxynitrates decreases with increasing chain length and

Card 2/8₃

29018-

S/020/61/140/004/019/023
B106/B110

New data on the behavior of ...

branching of the saturated alcohols used as solvents. Under equal conditions, oxynitrates of zirconium are better soluble in organic solvents than those of hafnium. There are 4 figures, 5 tables, and 7 references: 4 Soviet and 3 non-Soviet. The three references to English-language publications read as follows: Ref. 4: B. Lister, L. McDonald, J. Chem. Soc., 1952, 4315; Ref. 5: R. Connick, W. McVey, J. Am. Chem. Soc., 71, 3182 (1949); Ref. 6: R. Connick, N. McVey, J. Am. Chem. Soc., 73, 1171 (1951).

ASSOCIATION: Moskovskiy institut tonkoy khimicheskoy tekhnologii im. M. V. Lomonosova (Moscow Institute of Fine Chemical Technology imeni M. V. Lomonosov)

PRESENTED: April 25, 1961, by V. I. Spitsyn, Academician

SUBMITTED: April 22, 1961

Card 3/83

YURANOVA, L.I.; KOMISSAROVA, L.N.; PLYUSHCHEV, V.Ye.

Solubility and thermal stability of zirconium and hafnium
oxynitrates hexahydrates. Zhur.neorg.khim. 7 no.5:1062-1067
My '62. (MIRA 15:7)

1. Moskovskiy institut tonkoy khimicheskoy tekhnologii imeni
Lomonosova.

(Zirconium nitrate) (Hafnium nitrate)

PLYUSHCHEV, V.Ye.; YURANOVA, L.I.; KOMISSAROVA, L.N.

Basic oxynitrates of zirconium and hafnium. Zhur. neorg. khim.
10 no.3:643-646 Mr '65. (MIRA 18:7)

KHARITONOV, Yu.Ya.; YURANOVA, L.I.; PLYUSHCHEV, V.Ye.; PERVYKH, V.G.

Infrared absorption spectra of zirconium (IV) and hafnium (IV) nitrate compounds. Zhur.neorg.khim. 10 no.4:741-744 Ap '65.

(MIRA 18:6)

1. Institut obshchey i neorganicheskoy khimii AN SSSR imeni Kurnakova i Moskovskiy institut tonkoy khimicheskoy tekhnologii imeni Lomonosova.

YURAS, I. A.

USSR/Medicine - Virus Diseases, Influenza

Mar 53

"Etiology and Laboratory Diagnosis of Influenza," A. A. Smorodintsev, N. S. Klyachko, T. Ya. Luzyanina, M. A. Merozenko, Ye. S. Shikina, I. A. Yuras, V. P. Korotkova, Div of Virology, Inst of Exptl Med, Acad Med Sci USSR; Inst of Epidemiol imeni Pasteur

"Zhur Mikrobiol, Epidemiol, i Immunobiol" No 3, pp 69-78

At present, the subtype A₁ predominates in the USSR. The antigenic structure of A₁ isolated during the past few years is polymorphic: it is necessary to supplement cross-neutralization by cross-adsorption of antibodies according to a new method developed by the authors. Smorodintsev's rapid method of diagnosing influenza by the reaction of complement fixation is effective in 50% of the cases on sputum examined during the first week after infection; it is less effective on serum. The reaction of hemagglutination is effective in 40% of the cases when carried out under proper conditions with the use of human erythrocytes of the O group. It is necessary to produce and supply diagnostic preparations [literally "Diagnostica"] equally suitable for hemagglutination and complement fixation (dry A, A₁, and B influenza horse sera suitable for both hemagglutination and complement fixation; to supply from a central point through donor stations, human O-erythrocytes.

PA 244744

STRADYN', Ya. [Stadyn, J.]; YURASHEK, A. [Jurasek, A.]; REYKHMANNIS, G.
[Reihmanis, G.]

Polarographic behavior of 5-substituted furfuryl thiocyanates.
Zhur. ob. khim. 35 no.5:768-773 My '65. (MIRA 18:6)

1. Institut organicheskogo sinteze AN Latvyskoy SSR i Slovatskiy
politekhnicheskiy institut, khimicheskii fakul'tet, Chexoslovatskaya
SSR, Bratislava.

10

The hydrogenation of unsaturated compounds. N. K. Verzhbitskii, *J. Gen. Chem.* (U. S. S. R.) 3, 1058 (1932).—When mixts. of olefin deriva. are catalytically hydrogenated, it is not always true that the component with the greatest no. of H atoms attached to the doubly linked carbons hydrogenates first, to the exclusion of the other components. A higher energy content (heat of combustion) also favors hydrogenation. *Mixts. studied.*—Benzoylbenzene(I)—stilbene (II): simultaneous absorption of H, a little more rapidly by I. I—Na cinnamate (III): at 50% complete hydrogenation, I was 70% hydrogenated, III 30%. III—maleic acid (IV): IV begins to absorb H only after the reaction with III is complete. IV—fumaric acid (V): V hydrogenates first, but IV begins to take up H before the reaction with V is complete. IV—allyl ac. (VI), III—VI: in both pairs VI reacts completely before the other component begins. II—VI: simultaneous absorption of H. Limonene—III: III is hydrogenated first. IV—Me₂C=CHMe (VII): IV hydrogenates first, then VII. III—Me cinnamate (VIII), cinnamic acid—VIII: VIII hydrogenates first. *Expd.*—Hydrogenation was carried out according to the directions of Ginsberg and Ivanov (C. A. 25, 4173). One g. Ni, 0.1 g. PdCl₂·2NaCl, 30 cc. solvent (alc. alone or 30 cc. alc. plus varying amts. of H₂O or AcMe), and electrolytic H were employed. A correction was made for H absorbed by the catalyst. The course of hydrogenation was the same with the mixt. III—VI whether the solvent was 40 cc. alc. plus 3 cc. H₂O or 15 cc. AcMe plus 15 cc. alc. plus 5 cc. H₂O. I. W. H.

ASB-31A METALLURGICAL LITERATURE CLASSIFICATION

SEARCHED										SERIALIZED										INDEXED										FILED																			
DATE										AUTHOR										TITLE										SUBJECT																			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

1ST AND 2ND ORDERS PREVIOUS AND PREVIOUSLY 3RD AND 4TH ORDERS

CO

Catalysts of hydrogenation. III. Hydrogen number, a constant for fatty oils. A. S. Ginsberg and N. Yuzheva. *Izv. Akad. Nauk SSSR, Ser. Khim. Nauk* (U. S. S. R.) 5, 1108-70 (1955); *Chem. Abstr.* 50, 2687. The H nos. of 52 kinds of fatty oils, fats and waxes were detd. by the method of hydrogenation previously described. IV. Hydrogen number, a new constant for essential oils. A. S. Ginsberg and E. Evdokimova. *Ibid.* 1252-4. The H nos. of 34 essential oils were detd.
Chas. Hanc

57

620.51.6 METALLURGICAL LITERATURE CLASSIFICATION

1ST AND 2ND ORDERS PREVIOUS AND PREVIOUSLY 3RD AND 4TH ORDERS

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

PROPERTIES AND PREPARATION

17

ca

Alkaloids of *Dugesia tadshikorum* Vved. N. K. Yernaberskiĭ. *J. Gen. Chem. (U. S. S. R.)* 8, 949-52 (1958).—Alk. extr. of dry bulbs of *Dugesia tadshikorum* Vved. (fam. Amaryllidaceae), growing in Tajikistan (Central Asia), gave 0.31% of alkaloids, of which 10% is a cryst. base, $C_{16}H_{19}NO_3$, m. 265-6° (decomp.), $[\alpha]_D^{25} -119.9^\circ$ (alc.), insol. in H_2O , slightly sol. in hot alc. and CH_2N , poorly sol. in most org. solvents and easily sol. in dil. acids (HCl and H_2SO_4). It gives the following salts: HCl, PCl_5 , picrate, H_2CrO_4 and perchlorate, decomp. 313°, 210-11°, 195-7° and 229-30°, resp. It gives Gochel's test for 1 MeO group. It is identical with *lycoris* isolated from *Lycoris radiata* Herb. by Morishima (*Arch. exp. Path. Pharmacol.* 49, 221(1957)). The nature of other bases is being investigated. C. Blanc

ASB-31A METALLURGICAL LITERATURE CLASSIFICATION

SEARCHED	INDEXED	SERIALIZED	FILED
NOV 1964	NOV 1964	NOV 1964	NOV 1964
LIBRARY	LIBRARY	LIBRARY	LIBRARY

PROCESSING AND PROPERTIES UNIT

10

Chen

Alkaloids of *Arthropodium leptocladum* M. Pop. N. K. Yurashvskii. *J. Gen. Chem. (U. S. S. R.)* 6, 265-7(1939).—The green parts of the plant, collected in 1937, after alc. extrn. yield a resinous mist. of alkaloids (0.7% of the dry wt.) which, after ether extrn., yields *leptocladine* (I) C₁₈H₂₁N, long rectangular plates, m. 109-10°, isolated as the HCl salt (II), needles, m. 234-5° (decompn.), from which are also prepd. the *chloroplatinate*, orange, decomp. 197-8°; *picrate*, yellow needles, partially m. 93-5° completely at 112-14°; and *Bi deriv.*, m. 132-3°. II, dry-distd., yields a substance with fecal odor, probably an indole deriv. I is sol. in most org. solvents, insol. in water, is optically inactive and instantly decolorizes cold KMnO₄ in both alk. and acid medium.

John Livak

ABB-PLA DETAILORICAL LITERATURE CLASSIFICATION

33000 3300000000

330000 02	330000 017 00V 001	330000 017 00V 001	330000 017 00V 001
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z	A B C D E F G H I J K L M N O P Q R S T U V W X Y Z	A B C D E F G H I J K L M N O P Q R S T U V W X Y Z	A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

70

CP

Alkaloids. *Petrosimonia monandra* (Pall) Ege. (family Chenopodiaceae). N. K. Yurashevskii and S. I. Stepanov. *J. Gen. Chem.* (U. S. S. R.) 9, 1087-9 (1939). — Piperidine for the 1st time was found in a plant: 1.23% of piperidine, base, 100.5°, was found; HCl salt, m. 245-6°, mixed m. p. 241.5-2.5°; chlorophosphate, m. 280-1°. D. Arkhiv.

ASB-5LA METALLURGICAL LITERATURE CLASSIFICATION

PROCEEDS AND PROPERTIES NOTES

ca

10

Alkaloids of *Girgensohnia diptera* Bge. family *Cypripodiaceae*. N. K. Yurabevskii and S. I. Serpanov. *J. Gen. Chem. (U. S. S. R.)* 9, 2330-6 (1939). — Alk. extr. of green parts of dry *G. diptera* (gathered in Central Asia) gave 1% of *N*-methylpiperidine and 0.25% of a new alkaloid $C_{11}H_{17}N$; m. 87-8°, for which the name *dipserine* (I) is suggested. It contains 1 NH group, is optically inactive and is sol. in org. solvents and insol. in water. *HCl* salt, m. 177-8°; *picrate*, m. 180-90°; *chloroplatinate*, m. 107-9° (decompn.). The structure of I is being investigated. Chas. Mann

ASAC-516 METALLENKAL LITERATURE CLASSIFICATION

SEARCHED INDEXED SERIALIZED FILED

APR 1961

CA

16, 141-4 (1948). -- The green parts of *G. oppositifera* Pak yielded 2 bases: *N*-methylpiperidine (0.53%) and a new substance, *C₁₂H₁₇N*, which was named *guyonamine* (0.04%). The study of this base showed it to be *N*-piperidin-*p*-hydroxyphenylacetamide (I). The product, m. 144-5° (from Et₂O), m. 147-8° (from MeOH), is optically inactive; *HCl* salt, m. 135-8°, *picric acid*, m. 192-4° (dec.). Treatment with 10% alk. KOH yielded piperidine, HCN, and *p*-HO-benzaldehyde, m. 117-18° (from benzene). The synthesis of I was accomplished as follows: 0.5 g. *p*-hydroxybenzaldehyde in 1.25 cc. 38% NaHSO₃ and 10 cc. water were treated with 0.35 g. piperidine,

followed by 0.3 g. KCN, and the warm mist was allowed to stand for several hrs.; the crystal. was washed with water, and dissolved in Et₂O; evapn. of the latter gave 0.3 g. I, m. 147-8°, the identity being confirmed by mixed m.p. G. M. Kosolapoff

418-31A RETAIL/WHOLESALE LITERATURE CLASSIFICATION

14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14