

ZMIHORSKI, Edward

Studies on new high-speed cutting steels with increased carbon content.
Archiw hutn 9 no.2:203-235 '64.

ZMIHORSKI, Edward; ZYSK, Jan

Selection of optimum heat treatment parameters for thin flat springs
based on fatigue tests. Inst mech precyz 12 no.2:5-11 '64.

25(1); 18(3)

PHASE I BOOK EXPLOITATION

POL/2373

Zmihorski, Edward, Doctor, Master Engineer

Stal szybko tnąca (High-speed Steel) Warszawa, Państwowe Wydawnictwa Techniczne, 1958. 233 p. 3,617 copies printed.

Reviewer: Stanisław Jabłoński, Master Engineer; Scientific Ed. of Publishing House : Stefan Błażewski, Master Engineer; Tech. Ed.: W. Rocheński.

PURPOSE: This book is intended for engineers and technicians concerned with the manufacture of tools, and for tool designers, engineers and technologists working in the field of metal cutting.

COVERAGE: The author describes the basic properties and chemical composition of high-speed steels and their use in the manufacture of metal-cutting tools. Methods of brazing, resistance welding, hot press-forming, and forging of high-speed steels, and their use for hard-surfacing other tool materials are described. A detailed description of various methods of heat treatment is given and modern equipment for hardening cutting tools from high-speed steel is discussed. Data on types of high-speed steels produced in Poland,

Card 1/5

High-speed Steel

POL/2373

USA, USSR, and Germany are given. No personalities are mentioned. There are 66 references: 5 Soviet, 33 Polish, 23 German, and 5 English.

TABLE OF CONTENTS:

Ch. I. Introduction	5
Ch. II. Operating Conditions and Technological Requirements Imposed Upon High-speed Steel	8
Ch. III. Effect and Role of Alloying Elements	15
Ch. IV. High-speed Steel Production in Several Countries	37
Ch. V. Comparing High-speed Steel with Other Tool Materials	42
Ch. VI. Future Trends in the Development of High-speed Steel	48
Ch. VII. Selecting High-speed Steel for Tools Based on an Analysis of Their Operating Conditions	50

Card 2/5

POL/2373

High-speed Steel

Ch. VIII. Effect of Manufacturing Conditions on the Selection of Tool Materials	64
Ch. IX. Selecting Materials for Various Types of Tools	69
Ch. X. Acceptance Testing and Inspection of High-speed Steel by the Consumer	78
Ch. XI. Forging and Heating High-speed Steel	94
Ch. XII. Effect of Furnace Atmosphere on the Surface of High-speed Steel	99
Ch. XIII. Hot-Press-forming of Tools from High-speed Steel	104
Ch. XIV. Casting Tools from High-speed Steel	106
Ch. XV. Brazing High-speed Steel Plates	109
a. Brazing and hardening cutting-tool tips made from high-speed steel	109
b. Brazing cutting blades made from high-speed steel onto multi-edge cutters	113

Card 3/5

POL/2373

High-Speed Steel

Ch. XVI. Hard-surfacing by Welding Cutting Edges With High-speed Steel and Resistance Welding of Tools	116
Ch. XVII. Annealing High-speed Steel	122
Ch. XVIII. Hardening High-speed Steel	127
a. Theoretical basis for heat treating high-speed steels	127
b. Hardening temperature for high-speed steel	129
c. Heating time	135
d. Cooling high-speed steel during hardening	146
e. Conventional hardening	149
f. Step hardening	149
g. Isothermal heat treating	150
h. Cooling high-speed steel to a temperature below zero	153
Ch. XIX. Tempering High-speed Steel	156
Ch. XX. Significance of residual austenite in tools	166

Card 4/5

High-speed Steel	POL/2373	
Ch. XXI. Straightening Hardened Tools		168
Ch. XXII. Nitriding Tools		173
Ch. XXIII. Chrome-plating Tools		179
Ch. XXIV. Steam Tempering and Heating of Tools in Water or Phosphate Bath		185
Ch. XXV. Methods of Hardening Tools Made From High-speed Steel		187
Ch. XXVI. Change in Dimensions of Hardened Tools		206
Ch. XXVII. Most Important and Modern Equipment for Heat-treating Tools Made From High-speed Steel		209
Ch. XXVIII. Hardening Long Broaches Made from High-speed Steel		220
Ch. XXIX. Economy Problems in Using High-speed Steel		230
Bibliography		232

AVAILABLE: Library of Congress

Card 5/5

GO/1gb
10-26-59

ZMIHORSKI, E.

"Chroning Applied to Machine Tools", p. 104, (MECHANIK, Vol. 27, No. 3, Mar. 1954, Warszawa, Poland)

SO: Monthly List of East European Accessions, (REAL), IC, Vol. 4, No. 5, May 1955, Uncl.

ZMIHORSKI, E.

Coating cylinders and rings of combustion motors with chromium. p. 113.
(TECHNIKA MOTORYZACYJNA, Vol. 4, No. 4, Apr. 1954, Warszawa, Poland)

SO: Monthly List of East European Accessions, (EEAL). LC, Vol. 3, No. 12, Dec.
1954, Uncl.

ZMIHORSKI, Edward

Factors influencing economy of steel and quality improvement
in production. Przegl drobnej wytworczosci 12 no.6:14-15
Mr '62.

ZMIHORSKI, Edward

Influence of residual austenite upon the fatigue strength of steel
under very high pressing stresses. Archiw hutn 7 no.2:177-185 '62.

ZMIHORSKI, Edward, doc.dr.inz.

Modernization of starting equipment of electrode salt-bath furnaces.
Wiad elektrotechn 30 no.6:199-203 Je '62.

P/038/62/007/002/001/002
E193/E583

AUTHOR: Zmihorski, Edward

TITLE: The effect of residual austenite on the endurance of steel under very high compressive stresses

PERIODICAL: Archiwum hutnictwa, v. 7, no. 2, 1962, 177-195

TEXT: High pressures of the order of 300 kg/mm², required in cold extrusion of steel, give rise to problems of finding suitable materials of construction - hence the present investigation conducted on steels whose composition is given in Table 1. The test pieces were quenched from various temperatures and tempered for 1 hour at 175, 240, 280, 400, 530 and 570 °C, with or without preliminary sub-zero treatment in liquid air. The investigation comprised fatigue tests₂ under compressive stresses ranging from 35 - 330 kg/mm², determination of the proportion of residual austenite, measurements of resistance-to-abrasion, static compression tests, study of dimensional changes during and after heat-treatment and study of plastic deformation in compression. The results can be summarized as follows.
1) High-speed-cutting tungsten steel such as steel SW9 is the

Card 1/3

P/058/62/007/002/001/002
E193/E585

The effect of

most suitable for heavy-duty extrusion rams and other similar parts operating under very high (up to 300 kg/mm²) compressive stresses. Steel NWC could be used as an alternative.

2) Contrary to the generally accepted view, residual austenite has a beneficial effect on the endurance of heat-treated steel operating under high compressive stresses. There is, however, an optimum content of this constituent ($10 \pm 5\%$) whose effect, when present in quantities outside this range, becomes harmful.

3) With increasing tempering temperature (200 - 500 °C) the abrasion-resistance of the steels studied increases and their endurance rapidly decreases.

4) The optimum tempering temperature is 175 °C for steels no.1 and no.2 and 570 °C for steel no. 4. Tempering above or below these temperatures as well as sub-zero treatment brings about a considerable decrease in the resistance of these steels to cyclic compressive loads.

5) A tool, or a machine part, designed to operate under heavy cyclic compressive loads, made from suitable steel and given correct heat-treatment, should have the following characteristics:

Card 2/3

P/058/62/007/002/001/002
E193/E385

The effect of

homogeneous, finely-crystalline structure, consisting of $10 \pm 5\%$ residual austenite, 90% cubic martensite and carbide; the lowest possible internal stresses; hardness HRC = 62 - 63.. There are 15 figures and 1 table.

SUBMITTED: September 30, 1961

Table 1:

Nr	Skład chemiczny w % Chemical composition, %						Typ Cecha hutnicza
	C	Si	Mn	Cr	W	V	
1	1,4	0,3	0,6	1,4	—	—	NC6
2	1,1	0,3	1,0	1,1	1,5	—	NWC
3	1,7	0,4	0,4	12,0	—	—	NC10
4	0,85	—	—	4	9	2	SW9

Card 5/5

ZMIHORSKI, Jan, dr inz.

Suggestions concerning reorganization of pump designing and construction in Poland. Przegl mech 22 no.14:426-427 25 XI '63.

1. Kierownik Centralnego Ośrodka Badawczo-Koordynacyjnego Pomp, Warszawa.

ZMIHORSKI, Jan, mgr., inż.

Role of pump power stations in energetics. Gosp wodna 22 no. 3:95-97.
Mr '62

1. Instytut Energetyki, Warszawa.

ZMIHORSKI, Jan, mgr. inż.

Designing and construction costs of pumped storage electric power plants. Gosp wodna 22 no.4:142-146 Ap '62.

ZMIHORSKI, Jan, mgr inż.

Technical analysis of pumped-storage power plants both existing and under construction in foreign countries. Gosp wodna 22 no.9:414-418 S '62.

1. Instytut Energetyki, Warszawa.

ZMII, P. N.

The care of automobile tires. Izd. 2., perer. Moskva, Gos. nauch.-tekhn.
izd-vo khim. lit-ry, 1946. 100 p. (50-40944)

TL270.255 1946

ZMIJA, Ryszard, inz.

Influence of the method of carbon tool steel melting on its
hardening capacity. Wlad hut 19 no.10:275-276 0 '63

ZMIJA, Ryszard, inz.

Water and sewage problems in the metallurgic industry.
Wiad hut 19 no.7/8:215-219 J1/Ag '63.

ZMIJANIC, D.

Production of plane tree seedings. p. 17

SUMARSKI LIST, Zagreb, Vol 80, No. 1/2, Jan./Feb., 1956

SO: East European Accessions List, Vol 5, No. 10, Oct., 1956

YUGOSLAVIA / Forestry. Forest Crops.

K-3

Abs Jour: Ref Zhur-Biol., No 6, 1958, 24894.

Author : Zmijanac, Duro.

Inst : ~~Not given.~~

Title : Cultivation of Plantation Stock.

Orig Pub: Sumarski list, 1956, 80, No 1-2, 17-23.

Abstract: A comparative analysis of various ways of cultivation of high-yield stock sowing of seeds and grafting is given. The best growth is shown by plants obtained from planting of grafts prepared from two-year specimens.

Card 1/1

FUKARAK, P.; ZAFAR, J.; MESTROVIC, S.; KLEFAC, D.; LNEENICEK, Z.; ZMIJANAC, D.;
SEVNIK, F.; ZAGAR, B.; MIKLAVZIC, J.; KNEZ, A.; PIPAN, R.; FUNKL, L.;
SVETLICIC, A.; ZUMER, L.; KEVO, R.

Reveiw of periodicals; silviculture. Bul se Youg 9 no.4/5:144-
145 Ag-0 '64.

ZMIJESKA, Joanna

Eighth International Book Fair, Warsaw, May 18-26, 1963.
Przegl mech 22 no. 13:408-409 10 J1 '63.

P/046/60/005/011/017/018
D249/D303

AUTHORS: Minczewski, J., and Żmijewska, W.

TITLE: On the reaction of chromates with diphenylcarbazide

PERIODICAL: Nukleonika, v. 5, no. 11, 1960, 790

TEXT: (Abstract - Report No. 153/VII (IBJ - Institute of Nuclear Research, PAS)): Reactions of Cr(VI) with diphenylcarbazide (DPCD) and Cr (II) with diphenylcarbazone (DPCN) have been investigated spectrophotometrically and by potentiometric titration. The investigation concerned the reaction mechanism ~~in~~ the presence of excess reagents, conditions of extraction of the colored product, and the behavior of DPCN in solutions of organic and mineral acids. A mechanism is proposed for the reactions. [Abstractor's note: Complete translation].



Card 1/1

ZMIJEMSKA, Joanna

House of the Technician in Poznan. Przegl mech 22 no.14:455
25 J1 '63.

P/014/62/041/010/001/001
D214/D308

Akerman, Karol, Drafman, Marek, Kruszevska, Olga
and Zmijewska, Wanda

AUTHORS:

TITLE:

The purification of trichlorosilane and silicon
tetrachloride and the preparation of synthetic
quartz glass

PERIODICAL:

Przemys~~l~~ chemiczny, v. 41, no. 10, 1962, 574-577

TEXT:

Methods of determining small quantities of impuri-
ties in SiHCl_3 and SiCl_4 were developed to estimate the efficiency
of methods of purification of these compounds. The most efficient
purification was achieved by complexing the impurities with CH_3CN
and $(\text{C}_6\text{H}_5)_3\text{CCl}$ and removing them by fractional distillation. To
estimate the P and Fe contents present as the trichlorides, isotope
tracer techniques were used. Other impurities were determined by
neutron activation of the samples in the EWA reactor and by measure-
ment of their β -absorption and the decay of their β -activity.
The major impurity was found to be Fe ($1.6 \times 10^{-2}\%$). The purity of

Card 1/2

The purification ...

P/014/62/041/010/001/001
D214/D308

SiO₂ and that of quartz glass, obtained from SiCl₄ by a method developed by the authors, was studied by γ -spectroscopy. All γ -emitters of half-life shorter than that of ³¹Si could not be determined by this method. Quartz glass, obtained from high purity SiCl₄, contained only traces of As and Na but up to 10⁻²% Ta, which was introduced into the glass during the vacuum melting of SiO₂. This compares favorably with quartz glass produced outside Poland. Boron cannot be estimated by the above methods but other methods (5 are given) can be employed. The B content in the produced SiO₂ or the subsequent quartz glass was $> 3 \times 10^{-5}\%$. There are 1 figure and 1 table.

ASSOCIATION: Instytut Badań Jądrowych PAN (Institute of Nuclear Research PAS)

SUBMITTED: June 26, 1962

Card 2/2

AKERMAN, Karol; BRAFMAN, Marek; KRUSZEWSKA, Olga; ZMIJEWSKA, Wanda

Purification of trichlorosilane and silicium tetrachloride and the obtaining of synthetic quartz glass. Przem chem 41 no.10:574-577 0 '62.

1. Instytut Badan Jadrowych, Polska Akademia Nauk, Warszawa.

ZMIJEWSKI, Wanda

Precision of the determination of copper, arsenic and antimony from a photopeak decay curve of a gamma spectrum. Nukleonika 7 no.2:101-108 '62.

1. Institute of Nuclear Research, Polish Academy of Sciences, Warsaw.

MINCZEWSKI, Jerzy; ~~ZMIJEWSKA, Wanda~~

Remarks on the behavior of diphenylcarbazone as an analytic reagent. Chem anal 5 no.3:429-433 '60. (EEAI 10:8)

1. Zaklad Chemii Analitycznej Instytutu Badan Jadrowych PAN, Warszawa.

(Phenylazoformic acid phenylhydrazide)

ZMIJEWSKI, Bohdan

Mgr., inz. Bohdan Zmijewski; an obituary. Normalizacja 29 no. 9:431
'61.

(Engineers--Polish)

ZMIJEWSKI, Pawel, doc. mgr inz. [deceased]; SKARZYNSKA, Kryutyna, mgr inz.; KLASA-BRUNICKI, Hugo, mgr inz.

Utilization of postproduction waste materials for the needs of earthwork construction. Gosp wodna 24 no. 4:125-128 Ap '64.

GOLANT, V.Ye.; ZMILINSKIY, A.P.; KRIVOREYEV, M.V.; NEKRUTKINA, G.P.

Propagation of centimeter waves through wave guides filled with
the plasma of a positive discharge column. Part 1. Zhur. tekhn.
fiz. 31 no.1:55-62 Ja '61. (MIRA 13:12)


1. Leningradskiy Politekhicheskiy institut imeni M.I.Kalinina.
(Plasma (Ionized gases)) (Microwaves) (Wave guides)

AUTHOR: Nachiporenko, Ye. P. (Dr. of Technical Sciences); Znilya, V. I.; Potukhov, G. /

... (molybdenum, oxidation, molybdenum, tungsten, ...)

ABSTRACT: Heaters made of Mo and W and protected by the coatings, become ...

E 28460-66
ACC NR: AT5027945



It shows that the increase in resistance of the coating to oxidation at high temperature was caused by the formation of a dense layer of SiO₂ on the surface of the coating.

ACC NR: AP6017638 SOURCE CODE: UR/0363/65/001/008/1360/1363

AUTHOR: Ivanov, V. Ye.; Mechiporenko, Ye. P.; Krivoruchko, V. M.; Zmily, V. I. 4/

Kitrofanov, A. S.; Aleksandrov, O. M.

Cord

0000 01-731281

2

ZMITRENKO, V.. podpolkovnik.

Discipline is the soul of the army. Voenn.znan. 31 no.6:
8-9 Je '56.

(MLRA 9:10)

(Military discipline) (Russia--Armed forces)

ZMITROVICH, L.A.

Change in venous pressure during pregnancy. Akush. i gin. 36
no. 149-52 Ja-F '60. (MIRA 13:10)
(BLOOD PRESSURE) (PREGNANCY)

BOGOSLOVSKIY, B.M.; ZMIY, P.N.; ZYKOV, D.D., dotsent; PIK, I.Sh.; STRE-
PIKHEYEV, A.A.; ~~TUMENSON~~ I.I.; AVRAMOVA, N.S., redaktor; IUR'YE,
M.S., tekhnicheskiiy redaktor.

[General chemical technology of organic substances] Obshchaia khimi-
cheskaya tekhnologiya organicheskikh veshchestv. Pod red. D.D.Zyko-
va. Moskva, Gos. nauchno-tekhn.izd-vo khim. lit-ry, 1955. 463 p.
(Chemistry, Technical) (MIRA 8:4)

12a

PROCESSES AND PROPERTIES INDEX

THE PRODUCTION OF LAMPBLACK FROM ANTHRACENE AND NAPHTHALENE. P. Zmit. *J. Rubber Ind.* (U. S. S. R.) 12, 551-3 (1936).—A Discussion. A. Pestoff

8

COMMON ELEMENTS

COMMON CHARACTERISTICS

ASAC-ELA METALLURGICAL LITERATURE CLASSIFICATION


London 1937

10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

Co

Soviet tire manufacturing in the last twenty years
(1917-1937). P. Zwill, C. Goughout and Rutter (U.S.
S.R.) 1917. No. 11. 57-60 --A review. A. Petouff

ASD-SLA METALLURGICAL LITERATURE CLASSIFICATION



EST AND JNO GROUPS										PROCESS AND PROPERTIES INDEX									
111 Tornesite as an Anticorrosive Material. P. Tull (Pravda. Org. Khim. (Organic Chem. Ind.), 1936, 1, 294-296; O. 184, 1936, 30, 1103).—[In Russian.] Methods of production, properties, and use of tornesite in the protection of surfaces against corrosion are discussed.—N. B. V.																			
ASH-51A METALLURGICAL LITERATURE CLASSIFICATION																			
STANDARD #1										STANDARD #2									
STANDARD #3										STANDARD #4									

1ST AND 2ND CODING		PROCESSING AND PROPERTIES INDEX	
20 Vulcanizing molds. P. N. Zmil. <i>Kauchuk i Rezina</i> 1941, No. 5, 31-5; <i>Chem. Zvest.</i> 1942, II, 1071. In designing molds, attention must be paid to the flow of the rubber, and the surfaces should be such that adhesion is a min. The relative merits of C steels, Cr-Ni steel and Cr-plated metal are discussed. Cr-plating is advantageous only when the mold has plane surfaces. Molds can be cleaned either with aq. alkalis or by burning with an acetylene torch. C. C. Davis		Common symbols used	
ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION		FROM SYMBOL	
SYMBOLS		SYMBOLS	
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100		1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100	

BULINSKI, Romuald; ZMINDA, Mieczyslaw

Investigations on the vitamin C content in radish. Ann. Univ.,
Lublin sect.D 16:433-439 '61.

1. Z Katedry i Zakładu Nauki o Środkach Spożywczych i Higieny Żywności
Wydziału Farmaceutycznego Akademii Medycznej w Lublinie Kierownik:
prof. dr Alfred Trawinski.
(ASCORBIC ACID) (VEGETABLES)

1. ZMIRNOV, V., ZOTOV, G., Engs.
 2. USSR (600)
 4. Lumber
 7. Expand the production of glued parts. Za ekon mat. No. 1 1953.
9. Monthly List of Russian Accessions, Library of Congress, April 1953, Uncl.

ZMITKO, J

✓ Preparation and properties of kieselguhr used as support
in gas chromatography. J Jan Brezina and Jiri Zmitko
(Výzkumný ústav syntet. kautčuku, Gottwaldov, Czech. I.
Chem. July 52, 2012-13/1053).—Mixing Morovany kiesel-
guhr SK contg. SiO_2 61.5, R_2O_3 25.28, Mg 0.9, and mois-
ture 3.91%, with dusted H_2O to a thick pulp, drying the
pulp in the form of small lumps (diam 3-5 cm.) at $100-10^3$
evacuating 1 hr. at $500-60^3$ and crushing the hard lumps to
powder with particles 0.2-0.5 mm, removing dust by de-
cantation with dusted H_2O , drying the material at $100-10^3$
and vacuuming 1 hr. at 100^3 gives a fine light-brown fine
powder with good wetting properties which tolerate up to
30% by wt. liquid phase in inert liquid. L. J. Brezina

4

ZMITKO, J.

AUTHORS: Brodsky, J. and Zmitko, J. CZ/8/52(82)/10-54/19
TITLE: Preparation and Properties of Kieselguhr Used as a
Support in Gas Chromatography (Uprava a vlastnosti
kieseliny jako nosice pro plynovou chromatografii)
PERIODICAL: Chemické listy, 1958, Vol 52(82), Nr 10, pp 3012-3013
(Czechoslovakia)
ABSTRACT: Because of import difficulties connected with such
carriers as "Celite 545" and "Sterchanoli", the authors
report a method for treating indigenous Kieselguhr to
produce a suitable carrier. This involves the wetting
and redrying, baking and powdering of the Kieselguhr
to produce particles of a suitable and uniform size.
There are 3 references, all of which are Czech.
ASSOCIATION: Výzkumný ústav syntetického kaučuku, Gottwaldov
(Rubber Research Institute, Gottwaldov)
SUBMITTED: January 14, 1958

Card 1/1

COUNTRY : Czechoslovakia B-13
 CATEGORY : Physical Chemistry. Surface Phenomena.
 Adsorption. Chromatography. Ion Exchange.
 ABS. JOUR. : AZKhim., No. 23 1959, No. 81577
 AUTHOR : Brodsky, Jan; Zmitko, Jiri
 INST. : Not given.
 TITLE : Treatment and Properties of Diatomaceous
 Earth, used as a Carrier in Gas or Liquid
 Chromatography.
 ORIG. PUB. : Chem. Listy, 1958, 52, #10, 2012-2013.
 ABSTRACT : The preparation of treated diatomaceous
 earth (I) (Kisselghur SK) used in gas
 chromatography was described. Technical
 grade diatomaceous earth was wetted with
 distilled water, dried, calcined for 1 hour
 at 500-550°, ground and classified. The
 wettability with liquids commonly used as a
 stationary phase was tested. It was found
 that up to 25% of liquid may be incorporated
 into I. The above method may be used to
 obtain I with any desired particle size.

CARD: 1/1

-- Karel Getinek

~~ZMITKO, J.~~; BRODSKY, J.; BIZA, V.

"Automatic recording of analyses carried out by gas chromatography.

p. 414 (Chemický Průmysl) Vol. 7, no. 8, Aug. 1957
Prague, Czechoslovakia

SO: Monthly Index of East European Accessions (EEAI) LC. Vol. 7, no. 4,
April 1958

ZMITKO S.

CZECHOSLOVAKIA/Fitting Out of Laboratories. Instruments.
Their Theory, Construction, and Use.

F.

Abs Jour : Ref Zhur - Khimiya, No 9, 1950, 20585
Author : Znitko, J., Brodsky, J., and Biza, V.
Inst : -
Title : The Automatic Recording of the Results of Gas Chromato-
graphic Analysis.
Orig Pub : Chem Prumysl, 7, No 8, 414-416 (1957) (in Czech with
summaries in German, French, English, and Russian)
Abstract : A catharometer /TN: see RZhKhim, No 9, 1958, 20596,
for description of apparatus; latter is essentially a
thermal conductivity detector/ is installed at the out-
let of the column; the indications of the catharometer
are recorded on a moving strip of photosensitized paper
by means of a light-beam galvanometer. The apparatus
is suitable for the analysis of mixtures containing air,

Card 1/2

ZMITROVICH, A. M.

Material'naia chast' aviatsionnykh bombardirovochnykh ustanovok.
Moskva, Gos. voen. izd-vo, 1939. 146 p., illus.
Title tr.: Aircraft bombing material equipment.

UC630.26

SC: Aeronautical Sciences and Aviation in the Soviet Union, Library of
Congress, 1955.

ZMITROVICH, L.A.

Three cases of bilateral tubal pregnancy. Kaz. med. zhur. no.4:79-
80 J1-Ag '61. (MIRA 15:2)

1. Otdeleniye operativnoy ginekologii (zav. - prof. M.V.Dubnov)
Instituta akusherstva i ginekologii AMN SSSR.
(PREGNANCY, EXTRAUTERINE)

ZMITROVICH, Sergey Viktorovich; BEDRAK, T.V., red.; DAFIYEVA, Ye.U.,
tekh.n.red.

[Utilizing food industry waste in livestock raising]
Ispol'zovanie otkhodov pishchevoi promyshlennosti v zhivotno-
vodstve. Ordzhonikidze, Severo-Osetinskoe knizhnoe izd-vo,
1960. 37 p. (NIRA 14:2)

(Food industry--By-products)

(Feeding)

ZMITROVICH, S. V., Cand of Agric Sci -- (diss) " Utilization of malt grains for fattening pigs." Ordzhonikidze, 1957, 15 pp (North Ossetian Agricultural Institute), 100 copies (KL, 32-57, 95)

ACCESSION NR: AP4013097

8/0126/64/017/001/0094/0099

AUTHOR: Ivanov, V. Ye.; Nechiporenko, Ye. P.; Zmiy, V. I.

TITLE: Study of reaction diffusion in the Mo - Si system

SOURCE: Fizika metallov i metalloved., v. 17, no. 1, 1964, 94-99

TOPIC TAGS: metal diffusion, reaction diffusion, silicon diffusion, molybdenum silicide, molybdenum silicon system, silicide phase formation, vacuum silication

ABSTRACT: Previously published papers of the first two authors and others on various aspects of the reaction diffusion of silicon-saturated molybdenum, tungsten, and tantalum in vacuum have led to the conclusion that in the Mo - Si system the predominant role is played by diffusion of the silicon through the silicide layer; that is, the phase formation reaction takes place primarily on the internal boundary of the layer. The present article confirms this conclusion. The kinetic aspects of the vacuum silication of the molybdenum were also studied. The authors found that the growth of diffusion layers of Mo_5Si_3 and MoSi_2 , as a function of time, obeys a parabolic law. From the parabolic growth of the silicide layers the authors computed the silicon diffusion factors in Mo_5Si_3 and MoSi_2 at 1250C. Used in the diffusion study were flat molybdenum samples 4X6X1 millimeter in size. The

Card 1/2

ACCESSION NR: AP4013097

silicon employed in the tests was in the form of powder with a grain size of 5-7 microns (purity factor: 99.99%). The samples were located in a molybdenum bath and thoroughly sprinkled with the powder. The bath with the samples was inserted, through a precombustion chamber, into a furnace with a molybdenum heater set at the proper temperature. Orig. art. has: 6 figures, 2 formulas, and 1 table.

ASSOCIATION: Fiziko-tekhnicheskiy institut AN USSR (Physicotechnical Institute, AN USSR)

SUBMITTED: 03Mar63

DATE ACQ: 26Feb64

ENCL: 00

SUBCODE: ML; RH

NO REF SOV: 009

OTHER: 000

Card 2/2

ACCESSION NR: AP4013101

S/0126/64/017/001/0112/0144

AUTHOR: Ivanov, V. Ye.; Nechiporenko, Ye. P.; Zmiy, V. I.; Glushko, P. I.;
Aleksandrov, O. M.; Dorokhov, V. I.

TITLE: High-temperature oxidation of molybdenum disilicide

SOURCE: Fizika metallov i metalloved., v. 17, no. 1, 1964, 142-144

TOPIC TAGS: molybdenum, silicon, molybdenum disilicide, molybdenum disilicide
oxidation, molybdenum disilicide microhardness

ABSTRACT: Molybdenum disilicide is a metal with great promise for use in structures designed to withstand high temperatures. In the technical literature there are data on the oxidation of $MoSi_2$ achieved by various methods: hot pressing, sintering etc. The authors of this short article conducted a study of the kinetics of $MoSi_2$ oxidation in a temperature interval of 1400-1700C using a high-temperature resistance furnace. The heater was a spiral 5mm in diameter made from a molybdenum rod. For oxidation, samples of molybdenum disilicide 25X10X0.15 mm in size were used; these samples were obtained by the vacuum method. The temperature was controlled by a thermocouple (Pt - Rh 7% center: Pt-Rh 20%) and an optical pyrometer, the latter placed directly on the heater. The temperature gradient between the heater

Cord 1/2

ACCESSION NR: AP4013101

and the sample was not more than 30C. A metallographic analysis of the sample was carried out with an MDM-7 microscope, with microhardness tested on a PHT-3 instrument. Oxidation time was 10 hours. It was found that with increasing time and temperature the oxidizability of MoSi_2 increases, the rate of oxidation obeying a parabolic law. No transition from a parabolic law of oxidation to a logarithmic one was detected in the tests. X-ray analysis in the temperature range indicated (1400-1700C) revealed an amorphous oxide film on the surface of the oxidized samples. Preliminary analysis showed that this film, in addition to SiO_2 , contains unknown components. These are, apparently, lower molybdic oxides, the vapor tension of which is lower than that of MoO_3 . The microhardness of the molybdenum disilicide, which did not change during the oxidation process, was 1200 kg/mm^2 . Orig. art. has: 3 figures.

ASSOCIATION: Fiziko-tekhnicheskiy institut AN USSR (Physicotechnical Institute, AN USSR)

SUBMITTED: 03Mar63

DATE ACQ: 26Feb64

ENCL: 00

SUB CODE: ML

NO REF SOV: 005

OTHER: 003

Card 2/2

L 3434-66 EWT(m)/BTC/EPF(n)-2/EMG(m)/EMF(t)/EWP(b) 1965 08/15/35

ACCESSION NR: AT5024871

UR/0000/65/000/000/0045/0055

AUTHOR: Ivanov, V. Ye.; Nechiporenko, Ye. P.; Zmiy, V. I.; Krivoruchko, V. H.

TITLE: On the vacuum siliconizing of refractory metals

SOURCE: AN UkrSSR. Institut problem materii ovedeniya. Diffuzionnye pokrviya
metallov v vakuumie. Kiev, Ukraina SSSR. 1965. 15-55

TOPIC TAGS: metal diffusion plating; silicon; refractory metal; silicide; activation energy

ABSTRACT: The kinetics and mechanism of oxide-formation were investigated for Mo
and W. The results show that the rate of oxide-formation is 10⁻⁴ mm²/min. being covered
with a thin oxide layer. Metallographic and radiographic examination
has established that the formation of molybdenum silicide occurs in the follow-
ing sequence:



at the corresponding phase interfaces, i.e. the formation of MoSi₂ is due to the

Card 1/4

1. 74-4-66

ACCESSION NR. AT1024811

lower silicidals. Plotting of the curves of isothermal growth of the layers of MgSi and MgSi_2 on the $\sqrt{t}$ revealed that the increase in their thickness with time is proportional to $\sqrt{t}$. The curves of isothermal growth of the layers of MgSi and MgSi_2 in saturated atmosphere. The resulting curves also proved to follow a parabolic law. The growth of the layers of MgSi and MgSi_2 as a function of time, thus confirming that the diffusion of Si is the determining factor in the rate of siliciding. The rate of siliciding of the specimens of MgSi and MgSi_2 is determined by the temperature of the specimen and the temperature of the box. The rate of siliciding of the specimens of MgSi and MgSi_2 increases with increase in temperature of the specimen and decreases with decrease in this temperature as compared with the temperature of the box, while the growth in case thickness follows a parabolic curve. Original has

ASSOCIATION: none

Card 2/4

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002065320003-0

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002065320003-0"



Fig. 1. Diagram of setup

1 - furnace; 2 - thermocouple; 3 - specimen; 4 - box; 5 - Al_2O_3 ring;
6 - furnace lid; 7 - stainless-steel cooling pipe

Card 4/4 3.4.

IVANOV, V.Ye.; NECHIPORENKO, Ye.P.; ZMIY, V.I.

Studying the reactive diffusion in the system Mo - Si. Fiz. met. i
metalloved. 17 no.1:94-99 Ja '64. (MIRA 17:2)

1. Fiziko-tekhnicheskii institut AN UkrSSR.

IVANOV, V.Ye.; NECHIPORENKO, Ye.P.; ZMIY, V.I.; GLUSHKO, P.I.; ALEKSANDROV, O.M.;
DOROKHOV, V.I.

High-temperature oxidation of molybdenum disilicide. Fla. met. i metal-
loved. 17 no.1:142-144 Ja '64. (MIRA 17:2)

1. Fiziko-tekhnicheskii institut AN UkrSSR.

NECHIPORENKO, Ye.P.; ZMIY, V.I.

New high-temperature heaters for electric furnaces not requiring protective atmospheres. Porosh. met. 1 no.5:92-94 S-0 '61.

(MIRA 15:6)

1. Fiziko-tekhnicheskiy institut AN SSSR.
(Electric furnaces)

IVANOV, V. Ye.; NECHIPORENKO, Ye. P.; OSIPOV, A. D.; ZMIY, V. I.

Effect of stresses on defects in silicide layers on molybdenum.
Fiz. met. i metalloved. 14 no.4:574-577 O '62.

(MIRA 15:10)

(Metallic films—Defects)
(Thermal stresses)

S/137/62/000/004/049/201
A006/A101

AUTHORS: Nechiporenko, Ye.P.; Zmiy, V.I.

TITLE: New high-temperature heaters for electric furnaces which do not require shielding atmosphere

PERIODICAL: Referativnyy zhurnal, Metallurgiya, no. 4, 1962, 45, abstract 4G300 ("Poroshk. metallurgiya", 1961, no. 5, 92 - 94, English summary)

TEXT: For high-temperature furnaces (1900°C), the use of Mo-rods is proposed. The rods are 6 mm in diameter, 230 mm long, with a protective MoSi₂ and refractory enamel coating. The rise of temperature in the furnace operating in air atmosphere can be brought about rapidly. The heaters were tested for 100 h at 1,750°C. A deficiency of the described heaters is the necessity of using high-power transformers due to the low electric resistivity of Mo.

R. Andriyevskiy

[Abstracter's note: Complete translation]

Card 1/1

I 12058-66

EWI(m)/EMP(t)/EMP(b)

IJP(c)

JID/JG/NE

ACC NR: AP6001302

SOURCE CODE: UR/0363/65/001/008/1354/1359

1. 12058-66. Izvestiya. neorganicheskoye materialy, v. 1, no. 8, 1965, 1354-1359

TOPIC TAGS: molybdenum compound, silicide, oxidation kinetics, silicon dioxide

12058-66. Molybdenum compound, silicide, oxidation kinetics, silicon dioxide

Card 1/2

UDC: 040.77'281

ACC NR: AP6001302

Card 2/2 APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002065320003-0

ZMIYENKO, Petr Yakovlevich; SPASIBIN, Ivan Ignat'yevich; ZAFIVAKHIN, A.I.,
red.; TRUKHINA, O.N., tekhn. red.

[Agriculture of the German Democratic Republic] Sel'skoe khoziaistvo
Germanskoi Demokraticheskoi Respubliki. Moskva, Gos. izd-vo sel'khoz.
lit-ry, 1961. 165 p. (MIRA 14:7)
(Germany, East—Agriculture)

LEBEDEV, Mikhail Nikolayevich, kandidat tekhnicheskikh nauk; ASHEKO, Sof'ya
Mikhailovna, kandidat tekhnicheskikh nauk; ZMIYENKO, Sergey Mitro-
~~fanovich~~, kandidat tekhnicheskikh nauk; ERYUKOV, Georgiy Nikolayevich,
kandidat tekhnicheskikh nauk; SIDOROV, Nikolay Nikolayevich, kandidat
tekhnicheskikh nauk; PAUL', V.P., inzhener, redaktor; YUDZON, D.M.,
tekhnicheskiiy redaktor

[Building] Stroitel'noe proizvodstvo. Pod red. M.M.Lebadeva. 2-e
perer. izd. Moskva, Gos. transportnoe zheleznodor. izd-vo, 1954.
489 p. (MIRA 8:4)

(Building)

BALAKHONOV, V.P.; LOCHIN, N.A.; GUTERMAN, I.G.; ZAKHAROV, V.N.; ZMIVY, A.B.; KARMANOV, V.D.; KENJEN, A.M.; MARGOLIN, I.M.; TOPAL, I.D.

Brief news. Meteor.i gidrol no.2:61-64 P '63.
(Meteorology)

(MIRA 16:2)

ZMIYEV, D.M., inzhener.

Hard-alloy cutting heads used in cutting bevel gear teeth. Mashino-
stroitel' no.7:29-31 J1 '57. (MLRA 10:8)
(Gearing, Bevel) (Gear-cutting machines)

ZMIYEV, D.H.; YEVSTOKHNEV, Yu.A.

Investigating cutting forces in cutting globoid worms. Stan. 1
instr. 28 no. 5:1-2 My '57. (MLRA 10:6)
(Gearing, Worm) (Metal cutting)

LEBEDEV, N.H., ZMIYEV, D.M.

Dividing devices used in thread grinding and relieving machines
having no differential attachments. Mashinostroitel' no.1:36-37
Ja '57. (MLRA 10:4)

1. Moskovskiy zavod "Stankokonstruktsiya".
(Screw-cutting machines--Attachments)

ZMIYEV, D.M., inzh.

Quality and strength of gears. Vest.mash. 41 no.7:8-11 J1 161.
(Gearing) (MIRA 14:6)

ZMIYEV, K.

An extraordinary accident at a training exercise. Voen. znan. 41
no.1:28 Ja '65. (MIRA 18:2)

GAVRILIV, V.I.; ZMIYEVA, R.G.

Simplified method for deriving clones from single cells of continuous cell strains. Vop. virus. 8 no.3:361-364 My-Je'63.

(MIRA 16:10)

1. Kontrol'nyy institut meditsinskikh biologicheskikh preparatov imeni L.A. Tarasevicha.
(VIRUS RESEARCH)

GAVRILOV, V.I.; YERSHOV, F.I.; BLYUMKIN, V.N.; KVOKOV, I.I.; LEVINA, D.S.;
ZMIYEVA, R.G.

Characteristics of the morphogenesis of the cultures of the line of
transplantable CA-SV40-63.1 cells. Vop. virus. 10 no.3(2)-120 My.
1965.

(MIRA 18:2)

1. Institut virusologii imeni Ivanovskogo AMN SSSR, Moskva.

BLYUMKIN, V.N.; GAVRILOV, V.I.; VASIL'YEVA, N.N.; ZMIYEVA, R.G.

Cellular strains obtained from tumors caused by the SV40 virus.
Biul.eksp.biol. i med. 59 no.5:85-88 '65.

(MIRA 18:11)

1. Institut virusologii imeni D.I.Ivanovskogo (direktor --
deystvitel'nyy chlen AMN SSSR prof. V.M.Zhdanov) AMN SSSR i
Kontrol'nyy institut meditsinskikh biologicheskikh preparatov
imeni L.A.Tarassovicha (direktor I.F.Mikhaylov), Moskva. Sub-
mitted February 6, 1964.

ZMIVEV, YE. I.

BRILEVSKIY, Ye.A., inzhener; ZMIYEV, Ye.I., inzhener.

Large block building at the Ignat'ev mine. Shakht.stroi.

no.2:23-24 F '57.

(MIRA 10:7)

(Stalino--Apartment houses) (Mine buildings)

GAVRILOV, V.I.; VASIL'YEVA, N.N.; DODKOV, N.N. ZHIYEVA, R.G.

Line of transplantable cells from a Syrian hamster tumor caused
by the SV₄₀ virus. Vop. virus 8 no.5:583-590 S-0'63
(MIRA/17:1)

1. Institut virusologii imeni D.I.Ivanovskogo AMN SSSR i
Kontrol'nyy institut meditsinskikh biologicheskikh preparatov
imeni L.A. Tarasevicha.

GAVRILOV, V.I.; DEMIDOVA, S.A.; ZMIYEVA, R.G.

Clonal virological analysis of the cell population of the
KEM-1 strain. Vop. virus. 9 no.3:309-315 My-Je '64.

(MIRA 18:1)

1. Institut virusologii imeni D.I. Ivanovskogo AMN SSSR i Kontrol'-
nyy institut meditsinskikh biologicheskikh preparatov imeni L.A.
Tarasevicha, Moskva.

BLYUMKIN, V.N.; GAVRILOV, V.I.; SHCHEKOCHIKHINA, Ye.A. ZATYERNA, R.G.

Cytological, cytochemical and karyological characteristics of the
RES strain and its sensitivity to the Coxsackie virus V6. Vop. virus
9 no.4s474-482 J1-Ag '64.

1. Institut virusologii imeni D.I.Ivanovskogo AMN SSSR i Kon-
trol'nyy institut meditsinskikh biologicheskikh preparatov
imeni L.A. Tarasevicha, Moskva.

ZMIYEVA, Ye. S.

AID P - 1429

Subject : USSR/Meteorology and Hydrology

Card 1/2 Pub. 71-a - 3/23

Authors : Kalinin, G. P., Dr. of Geogr. Sciences, Prof. and
Zmiyeva, E. S., Kandidat of Tech. Sci.

Title : On the regulation of the flow of melted water from farm
lands

Periodical : Met. i gidro., 1, 16-22, Ja - F 1955

Abstract : A formula is suggested which would correlate the total
amount of the surface discharge of melted water with
the depth of the thawed layer of the soil, the deficiency
in the absorption by the soil, the area of the thawed sur-
face over which the water flows, its unthawed and snow-
covered area, and the total area. For practical computation
of the depth of thawed soil, a formula is given in
connection with air mean daily positive temperature
(centigrade). These formulae show how to control the

USSR/Physics of the Hydrosphere - General Problems, N-1

Abst Journal: Referat Zhur - Fizika, No 12, 1956, 36246

Author: Kalinin, G. P., Zmiyeva, Ye. S.

Institution: None

Title: On the Use of Aerial Photography for the Study of the Process of the Descent of the Snow Cover

Original

Periodical: Tr. Tsentr. in-ta prognozov, 1956, No 44, 107-119

Abstract: Description of the aerial photographs, taken by the Central Institute of Forecasting in the spring of 1954. Possible errors in the determination of the mean arithmetic value of the different number of observations of the amount of snow in a given locality are discussed.

Card 1/1

ZMIYEVA, Ye.S.

Prognoses of high rain floods of the river Volga in line with the
Uglich Hydroelectric Power Station. Trudy TSIP no. 50:122-136 '57.
(Volga River--Floods) (MLRA 10:8)

ZMIYEVA, Ye.S.; PODVISHENSKAYA, N.Ya.

Distribution and dynamics of the snow blanket descent in river
basins. Trudy TSIF no. 54:43-61 '57. (MIRA 10:8)
(Snow) (Rivers)

ZMIYEVA, Ye.S.

Use of the synoptic-climatological method of the Main Geophysical
Observatory for the forecasts of water conditions in the rivers.
Meteor.i gidrol. no.8:46-52 Ag '63. (MIRA 16:10)

1. TSentral'nyy institut prognozov.

ZMIYEVA, Ye.S.; MAKAROVA, T.T.

Results of soil moisture measurement with the ohmic soil moisture
meter. Trudy TSIP no.99:33-40 '61. (MIRA 14:5)
(Soil moisture--Measurement)

ZMIYEVA, Ye.S.

Determining soil moisture characteristics of drainage basins from
hydrometeorological data. Trudy TSIP no.99:41-52 '61. (MIRA 14:5)
(Soil moisture)

ZMIYVA, Te. 8.

Precalculating the water discharge during the flood descent
under conditions of considerable inflow of melted-snow and
rain water. Trudy TSIP no. 65:71-83 '58. (MIRA 11:6)
(Hydrology)

ZMIYEVA, Ye.S.

Utilizing water supply draining curves of river systems for forecasting flood recessions. Trudy TSIP no. 59:44-72 '57. (MIRA 114)
(Floods)

ZMIYEVA, Yelena Stepanovna; SHASTIN, A.P., otv. red.; MINENKO,
V.M., red.

[Forecasts of the inflow of water into the Kuybyshev and
Volgograd Reservoirs] Prognozy pritoka vody k Kuibyshev-
skomu i Volgogradskomu vodokhranilishcham. Moskva, Gid-
rometeoizdat, 1964. 255 p. (MIRA 17:12)