

**Page Denied**

ROUTING			
TO:	NAME AND ADDRESS	DATE	INITIALS
1			
2			
3			
4			
	ACTION	DIRECT REPLY	PREPARE REPLY
	APPROVAL	DISPATCH	RECOMMENDATION
	COMMENT	FILE	RETURN
	CONCURRENCE	INFORMATION	SIGNATURE
REMARKS:			
FROM: NAME, ADDRESS, AND PHONE NO.			DATE

**SECRET**

39

(Security Classification)

25X1

(See inside cover)

CONTROL NO. Z-16069/82

NPIC/IEG (12/82)


COPY \_\_\_\_\_ OF \_\_\_\_\_

**Warning Notice**

Intelligence Sources or Methods Involved

**NATIONAL SECURITY INFORMATION**

Unauthorized Disclosure Subject to Criminal Sanctions

**SECRET**

(Security Classification)

**Warning Notice**  
**Intelligence Sources or Methods Involved**  
**(WNINTEL) or (D)**

**NATIONAL SECURITY INFORMATION**  
**Unauthorized Disclosure Subject to Criminal Sanctions**

**DISSEMINATION CONTROL ABBREVIATIONS**

<b>NOFORN-</b>	<b>Not Releasable to Foreign Nationals</b>
<b>NOCONTRACT-</b>	<b>Not Releasable to Contractors or Contractor/Consultants</b>
<b>PROPIN-</b>	<b>Caution-Proprietary Information Involved</b>
<b>ORCON-</b>	<b>Dissemination and Extraction of Information Controlled by Originator</b>
<b>REL . . .</b>	<b>This Information has been Authorized for Release to . . .</b>

**SECRET**

25X1

**(c) NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER**Page 1 of 1Attachment to Z-16069/82  
NPIC/IEG (12/82)  
21 DECEMBER 1982

Copy \_\_\_\_\_

PROBABLE ENVIRONMENTAL SHELTER UNDER CONSTRUCTIONSAKI AIRFIELD, USSR

25X1

1. (SWN) SIGNIFICANCE: CONSTRUCTION OF A PROBABLE ENVIRONMENTAL SHELTER OVER A CATAPULT TROUGH AT SAKI AIRFIELD SUGGESTS THAT EMPLACEMENT OF THE LAUNCH ENGINE CYLINDERS IS UNDERWAY.
2. (SWN) REMARKS: A RECTANGULAR STRUCTURAL FRAMEWORK FOR A PROBABLE ENVIRONMENTAL SHELTER WAS ERECTED OVER THE CATAPULT TROUGH ORIENTED AT 045 DEGREES AT SAKI AIRFIELD. THE FRAMEWORK EXTENDED OVER THE ENTIRE LENGTH AND WIDTH OF THE TROUGH

25X1  
25X1  
25X1

CONSTRUCTION OF THE FRAMEWORK BEGAN  
WHEN AT LEAST SEVEN  
SECTIONS OF THE FRAMEWORK WERE ERECTED OVER THE CATAPULT TROUGH.

(SWN) ANALYST'S COMMENTS -- THIS IS THE FIRST OBSERVATION OF THIS TYPE OF ACTIVITY AT SAKI. NO SHELTER WAS OBSERVED AT THE CATAPULT TROUGH ORIENTED AT 225 DEGREES, WHICH HAD BEEN COVERED WITH DECK PLATES DURING THE SUMMER.

(SWN) ENVIRONMENTAL SHELTERS ARE USED TO FACILITATE THE EMPLACEMENT AND ALIGNMENT OF LAUNCH ENGINE CYLINDERS IN THE CATAPULT TROUGH. THE PLACEMENT TOLERANCES OF THE CYLINDERS IN THE TROUGH ARE CRITICAL AND ENVIRONMENTALLY SENSITIVE. ANY INACCURACIES IN THE PLACEMENT OF THE CYLINDERS COULD CAUSE THE PISTON ASSEMBLIES, WHICH TRANSMIT POWER TO THE LAUNCH AIRCRAFT, TO DAMAGE THE CYLINDERS WHEN THE CATAPULT IS FIRED. SIMILAR ENVIRONMENTAL SHELTERS HAVE BEEN BUILT OVER THE CATAPULT TROUGHS DURING THE INSTALLATION AND ALIGNMENT OF LAUNCH ENGINE CYLINDERS ON US NAVY AIRCRAFT CARRIER CATAPULTS (SEE INSET).

25X1

3. (S) COORDINATES 45-05-35N 033-36-21E

25X1

These notes have been prepared for briefing purposes only and should not be used for detailed analytical work. Their use should be restricted to the particular briefing board(s) they were prepared for and must be considered valid only for the reporting period as indicated by the date of issue.

25X1

**WARNING NOTICE**  
Intelligence Sources  
and Methods Involved

**SECRET**

25X1